```
smacc2::ISmaccClientBehavior

    stateMachine

    currentState

    currentOrthogonal

 + ISmaccClientBehavior()
 + ~ISmaccClientBehavior()
 + getStateMachine()
 + getName()
 + requiresClient()
 + requiresComponent()
# runtimeConfigure()
# onEntry()
# onExit()
# postEvent()
# postEvent()
# getCurrentState()
# dispose()
# getNode()
# getLogger()
 - executeOnEntry()
 executeOnExit()
 - onOrthogonalAllocation()
                Λ
smacc2::SmaccAsyncClient
            Behavior
onEntryThread

    onExitThread

postFinishEventFn
- postSuccessEventFn
postFailureEventFn_

    onFinished

- onSuccess

    onFailure

    isShutdownRequested_

+ onOrthogonalAllocation()
+ ~SmaccAsyncClientBehavior()
+ onSuccess()
+ onFinished()
+ onFailure()
# postSuccessEvent()
# postFailureEvent()
# dispose()
#isShutdownRequested()
- waitFutureIfNotFinished()
executeOnEntry()
executeOnExit()
sm_autoware_avp::clients
::autoware_client::CbSetupInitial
        PoseEstimation
```

initialStatePose

+ CbSetupInitialPoseEstimation()

+ onEntry() + onExit()