```
smacc2::ISmaccClientBehavior

    stateMachine

    currentState

    currentOrthogonal

  + ISmaccClientBehavior()
  + ~ISmaccClientBehavior()
  + getStateMachine()
  + getName()
  + requiresClient()
  + requiresComponent()
  # runtimeConfigure()
  # onEntry()
  # onExit()
  # postEvent()
  # postEvent()
  # getCurrentState()
  # dispose()
  # getNode()
  # getLogger()
  executeOnEntry()
  executeOnExit()
  - onOrthogonalAllocation()
 smacc2::SmaccAsyncClient
              Behavior

    onEntryThread

    onExitThread

    postFinishEventFn

 - postSuccessEventFn

    postFailureEventFn

    onFinished

 - onSuccess
 - onFailure

    isShutdownRequested_

 + onOrthogonalAllocation()
 + ~SmaccAsyncClientBehavior()
 + onSuccess()
 + onFinished()
 + onFailure()
 # postSuccessEvent()
 # postFailureEvent()
 # dispose()
 # isShutdownRequested()
 - waitFutureIfNotFinished()
 executeOnEntry()
 executeOnExit()
sm_autoware_avp::clients
::autoware_client::CbNavigateGlobal
              Position

    goalPose

+ CbNavigateGlobalPosition()
+ onEntry()
```

+ onExit()