```
smacc2::ISmaccClientBehavior
    stateMachine
    currentState
    currentOrthogonal
    ISmaccClientBehavior()
 +
    ~ISmaccClientBehavior()
 getStateMachine()
 + getName()
 + requiresClient()
 +
   requiresComponent()
 + onEntry()
   onExit()
 + executeOnEntry()
   executeOnExit()
 # runtimeConfigure()
 # postEvent()
 # postEvent()
 #
    getCurrentState()
 # dispose()
 # getNode()
 # getLogger()
    onOrthogonalAllocation()
  smacc2::SmaccAsyncClient
           Behavior
- onEntryThread

    onExitThread

- postFinishEventFn
 postSuccessEventFn_

    postFailureEventFn_

    onFinished

    onSuccess

onFailure
- isShutdownRequested
+ onOrthogonalAllocation()
+ ~SmaccAsyncClientBehavior()
+ onSuccess()
+ onFinished()
+ onFailure()
+ requestForceFinish()
+ executeOnEntry()
+ executeOnExit()
+ waitOnEntryThread()
+ onSuccess()
+ onFinished()
+ onFailure()
# postSuccessEvent()
# postFailureEvent()
# dispose()
# isShutdownRequested()

    waitFutureIfNotFinished()

   smacc2::client_behaviors
         ::CbRosStop2
   + packageName_
  + launchFileName_
  # result
  # client_
  # future
    detached_futures
```

+ CbRosStop2()+ CbRosStop2()+ ~CbRosStop2()

+ onEntry()

+ onOrthogonalAllocation()