```
smacc2::ISmaccClientBehavior

    stateMachine

    currentState

    currentOrthogonal

+ ISmaccClientBehavior()
+ ~ISmaccClientBehavior()
+ getStateMachine()
+ getName()
+ requiresClient()
+ requiresComponent()
# runtimeConfigure()
# onEntry()
# onExit()
# postEvent()
# postEvent()
# getCurrentState()
# dispose()
#getNode()
#getLogger()
executeOnEntry()
executeOnExit()
- onOrthogonalAÎlocation()
smacc2::SmaccAsyncClient
            Behavior
onEntryThread
onExitThread

    postFinishEventFn

- postSuccessEventFn
postFailureEventFn

    onFinished

- onSuccess
- on Failure

    isShutdownRequested

+ onOrthogonalAllocation()
+ ~SmaccAsyncClientBehavior()
+ onSuccess()
+ onFinished()
+ onFailure()
+ requestForceFinish()
# postSuccessEvent()
# postFailureEvent()
# dispose()
#isShutdownRequested()
- waitFutureIfNotFinished()
- executeOnEntry()
executeOnExit()
               Λ
     _move_group_interface
     ::CbMoveNamedTarget
  # movegroupClient
  # namedTarget_
  + CbMoveNamedTarget()
  + onEntry()
  + onExit()
  + getNamedTargetValues()
```