```
smacc2::ISmaccClientBehavior

    stateMachine

    currentState

    currentOrthogonal

 + ISmaccClientBehavior()
 + ~ISmaccClientBehavior()
 + getStateMachine()
 + getName()
 + requiresClient()
 + requiresComponent()
# runtimeConfigure()
# onEntry()
# onExit()
# postEvent()
# postEvent()
# getCurrentState()
# dispose()
#getNode()
#getLogger()
 - executeOnEntry()
 executeOnExit()
 - onOrthogonalAllocation()
               Λ
smacc2::SmaccAsyncClient
            Behavior

    onEntryThread

onExitThread
postFinishEventFn
- postSuccessEventFn

    postFailureEventFn

- onFinished

    onSuccess

    onFailure

- isShutdownRequested
+ onOrthogonalAllocation()
+ ~SmaccAsyncClientBehavior()
+ onSuccess()
+ onFinished()
+ onFailure()
+ requestForceFinish()
# postSuccessEvent()
# postFailureEvent()
# dispose()
#isShutdownRequested()
- waitFutureIfNotFinished()
executeOnEntry()
executeOnExit()
sm autoware avp::clients
::autoware client::CbSetupInitial
         PoseEstimation

    initialStatePose
```

+ CbSetupInitialPoseEstimation()

+ onEntry() + onExit()