
{std::enable_shared _from_this< SmaccStateInfo > ||}
{map< const std::type _info *, std::vector < smacc2::introspection ::ClientBehaviorInfoEntry > > ||}
{map< const std::type _info *, std::vector < std::shared_ptr< smacc2 ::introspection::SmaccStateReactor Info > > > ||}
{map< const std::type _info *, std::vector < std::shared_ptr< smacc2 ::introspection::SmaccEventGenerator Info > > > ||}
{int ||}
{string ||}
{shared_ptr< smacc2 ::introspection::SmaccState MachineInfo > ||}
{shared_ptr< smacc2 ::introspection::SmaccState Info > ||}
{vector< smacc2::introspection ::SmaccTransitionInfo > ||}
{vector< std::shared _ptr< smacc2::introspection ::SmaccStateInfo > > ||}
{type_info * ||}
+staticBehaviorInfo
+stateReactorsInfo
+eventGeneratorsInfo
+depth_
+stateIndex_
+demangledStateName
+fullStateName
+stateMachine_
+parentState_
+transitions_
+children_
+tid_
{smacc2::introspection ::SmaccStateInfo ||+ SmaccStateInfo() + getStateLevel() + depth() + getAncestors() + getFullPath() + createChildState() + declareTransition() + toShortName() + getDemangledFullName() + getNode() + getLogger() }
{SharedPtr ||}
{shared_ptr< rclcpp ::Logger > ||}
{vector< std::shared _ptr< smacc2::StateReactor > > ||}
{vector< std::shared _ptr< smacc2::SmaccEventGenerator > > ||}
#node_
#logger_
#stateReactors_
#eventGenerators_
#stateInfo_
{smacc2::ISmaccState ||+ getStateMachine() + getName() + getParentState() + getNode() + getLogger() + getClassName() + configure() + requiresComponent() + requiresClient() + getGlobalSMData() + setGlobalSMData() + createStateReactor() + createStateReactor() + createEventGenerator() + postEvent() + postEvent() + notifyTransition() + notifyTransitionFromTransition TypeInfo() + getStateReactors() + getEventGenerators() + getOrthogonal() + getClientBehavior() + getEventGenerator() + getStateReactor() }
#parentState_
{boost::statechart:: simple_state< MostDerived, Context, mpl::list<>, sc ::has_deep_history > ||}
{list<> * ||}
{bool ||}
+smacc_inner_type
+finishStateThrown
{smacc2::SmaccState < MostDerived, Context, InnerInitial, historyMode > ||+ SmaccState() + SmaccState() + ~SmaccState() + getStateInfo() + getName() + getFullName() + getShortName() + getParentState() + exit() + runtimeConfigure() + onEntry() + onExit() + getGlobalSMData() + setGlobalSMData() + requiresComponent() + getStateMachine() + checkWhileLoopConditionAnd ThrowEvent() + throwSequenceFinishedEvent() + configure_orthogonal _runtime() + configure_orthogonal _runtime() + configure_orthogonal() + static_createStateReactor() + static_createEventGenerator() + static_createStateReactor _aux() + initial_deep_construct() + deep_construct() + shallow_construct() - entryStateInternal() - configure_orthogonal _internal() }
{boost::statechart:: simple_state< State2, SmAtomicPerformanceTrace1, mpl::list<>, sc::has_deep _history > ||}
+smacc_inner_type
+finishStateThrown
< State2, SmAtomicPerformance Trace1 >
{smacc2::SmaccState < State2, SmAtomicPerformance Trace1 > ||+ SmaccState() + SmaccState() + ~SmaccState() + getStateInfo() + getName() + getFullName() + getShortName() + getParentState() + exit() + runtimeConfigure() + onEntry() + onExit() + getGlobalSMData() + setGlobalSMData() + requiresComponent() + getStateMachine() + checkWhileLoopConditionAnd ThrowEvent() + throwSequenceFinishedEvent() + configure_orthogonal _runtime() + configure_orthogonal _runtime() + configure_orthogonal() + static_createStateReactor() + static_createEventGenerator() + static_createStateReactor _aux() + initial_deep_construct() + deep_construct() + shallow_construct() - entryStateInternal() - configure_orthogonal _internal() }
{sm_atomic_performance _trace_1::State2 ||+ runtimeConfigure() + onEntry() + onExit() + staticConfigure() }