
map< const std::type_info *, std::vector< std::shared_ptr< smacc::introspection::SmaccStateReactorInfo > > >
map< const std::type_info *, std::vector< std::shared_ptr< smacc::introspection::SmaccEventGeneratorInfo > > >
int
string
std::enable_shared_from_this< SmaccStateInfo >
vector< smacc::introspection::SmaccTransitionInfo >
vector< std::shared_ptr< smacc::introspection::SmaccStateInfo > >
type_info *
map< const std::type_info *, std::vector< smacc::introspection::ClientBehaviorInfoEntry > >
shared_ptr< smacc::introspection::SmaccStateMachineInfo >
shared_ptr< smacc::introspection::SmaccStateInfo >
+stateReactorsInfo
+eventGeneratorsInfo
+depth_
+stateIndex_
+demangledStateName
+fullStateName
+transitions_
+children_
+tid_
+staticBehaviorInfo
+stateMachine_
+parentState_
smacc::introspection::SmaccStateInfo
+ SmaccStateInfo()
+ getStateLevel()
+ depth()
+ getAncestors()
+ getFullPath()
+ createChildState()
+ declareTransition()
+ toShortName()
+ getDemangledFullName()
vector< std::shared_ptr< smacc::SmaccEventGenerator > >
vector< std::shared_ptr< smacc::StateReactor > >
NodeHandle
#eventGenerators_
#stateInfo_
#stateReactors_
-stateMachineInfo_
#currentStateInfo_
#contextNh
#nh
smacc::ISmaccState
+ getStateMachine()
+ getParentState()
+ getROSNode()
+ getClassName()
+ configure()
+ requiresComponent()
+ requiresClient()
+ getGlobalSMData()
+ setGlobalSMData()
+ createStateReactor()
+ createStateReactor()
+ createEventGenerator()
+ postEvent()
+ postEvent()
+ notifyTransition()
+ notifyTransitionFromTransitionTypeInfo()
+ getStateReactors()
+ getEventGenerators()
+ getParam()
+ setParam()
+ param()
+ getOrthogonal()
+ getEventGenerator()
+ getStateReactor()
#parentState_
ServiceServer
Timer
SmaccStatus
map< std::string, std::shared_ptr< smacc::ISmaccOrthogonal > >
recursive_mutex
StateMachineInternalAction
list< boost::signals2::connection >
map< std::string, std::pair< std::function< std::string()>, boost::any > >
vector< smacc_msgs::SmaccTransitionLogEntry >
SMRunMode
unsigned long
Publisher
#nh_
#private_nh_
#transitionHistoryService_
#timer_
#status_msg_
#orthogonals_
-eventQueueMutex_
-m_mutex_
-stateMachineCurrentAction
-stateCallbackConnections
-globalData_
-transitionLogHistory_
-runMode_
-stateSeqCounter_
#currentState_
#stateMachinePub_
#stateMachineStatusPub
#transitionLogPub_
-nh_
smacc::ISmaccStateMachine
+ ISmaccStateMachine()
+ ~ISmaccStateMachine()
+ reset()
+ stop()
+ eStop()
+ getOrthogonal()
+ getOrthogonals()
+ requiresComponent()
+ postEvent()
+ postEvent()
+ getTransitionLogHistory()
+ getGlobalSMData()
+ setGlobalSMData()
+ mapBehavior()
+ getStateMachineName()
+ state_machine_visualization()
+ getCurrentStateInfo()
+ publishTransition()
+ onInitialize()
+ getTransitionLogHistory()
+ createSignalConnection()
+ notifyOnStateEntryStart()
+ notifyOnStateEntryEnd()
+ notifyOnRuntimeConfigured()
+ notifyOnStateExitting()
+ notifyOnStateExited()
+ notifyOnRuntimeConfigurationFinished()
+ getCurrentStateCounter()
+ getCurrentState()
+ getStateMachineInfo()
+ buildStateMachineInfo()
+ getNode()
# checkStateMachineConsistence()
# initializeROS()
# onInitialized()
# createOrthogonal()
# getParam()
# setParam()
# param()
- lockStateMachine()
- unlockStateMachine()
- propagateEventToStateReactors()
- updateStatusMessage()
vector< std::shared_ptr< smacc::ISmaccClientBehavior > >
vector< std::shared_ptr< smacc::ISmaccClient > >
vector< smacc::ISmaccUpdatable * >
atomic< unsigned long >
double
atomic< bool >
SmaccFifoScheduler *
processor_handle
thread
-statusPub_
boost::signals2::signal < Signature, optional_last_value< typename boost::function_traits< Signature >::result_type >, int, std::less< int >, function< Signature >, typename extended_signature< function_traits< Signature >::arity, Signature >::function_type, boost::signals2::mutex >
-clientBehaviors_
#clients_
-stateMachine_
-signalDetector_
-smaccStateMachine_
-updatableClients_
-updatableStateElements_
-lastState_
-loop_rate_hz
-end_initialized_
-scheduler_
-processorHandle_
-signalDetectorThread_
#nh_
smacc::ISmaccOrthogonal
+ setStateMachine()
+ getStateMachine()
+ addClientBehavior()
+ runtimeConfigure()
+ onEntry()
+ onExit()
+ getName()
+ requiresComponent()
+ requiresClient()
+ getClients()
+ getClientBehaviors()
+ setGlobalSMData()
+ getGlobalSMData()
+ getClientBehavior()
# onInitialize()
# assignClientToOrthogonal()
smacc::SignalDetector
+ SignalDetector()
+ initialize()
+ setProcessorHandle()
+ runThread()
+ join()
+ stop()
+ pollingLoop()
+ pollOnce()
+ postEvent()
- findUpdatableClients()
- findUpdatableStateElements()
map< smacc::ComponentKey, std::shared_ptr< smacc::ISmaccComponent > >
boost::signals2::signal < bool(TServiceRequest &, std::shared_ptr< TServiceResponse >), optional_last_value< typename boost::function_traits< bool(TServiceRequest &, std::shared_ptr< TServiceResponse >) >::result_type >, int, std::less< int >, function< bool(TServiceRequest &, std::shared_ptr< TServiceResponse >) >, typename extended_signature< function_traits< bool(TServiceRequest &, std::shared_ptr< TServiceResponse >) >::arity, bool(TServiceRequest &, std::shared_ptr< TServiceResponse >) >::function_type, boost::signals2::mutex >
smacc::SmaccSignal < Signature, Combiner, Group, GroupCompare, SlotFunction, ExtendedSlotFunction, Mutex >
-server_
-stateMachine_
-orthogonal_
#components_
< bool(TServiceRequest &, std::shared_ptr< TServiceResponse >)>
smacc::ISmaccClient
+ ISmaccClient()
+ ~ISmaccClient()
+ initialize()
+ getName()
+ postEvent()
+ postEvent()
+ getComponent()
+ getComponent()
+ getType()
+ getStateMachine()
+ connectSignal()
+ requiresClient()
+ getComponents()
# onOrthogonalAllocation()
# createComponent()
# createNamedComponent()
# setStateMachine()
# setOrthogonal()
optional< std::string >
smacc::SmaccSignal < bool(TServiceRequest &, std::shared_ptr< TServiceResponse >)>
bool
+serviceName_
+onServiceRequestReceived_
-initialized_
smacc::client_bases::SmaccServiceServerClient < TService >
+ SmaccServiceServerClient()
+ SmaccServiceServerClient()
+ ~SmaccServiceServerClient()
+ onServiceRequestReceived()
+ initialize()
- serviceCallback()