int

type_info *

std::enable_shared_from_this< SmaccStateInfo >

map< const std::type_info *, std::vector< smacc2::introspection::ClientBehaviorInfoEntry > >

map< const std::type_info *, std::vector< std::shared_ptr< smacc2::introspection::SmaccStateReactorInfo > > >

map< const std::type_info *, std::vector< std::shared_ptr< smacc2::introspection::SmaccEventGeneratorInfo > > >

string

vector< smacc2::introspection::SmaccTransitionInfo >

vector< std::shared_ptr< smacc2::introspection::SmaccStateInfo > >

shared_ptr< smacc2::introspection::SmaccStateInfo >

shared_ptr< smacc2::introspection::SmaccStateMachineInfo >

SharedPtr

recursive_mutex

StateMachineInternalAction

map< void *, std::shared_ptr< smacc2::CallbackCounterSemaphore > >

map< std::string, std::pair< std::function< std::string()>, boost::any > >

vector< smacc2_msgs::msg::SmaccTransitionLogEntry >

SMRunMode

int64_t

SharedPtr

vector< smacc2::ISmaccState * >

SmaccStatus

map< std::string, std::shared_ptr< smacc2::ISmaccOrthogonal > >

vector< boost::signals2::scoped_connection >

SharedPtr

+depth_
+stateIndex_

+Id_

+staticBehaviorInfo

+stateReactorsInfo

+eventGeneratorsInfo

+demangledStateName
+fullStateName

+transitions_

+children_

+parentState_

#currentStateInfo_

+stateMachine_

#stateMachineInfo_

#Id_

-eventQueueMutex_
-m_mutex_

-stateMachineCurrentAction

-stateCallbackConnections_

-globalData_

-transitionLogHistory_

-runMode_

-stateSeqCounter_

#timer_

#currentState_

#status_msg_

#orthogonals_

#longLivedSignalConnections_

#eventsLogPub_
#stateMachinePub

#stateMachineStatusPub_
#transitionHistoryService_
#transitionLogPub_

smacc2::ISmaccStateMachine

+ ISmaccStateMachine()
+ ~ISmaccStateMachine()
+ reset()
+ stop()
+ eStop()
+ getOrthogonal()
+ getClientBehavior()
+ getOrthogonals()
+ requiresComponent()
+ postEvent()
+ postEvent()
+ getGlobalSMData()
+ setGlobalSMData()
+ getStateMachineName()
+ state_machine_visualization()
+ getCurrentStateInfo()
+ publishTransition()
+ onInitialize()
+ getTransitionLogHistory()
+ createSignalConnection()
+ disconnectSmaccSignalObject()
+ notifyOnStateEntryStart()
+ notifyOnStateEntryEnd()
+ notifyOnRuntimeConfigured()
+ notifyOnStateExitting()
+ notifyOnStateExited()
+ notifyOnRuntimeConfiguration Finished()
+ getCurrentStateCounter()
+ getCurrentState()
+ getStateMachineInfo()
+ buildStateMachineInfo()
+ getHodel()
+ getLogger()
+ getMutex()
# checkStateMachineConsistence()
# initializeROS()
# onInitialized()
# createOrthogonal()
- lockStateMachine()
- unlockStateMachine()
- propagateEventToStateReactors()
- updateStatusMessage()

-statusPub_

boost::signals2::signal< Signature, optional_last_value< typename boost::function_traits< Signature >::result_type >, int, std::less< int >, function< Signature >, typename extended_signature< function_traits< Signature >::arity, Signature >::function_type, boost::signals2::mutex >

vector< std::shared_ptr< smacc2::ISmaccClient > >

vector< std::vector < std::shared_ptr< smacc2::ISmaccClientBehavior > > >

mutex

smacc2::introspection::SmaccStateInfo

+ SmaccStateInfo()
+ getStateLevel()
+ depth()
+ getAncestors()
+ getFullPath()
+ createChildState()
+ declareTransition()
+ toShortName()
+ getDemangledFullName()
+ getNode()
+ getLogger()

vector< std::shared_ptr< smacc2::SmaccReactor > >

vector< std::shared_ptr< smacc2::SmaccEventGenerator > >

shared_ptr< rclcpp::Logger >

#node_

vector< smacc2::ISmaccUpdatable * >

vector< std::vector < smacc2::ISmaccUpdatable * > >

atomic< int64_t >

double

atomic< bool >

SmaccFifoScheduler *

processor_handle

thread

ExecutionModel

#clients_
-clientBehaviors_
-mutex_

#stateInfo_

#stateReactors_
#eventGenerators_

#logger_

-stateMachine_

-smaccStateMachine_
-signalDetector_

-updatableClients_

-updatableStateElements_

-lastState_

-loop_rate_hz_

-end_
-enabled_

-scheduler_

-processorHandle_

-signalDetectorThread_

-executionModel_

smacc2::ISmaccOrthogonal

+ setStateMachine()
+ getStateMachine()
+ initState()
+ addClientBehavior()
+ runtimeConfigure()
+ onEntry()
+ onExit()
+ onDispose()
+ getName()
+ requiresComponent()
+ requiresClient()
+ getClients()
+ getClientBehaviors()
+ setGlobalSMData()
+ getGlobalSMData()
+ getClientBehavior()
+ getNode()
+ getLogger()
# onInitialize()
# initializeClients()
# assignClientToOrthogonal()

smacc2::ISmaccState

+ getStateMachine()
+ getName()
+ getParentState()
+ getHodel()
+ getLogger()
+ getClassName()
+ configure()
+ requiresComponent()
+ requiresClient()
+ getGlobalSMData()
+ setGlobalSMData()
+ createStateReactor()
+ createEventGenerator()
+ postEvent()
+ postEvent()
+ notifyTransition()
+ notifyTransitionFromTransition TypeInfo()
+ getStateReactors()
+ getEventGenerators()
+ getOrthogonal()
+ getClientBehavior()
+ getEventGenerator()
+ getStateReactor()

smacc2::SignalDetector

+ SignalDetector()
+ initialize()
+ setProcessorHandle()
+ runThread()
+ join()
+ stop()
+ terminateScheduler()
+ pollingLoop()
+ postEvent()
+ getNode()
+ getLogger()
+ notifyStateConfigured()
+ notifyStateExited()
- pollOnce()
- findUpdatableClientsAndComponents()
- findUpdatableStateElements()

#parentState_

-stateMachine_

-stateMachine_

boost::signals2::signal< void(const TResponse &), optional_last_value <typename boost::function_traits<void(const TResponse &)>::result_type>, int, std::less<int>, function<void(const TResponse &)>, typename extended_signature<function_traits<void(const TResponse &)>::arity, void(const TResponse &)>::function_type, boost::signals2::mutex >

map< smacc2::ComponentKey, std::shared_ptr< smacc2::ISmaccComponent > >

smacc2::SmaccSignal< Signature, Combiner, Group, GroupCompare, SlotFunction, ExtendedSlotFunction, Mutex >

< void(const TResponse &)>

#components_
-orthogonal_

-currentOrthogonal_
-currentState_

smacc2::ISmaccClient

+ ISmaccClient()
+ ~ISmaccClient()
+ onInitialize()
+ getName()
+ getComponent()
+ getComponent()
+ getComponent()
+ getType()
+ getStateMachine()
+ connectSignal()
+ requiresClient()
+ getOrthogonals()
+ iterateComponents()
+ postEvent()
+ postEvent()
# onComponentInitialization()
# onStateOrthogonalAllocation()
# createComponent()
# createNamedComponent()
# getNode()
# getLogger()
- initialize()
- setStateMachine()
- setOrthogonal()

smacc2::ISmaccClientBehavior

+ ISmaccClientBehavior()
+ ~ISmaccClientBehavior()
+ getStateMachine()
+ getName()
+ requiresClient()
+ requiresComponent()
+ onEntry()
+ onExit()
+ executeOnEntry()
+ executeOnExit()
# runtimeConfigure()
# postEvent()
# postEvent()
# getCurrentState()
# dispose()
# getNode()
# getLogger()
- onStateOrthogonalAllocation()

bool

SimpleActionServer< odom_tracker::CpOdomTrackerAction >

io_context

executor_work_guard< decltype(io_context_).executor_type >

thread

context

function< void(TResponse)>

smacc2::SmaccSignal< void(const TResponse &)>

const int

-initialized_
-io_ssl_

-server_

-io_context_

-worker_guard_

-tcp_connection_runner_

-ssl_context_

-callbackHandler

-onResponseReceived_

-HTTP_VERSION

cl_http::ClHttp

+ onResponseReceived()
+ ClHttp()
+ ~ClHttp()
+ onInitialize()
+ makeRequest()

kHttpRequestMethod

smacc2::SmaccClientBehavior

+ ~SmaccClientBehavior()
+ onEntry()
+ onExit()

-cl_http_

-kRequestType

cl_http::ClbHttpRequestBase

+ ClbHttpRequestBase()
+ onStateOrthogonalAllocation()
+ runtimeConfigure()
+ onResponseReceived()
+ onEntry()
+ onExit()

cl_http::ClbHttpGetRequest

+ ClbHttpGetRequest()