vector< std::shared _ptr< smacc2::introspection ::SmaccStateInfo > >

type_info *

std::enable_shared _from_this< SmaccStateInfo >

map< const std::type _info *, std::vector < smacc2::introspection ::ClientBehaviorInfoEntry > >

map< const std::type _info *, std::vector < std::shared_ptr< smacc2 ::introspection::SmaccStateReactor Info > > >

map< const std::type _info *, std::vector < std::shared_ptr< smacc2 ::introspection::SmaccEventGenerator Info > > >

weak_ptr< smacc2::introspection ::SmaccStateInfo >

string

weak_ptr< smacc2::introspection ::SmaccStateMachineInfo >

vector< smacc2::introspection ::SmaccTransitionInfo >

int

SharedPtr

shared_ptr< smacc2 ::introspection::SmaccState Info >

SmaccStatus

map< std::string, std ::shared_ptr< smacc2 ::ISmaccOrthogonal > >

shared_ptr< smacc2 ::introspection::SmaccState MachineInfo >

recursive_mutex

atomic< StateMachineInternal Action >

map< void *, std::shared _ptr< smacc2::CallbackCounterSemaphore > >

map< std::string, std ::pair< std::function < std::string()>, boost ::any > >

deque< smacc2_msgs ::msg::SmaccTransitionLogEntry >

size_t

SMRunMode

int64_t

SharedPtr

vector< smacc2::ISmaccState * >

mutex

SharedPtr

+children_

+fid_

+staticBehaviorInfo

+stateReactorsInfo_

+eventGeneratorsInfo

+parentState_

+demangledStateName +fullStateName

+stateMachine_

+transitions_

+depth_ +stateIndex_

-reactorWalkDepth_

#fn_

#currentStateInfo_

#status_msg_

#orthogonals_

#stateMachineInfo_

-eventQueueMutex_ -m_mutex_

-stateMachineCurrentAction

-stateCallbackConnections

-globalData_

-transitionLogHistory_

-transitionLogHistorySize_

-runMode_

-stateSeqCounter_

#timer_

#currentState_

-transitionLogMutex_

#eventsLogPub_ #stateMachinePub

#stateMachineStatus Pub_ #transitionHistory Service_ #transitionLogPub_

smacc2::introspection ::SmaccStateInfo

+ SmaccStateInfo()
+ getStateLevel()
+ getStateMachineInfo()
+ getParentState()
+ depth()
+ getAncestors()
+ getFullPath()
+ createChildState()
+ declareTransition()
+ toShortName()
+ getDemangledFullName()
+ getNode()
+ getLogger()

bool

shared_ptr< rclcpp ::Logger >

vector< std::shared _ptr< smacc2::SmaccEventGenerator > >

vector< std::shared _ptr< smacc2::SmaccStateReactor > >

#node_

smacc2::ISmaccStateMachine

+ ISmaccStateMachine()
+ ~ISmaccStateMachine()
+ ISmaccStateMachine()
+ operator=()
+ ISmaccStateMachine()
+ operator~()
+ reset()
+ stop()
+ eStop()
+ joinAsyncClientBehaviorThreads()
+ getOrthogonal()
+ getClientBehavior()
+ getOrthogonals()
+ requiresComponent()
+ requiresComponent()
+ postEvent()
+ postEvent()
+ getGlobalSMData()
+ setGlobalSMData()
+ getStateMachineName()
+ state_machine_visualization()
+ getCurrentStateInfo()
+ publishTransition()
+ onInitialize()
+ onUnhandledStInitialization Failure()
+ getTransitionLogHistory()
+ createSignalConnection()
+ disconnectSmaccSignalObject()
+ disconnectSmaccSignalObject()
+ notifyOnStateEntryStart()
+ notifyOnStateEntryEnd()
+ notifyOnRuntimeConfigured()
+ notifyOnStateExiting()
+ notifyOnStateExited()
+ notifyOnRuntimeConfiguration Finished()
+ getCurrentStateCounter()
+ getCurrentState()
+ getStateMachineInfo()
+ buildStateMachineInfo()
+ getNode()
+ getLogger()
+ getMutex()
# checkStateMachineConsistence()
# initializeROS()
# onInitialized()
# createOrthogonal()
- lockStateMachine()
- unlockStateMachine()
- propagateEventToStateReactors()
- updateStatusMessage()

vector< std::vector < std::shared_ptr< smacc2 ::ISmaccClientBehavior > > >

vector< std::shared _ptr< smacc2::ISmaccClient > >

-mutex_

vector< smacc2::ISmaccUpdatable * >

vector< std::vector < smacc2::ISmaccUpdatable * > >

double

SmaccFifoScheduler *

processor_handle

thread

ExecutionModel

atomic< bool >

-statusPub_

#initializationFailed_

#stateInfo_

#logger_

#eventGenerators_

#stateReactors_

smacc2::ISmaccState

+ ISmaccState()
+ ~ISmaccState()
+ ISmaccState()
+ operator~()
+ ISmaccState()
+ operator=()
+ getStateMachine()
+ getName()
+ getParentState()
+ getNode()
+ getLogger()
+ initializationFailed()
+ getClassName()
+ configure()
+ requiresComponent()
+ requiresComponent()
+ requiresClient()
+ getGlobalSMData()
+ setGlobalSMData()
+ createStateReactor()
+ createStateReactor()
+ createEventGenerator()
+ postEvent()
+ postEvent()
+ notifyTransition()
+ notifyTransitionFromTransition TypeInfo()
+ getStateReactors()
+ getEventGenerators()
+ getOrthogonal()
+ getClientBehavior()
+ getEventGenerator()
+ getStateReactor()

map< smacc2::ComponentKey, std::shared_ptr< smacc2 ::ISmaccComponent > >

#components_

#parentState_

#clientBehaviors_

#clients_

-stateMachine_

-signalDetector_

-smaccStateMachine_

-updatableClients_

-updatableStateElements_

#DefaultLoopRateHz -initializationPollRateHz -loop_rate_hz

-scheduler_

-processorHandle_

-signalDetectorThread_

-executionModel_

-end_ -initialized_ -rosInitialized_

smacc2::ISmaccOrthogonal

+ ISmaccOrthogonal()
+ ~ISmaccOrthogonal()
+ ISmaccOrthogonal()
+ operator=()
+ ISmaccOrthogonal()
+ operator~()
+ setStateMachine()
+ getStateMachine()
+ initState()
+ addClientBehavior()
+ runtimeConfigure()
+ onEntry()
+ onExit()
+ onDispose()
+ getName()
+ requiresComponent()
+ requiresClient()
+ getClients()
+ getClientBehaviors()
+ setGlobalSMData()
+ getGlobalSMData()
+ getClientBehavior()
+ getNode()
+ getLogger()
# onInitialize()
# initializeClients()
# assignClientToOrthogonal()
- currentClientBehaviors()

smacc2::SignalDetector

+ SignalDetector()
+ initialize()
+ setProcessorHandle()
+ runThread()
+ join()
+ stop()
+ terminateScheduler()
+ joinAsyncClientBehaviorThreads()
+ pollingLoop()
+ postEvent()
+ queueWorkItem()
+ getNode()
+ getLogger()
+ notifyStateConfigured()
+ notifyStateExited()
+ notifyStateInitialization Failed()
+ notifyRosInitialized()
- pollOnce()
- findUpdatableClientsAndComponents()
- findUpdatableStateElements()

boost::signals2::signal < Signature, optional _last_value< typename boost ::function_traits< Signature >::result_type >, int, std ::less< int >, function< Signature >, typename extended_signature< function_traits< Signature >::arity, Signature >::function_type, boost:: signals2::mutex >

#stateMachine_

#components_

#parentState_

-stateMachine_

-stateMachine_

#stateMachine_

-orthogonal_

-currentState_

-currentOrthogonal_

smacc2::ISmaccClient

+ ISmaccClient()
+ ~ISmaccClient()
+ ISmaccClient()
+ operator=()
+ ISmaccClient()
+ operator~()
+ onInitialize()
+ getName()
+ getComponent()
+ getComponent()
+ getComponent()
+ getType()
+ getStateMachine()
+ connectSignal()
+ requiresClient()
+ getComponents()
+ iterateComponents()
+ postEvent()
+ postEvent()
# onComponentInitialization()
# onStateOrthogonalAllocation()
# createComponent()
# createNamedComponent()
# getNode()
# getLogger()
- initialize()
- setStateMachine()
- setOrthogonal()

smacc2::ISmaccClientBehavior

+ ISmaccClientBehavior()
+ ~ISmaccClientBehavior()
+ ISmaccClientBehavior()
+ operator=()
+ ISmaccClientBehavior()
+ operator~()
+ getStateMachine()
+ getName()
+ requiresClient()
+ requiresComponent()
+ requiresComponent()
+ onEntry()
+ onExit()
+ executeOnEntry()
+ executeOnExit()
# runtimeConfigure()
# postEvent()
# postEvent()
# getCurrentState()
# dispose()
# getNode()
# getLogger()
- onStateOrthogonalAllocation()

boost::signals2::signal < void(), optional_last _value< typename boost:: function_traits< void()> ::result_type >, int, std ::less< int >, function< void ()>, typename extended_signature < function_traits< void()>::arity, void()>::function_type, boost::signals2::mutex >

smacc2::SmaccSignal < Signature, Combiner, Group, GroupCompare, SlotFunction, ExtendedSlotFunction, Mutex >

-owner_

smacc2::ISmaccComponent

+ ISmaccComponent()
+ ~ISmaccComponent()
+ ISmaccComponent()
+ operator=()
+ ISmaccComponent()
+ operator=()
+ getName()
# onInitialize()
# onComponentInitialization()
# postEvent()
# postEvent()
# onStateOrthogonalAllocation()
# requiresComponent()
# requiresComponent()
# requiresClient()
# createSiblingComponent()
# createSiblingNamedComponent()
# getNode()
# getLogger()
# getStateMachine()
- initialize()
- setStateMachine()

vector< cl_moveit2z ::TrajectoryHistoryEntry >

Options

shared_ptr< moveit ::planning_interface ::MoveGroupInterface >

shared_ptr< moveit ::planning_interface ::PlanningSceneInterface >

function< void()>

smacc2::SmaccSignal < void()>

optional< std::future < int > >

-mutex_

-trajectoryHistory_

-options_

-moveGroupClientInterface_

-planningSceneInterface_

-postEventMotionExecution Failed_ -postEventMotionExecution Succeeded_

-onFailed_ -onSucceeded_

-postFailureEventFn -postFinishEventFn -postSuccessEventFn_

-onFailure_ -onFinished_ -onSuccess_

-onEntryThread_ -onExitThread_

smacc2::SmaccAsyncClient Behavior

+ onStateOrthogonalAllocation()
+ SmaccAsyncClientBehavior()
+ ~SmaccAsyncClientBehavior()
+ SmaccAsyncClientBehavior()
+ operator=()
+ SmaccAsyncClientBehavior()
+ operator=()
+ onSuccess()
+ onFinished()
+ onFailure()
+ requestForceFinish()
+ executeOnEntry()
+ executeOnExit()
+ waitOnEntryThread()
+ onSuccess()
+ onFinished()
+ onFailure()
# postSuccessEvent()
# postFailureEvent()
# dispose()
# isShutdownRequested()
- waitFutureIfNotFinished()

-isShutdownRequested_

cl_moveit2z::CpTrajectory History

+ getLastTrajectory()
+ getLastTrajectory()
+ pushTrajectory()

cl_moveit2z::CpMoveGroup Interface

+ CpMoveGroupInterface()
+ onInitialize()
+ onStateOrthogonalAllocation()
+ postEventMotionExecution Succeeded()
+ postEventMotionExecution Failed()
+ onMotionExecutionSucceeded()
+ onMotionExecutionFailed()

#trajectoryHistory_

#cpMoveGroupInterface_

#cpMoveGroupInterface_

#cpTrajectoryHistory_

#cpMoveGroup_

cl_moveit2z::CpTrajectory Executor

+ CpTrajectoryExecutor()
+ ~CpTrajectoryExecutor()
+ onInitialize()
+ execute()
+ executePlan()
+ cancel()
+ getTrajectoryHistory()
- applyExecutionOptions()
- recordToHistory()

cl_moveit2z::CpMotionPlanner

+ CpMotionPlanner()
+ ~CpMotionPlanner()
+ onInitialize()
+ planToPose()
+ planToJointTarget()
+ planCartesianPath()
+ getCurrentState()
- applyPlanningOptions()

#cpTrajectoryExecutor_

#cpMotionPlanner_

cl_moveit2z::ClMoveit2zClient BehaviorBase

+ onStateOrthogonalAllocation()
+ ~ClMoveit2zClientBehavior Base()
# postMotionSuccess()
# postMotionFailure()