vector< smacc2::ISmaccUpdatable * >

vector< std::vector < smacc2::ISmaccUpdatable * > >

double

SmaccFifoScheduler *

processor_handle

thread

ExecutorModel

SharedPtr

atomic< bool >

-updatableClients_

-updatableStateElements_

#DefaultLoopRateHz
#InitializationPollRateHz
loop_rate_hz

-scheduler_

-processorHandle_

-signalDetectorThread_

-executorModel_

-statusPub_

-end_
-initialized_
-costInitialized_

smacc2::SignalDetector

+ SignalDetector()
+ initialize()
+ setProcessorHandle()
+ runThread()
+ join()
+ stop()
+ terminateScheduler()
+ joinAsyncClientBehaviorThreads()
+ pollingLoop()
+ postEvent()
+ queueWorkItem()
+ getNode()
+ getLogger()
+ notifyStateConfigured()
+ notifyStateExited()
+ notifyStateInitialization Failed()
+ notifyRosInitialized()
- pollOnce()
- findUpdatableClientsAndComponents()
- findUpdatableStateElements()

SharedPtr

SharedPtr

#eventLogPub_
#stateMachinePub_
#stateMachineStatus Pub_
#transitionHistory Service_
#transitionLogPub_

vector< smacc2::ISmaccState * >

shared_ptr< smacc2 ::introspection::SmaccState Info >

SmaccStatus

map< std::string, std ::shared_ptr< smacc2 ::ISmaccOrthogonal > >

shared_ptr< smacc2 ::introspection::SmaccState MachineInfo >

recursive_mutex

atomic< StateMachineInternal Action >

map< void *, std::shared _ptr< smacc2::CallbackCounterSemaphore > >

map< std::string, std ::pair< std::function < std::string()>, boost ::any > >

dequeu< smacc2::msgs ::msg::SmaccTransitionLogEntry >

size_t

SMRunMode

int64_t

int

mutex

#n_
-smaccStateMachine_
-signalDetector_
#timer_
#currentState_
#currentStateInfo_
#status_msg_
#orthogonals_
#stateMachineInfo_
-eventQueueMutex_
-m_mutex_
-stateMachineCurrentAction
-stateCallbackConnections
-globalData_
-transitionLogHistory_
-transitionLogHistorySize_
-runMode_
-stateSeqCounter_
-reactorWalkDepth_
-transitionLogMutex_

smacc2::ISmaccStateMachine

+ ISmaccStateMachine()
+ ~ISmaccStateMachine()
+ ISmaccStateMachine()
+ operator=()
+ ISmaccStateMachine()
+ operator=()
+ reset()
+ stop()
+ eStop()
+ joinAsyncClientBehaviorThreads()
+ getOrthogonal()
+ getClientBehavior()
+ getOrthogonals()
+ requiresComponent()
+ requiresComponent()
+ postEvent()
+ postEvent()
+ getGlobalSMData()
+ setGlobalSMData()
+ getStateMachineName()
+ state_machine_visualization()
+ getCurrentStateInfo()
+ publishTransition()
+ onInitialize()
+ onUnhandledStInitialization Failure()
+ getTransitionLogHistory()
+ createSignalConnection()
+ disconnectSmaccSignalObject()
+ disconnectSmaccSignalObject()
+ notifyOnStateEntryStart()
+ notifyOnStateEntryEnd()
+ notifyOnRuntimeConfigured()
+ notifyOnStateExiting()
+ notifyOnStateExited()
+ notifyOnRuntimeConfiguration Finished()
+ getCurrentStateCounter()
+ getCurrentState()
+ getStateMachineInfo()
+ buildStateMachineInfo()
+ getNode()
+ getLogger()
+ getMutex()
# checkStateMachineConsistence()
# initializeROS()
# onInitialized()
# createOrthogonal()
- lockStateMachine()
- unlockStateMachine()
- propagateEventToStateReactors()
- updateStatusMessage()

vector< std::shared _ptr< smacc2::ISmaccClient > >

vector< std::vector < std::shared_ptr< smacc2 ::ISmaccClientBehavior > > >

-mutex_

-depth_
-stateIndex_

map< const std::type _info *, std::vector < smacc2::introspection ::ClientBehaviorInfoEntry > >

map< const std::type _info *, std::vector < std::shared_ptr< smacc2 ::introspection::SmaccStateReactor Info > > >

map< const std::type _info *, std::vector < std::shared_ptr< smacc2 ::introspection::SmaccEventGenerator Info > > >

weak_ptr< smacc2::introspection ::SmaccStateMachineInfo >

weak_ptr< smacc2::introspection ::SmaccStateInfo >

vector< smacc2::introspection ::SmaccTransitionInfo >

vector< std::shared _ptr< smacc2::introspection ::SmaccStateInfo > >

type_info *

std::enable_shared _from_this< SmaccStateInfo >

string

-node_

-stateMachine_
-clients_
-demangledStateName
-fullStateName
-clientBehaviors_

smacc2::ISmaccOrthogonal

+ ISmaccOrthogonal()
+ ~ISmaccOrthogonal()
+ ISmaccOrthogonal()
+ operator=()
+ ISmaccOrthogonal()
+ operator=()
+ setStateMachine()
+ getStateMachine()
+ initState()
+ addClientBehavior()
+ runtimeConfigure()
+ onEntry()
+ onExit()
+ onDispose()
+ getName()
+ requiresComponent()
+ requiresClient()
+ getClients()
+ getClientBehaviors()
+ setGlobalSMData()
+ getGlobalSMData()
+ getClientBehavior()
+ getNode()
+ getLogger()
# onInitialize()
# initializeClients()
# assignClientToOrthogonal()
- currentClientBehaviors()

-stateMachine_

-isShutdownRequested_

-mutex_

-stateBehaviorsInfo_
-stateReactorsInfo_
-eventGeneratorsInfo_
-stateMachine_
-parentState_
-transitions_
-children_
-info_

smacc2::introspection ::SmaccStateInfo

+ SmaccStateInfo()
+ getStateLevel()
+ getStateMachineInfo()
+ getParentState()
+ depth()
+ getAncestors()
+ getFullPath()
+ createChildState()
+ declareTransition()
+ toShortName()
+ getDemangledFullName()
+ getNode()
+ getLogger()

map< smacc2::ComponentKey, std::shared_ptr< smacc2 ::ISmaccComponent > >

boost::signals2::signal < void(), boost::signals2::mutex >

boost::signals2::signal < void(const WrappedResult &), boost::signals2::mutex >

smacc2::SmaccSignal < Signature, Combiner, Group, GroupCompare, SlotFunction, ExtendedSlotFunction, Mutex >

boost::signals2::signal < void(const Feedback &), boost::signals2::mutex >

boost::signals2::signal < Signature, optional _last_value= typename boost ::function_traits< Signature >::result_type >, int, std ::less< int >, function< Signature >, typename extended_signature< function_traits< Signature >::arity_ , Signature > ::function_type, boost:: signals2::mutex >

bool

shared_ptr< rclcpp ::Logger >

vector< std::shared _ptr< smacc2::StateReactor > >

vector< std::shared _ptr< smacc2::SmaccEventGenerator > >

-initializationFailed_
-logger_
-stateReactors_
-eventGenerators_
-stateMachine_
-stateMachine_
-stateInfo_
-orthogonal_

smacc2::ISmaccState

+ ISmaccState()
+ ~ISmaccState()
+ ISmaccState()
+ operator=()
+ ISmaccState()
+ operator=()
+ getStateMachine()
+ getName()
+ getParentState()
+ getNode()
+ getLogger()
+ initializationFailed()
+ getClassName()
+ configure()
+ requiresComponent()
+ requiresComponent()
+ requiresClient()
+ getGlobalSMData()
+ setGlobalSMData()
+ createStateReactor()
+ createStateReactor()
+ createEventGenerator()
+ postEvent()
+ postEvent()
+ notifyTransition()
+ notifyTransitionFromTransition TypeInfo()
+ getStateReactors()
+ getEventGenerators()
+ getOrthogonal()
+ getClientBehavior()
+ getEventGenerator()
+ getStateReactor()

-parentState_

smacc2::ISmaccClient

+ ISmaccClient()
+ ~ISmaccClient()
+ ISmaccClient()
+ operator=()
+ ISmaccClient()
+ operator=()
+ onInitialize()
+ getName()
+ getComponent()
+ getComponent()
+ getComponent()
+ getType()
+ getStateMachine()
+ connectSignal()
+ requiresClient()
+ getComponents()
+ iterateComponents()
+ postEvent()
+ postEvent()
# onComponentInitialization()
# onStateOrthogonalAllocation()
# createComponent()
# createNamedComponent()
# getNode()
# getLogger()
- initialize()
- setStateMachine()
- setOrthogonal()

-currentOrthogonal

#actionClientName_

-currentState_

-owner_

smacc2::ISmaccClientBehavior

+ ISmaccClientBehavior()
+ ~ISmaccClientBehavior()
+ ISmaccClientBehavior()
+ operator=()
+ ISmaccClientBehavior()
+ operator=()
+ getStateMachine()
+ getName()
+ requiresClient()
+ requiresComponent()
+ requiresComponent()
+ onEntry()
+ onExit()
+ executeOnEntry()
+ executeOnExit()
+ runtimeConfigure()
# postEvent()
# postEvent()
# getCurrentState()
# dispose()
# getNode()
# getLogger()
- onStateOrthogonalAllocation()

smacc2::ISmaccComponent

+ ISmaccComponent()
+ ~ISmaccComponent()
+ ISmaccComponent()
+ operator=()
+ ISmaccComponent()
+ operator=()
+ getName()
# onInitialize()
# onComponentInitialization()
# postEvent()
# postEvent()
# onStateOrthogonalAllocation()
# requiresComponent()
# requiresComponent()
# requiresClient()
# createSiblingComponent()
# createSiblingNamedComponent()
# getNode()
# getLogger()
# getStateMachine()
- initialize()
- setStateMachine()

function< void()>

optional< std::future < int > >

-resultConnectionsInitialized_

-postFailureEventFn_
-postFinishEventFn_
-postSuccessEventFn_

-onEntryThread_
-onExitThread_

smacc2::SmaccSignal < void()>

optional< std::shared _future< typename rclcpp ::action::Client< ActionType >::CancelResponse::SharedPtr > >

FeedbackCallback

smacc2::SmaccSignal < void(const WrappedResult &)>

smacc2::SmaccSignal < void(const Feedback &)>

optional< std::string >

optional< std::chrono ::milliseconds >

function< void(const WrappedResult &)>

function< void(const Feedback &)>

shared_ptr< ActionClient >

optional< std::shared _future< typename GoalHandle ::SharedPtr > >

< void()>

< void(const WrappedResult &)>

< void(const Feedback &)>

-onFailure_
-onFinished_
-onSuccess_

+onGoalAccepted_
+onGoalRejected_

-lastCancelResponse_

-feedbackCallback_

+onActionAborted
+onActionCancelled
+onActionSucceeded

+onActionFeedback_

+actionServerName

+serverTimeout

-postAbortedEvent
+postCancelledEvent
+postSuccessEvent

-postFeedbackEvent

-client_

-lastRequest_

smacc2::client_core _components::CpActionClient < ActionType >

+ CpActionClient()
+ CpActionClient()
+ ~CpActionClient()
+ sendGoal()
+ cancelGoal()
+ isServerReady()
+ waitForServer()
+ onInitialize()
+ onComponentInitialization()
+ onSucceeded()
+ onAborted()
+ onCancelled()
+ onFeedback()
+ getActionClient()
- onFeedback()
- onResult()
- postResultEvents()

-components_
-actionMutex_

-goalActivityGoen_
-goalIsFight_

-dockId_
-dockType_

-useDockId_

-resultConnectionsInitialized_

-actionClientName_

smacc2::SmaccAsyncClient Behavior

+ onStateOrthogonalAllocation()
+ SmaccAsyncClientBehavior()
+ ~SmaccAsyncClientBehavior()
+ SmaccAsyncClientBehavior()
+ operator=()
+ SmaccAsyncClientBehavior()
+ operator=()
+ onSuccess()
+ onFinished()
+ onFailure()
+ requestForceFinish()
+ executeOnEntry()
+ executeOnExit()
+ waitOnEntryThread()
+ onSuccess()
+ onFinished()
+ onFailure()
# postSuccessEvent()
# postFailureEvent()
# dispose()
# isShutdownRequested()
- waitFutureIfNotFinished()

milliseconds

ResultCode

-goalResponseTimeout_

-actionClient_

-actionResult_

smacc2::client_behavior _bases::CbActionClientBehavior Base< TAction >

+ onStateOrthogonalAllocation()
+ ~CbActionClientBehaviorBase()
+ onExit()
# sendGoal()
# cancelGoal()
# onActionSuccess()
# onActionAbort()
# onActionFeedback()
# setActionClientName()
- dispatchActionSuccess()
- dispatchActionAbort()
- dispatchActionFeedback()

-goalResponseTimeout_

-actionClient_

-actionResult_

nav2_msgs::action ::DockRobot >

smacc2::client_behavior _bases::CbActionClientBehavior Base< nav2_msgs::action::DockRobot >

+ onStateOrthogonalAllocation()
+ ~CbActionClientBehaviorBase()
+ onExit()
# sendGoal()
# cancelGoal()
# onActionSuccess()
# onActionAbort()
# onActionFeedback()
# setActionClientName()
- dispatchActionSuccess()
- dispatchActionAbort()
- dispatchActionFeedback()

PoseStamped

-dockPose_

cl_nav2z::ClzDockRobot

+ ClzDockRobot()
+ ClzDockRobot()
+ onEntry()