mutex
size_t
SMRunMode
int64_t
int
SharedPtr
vector< smacc2::ISmaccState * >
shared_ptr< smacc2 ::introspection::SmaccState Info >
SmaccStatus
map< std::string, std ::shared_ptr< smacc2 ::ISmaccOrthogonal > >
atomic< StateMachineInternal Action >
shared_ptr< smacc2 ::introspection::SmaccState MachineInfo >
map< void *, std::shared _ptr< smacc2::CallbackCounterSemaphore > >
recursive_mutex
map< std::string, std ::pair< std::function < std::string()>, boost ::any > >
deque< smacc2_msgs ::msg::SmaccTransitionLogEntry >
SharedPtr
SharedPtr
-transitionLogMutex_
-transitionLogHistorySize_
-runMode_
-stateSeqCounter_
-reactorWalkDepth_
#nh_
#currentState_
#currentStateInfo_
#status_msg_
#orthogonals_
-stateMachineCurrentAction
#stateMachineInfo_
-stateCallbackConnections
-eventQueueMutex_ -m_mutex_
-globalData_
-transitionLogHistory_
#eventsLogPub_ #stateMachinePub
#stateMachineStatus Pub_ #transitionHistory Service_ #transitionLogPub_
#timer_
smacc2::ISmaccStateMachine
+ ISmaccStateMachine()
+ ~ISmaccStateMachine()
+ reset()
+ stop()
+ eStop()
+ joinAsyncClientBehaviorThreads()
+ getOrthogonal()
+ getClientBehavior()
+ getOrthogonals()
+ requiresComponent()
+ requiresComponent()
+ postEvent()
+ postEvent()
+ getGlobalSMData()
+ setGlobalSMData()
+ getStateMachineName()
+ state_machine_visualization()
+ getCurrentStateInfo()
+ publishTransition()
+ onInitialize()
+ getTransitionLogHistory()
+ createSignalConnection()
+ disconnectSmaccSignalObject()
+ disconnectSmaccSignalObject()
+ notifyOnStateEntryStart()
+ notifyOnStateEntryEnd()
+ notifyOnRuntimeConfigured()
+ notifyOnStateExiting()
+ notifyOnStateExited()
+ notifyOnRuntimeConfiguration Finished()
+ getCurrentStateCounter()
+ getCurrentState()
+ getStateMachineInfo()
+ buildStateMachineInfo()
+ getNode()
+ getLogger()
+ getMutex()
# checkStateMachineConsistence()
# initializeROS()
# onInitialized()
# createOrthogonal()
- lockStateMachine()
- unlockStateMachine()
- propagateEventToStateReactors()
- updateStatusMessage()
-mutex_
vector< std::vector < std::shared_ptr< smacc2 ::ISmaccClientBehavior > > >
vector< std::shared _ptr< smacc2::ISmaccClient > >
-clientBehaviors_
#clients_
-stateMachine_
-signalDetector_
-smaccStateMachine_
-statusPub_
processor_handle
thread
ExecutionModel
vector< smacc2::ISmaccUpdatable * >
vector< std::vector < smacc2::ISmaccUpdatable * > >
double
atomic< bool >
SmaccFifoScheduler *
-processorHandle_
-signalDetectorThread_
-executionModel_
-updatableClients_
-updatableStateElements_
kDefaultLoopRateHz -kInitializationPollRateHz -loop_rate_hz
-end_ -initialized_ -rosInitialized_
-scheduler_
smacc2::SignalDetector
+ SignalDetector()
+ initialize()
+ setProcessorHandle()
+ runThread()
+ join()
+ stop()
+ terminateScheduler()
+ joinAsyncClientBehaviorThreads()
+ pollingLoop()
+ postEvent()
+ queueWorkItem()
+ getNode()
+ getLogger()
+ notifyStateConfigured()
+ notifyStateExited()
+ notifyRosInitialized()
- pollOnce()
- findUpdatableClientsAndComponents()
- findUpdatableStateElements()
boost::signals2::signal < Signature, optional _last_value< typename boost ::function_traits< Signature >::result_type >, int, std ::less< int >, function< Signature >, typename extended_signature< function_traits< Signature >::arity, Signature >::function_type, boost:: signals2::mutex >
smacc2::ISmaccOrthogonal
+ ~ISmaccOrthogonal()
+ setStateMachine()
+ getStateMachine()
+ initState()
+ addClientBehavior()
+ runtimeConfigure()
+ onEntry()
+ onExit()
+ onDispose()
+ getName()
+ requiresComponent()
+ requiresClient()
+ getClients()
+ getClientBehaviors()
+ setGlobalSMData()
+ getGlobalSMData()
+ getClientBehavior()
+ getNode()
+ getLogger()
# onInitialize()
# initializeClients()
# assignClientToOrthogonal()
- currentClientBehaviors()
map< smacc2::ComponentKey, std::shared_ptr< smacc2 ::ISmaccComponent > >
-stateMachine_
-orthogonal_
#components_
smacc2::ISmaccClient
+ ISmaccClient()
+ ~ISmaccClient()
+ onInitialize()
+ getName()
+ getComponent()
+ getComponent()
+ getComponent()
+ getType()
+ getStateMachine()
+ connectSignal()
+ requiresClient()
+ getComponents()
+ iterateComponents()
+ postEvent()
+ postEvent()
# onComponentInitialization()
# onStateOrthogonalAllocation()
# createComponent()
# createNamedComponent()
# getNode()
# getLogger()
- initialize()
- setStateMachine()
- setOrthogonal()
#stateMachine_
-sub_
boost::signals2::signal < void(const AprilTagDetection Array::SharedPtr &), optional _last_value< typename boost:: function_traits< void(const AprilTagDetection Array::SharedPtr &)>::result_type >, int, std::less< int >, function< void(const AprilTagDetectionArray::SharedPtr &)>, typename extended_signature< function_traits< void(const AprilTagDetectionArray::SharedPtr &)>::arity, void (const AprilTagDetectionArray::SharedPtr &)>::function _type, boost::signals2::mutex >
smacc2::SmaccSignal < Signature, Combiner, Group, GroupCompare, SlotFunction, ExtendedSlotFunction, Mutex >
boost::signals2::signal < void(const MessageType &), optional_last_value < typename boost::function _traits< void(const MessageType &)>::result_type >, int, std ::less< int >, function< void(const MessageType &)>, typename extended _signature< function_traits< void(const MessageType &)>::arity, void(const MessageType &)>::function_type, boost::signals2::mutex >
boost::signals2::signal < void(const AprilTagDetection Array &), optional_last_value < typename boost::function_traits < void(const AprilTagDetectionArray &)>::result_type >, int, std::less < int >, function< void(const AprilTagDetection Array &)>, typename extended_signature< function _traits< void(const AprilTagDetectionArray &)> ::arity, void(const AprilTagDetectionArray &)> ::function_type, boost::signals2::mutex >
< void(const AprilTagDetection Array::SharedPtr &)>
< void(const MessageType &)>
< void(const AprilTagDetection Array &)>
#owner_
-mutex_
smacc2::ISmaccComponent
+ ISmaccComponent()
+ ~ISmaccComponent()
+ getName()
# onInitialize()
# onComponentInitialization()
# postEvent()
# postEvent()
# onStateOrthogonalAllocation()
# requiresComponent()
# requiresComponent()
# requiresClient()
# createSiblingComponent()
# createSiblingNamedComponent()
# getNode()
# getLogger()
# getStateMachine()
- initialize()
- setStateMachine()
#m_mutex_
#markerPublisher_
smacc2::SmaccSignal < void(const AprilTagDetection Array::SharedPtr &)>
string
SharedPtr
smacc2::SmaccSignal < void(const MessageType &)>
function< void(const MessageType &)>
bool
optional< int >
smacc2::SmaccSignal < void(const AprilTagDetection Array &)>
-topicName_
-sub_
+onFirstMessageReceived
+onMessageReceived_
+postInitialMessageEvent
+postMessageEvent
-firstMessage_ -initialized_
+queueSize
smacc2::client_core _components::CpTopicSubscriber < MessageType >
+ CpTopicSubscriber()
+ CpTopicSubscriber()
+ ~CpTopicSubscriber()
+ onMessageReceived()
+ onFirstMessageReceived()
+ onStateOrthogonalAllocation()
+ onInitialize()
- messageCallback()
-topicName_
-firstMessage_ -initialized_
+queueSize
+onFirstMessageReceived
+onMessageReceived_
function< void(const AprilTagDetectionArray &)>
+onAprilTagDetection_
-targetFrame_
< AprilTagDetectionArray >
+postInitialMessageEvent
+postMessageEvent
smacc2::client_core _components::CpTopicSubscriber < AprilTagDetectionArray >
+ CpTopicSubscriber()
+ CpTopicSubscriber()
+ ~CpTopicSubscriber()
+ onMessageReceived()
+ onFirstMessageReceived()
+ onStateOrthogonalAllocation()
+ onInitialize()
- messageCallback()
optional< rclcpp::Duration >
optional< rclcpp::Time >
shared_ptr< tf2_ros ::Buffer >
shared_ptr< tf2_ros ::TransformListener >
map< std::string, geometry _msgs::msg::PoseStamped >
-periodDuration_
-lastUpdate_
-tfBuffer_
-tfListener_
-detectedAprilTagsMapPose_
-topicSubscriber_
smacc2::ISmaccUpdatable
+ ISmaccUpdatable()
+ ISmaccUpdatable()
+ ~ISmaccUpdatable()
+ executeUpdate()
+ setUpdatePeriod()
# update()
cl_isaac_apriltag:: CpAprilTagTracker
+ CpAprilTagTracker()
+ ~CpAprilTagTracker()
+ onInitialize()
+ onComponentInitialization()
+ getTagsWithinTime()
+ getTagPose()
+ onAprilTagDetected()
- onAprilTagMessage()
#tracker_
optional< tf2::Transform >
#globalAprilTagTransform_
cl_isaac_apriltag:: CpAprilTagVisualization
+ CpAprilTagVisualization()
+ ~CpAprilTagVisualization()
+ onInitialize()
+ getGlobalAprilTagTransform()
+ computeAggregatedMarker()
+ update()