cl_px4_mr::CbFollowNedPath
+ CbFollowNedPath()
+ setPath()
+ path()
+ reachedCount()
# buildPath()
# behaviorName()
cl_px4_mr::CbPx4PathFollowerBase
+ CbPx4PathFollowerBase()
+ ~CbPx4PathFollowerBase()
+ onStateOrthogonalAllocation()
+ setFollowerParams()
+ followerParams()
+ onEntry()
+ onExit()
+ update()
# buildPath()
# behaviorName()
# onPathStarted()
# onPathCompleted()
# totalLength()
# progressFraction()
# carrotVertexIndex()
- commandFor()
- applyCentering()
- tangentYawAt()
atomic< size_t >
-cumLen_
-carrotVertex_
cl_px4_mr::CbPx4ClientBehaviorBase
+ onStateOrthogonalAllocation()
+ ~CbPx4ClientBehaviorBase()
+ setTimeout()
+ hasTimeout()
+ update()
# wireCompletionSignals()
# postPx4Success()
# postPx4Failure()
optional< std::chrono ::steady_clock::time _point >
-watchdogStart_
#goalChecker_
cl_px4_mr::CpTunnelCentering
+ CpTunnelCentering()
+ ~CpTunnelCentering()
+ onInitialize()
+ lateralOffsetM()
+ verticalOffsetM()
+ valid()
+ leftWallM()
+ rightWallM()
+ floorM()
+ ceilingM()
+ params()
- onCloud()
- onAttitude()
-params_
-subscriber_
#tunnelCentering_
smacc2::ISmaccStateMachine
smacc2::introspection::SmaccStateInfo
smacc2::ISmaccState
smacc2::ISmaccOrthogonal
smacc2::ISmaccClient
smacc2::ISmaccClientBehavior
smacc2::ISmaccComponent
smacc2::SignalDetector
smacc2::SmaccSignal
smacc2::ISmaccUpdatable
smacc2::SmaccAsyncClientBehavior
cl_px4_mr::CpVehicleLocalPosition
cl_px4_mr::CpVehicleStatus
cl_px4_mr::CpVehicleCommand
cl_px4_mr::MapProjection
cl_px4_mr::CpTrajectorySetpoint
cl_px4_mr::CpGoalChecker
cl_px4_mr::CpOffboardKeepAlive
cl_px4_mr::TunnelCenteringParams
cl_px4_mr::PathFollowerParams
cl_px4_mr::NedPoint
smacc2::client_core_components::CpTopicSubscriber< MessageType >
smacc2::client_core_components::CpTopicSubscriber< sensor_msgs::msg::PointCloud2 >
TrajectorySetpoint
string
mutex
SharedPtr
bool
float
double
int
uint64_t
uint8_t
YawMode
atomic< bool >
atomic< float >
atomic< int64_t >
array< float, 4 >
time_point
vector< float >
vector< cl_px4_mr::NedPoint >
-path_