map< void *, std::shared
_ptr< smacc2::CallbackCounterSemaphore > >

map< std::string, std
::pair< std::function
< std::string()>, boost
::any > >

vector< smacc2_msgs
::msg::SmaccTransitionLogEntry >

SMRunMode

int64_t

vector< smacc2::ISmaccState * >

SharedPtr

SmaccStatus

map< std::string, std
::shared_ptr< smacc2
::ISmaccOrthogonal > >

recursive_mutex

atomic< StateMachineInternal
Action >

shared_ptr< smacc2
::introspection::SmaccState
Info >

SharedPtr

SharedPtr

shared_ptr< smacc2
::introspection::SmaccState
MachineInfo >

map< const std::type
_info *, std::vector
< std::shared_ptr< smacc2
::introspection::SmaccEventGenerator
Info > > >

int

vector< smacc2::introspection
::SmaccTransitionInfo >

vector< std::shared
_ptr< smacc2::introspection
::SmaccStateInfo > >

type_info *

std::enable_shared
_from_this< SmaccStateInfo >

map< const std::type
_info *, std::vector
< smacc2::introspection
::ClientBehaviorInfoEntry > >

map< const std::type
_info *, std::vector
< std::shared_ptr< smacc2
::introspection::SmaccStateReactor
Info > > >

string

-stateCallbackConnections

-globalData_

-transitionLogHistory_

-runMode_

-stateSeqCounter_

#currentState_

#timer_

#status_msg_

#orthogonals_

-eventQueueMutex_
-m_mutex_

-stateMachineCurrentAction

#currentStateInfo_

#nh_

+parentState_

#eventsLogPub_
#stateMachinePub

#stateMachineStatus
Pub_
#transitionHistory
Service_
#transitionLogPub_

#stateMachineInfo_

+stateMachine_

+eventGeneratorsInfo

+depth_
+stateIndex_

+transitions_

+children_

+tid_

+staticBehaviorInfo

+stateReactorsInfo

+demangledStateName
+fullStateName

smacc2::ISmaccStateMachine

+ ISmaccStateMachine()
+ ~ISmaccStateMachine()
+ reset()
+ stop()
+ eStop()
+ getOrthogonal()
+ getClientBehavior()
+ getOrthogonals()
+ requiresComponent()
+ requiresComponent()
+ postEvent()
+ postEvent()
+ getGlobalSMData()
+ setGlobalSMData()
+ getStateMachineName()
+ state_machine_visualization()
+ getCurrentStateInfo()
+ publishTransition()
+ onInitialize()
+ getTransitionLogHistory()
+ createSignalConnection()
+ disconnectSmaccSignalObject()
+ disconnectSmaccSignalObject()
+ notifyOnStateEntryStart()
+ notifyOnStateEntryEnd()
+ notifyOnRuntimeConfigured()
+ notifyOnStateExiting()
+ notifyOnStateExited()
+ notifyOnRuntimeConfiguration
Finished()
+ getCurrentStateCounter()
+ getCurrentState()
+ getStateMachineInfo()
+ buildStateMachineInfo()
+ getNode()
+ getLogger()
+ getMutex()
# checkStateMachineConsistence()
# initializeROS()
# onInitialized()
# createOrthogonal()
- lockStateMachine()
- unlockStateMachine()
- propagateEventToStateReactors()
- updateStatusMessage()

smacc2::introspection
::SmaccStateInfo

+ SmaccStateInfo()
+ getStateLevel()
+ depth()
+ getAncestors()
+ getFullPath()
+ createChildState()
+ declareTransition()
+ toShortName()
+ getDemangledFullName()
+ getNode()
+ getLogger()

vector< std::vector
< std::shared_ptr< smacc2
::ISmaccClientBehavior > > >

mutex

vector< std::shared
_ptr< smacc2::ISmaccClient > >

shared_ptr< rclcpp
::Logger >

vector< std::shared
_ptr< smacc2::StateReactor > >

vector< std::shared
_ptr< smacc2::SmaccEventGenerator > >

#node_

atomic< bool >

-statusPub_

vector< smacc2::ISmaccUpdatable * >

vector< std::vector
< smacc2::ISmaccUpdatable * > >

atomic< int64_t >

double

SmaccFifoScheduler *

processor_handle

thread

ExecutionModel

-clientBehaviors_

-mutex_

#clients_

-stateMachine_

#logger_

#stateReactors_

#eventGenerators_

-signalDetector_

#stateInfo_

-smaccStateMachine_

-end_
-initialized_
-rosInitialized_

-updatableClients_

-updatableStateElements_

-lastState_

-loop_rate_hz

-scheduler_

-processorHandle_

-signalDetectorThread_

-executionModel_

smacc2::ISmaccState

+ getStateMachine()
+ getName()
+ getParentState()
+ getNode()
+ getLogger()
+ getClassName()
+ configure()
+ requiresComponent()
+ requiresClient()
+ getGlobalSMData()
+ setGlobalSMData()
+ createStateReactor()
+ createStateReactor()
+ createEventGenerator()
+ postEvent()
+ postEvent()
+ notifyTransition()
+ notifyTransitionFromTransition
TypeInfo()
+ getStateReactors()
+ getEventGenerators()
+ getOrthogonal()
+ getClientBehavior()
+ getEventGenerator()
+ getStateReactor()

smacc2::SignalDetector

+ SignalDetector()
+ initialize()
+ setProcessorHandle()
+ runThread()
+ join()
+ stop()
+ terminateScheduler()
+ pollingLoop()
+ postEvent()
+ getNode()
+ getLogger()
+ notifyStateConfigured()
+ notifyStateExited()
+ notifyRosInitialized()
- pollOnce()
- findUpdatableClientsAndComponents()
- findUpdatableStateElements()

smacc2::ISmaccOrthogonal

+ setStateMachine()
+ getStateMachine()
+ initState()
+ addClientBehavior()
+ runtimeConfigure()
+ onEntry()
+ onExit()
+ onDispose()
+ getName()
+ requiresComponent()
+ requiresClient()
+ getClients()
+ getClientBehaviors()
+ setGlobalSMData()
+ getGlobalSMData()
+ getClientBehavior()
+ getNode()
+ getLogger()
# onInitialize()
# initializeClients()
# assignClientToOrthogonal()

map< smacc2::ComponentKey,
std::shared_ptr< smacc2
::ISmaccComponent > >

boost::signals2::signal
< Signature, optional
_last_value< typename boost
::function_traits< Signature
>::result_type >, int, std
::less< int >, function< Signature
>, typename extended_signature<
function_traits< Signature >::arity,
Signature >::function_type, boost::
signals2::mutex >

-stateMachine_

-stateMachine_

#parentState_

#components_

#orthogonal_

-currentOrthogonal

#stateMachine_

-currentState

smacc2::ISmaccClient

+ ISmaccClient()
+ ~ISmaccClient()
+ onInitialize()
+ getName()
+ getComponent()
+ getComponent()
+ getComponent()
+ getType()
+ getStateMachine()
+ connectSignal()
+ requiresClient()
+ getComponents()
+ iterateComponents()
+ postEvent()
+ postEvent()
# onComponentInitialization()
# onStateOrthogonalAllocation()
# createComponent()
# createNamedComponent()
# getNode()
# getLogger()
- initialize()
- setStateMachine()
- setOrthogonal()

smacc2::ISmaccClientBehavior

+ ISmaccClientBehavior()
+ ~ISmaccClientBehavior()
+ getStateMachine()
+ getName()
+ requiresClient()
+ requiresComponent()
+ requiresComponent()
+ onEntry()
+ onExit()
+ executeOnEntry()
+ executeOnExit()
# runtimeConfigure()
# postEvent()
# postEvent()
# getCurrentState()
# dispose()
# getNode()
# getLogger()
- onStateOrthogonalAllocation()

-isShutdownRequested_

boost::signals2::signal
< void(), optional_last
_value< typename boost::
function_traits< void()>
::result_type >, int, std
::less< int >, function< void
()>, typename extended_signature
< function_traits< void()>::arity,
void()>::function_type, boost::signals2::mutex >

smacc2::SmaccSignal
< Signature, Combiner,
Group, GroupCompare,
SlotFunction, ExtendedSlotFunction,
Mutex >

< void()>

#owner_

smacc2::ISmaccComponent

+ ISmaccComponent()
+ ~ISmaccComponent()
+ getName()
# onInitialize()
# onComponentInitialization()
# postEvent()
# postEvent()
# onStateOrthogonalAllocation()
# requiresComponent()
# requiresComponent()
# requiresClient()
# createSiblingComponent()
# createSiblingNamedComponent()
# getNode()
# getLogger()
# getStateMachine()
- initialize()
- setStateMachine()

shared_ptr< moveit
::planning_interface
::PlanningSceneInterface >

Options

shared_ptr< moveit
::planning_interface
::MoveGroupInterface >

smacc2::SmaccSignal
< void()>

function< void()>

vector< cl_moveit2z
::TrajectoryHistoryEntry >

optional< std::future
< int > >

+planningSceneInterface

-options_

+moveGroupClientInterface

-onFailed_
-onSucceeded_

-postEventMotionExecution
Failed_
-postEventMotionExecution
Succeeded_

-onFailure_
-onFinished_
-onSuccess_

-trajectoryHistory_

-postFailureEventFn_

-postFinishEventFn_

-postSuccessEventFn_

smacc2::SmaccAsyncClient
Behavior

+ onStateOrthogonalAllocation()
+ ~SmaccAsyncClientBehavior()
+ onSuccess()
+ onFinished()
+ onFailure()
+ requestForceFinish()
+ executeOnEntry()
+ executeOnExit()
+ waitOnEntryThread()
+ onSuccess()
+ onFinished()
+ onFailure()
# postSuccessEvent()
# postFailureEvent()
# dispose()
# isShutdownRequested()
- waitFutureIfNotFinished()

-onEntryThread_
-onExitThread_

-config_path_
-tPkg_

cl_moveit2z::CpMoveGroup
Interface

+ CpMoveGroupInterface()
+ onInitialize()
+ onStateOrthogonalAllocation()
+ postEventMotionExecution
Succeeded()
+ postEventMotionExecution
Failed()
+ onMotionExecutionSucceeded()
+ onMotionExecutionFailed()

cl_moveit2z::CpTrajectory
History

+ getLastTrajectory()
+ getLastTrajectory()
+ pushTrajectory()

-cpMoveGroupInterface_

-cpMoveGroupInterface_

-trajectoryHistory_

cl_moveit2z::CpMotionPlanner

+ CpMotionPlanner()
+ ~CpMotionPlanner()
+ onInitialize()
+ planToPose()
+ planToJointTarget()
+ planCartesianPath()
+ getCurrentState()
- applyPlanningOptions()

cl_moveit2z::CpTrajectory
Executor

+ CpTrajectoryExecutor()
+ ~CpTrajectoryExecutor()
+ onInitialize()
+ execute()
+ executePlan()
+ cancel()
+ getTrajectoryHistory()
- applyExecutionOptions()
- recordToHistory()

#cpMoveGroup_

#cpMotionPlanner_

#cpTrajectoryExecutor_

#cpTrajectoryHistory_

cl_moveit2z::CbMoveit2zClient
BehaviorBase

+ onStateOrthogonalAllocation()
+ ~CbMoveit2zClientBehavior
Base()
# postMotionSuccess()
# postMotionFailure()

optional< double >

map< std::string, double >

optional< std::string >

+scallingFactor_

+jointValueTarget_

+group_

cl_moveit2z::CbMoveJoints

+ CbMoveJoints()
+ CbMoveJoints()
+ onEntry()
+ onExit()
# moveJoints()
# currentJointStatesToString()

cl_moveit2z::CbMoveKnown
State

+ CbMoveKnownState()
+ ~CbMoveKnownState()
+ onEntry()
- loadJointStatesFromFile()