map< const std::type
_info *, std::vector
< std::shared_ptr< smacc2
::introspection::SmaccEventGenerator
Info > > >

int

vector< smacc2::introspection
::SmaccTransitionInfo >

vector< std::shared
_ptr< smacc2::introspection
::SmaccStateInfo > >

type_info *

std::smatic_shared
_from_this< SmaccStateInfo >

map< const std::type
_info *, std::vector
< smacc2::introspection
::ClientBehaviorInfoEntry > >

map< const std::type
_info *, std::vector
< std::shared_ptr< smacc2
::introspection::SmaccStateReactor
Info > > >

shared_ptr< smacc2
::introspection::SmaccState
Info >

shared_ptr< smacc2
::introspection::SmaccState
MachineInfo >

vector< smacc2::ISmaccState * >

SmaccStatus

map< std::string, std
::shared_ptr< smacc2
::ISmaccOrthogonal > >

recursive_mutex

StateMachineInternalAction

map< void *, std::shared
_ptr< smacc2::CallbackCounterSemaphore > >

map< std::string, std
::pair< std::function
< std::string()>, boost
::any > >

vector< smacc2_msgs
::msg::SmaccTransitionLogEntry >

SMRunMode

int64_t

SharedPtr

string

SharedPtr

SharedPtr

smacc2::ISmaccStateMachine

+ ISmaccStateMachine()
+ ~ISmaccStateMachine()
+ reset()
+ stop()
+ eStop()
+ getOrthogonal()
+ getClientBehavior()
+ getOrthogonals()
+ requiresComponent()
+ postEvent()
+ postEvent()
+ getGlobalSMData()
+ setGlobalSMData()
+ getStateMachineName()
+ state_machine_visualization()
+ getCurrentStateInfo()
+ publishTransition()
+ onInitialize()
+ getTransitionLogHistory()
+ createSignalConnection()
+ disconnectSmaccSignalObject()
+ notifyOnStateEntryStart()
+ notifyOnStateEntryEnd()
+ notifyOnRuntimeConfigured()
+ notifyOnStateExiting()
+ notifyOnStateExited()
+ notifyOnRuntimeConfiguration
Finished()
+ getCurrentStateCounter()
+ getCurrentState()
+ getStateMachineInfo()
+ buildStateMachineInfo()
+ getNode()
+ getLogger()
+ getMutex()
# checkStateMachineConsistence()
# initiateRTOS()
# onInitialized()
# createOrthogonal()
- lockStateMachine()
- unlockStateMachine()
- propagateEventToStateReactors()
- updateStatusMessage()

smacc2::introspection
::SmaccStateInfo

+ SmaccStateInfo()
+ getStateLevel()
+ depth()
+ getAncestors()
+ getFullPath()
+ createChildState()
+ declareTransition()
+ toShortName()
+ getDemangledFullName()
+ getNode()
+ getLogger()

vector< std::vector
< std::shared_ptr< smacc2
::ISmaccClientBehavior > > >

vector< std::shared
_ptr< smacc2::ISmaccClient > >

mutex

shared_ptr< rclcpp
::Logger >

vector< std::shared
_ptr< smacc2::StateReactor > >

vector< std::shared
_ptr< smacc2::SmaccEventGenerator > >

double

thread

ExecutionMode

vector< smacc2::ISmaccUpdatable * >

vector< std::vector
< smacc2::ISmaccUpdatable * > >

atomic< int64_t >

atomic< bool >

SmaccFifoScheduler *

processor_handle

smacc2::ISmaccState

+ getStateMachine()
+ getName()
+ getParentState()
+ getNode()
+ getLogger()
+ getClassName()
+ configure()
+ requiresComponent()
+ requiresClient()
+ getGlobalSMData()
+ setGlobalSMData()
+ createStateReactor()
+ createStateReactor()
+ createEventGenerator()
+ postEvent()
+ postEvent()
+ notifyTransition()
+ notifyTransitionFromTransition
Type(info)
+ getStateReactors()
+ getEventGenerators()
+ getOrthogonal()
+ getClientBehavior()
+ getEventGenerator()
+ getStateReactor()

smacc2::ISmaccOrthogonal

+ setStateMachine()
+ getStateMachine()
+ initState()
+ addClientBehavior()
+ runtimeConfigure()
+ onEntry()
+ onExit()
+ onDispose()
+ getName()
+ requiresComponent()
+ requiresClient()
+ getClients()
+ getClientBehaviors()
+ setGlobalSMData()
+ getGlobalSMData()
+ getClientBehavior()
+ getNode()
+ getLogger()
# onInitialize()
# initializeClients()
# assignClientToOrthogonal()

map< smacc2::ComponentKey,
std::shared_ptr< smacc2
::ISmaccComponent > >

smacc2::SignalDetector

+ SignalDetector()
+ initialize()
+ setProcessorHandle()
+ runThread()
+ join()
+ stop()
+ terminateScheduler()
+ pollingLoop()
+ postEvent()
+ getNode()
+ getLogger()
+ notifyStateConfigured()
+ notifyStateExited()
+ notifyRosInitialized()
- pollOnce()
- findUpdatableClientsAndComponents()
- findUpdatableStateElements()

boost::signals2::signal
< Signature, optional
_last_value< typename boost
::function_traits< Signature
>::result_type >, int, std
::less< int >, function< Signature
>, typename extended_signature<
function_traits< Signature >::arity,
Signature > >function_type, boost::
signals2::mutex >

smacc2::ISmaccClientBehavior

+ ISmaccClientBehavior()
+ ~ISmaccClientBehavior()
+ getStateMachine()
+ getName()
+ requiresClient()
+ requiresComponent()
+ onEntry()
+ onExit()
+ executeOnEntry()
+ executeOnExit()
+ runtimeConfigure()
# postEvent()
# postEvent()
# getCurrentState()
# dispose()
# getNode()
# getLogger()
- onStateOrthogonalAllocation()

smacc2::ISmaccClient

+ ISmaccClient()
+ ~ISmaccClient()
+ onInitialize()
+ getName()
+ getComponent()
+ getComponent()
+ getComponent()
+ getType()
+ getStateMachine()
+ connectSignal()
+ requiresClient()
+ getComponents()
+ iterateComponents()
+ postEvent()
+ postEvent()
# onComponentInitialization()
# onStateOrthogonalAllocation()
# createComponent()
# createNamedComponent()
# getNode()
# getLogger()
- initialize()
- setStateMachine()
- setOrthogonal()

optional< rclcpp::Duration >

optional< rclcpp::Time >

smacc2::ISmaccUpdatable

+ ISmaccUpdatable()
+ ISmaccUpdatable()
+ executeUpdate()
+ setUpdatePeriod()
# update()

PoseStamped

shared_ptr< tf2_ros
::Buffer >

shared_ptr< tf2_ros
::TransformListener >

mutex

boost::signals2::signal
< void()const Feedback
&,i, optional_last_value
< typename boost::function
_traits< void()const Feedback
&,i>::result_type >, int, std
::less< int >, function< void
(const Feedback &,i>, typename extended
_signature< function_traits< void()const
Feedback &,i>::arity, void()const Feedback
&,i>::function_type, boost::signals2::mutex >

smacc2::SmaccSignal
< Signature, Combiner,
Group, GroupCompare,
SlotFunction, ExtendedSlotFunction,
Mutex >

boost::signals2::signal
< void(), optional_last
_value< typename boost::
function_traits< void()>
::result_type >, int, std
::less< int >, function< void
()>, typename extended_signature
< function_traits< void()>::arity,
void()>::function_type, boost::signals2::mutex >

boost::signals2::signal
< void(const WrappedResult
&),i, optional_last_value
< typename boost::function
_traits< void()const WrappedResult
&,i>::result_type >, int, std
::less< int >, function< void()const
WrappedResult &,i>, typename extended
_signature< function_traits< void()const
WrappedResult &,i>::arity, void()const WrappedResult
&,i>::function_type, boost::signals2::mutex >

optional< std::string >

optional< std::chrono
::milliseconds >

smacc2::SmaccSignal
< void(const Feedback &)>

function< void(const
Feedback &)>

smacc2::SmaccSignal
< void()>

smacc2::SmaccSignal
< void(const WrappedResult &)>

optional< std::shared
_future< typename rclcpp
_action::Client< ActionType
>::CancelResponse::SharedPtr > >

shared_ptr< ActionClient >

function< void(const
WrappedResult &)>

CpActionClient< ActionType >

optional< std::shared
_future< typename rclcpp_action
::ClientGoalHandle
< ISharedPtr > > >

FeedbackCallback

function< void()>

optional< std::future
< tf1 > >

bool

smacc2::ISmaccComponent

+ ISmaccComponent()
+ ~ISmaccComponent()
+ getName()
# onInitialize()
# onComponentInitialization()
# postEvent()
# postEvent()
# getStateOrthogonalAllocation()
# requiresComponent()
# requiresClient()
# requiresClient()
# createSiblingComponent()
# createSiblingNamesComponent()
# getNode()
# get_logger()
# getStateMachine()
- initialize()
- setStateMachine()

smacc2::client_core
_components::CpActionClient
< ActionType >

+ CpActionClient()
+ CpActionClient()
+ ~CpActionClient()
+ sendGoal()
+ cancelGoal()
+ isServerReady()
+ waitForServer()
+ onInitialize()
+ onComponentInitialization()
+ onSucceeded()
+ onAborted()
+ onCancelled()
+ onFeedback()
+ getActionClient()
- onFeedback()
- onResult()
- postResultEvent()

cl_navl2z::components
::CpNavActionInterface

+ CpNavActionInterface()
+ ~CpNavActionInterface()
+ sendNavigationGoal()
+ sendGoal()
+ cancelNavigation()
+ isNavigationServerReady()
+ waitForNavigationServer()
+ onComponentInitialization()
+ onInitialize()
+ getActionClient()
+ onNavigationSucceeded()
+ onNavigationAborted()
+ onNavigationCancelled()
+ onNavigationFeedback()
- onNavigationSuccessCallback()
- onNavigationAbortedCallback()
- onNavigationCancelledCallback()
- onNavigationFeedbackCallback()

optional< std::shared
_future< typename rclcpp
_action::Client< nav2_msgs
::action::NavigateToPose >
::CancelResponse::SharedPtr > >

smacc2::SmaccAsyncClient
Behavior

+ onStateOrthogonalAllocation()
+ ~SmaccAsyncClientBehavior()
+ onSuccess()
+ onFinished()
+ onFailure()
+ requestForcePreempt()
+ executeOnEntry()
+ executeOnExit()
+ waitOnEntryThread()
+ onSuccess()
+ onFinished()
+ onFailure()
# postSuccessEvent()
# postFailureEvent()
# dispose()
# isShutdownRequested()
- waitFutureIfNotFinished()

cl_nav2z::CpPose

+ CpPose()
+ CpPose()
+ onInitialize()
+ update()
+ waitTransformUpdate()
+ toPoseMsg()
+ toPoseStampedMsg()
+ getYaw()
+ getX()
+ getY()
+ getZ()
+ setReferenceFrame()
+ getReferenceFrame()
+ getFrameId()
+ freezeReferenceFrame()
+ unfreezeReferenceFrame()

Path

IWorkingMode

vector< nav_msgs::msg
::Path >

vector< cl_nav2z::odom
_tracker::CpOdomTracker
::PathInfo >

OdomTrackerStrategy

optional< geometry
_msgs::msg::PoseStamped >

cl_nav2z::odom_tracker
::CpOdomTracker

+ CpOdomTracker()
+ processNewPose()
+ odomMessageCallback()
+ update()
+ setWorkingMode()
+ setIfPublishMessages()
+ pushPath()
+ pushPath()
+ popPath()
+ clearPath()
+ setStartPoint()
+ setStartPoint()
+ setCurrentMotionGoal()
+ setCurrentPathName()
+ getCurrentMotionGoal()
+ getPath()
+ toglStateString()
+ updateParameters()
+ setOdomFrame()
# onInitialize()
# updateConfiguration()
# rtPublishPaths()
# updateRecordPath()
# updateClearPath()
# updateAggregatedStackPath()
# parametersCallback()

smacc2::client_core
_components::CpActionClient
< nav2_msgs::action::NavigateToPose >

+ CpActionClient()
+ CpActionClient()
+ ~CpActionClient()
+ sendGoal()
+ cancelGoal()
+ isServerReady()
+ waitForServer()
+ onInitialize()
+ onComponentInitialization()
+ onSucceeded()
+ onAborted()
+ onCancelled()
+ onFeedback()
+ getActionClient()
- onFeedback()
- onResult()
- postResultEvent()

ResultCode

cl_navl2z::ClNavl2ZClientBehaviorBase

+ ~ClNavl2ZClientBehaviorBase()
+ onStateOrthogonalAllocation()
# sendGoal()
# cancelGoal()
# onNavigationSucceeded()
# onNavigationAborted()
# onNavigationCancelled()
# onNavigationResult()
# onNavigationActionSuccess()
# onNavigationActionAbort()

float

optional< float >

cl_navl2z::ClNavigateBackwards

+ ClNavigateBackwards()
+ onEntry()
+ onExit()