

smacc2_client_library
/cl_nav2z/cl_nav2z/include
/cl_nav2z/client_behaviors
/cb_navigate_named_waypoint.hpp

```
graph BT; A["smacc2_client_library  
/cl_nav2z/cl_nav2z/include  
/cl_nav2z/client_behaviors  
/cb_navigate_named_waypoint.hpp"] --> B["smacc2_client_library  
/cl_nav2z/cl_nav2z/include  
/cl_nav2z/client_behaviors  
/cb_navigate_named_waypoint.cpp"]; A --> C["smacc2_client_library  
/cl_nav2z/cl_nav2z/src  
/cl_nav2z/client_behaviors  
/cb_navigate_named_waypoint.cpp"];
```

The diagram illustrates the compilation of two source files into a single library. At the top, a grey box represents the final library, containing the header file `/cb_navigate_named_waypoint.hpp`. Below it, two white boxes represent the source files: one with the header `/cl_nav2z/client_behaviors/cb_navigate_named_waypoint.hpp` and another with the source file `/cl_nav2z/client_behaviors/cb_navigate_named_waypoint.cpp`. Blue arrows point from each source file box to the library box, indicating that both are used to create the library.

smacc2_client_library
/cl_nav2z/cl_nav2z/include
/cl_nav2z/client_behaviors.hpp

smacc2_client_library
/cl_nav2z/cl_nav2z/src
/cl_nav2z/client_behaviors
/cb_navigate_named_waypoint.cpp