
string
weak_ptr< smacc2::introspection ::SmaccStateMachineInfo >
weak_ptr< smacc2::introspection ::SmaccStateInfo >
vector< smacc2::introspection ::SmaccTransitionInfo >
vector< std::shared _ptr< smacc2::introspection ::SmaccStateInfo* > >
type_info *
std::enable_shared _from_this< SmaccStateInfo >
map< const std::type _info *, std::vector < smacc2::introspection ::ClientBehaviorInfoEntry* > >
map< const std::type _info *, std::vector < std::shared_ptr< smacc2 ::introspection::SmaccStateReactor Info* > > >
map< const std::type _info *, std::vector < std::shared_ptr< smacc2 ::introspection::SmaccEventGenerator Info* > > >
int
SharedPtr
vector< smacc2_msgs ::msg::SmaccTransitionLogEntry >
SMRunMode
int64_t
SharedPtr
vector< smacc2::ISmaccState* >
shared_ptr< smacc2 ::introspection::SmaccState Info >
SmaccStatus
map< std::string, std ::shared_ptr< smacc2 ::ISmaccOrthogonal* > >
shared_ptr< smacc2 ::introspection::SmaccState MachineInfo >
recursive_mutex
atomic< StateMachineInternal Action >
map< void*, std::shared _ptr< smacc2::CallbackCounterSemaphore* > >
map< std::string, std ::pair< std::function< std::string()>, boost ::any* > >
SharedPtr
+demangledStateName +fullStateName
+stateMachine_
+parentState_
+transitions_
+children_
+id_
+staticBehaviorInfo
+stateReactorsInfo
+eventGeneratorsInfo
+depth_ +stateIndex_
#info_
-transitionLogHistory_
-runMode_
-stateSeqCounter_
#timer_
#currentState_
#currentStateInfo_
#status_msg_
#orthogonals_
#stateMachineInfo_
-eventQueueMutex_ -m_mutex_
-stateMachineCurrentAction
-stateCallbackConnections
-globalData_
#eventsLogPub_ #stateMachinePub_
#stateMachineStatus Pub_ #transitionHistory Service_ #transitionLogPub_
smacc2::ISmaccStateMachine
+ ISmaccStateMachine()
+ ~ISmaccStateMachine()
+ reset()
+ stop()
+ eStop()
+ joinAsyncClientBehaviorThreads()
+ getOrthogonal()
+ getClientBehavior()
+ getOrthogonals()
+ requiresComponent()
+ requiresComponent()
+ postEvent()
+ postEvent()
+ getGlobalSMData()
+ setGlobalSMData()
+ getStateMachineName()
+ state_machine_visualization()
+ getCurrentStateInfo()
+ publishTransition()
+ onInitialize()
+ getTransitionLogHistory()
+ createSignalConnections()
+ disconnectSmaccSignalObjects()
+ disconnectSmaccSignalObject()
+ notifyOnStateEntryStart()
+ notifyOnStateEntryEnd()
+ notifyOnRuntimeConfigured()
+ notifyOnStateExiting()
+ notifyOnStateExited()
+ notifyOnRuntimeConfiguration Finished()
+ getCurrentStateCounter()
+ getCurrentState()
+ getStateMachineInfo()
+ buildStateMachineInfo()
+ getNode()
+ getLogger()
+ getMutex()
# checkStateMachineConsistence()
# initializeROS()
# onInitialized()
# createOrthogonal()
- lockStateMachine()
- unlockStateMachine()
- propagateEventToStateReactors()
- updateStatusMessage()
smacc2::introspection ::SmaccStateInfo
+ SmaccStateInfo()
+ getStateLevel()
+ getStateMachineInfo()
+ getParentState()
+ depth()
+ getAncestors()
+ getFullPath()
+ createChildState()
+ declareTransition()
+ toShortName()
+ getDemangledFullName()
+ getNode()
+ getLogger()
vector< std::shared _ptr< smacc2::StateReactor* > >
vector< std::shared _ptr< smacc2::SmaccEventGenerator* > >
shared_ptr< rclcpp ::Logger >
#stateReactors_
#eventGenerators_
#stateInfo_
#logger_
smacc2::ISmaccState
+ ~ISmaccState()
+ getStateMachine()
+ getName()
+ getParentState()
+ getNode()
+ getLogger()
+ getClassName()
+ configure()
+ requiresComponent()
+ requiresComponent()
+ requiresClient()
+ getGlobalSMData()
+ setGlobalSMData()
+ createStateReactor()
+ createStateReactor()
+ createEventGenerator()
+ postEvent()
+ postEvent()
+ notifyTransition()
+ notifyTransitionFromTransition TypeInfo()
+ getStateReactors()
+ getEventGenerators()
+ getOrthogonal()
+ getClientBehavior()
+ getEventGenerator()
+ getStateReactor()
#parentState_
#node_
vector< std::shared _ptr< smacc2::ISmaccClient* > >
vector< std::vector < std::shared_ptr< smacc2 ::ISmaccClientBehavior* > > >
atomic< bool >
#clients_
-clientBehaviors_
#stateMachine_
-error_ -initialized_ -isInitializing_
-smaccStateMachine_
-signalDetector_
-signalDetectorThread_
-executionModel_
-updatableClients_
-updatableStateElements_
-lastState_
-scheduler_
-processorHandle_
-mutex_
-loop_rate_hz
thread
ExecutionModel
vector< smacc2::ISmaccUpdatable* > >
vector< std::vector < smacc2::ISmaccUpdatable* > > >
-statusPub_
atomic< int64_t >
SmaccFifoScheduler *
processor_handle
double
mutex
smacc2::ISmaccOrthogonal
+ ~ISmaccOrthogonal()
+ setStateMachine()
+ getStateMachine()
+ initState()
+ addClientBehavior()
+ runtimeConfigure()
+ onEntry()
+ onExit()
+ onDispose()
+ getName()
+ requiresComponent()
+ requiresClient()
+ getClients()
+ getClientBehaviors()
+ setGlobalSMData()
+ getGlobalSMData()
+ getClientBehavior()
+ getNode()
+ getLogger()
# onInitialize()
# initializeClients()
# assignClientToOrthogonal()
- currentClientBehaviors()
smacc2::SignalDetector
+ SignalDetector()
+ initialize()
+ setProcessorHandle()
+ runThread()
+ join()
+ stop()
+ terminateScheduler()
+ joinAsyncClientBehaviorThreads()
+ pollingLoop()
+ postEvent()
+ getNode()
+ getLogger()
+ notifyStateConfigured()
+ notifyStateExited()
+ notifyRosInitialized()
- pollOnce()
- findUpdatableClientsAndComponents()
- findUpdatableStateElements()
boost::signals2::signal < Signature, optional _last_value< typename boost ::function_traits< Signature >::result_type >, int, std ::less< int >, function< Signature >, typename extended_signature< function_traits< Signature >::arity, Signature >::function_type, boost:: signals2::mutex >
-stateMachine_
map< smacc2::ComponentKey, std::shared_ptr< smacc2 ::ISmaccComponent* > >
-stateMachine_
#currentState_
#currentOrthogonal
-orthogonal_
#stateMachine_
#components_
smacc2::ISmaccClientBehavior
+ ISmaccClientBehavior()
+ ~ISmaccClientBehavior()
+ getStateMachine()
+ getName()
+ requiresClient()
+ requiresComponent()
+ requiresComponent()
+ onEntry()
+ onExit()
+ executeOnEntry()
+ executeOnExit()
# runtimeConfigure()
# postEvent()
# postEvent()
# getCurrentState()
# dispose()
# getNode()
# getLogger()
- onStateOrthogonalAllocation()
smacc2::SmaccSignal < Signature, Combiner, Group, GroupCompare, SlotFunction, ExtendedSlotFunction, Mutex >
boost::signals2::signal < void(), optional_last _value< typename boost:: function_traits< void()> ::result_type >, int, std ::less< int >, function< void ()>, typename extended_signature < function_traits< void()>::arity, void()>::function_type, boost::signals2::mutex >
< void()>
smacc2::ISmaccClient
+ ISmaccClient()
+ ~ISmaccClient()
+ onInitialize()
+ getName()
+ getComponent()
+ getComponent()
+ getComponent()
+ getType()
+ getStateMachine()
+ connectSignal()
+ requiresClient()
+ getComponents()
+ iterateComponents()
+ postEvent()
+ postEvent()
# onComponentInitialization()
# onStateOrthogonalAllocation()
# createComponent()
# createNamedComponent()
# getNode()
# getLogger()
- initialize()
- setStateMachine()
- setOrthogonal()
#shutdownRequested_
#owner_
smacc2::ISmaccComponent
+ ISmaccComponent()
+ ~ISmaccComponent()
+ getName()
# onInitialize()
# onComponentInitialization()
# postEvent()
# postEvent()
# onStateOrthogonalAllocation()
# requiresComponent()
# requiresComponent()
# requiresClient()
# createSiblingComponent()
# createSiblingNamedComponent()
# getNode()
# getLogger()
# getStateMachine()
- initialize()
- setStateMachine()
-globalFrame_
-markerScale_ -publishRate_
-markersMutex_
-m_mutex_
optional< std::future < int > >
function< void()>
smacc2::SmaccSignal < void()>
Options
shared_ptr< moveit ::planning_interface ::MoveGroupInterface >
shared_ptr< moveit ::planning_interface ::PlanningSceneInterface >
vector< cl_moveit2z ::TrajectoryHistoryEntry >
mutex
shared_ptr< tf2_ros ::Buffer >
shared_ptr< tf2_ros ::TransformListener >
weak_ptr< tf2_ros:: Buffer >
weak_ptr< tf2_ros:: TransformListener >
optional< rclcpp::Time >
optional< rclcpp::Duration >
-onErrorThread_ -onExitThread_
-postFailureEventFn -postFinishEventFn -postSuccessEventFn_
-postEventMotionExecution Failed_ -postEventMotionExecution Succeeded_
-onFailure_ -onFinished_ -onSuccess_
-onFailed_ -onSucceeded_
-options_
+moveGroupClientInterface
+planningSceneInterface_
-trajectoryHistory_
-tfMutex_
-tfBuffer_
-tfListener_
-sharedTfBuffer_
-sharedTfListener_
-lastUpdate_
-periodDuration_
-m_mutex_
smacc2::SmaccAsyncClient Behavior
+ onStateOrthogonalAllocation()
+ ~SmaccAsyncClientBehavior()
+ onSuccess()
+ onFinished()
+ onFailure()
+ requestForceFinish()
+ executeOnEntry()
+ executeOnExit()
+ waitOnEntryThread()
+ onSuccess()
+ onFinished()
+ onFailure()
# postSuccessEvent()
# postFailureEvent()
# dispose()
# isShutdownRequested()
- waitFutureIfNotFinished()
cl_moveit2z::ClpMoveGroup Interface
+ ClpMoveGroupInterface()
+ onInitialize()
+ onStateOrthogonalAllocation()
+ postEventMotionExecution Succeeded()
+ postEventMotionExecution Failed()
+ onMotionExecutionSucceeded()
+ onMotionExecutionFailed()
cl_moveit2z::ClpTrajectory History
+ getLastTrajectory()
+ getLastTrajectory()
+ pushTrajectory()
SharedPtr
cl_moveit2z::ClpTfListener
+ ClpTfListener()
+ ~ClpTfListener()
+ onInitialize()
+ lookupTransform()
+ transformPose()
+ canTransform()
+ getBuffer()
float
Time
smacc2::ISmaccUpdatable
+ ISmaccUpdatable()
+ ISmaccUpdatable()
+ ~ISmaccUpdatable()
+ executeUpdate()
+ setUpdatePeriod()
# update()
MarkerArray
bool
-cpMoveGroupInterface_
-cpMoveGroupInterface_
-trajectoryHistory_
-cpMoveGroupInterface_
-tfClient_
-markersPub_
-markerColor_
-lastPublishTime_
-markers_
-enabled -markersReady_
cl_moveit2z::ClpMotionPlanner
+ ClpMotionPlanner()
+ ~ClpMotionPlanner()
+ onInitialize()
+ planToPose()
+ planToJointTarget()
+ planCartesianPath()
+ getCurrentState()
- applyPlanningOptions()
cl_moveit2z::ClpTrajectory Executor
+ ClpTrajectoryExecutor()
+ ~ClpTrajectoryExecutor()
+ onInitialize()
+ execute()
+ executePlan()
+ cancel()
+ getTrajectoryHistory()
- applyExecutionOptions()
- recordToHistory()
cl_moveit2z::ClpJointSpace TrajectoryPlanner
+ ClpJointSpaceTrajectoryPlanner()
+ ~ClpJointSpaceTrajectoryPlanner()
+ onInitialize()
+ planFromWaypoints()
cl_moveit2z::ClpTrajectory Visualizer
+ ClpTrajectoryVisualizer()
+ ~ClpTrajectoryVisualizer()
+ onInitialize()
+ update()
+ setTrajectory()
+ clearMarkers()
+ setColor()
+ setScale()
+ setEnabled()
+ isEnabled()
-tfClient_
-tfListener_
-markersPub_
-lastPublishTime_
#cpMoveGroup_
#cpMotionPlanner_
#cpTrajectoryHistory_
#cpTrajectoryExecutor_
#cpJointSpaceTrajectoryPlanner_
#cpTrajectoryVisualizer_
#beahviorMarkers_
-autoclearmarkers
-postMotionExecutionFailure Events
cl_moveit2z::ClbMoveit2zClient BehaviorBase
+ onStateOrthogonalAllocation()
+ ~ClbMoveit2zClientBehavior Base()
# postMotionSuccess()
# postMotionFailure()
optional< std::string >
optional< bool >
vector< geometry_msgs ::msg::PoseStamped >
function< void(moveit ::msgs::msg::RobotTrajectory &)>
-group_ -ptpLink_
+allowInitialTrajectoryState JointDiscontinuity_
#endEffectorTrajectory_
-postIncorrectInitialState Event -postJointDiscontinuity Event
cl_moveit2z::ClbMoveEndEffector Trajectory
+ ClbMoveEndEffectorTrajectory()
+ ClbMoveEndEffectorTrajectory()
+ onStateOrthogonalAllocation()
+ onEntry()
+ onExit()
# computeJointSpaceTrajectory()
# executeJointSpaceTrajectory()
# generateTrajectory()
# createMarkers()
# getCurrentEndEffectorPose()
- initializeROS()
Vector3
optional< double >
-offset_
+linearSpeed_m_s_
cl_moveit2z::ClbMoveCartesian Relativ2
+ ClbMoveCartesianRelativ2()
+ ClbMoveCartesianRelativ2()
+ ~ClbMoveCartesianRelativ2()
+ generateTrajectory()