seconds
string
optional< std::string >
vector< std::string >
int
+heartbeat_interval
+poll_interval
+gcalcli_path
+config_folder
+calendars
+agenda_days
+max_consecutive
_failures
atomic< StateMachineInternal
Action >
map< void *, std::shared
_ptr< smacc2::CallbackCounterSemaphore > >
vector< smacc2_msgs
::msg::SmaccTransitionLogEntry >
SMRunMode
int64_t
SharedPtr
SharedPtr
vector< smacc2::ISmaccState * >
shared_ptr< smacc2
::introspection::SmaccState
Info >
SmaccStatus
map< std::string, std
::pair< shared_ptr< smacc2
::ISmaccOrthogonal > >
shared_ptr< smacc2
::introspection::SmaccState
MachineInfo >
recursive_mutex
SharedPtr
-reactorWalkDepth_
-stateMachineCurrentAction
-stateCallbackConnections
-transitionLogHistory_
-runMode_
-stateSeqCounter_
#timer_
#hh_
#currentState_
#currentStateInfo_
#status_msg_
-globalData_
#orthogonals_
#stateMachineInfo_
-eventQueueMutex_
-m_mutex_
#eventsLogPub_
#stateMachineStatus
Pub_
#transitionHistory
Service_
#transitionLogPub_
smacc2::ISmaccStateMachine
+ ISmaccStateMachine()
+ ~ISmaccStateMachine()
+ reset()
+ stop()
+ eStop()
+ joinAsyncClientBehaviorThreads()
+ getOrthogonal()
+ getClientBehavior()
+ getOrthogonals()
+ requiresComponent()
+ requiresComponent()
+ postEvent()
+ postEvent()
+ getGlobalSMData()
+ setGlobalSMData()
+ getStateMachineName()
+ state_machine_visualization()
+ getCurrentStateInfo()
+ publishTransition()
+ onInitialize()
+ getTransitionLogHistory()
+ createSignalConnection()
+ disconnectSmaccSignalObject()
+ disconnectSmaccSignalObject()
+ notifyOnStateEntryStart()
+ notifyOnStateEntryEnd()
+ notifyOnRuntimeConfigured()
+ notifyOnStateExiting()
+ notifyOnStateExited()
+ notifyOnRuntimeConfiguration
Finished()
+ getCurrentStateCounter()
+ getCurrentState()
+ getStateMachineInfo()
+ buildStateMachineInfo()
+ getNode()
+ getLogger()
+ getMutex()
# checkStateMachineConsistence()
# initializeROS()
# onInitialized()
# createOrthogonal()
- lockStateMachine()
- unlockStateMachine()
- propagateEventToStateReactors()
- updateStatusMessage()
cl_gcalcli::GcalcliConfig
mutex
vector< std::vector
< std::shared_ptr< smacc2
::ISmaccClientBehavior > > >
vector< std::shared
_ptr< smacc2::ISmaccClient > >
vector< smacc2::ISmaccUpdatable * >
vector< std::vector
< smacc2::ISmaccUpdatable * > >
double
atomic< bool >
SmaccFifoScheduler *
processor_handle
thread
ExecutionModel
-statusPub_
-mutex_
-clientBehaviors_
#clients_
-stateMachine_
-smaccStateMachine_
-signalDetector_
-updatableClients_
-updatableStateElements_
-loop_rate_hz_
-end_
-initialized_
-rosInitialized_
-scheduler_
-processorHandle_
-signalDetectorThread_
-executionModel_
smacc2::ISmaccOrthogonal
+ ~ISmaccOrthogonal()
+ setStateMachine()
+ getStateMachine()
+ initState()
+ addClientBehavior()
+ runtimeConfigure()
+ onEntry()
+ onExit()
+ onDispose()
+ getName()
+ requiresComponent()
+ requiresClient()
+ getClients()
+ getClientBehaviors()
+ setGlobalSMData()
+ getGlobalSMData()
+ getClientBehavior()
+ getNode()
+ getLogger()
# onInitialize()
# initializeClients()
# assignClientToOrthogonal()
- currentClientBehaviors()
smacc2::SignalDetector
+ SignalDetector()
+ initialize()
+ setProcessorHandle()
+ runThread()
+ join()
+ stop()
+ terminateScheduler()
+ joinAsyncClientBehaviorThreads()
+ pollingLoop()
+ postEvent()
+ queueWorkItem()
+ getNode()
+ getLogger()
+ notifyStateConfigured()
+ notifyStateExited()
+ notifyPosInitialized()
- pollOnce()
- findUpdatableClientsAndComponents()
- findUpdatableStateElements()
boost::signals2::signal
< void(int exit_code,
const std::string &output)
, optional_last_value< typename
boost::function_traits< void
(int exit_code, const std::string
&output)>::result_type >, int, std
::less< int >, function< void(int exit
_code, const std::string &output)>, typename
extended_signature< function_traits< void
(int exit_code, const std::string &output)>
::arity, void(int exit_code, const std::string
&output)>::function_type, boost::signals2::mutex >
boost::signals2::signal
< void(const std::string
&error), optional_last
_value< typename boost::function
_traits< void(const std::string
&error)>::result_type >, int, std
::less< int >, function< void(const
std::string &error)>, typename extended
_signature< function_traits< void(const
std::string &error)>::arity, void(const
std::string &error)>::function_type, boost
::signals2::mutex >
smacc2::SmaccSignal
< Signature, Combiner,
Group, GroupCompare,
SlotFunction, ExtendedSlotFunction,
Mutex >
boost::signals2::signal
< void(), optional_last
_value< typename boost::
function_traits< void()>
::result_type >, int, std
::less< int >, function< void
()>, typename extended_signature
< function_traits< void()>::arity,
void()>::function_type, boost::signals2::mutex >
boost::signals2::signal
< void(const std::vector
< cl_gcalcli::CalendarEvent
> &), optional_last_value
< typename boost::function_traits
< void(const std::vector< cl_gcalcli
::CalendarEvent > &)>::result_type
>, int, std::less< int >, function
< void(const std::vector< cl_gcalcli
::CalendarEvent > &)>, typename extended
_signature< function_traits< void(const
std::vector< cl_gcalcli::CalendarEvent >
&)>::arity, void(const std::vector< cl_gcalcli
::CalendarEvent > &)>::function_type, boost::signals2::mutex >
-consecutive_failures_
-execution_mutex_
-config_
-events_mutex_
-state_mutex_
< void()>
< void(const std::vector
< cl_gcalcli::CalendarEvent > &)>
#owner_
< void(int exit_code,
const std::string &output)>
< void(const std::string
&error)>
smacc2::SmaccSignal
< void(int exit_code,
const std::string &output)>
smacc2::SmaccSignal
< void(const std::string
&error)>
smacc2::SmaccSignal
< void()>
smacc2::ISmaccComponent
+ ISmaccComponent()
+ ~ISmaccComponent()
+ getName()
# onInitialize()
# onComponentInitialization()
# postEvent()
# postEvent()
# onStateOrthogonalAllocation()
# requiresComponent()
# requiresComponent()
# requiresClient()
# createSiblingComponent()
# createSiblingNamedComponent()
# getNode()
# getLogger()
# getStateMachine()
- initialize()
- setStateMachine()
smacc2::SmaccSignal
< void(const std::vector
< cl_gcalcli::CalendarEvent > &)>
optional< rclcpp::Time >
optional< rclcpp::Duration >
bool
-lastUpdate_
-periodDuration_
-initialized_
+onCommandCompleted_
+onCommandFailed_
smacc2::ISmaccUpdatable
+ ISmaccUpdatable()
+ ISmaccUpdatable()
+ ~ISmaccUpdatable()
+ executeUpdate()
+ setUpdatePeriod()
# update()
smacc2::client_core
_components::CpSubprocessExecutor
+ CpSubprocessExecutor()
+ ~CpSubprocessExecutor()
+ onInitialize()
+ executeCommand()
+ executeCommandAsync()
+ onCommandCompleted()
+ onCommandFailed()
function< void()>
ConnectionState
-initialized_
+postAuthenticationRequired
Event_
+postConnectionLostEvent
+postConnectionRestored
Event_
-connection_state_
-subprocess_executor_
+onAuthenticationRequired
+onConnectionLost
+onConnectionRestored_
time_point
-last_heartbeat_time_
+onAgendaUpdated_
cl_gcalcli::CpGcalcliConnection
+ CpGcalcliConnection()
+ ~CpGcalcliConnection()
+ onInitialize()
+ configure()
+ getConnectionState()
+ isConnected()
+ checkConnection()
+ restartConnection()
+ executeGcalcli()
+ getConfig()
+ onConnectionLost()
+ onConnectionRestored()
+ onAuthenticationRequired()
+ onStateOrthogonalAllocation()
# update()
- performHeartbeat()
- handleConnectionStateChange()
- isAuthenticationError()
function< void(const
std::vector< cl_gcalcli
::CalendarEvent > &)>
vector< cl_gcalcli
::CalendarEvent >
time_point
-last_poll_attempt_
-connection_
+postAgendaUpdatedEvent_
-cached_events_
-last_poll_time_
cl_gcalcli::CpCalendarPoller
+ CpCalendarPoller()
+ ~CpCalendarPoller()
+ onInitialize()
+ refreshAgenda()
+ getEvents()
+ findEvents()
+ getEventsInWindow()
+ getActiveEvents()
+ getLastPollTime()
+ onAgendaUpdated()
+ onStateOrthogonalAllocation()
# update()
- parseTsvOutput()
- parseTsvLine()
- parseDateTime()
- generateEventId()