cl_px4_mr::CbSpiral
+ CbSpiral()
+ setParams()
+ params()
+ setCenter()
# buildPath()
# behaviorName()
cl_px4_mr::CbPx4PathFollowerBase
+ CbPx4PathFollowerBase()
+ ~CbPx4PathFollowerBase()
+ onStateOrthogonalAllocation()
+ setFollowerParams()
+ followerParams()
+ onEntry()
+ onExit()
+ update()
# buildPath()
# behaviorName()
# onPathStarted()
# onPathCompleted()
# totalLength()
# progressFraction()
# carrotVertexIndex()
- commandFor()
- applyCentering()
- tangentYawAt()
vector< cl_px4_mr::NedPoint >
vector< float >
atomic< size_t >
-path_
-cumLen_
-carrotVertex_
#tunnelCentering_
-lastUpdateTime_
cl_px4_mr::FlightPatternSpiralParams
cl_px4_mr::PathFollowerParams
cl_px4_mr::NedPoint
Turn
YawMode
float
function< void()>
optional< std::future< int > >
+direction
+inward
+yawMode
+prependCurrentPosition
+useTunnelCentering
+altitudeAgl
+centerX
+centerY
+endRadius
+sampleSpacing
+spacing
+startRadius
+arrivalXyTol
+arrivalZTol
+autoTimeoutFactor
+fixedYaw
+groundSpeed
+leash
+minSegmentLength
+x
+y
+yaw
+z
smacc2::SmaccAsyncClientBehavior
cl_px4_mr::MapProjection
cl_px4_mr::CpVehicleLocalPosition
cl_px4_mr::CpTrajectorySetpoint
TrajectorySetpoint
smacc2::ISmaccUpdatable
cl_px4_mr::CpGoalChecker
cl_px4_mr::CpVehicleStatus
cl_px4_mr::CpVehicleCommand
cl_px4_mr::TunnelCenteringParams
cl_px4_mr::CpOffboardKeepAlive
cl_px4_mr::CpTunnelCentering
smacc2::client_core_components::CpTopicSubscriber< sensor_msgs::msg::PointCloud2 >
atomic< int64_t >
array< float, 4 >
atomic< float >
time_point
optional< std::chrono::steady_clock::time_point >
cl_px4_mr::CpPx4ClientBehaviorBase
smacc2::ISmaccStateMachine
smacc2::ISmaccState
smacc2::ISmaccOrthogonal
smacc2::ISmaccClientBehavior
smacc2::ISmaccClient
smacc2::ISmaccComponent
smacc2::SignalDetector
smacc2::introspection::SmaccStateInfo
map< const std::type_info *, std::vector< smacc2::introspection::ClientBehaviorInfoEntry > >
map< const std::type_info *, std::vector< std::shared_ptr< smacc2::introspection::SmaccStateReactorInfo > > >
map< const std::type_info *, std::vector< std::shared_ptr< smacc2::introspection::SmaccEventGeneratorInfo > > >
weak_ptr< smacc2::introspection::SmaccStateMachineInfo >
weak_ptr< smacc2::introspection::SmaccStateInfo >
vector< smacc2::introspection::SmaccTransitionInfo >
vector< std::shared_ptr< smacc2::introspection::SmaccStateInfo > >
type_info *
std::enable_shared_from_this< SmaccStateInfo >
SharedPtr
mutex
vector< smacc2::ISmaccState * >
shared_ptr< smacc2::introspection::SmaccStateInfo >
SmaccStatus
map< std::string, std::shared_ptr< smacc2::ISmaccOrthogonal > >
shared_ptr< smacc2::introspection::SmaccStateMachineInfo >
recursive_mutex
atomic< StateMachineInternalAction >
map< void *, std::shared_ptr< smacc2::CallbackCounterSemaphore > >
map< std::string, std::pair< std::function< std::string()>, boost::any > >
deque< smacc2_msgs::msg::SmaccTransitionLogEntry >
size_t
SMRunMode
int64_t
int
string
+staticBehaviorInfo
+stateReactorsInfo
+eventGeneratorsInfo
+stateMachine_
+parentState_
+transitions_
+children_
+tid_