weak_ptr< smacc2::introspection ::SmaccStateMachineInfo >
weak_ptr< smacc2::introspection ::SmaccStateInfo >
vector< smacc2::introspection ::SmaccTransitionInfo >
vector< std::shared _ptr< smacc2::introspection ::SmaccStateInfo > >
type_info *
std::enable_shared _from_this< SmaccStateInfo >
map< const std::type _info *, std::vector < smacc2::introspection ::ClientBehaviorInfoEntry > >
map< const std::type _info *, std::vector < std::shared_ptr< smacc2 ::introspection::SmaccStateReactor Info > > >
map< const std::type _info *, std::vector < std::shared_ptr< smacc2 ::introspection::SmaccEventGenerator Info > > >
int
SharedPtr
vector< smacc2::ISmaccState * >
shared_ptr< smacc2 ::introspection::SmaccState Info >
SmaccStatus
map< std::string, std ::shared_ptr< smacc2 ::ISmaccOrthogonal > >
shared_ptr< smacc2 ::introspection::SmaccState MachineInfo >
recursive_mutex
atomic< StateMachineInternal Action >
map< void *, std::shared _ptr< smacc2::CallbackCounterSemaphore > >
map< std::string, std ::pair< std::function < std::string()>, boost ::any > >
vector< smacc2_msgs ::msg::SmaccTransitionLogEntry >
SMRunMode
int64_t
smacc2::ISmaccStateMachine
smacc2::introspection ::SmaccStateInfo
vector< std::shared _ptr< smacc2::SmaccEventGenerator > >
shared_ptr< rclcpp ::Logger >
vector< std::shared _ptr< smacc2::StateReactor > >
smacc2::ISmaccState
vector< std::vector < std::shared_ptr< smacc2 ::ISmaccClientBehavior > > >
vector< std::shared _ptr< smacc2::ISmaccClient > >
mutex
smacc2::ISmaccOrthogonal
map< smacc2::ComponentKey, std::shared_ptr< smacc2 ::ISmaccComponent > >
smacc2::ISmaccClient
smacc2::ISmaccClientBehavior
boost::signals2::signal < Signature, optional _last_value< typename boost ::function_traits< Signature >::result_type >, int, std ::less< int >, function< Signature >, typename extended_signature< function_traits< Signature >::arity, Signature >::function_type, boost:: signals2::mutex >
boost::signals2::signal < void(const MessageType &), optional_last_value < typename boost::function _traits< void(const MessageType &)>::result_type >, int, std ::less< int >, function< void(const MessageType &)>, typename extended _signature< function_traits< void(const MessageType &)>::arity, void(const MessageType &)>::function_type, boost::signals2::mutex >
smacc2::SmaccSignal < Signature, Combiner, Group, GroupCompare, SlotFunction, ExtendedSlotFunction, Mutex >
boost::signals2::signal < void(const sensor_msgs ::msg::PointCloud2 &), optional _last_value< typename boost:: function_traits< void(const sensor _msgs::msg::PointCloud2 &)>::result _type >, int, std::less< int >, function < void(const sensor_msgs::msg::PointCloud2 &)>, typename extended_signature< function _traits< void(const sensor_msgs::msg::PointCloud2 &)>::arity, void(const sensor_msgs::msg::PointCloud2 &)>::function_type, boost::signals2::mutex >
boost::signals2::signal < void(), optional_last _value< typename boost:: function_traits< void()>::result_type >, int, std ::less< int >, function< void()>, typename extended_signature < function_traits< void()>::arity, void()>::function_type, boost::signals2::mutex >
uint64_t
double
bool
cl_px4_mr::MapProjection
smacc2::ISmaccComponent
YawMode
optional< std::future < int > >
function< void()>
float
atomic< bool >
smacc2::SmaccSignal < void()>
optional< rclcpp::Time >
uint8_t
optional< rclcpp::Duration >
atomic< int64_t >
optional< int >
function< void(const MessageType &)>
smacc2::SmaccSignal < void(const MessageType &)>
smacc2::SmaccSignal < void(const sensor _msgs::msg::PointCloud2 &)>
vector< smacc2::ISmaccUpdatable * >
vector< std::vector < smacc2::ISmaccUpdatable * > >
SmaccFifoScheduler *
processor_handle
thread
ExecutionModel
smacc2::SmaccAsyncClient Behavior
cl_px4_mr::PathFollowerParams
cl_px4_mr::NedPoint
cl_px4_mr::CpVehicleStatus
smacc2::ISmaccUpdatable
cl_px4_mr::CpVehicleLocal Position
cl_px4_mr::CpVehicleCommand
TrajectorySetpoint
cl_px4_mr::TunnelCentering Params
smacc2::client_core _components::CpTopicSubscriber < MessageType >
function< void(const sensor_msgs::msg::PointCloud2 &)>
smacc2::SignalDetector
smacc2::client_core _components::CpTopicSubscriber < sensor_msgs::msg::PointCloud2 >
array< float, 4 >
atomic< float >
time_point
cl_px4_mr::CpGoalChecker
cl_px4_mr::CpTrajectorySetpoint
cl_px4_mr::CpOffboardKeep Alive
optional< std::chrono ::steady_clock::time _point >
cl_px4_mr::CpTunnelCentering
vector< cl_px4_mr:: NedPoint >
vector< float >
atomic< size_t >
cl_px4_mr::CbPx4ClientBehaviorBase
+ onStateOrthogonalAllocation()
+ ~CbPx4ClientBehaviorBase()
+ setTimeout()
+ hasTimeout()
+ update()
# wireCompletionSignals()
# postPx4Success()
# postPx4Failure()
#goalChecker_
-path_
-cumLen_
-carrotVertex_
#tunnelCentering_
cl_px4_mr::CbPx4PathFollowerBase
+ CbPx4PathFollowerBase()
+ ~CbPx4PathFollowerBase()
+ onStateOrthogonalAllocation()
+ setFollowerParams()
+ followerParams()
+ onEntry()
+ onExit()
+ update()
# buildPath()
# behaviorName()
# onPathStarted()
# onPathCompleted()
# totalLength()
# progressFraction()
# carrotVertexIndex()
- commandFor()
- applyCentering()
- tangentYawAt()