std::enable_shared_from_this< SmaccStateInfo >
map< const std::type_info *, std::vector< smacc2::introspection::ClientBehaviorInfoEntry > >
map< const std::type_info *, std::vector< std::shared_ptr< smacc2::introspection::SmaccStateReactorInfo > > >
map< const std::type_info *, std::vector< std::shared_ptr< smacc2::introspection::SmaccEventGeneratorInfo > > >
int
string
vector< smacc2::introspection::SmaccTransitionInfo >
vector< std::shared_ptr< smacc2::introspection::SmaccStateInfo > >
type_info *
shared_ptr< smacc2::introspection::SmaccStateInfo >
shared_ptr< smacc2::introspection::SmaccStateMachineInfo >
SharedPtr
vector< smacc2_msgs::msg::SmaccTransitionLogEntry >
SMRunMode
int64_t
SharedPtr
SharedPtr
vector< smacc2::ISmaccState * >
SmaccStatus
map< std::string, std::shared_ptr< smacc2::ISmaccOrthogonal > >
recursive_mutex
atomic< StateMachineInternalAction >
map< void *, std::shared_ptr< smacc2::CallbackCounterSemaphore > >
map< std::string, std::pair< std::function< std::string()>, boost::any > >
+staticBehaviorInfo
+stateReactorsInfo
+eventGeneratorsInfo
-depth_
+stateIndex_
+demangledStateName_
+fullStateName
+transitions_
+children_
+tid_
+parentState_
+stateMachine_
#currentStateInfo_
#stateMachineInfo_
#rh_
-transitionLogHistory_
-runMode_
-stateSeqCounter_
#timer_
#eventsLogPub_
#stateMachinePub
#stateMachineStatusPub_
#transitionHistoryService_
#transitionLogPub_
#currentState_
#status_msg_
#orthogonals_
-eventQueueMutex_
-m_mutex_
-stateMachineCurrentAction
-stateCallbackConnections
-globalData_
smacc2::ISmaccStateMachine
+ ISmaccStateMachine()
+ ~ISmaccStateMachine()
+ reset()
+ stop()
+ eStop()
+ joinAsyncClientBehaviorThreads()
+ getOrthogonal()
+ getClientBehavior()
+ getOrthogonals()
+ requiresComponent()
+ requiresComponent()
+ postEvent()
+ postEvent()
+ getGlobalSMData()
+ setGlobalSMData()
+ getStateMachineName()
+ state_machine_visualization()
+ getCurrentStateInfo()
+ publishTransition()
+ onInitialize()
+ getTransitionLogHistory()
+ createSignalConnection()
+ disconnectSmaccSignal(Object)
+ disconnectSmaccSignal(Object)
+ notifyOnStateEntryStart()
+ notifyOnStateEntryEnd()
+ notifyOnRuntimeConfigured()
+ notifyOnStateExiting()
+ notifyOnStateExited()
+ notifyOnRuntimeConfiguration Finished()
+ getCurrentStateCounter()
+ getCurrentState()
+ getStateMachineInfo()
+ buildStateMachineInfo()
+ getNode()
+ getLogger()
+ getMutex()
# checkStateMachineConsistence()
# initializeROS()
# onInitialized()
# createOrthogonal()
- lockStateMachine()
- unlockStateMachine()
- propagateEventToStateReactors()
- updateStatusMessage()
smacc2::introspection::SmaccStateInfo
+ SmaccStateInfo()
+ getStateLevel()
+ depth()
+ getAncestors()
+ getFullPath()
+ createChildState()
+ declareTransition()
+ toShortName()
+ getDemangledFullName()
+ getNode()
+ getLogger()
vector< std::shared_ptr< smacc2::StateReactor > >
vector< std::shared_ptr< smacc2::SmaccEventGenerator > >
#node_
shared_ptr< rclcpp::Logger >
atomic< bool >
vector< smacc2::ISmaccUpdatable * >
vector< std::vector< smacc2::ISmaccUpdatable * > >
atomic< int64_t >
-statusPub_
SmaccFifoScheduler *
processor_handle
thread
ExecutionModel
vector< std::vector< smacc2::ISmaccClientBehavior > >
double
vector< std::shared_ptr< smacc2::ISmaccClient > >
mutex
#stateReactors_
#eventGenerators_
#stateInfo_
#logger_
-end_
-initialized_
-rosInitialized_
-updatableClients_
-updatableStateElements_
-lastState_
-scheduler_
processorHandle_
signalDetectorThread_
executionModel_
-smaccStateMachine_
-signalDetector_
loop_rate_hz
-stateMachine_
-clientBehaviors_
#clients_
-mutex_
smacc2::ISmaccState
+ getStateMachine()
+ getName()
+ getParentState()
+ getNode()
+ getLogger()
+ getClassName()
+ configure()
+ requiresComponent()
+ requiresComponent()
+ requiresClient()
+ getGlobalSMData()
+ setGlobalSMData()
+ createStateReactor()
+ createStateReactor()
+ createEventGenerator()
+ postEvent()
+ postEvent()
+ notifyTransition()
+ notifyTransitionFromTransitionTypeInfo()
+ getStateReactors()
+ getEventGenerators()
+ getOrthogonal()
+ getClientBehavior()
+ getEventGenerator()
+ getStateReactor()
smacc2::SignalDetector
+ SignalDetector()
+ initialize()
+ setProcessorHandle()
+ runThread()
+ join()
+ stop()
+ terminateScheduler()
+ joinAsyncClientBehaviorThreads()
+ pollingLoop()
+ postEvent()
+ getNode()
+ getLogger()
+ notifyStateConfigured()
+ notifyStateExited()
+ notifyRosInitialized()
- pollOnce()
- findUpdatableClientsAndComponents()
- findUpdatableStateElements()
smacc2::ISmaccOrthogonal
+ setStateMachine()
+ getStateMachine()
+ initState()
+ addClientBehavior()
+ runtimeConfigure()
+ onEntry()
+ onExit()
+ onDispose()
+ getName()
+ requiresComponent()
+ requiresClient()
+ getClients()
+ getClientBehaviors()
+ setGlobalSMData()
+ getGlobalSMData()
+ getClientBehavior()
+ getNode()
+ getLogger()
# onInitialize()
# initializeClients()
# assignClientToOrthogonal()
boost::signals2::signal< Signature, optional_last_value< typename boost::function_traits< Signature >::result_type >, int, std::less< int >, function< Signature >, typename extended_signature< function_traits< Signature >::arity, Signature >::function_type, boost::signals2::mutex >
map< smacc2::ComponentKey, std::shared_ptr< smacc2::ISmaccComponent > >
-stateMachine_
-stateMachine_
#stateMachine_
-currentOrthogonal_
-orthogonal_
#components_
smacc2::ISmaccClient
+ ISmaccClient()
+ ~ISmaccClient()
+ onInitialize()
+ getName()
+ getComponent()
+ getComponent()
+ getComponent()
+ getType()
+ getStateMachine()
+ connectSignal()
+ requiresClient()
+ getComponents()
+ iterateComponents()
+ postEvent()
+ postEvent()
# onComponentInitialization()
# onStateOrthogonalAllocation()
# createComponent()
# createNamedComponent()
# getNode()
# getLogger()
- initialize()
- setStateMachine()
- setOrthogonal()
#owner_
smacc2::ISmaccComponent
+ ISmaccComponent()
+ ~ISmaccComponent()
+ getName()
# onInitialize()
# onComponentInitialization()
# postEvent()
# postEvent()
# onStateOrthogonalAllocation()
# requiresComponent()
# requiresComponent()
# requiresClient()
# createSiblingComponent()
# createSiblingNamedComponent()
# getNode()
# getLogger()
# getStateMachine()
- initialize()
- setStateMachine()
-markersMutex_
-markerScale_
-publishRate_
-isShutdownRequested_
smacc2::ISmaccClientBehavior
+ ISmaccClientBehavior()
+ ~ISmaccClientBehavior()
+ getStateMachine()
+ getName()
+ requiresClient()
+ requiresComponent()
+ requiresComponent()
+ onEntry()
+ onExit()
+ executeOnEntry()
+ executeOnExit()
# runtimeConfigure()
# postEvent()
# postEvent()
# getCurrentState()
# dispose()
# getNode()
# getLogger()
- onStateOrthogonalAllocation()
smacc2::SmaccSignal< Signature, Combiner, Group, GroupCompare, SlotFunction, ExtendedSlotFunction, Mutex >
boost::signals2::signal< void(), optional_last_value< typename boost::function_traits< void()>::result_type >, int, std::less< int >, function< void()>, typename extended_signature< function_traits< void()>::arity, void()>::function_type, boost::signals2::mutex >
< void()>
optional< std::future< int > >
smacc2::SmaccSignal< void()>
function< void()>
vector< cl_moveit2z::TrajectoryHistoryEntry >
shared_ptr< moveit::planning_interface::MoveGroupInterface >
shared_ptr< moveit::planning_interface::PlanningSceneInterface >
Options
mutex
shared_ptr< tf2_ros::Buffer >
shared_ptr< tf2_ros::TransformListener >
optional< rclcpp::Duration >
optional< rclcpp::Time >
-m_mutex_
-onEntryThread_
-onExitThread_
-onFailure_
-onFinished_
-onSuccess_
-postFailureEventFn
-postFinishEventFn
-postSuccessEventFn_
-onFailed_
-onSucceeded_
-postEventMotionExecutionFailed_
-postEventMotionExecutionSucceeded_
-trajectoryHistory_
+moveGroupClientInterface
+planningSceneInterface
-options_
-tfMutex_
-tfBuffer_
-tfListener_
-periodDuration_
-lastUpdate_
smacc2::SmaccAsyncClientBehavior
+ onStateOrthogonalAllocation()
+ ~SmaccAsyncClientBehavior()
+ onSuccess()
+ onFinished()
+ onFailure()
+ requestForceFinish()
+ executeOnEntry()
+ executeOnExit()
+ waitOnEntryThread()
+ onSuccess()
+ onFinished()
+ onFailure()
# postSuccessEvent()
# postFailureEvent()
# dispose()
# isShutdownRequested()
- waitFutureIfNotFinished()
cl_moveit2z::ClMoveGroup Interface
+ ClMoveGroupInterface()
+ onInitialize()
+ onStateOrthogonalAllocation()
+ postEventMotionExecution Succeeded()
+ postEventMotionExecution Failed()
+ onMotionExecutionSucceeded()
+ onMotionExecutionFailed()
cl_moveit2z::ClTrajectory History
+ getLastTrajectory()
+ getLastTrajectory()
+ pushTrajectory()
cl_moveit2z::ClTFListener
+ ClTFListener()
+ ~ClTFListener()
+ onInitialize()
+ lookupTransform()
+ transformPose()
+ canTransform()
+ getBuffer()
smacc2::ISmaccUpdatable
+ ISmaccUpdatable()
+ ISmaccUpdatable()
+ executeUpdate()
+ setUpdatePeriod()
# update()
SharedPtr
float
Time
MarkerArray
bool
-trajectoryHistory_
-cpMoveGroupInterface_
-cpMoveGroupInterface_
-cpMoveGroupInterface
-trClient_
-markersPub_
-markerColor_
-lastPublishTime_
-markers_
-enabled_
-markersReady_
cl_moveit2z::ClMotionPlanner
+ ClMotionPlanner()
+ ~ClMotionPlanner()
+ onInitialize()
+ planToPose()
+ planToJointTarget()
+ planCartesianPath()
+ getCurrentState()
- applyPlanningOptions()
cl_moveit2z::ClTrajectory Executor
+ ClTrajectoryExecutor()
+ ~ClTrajectoryExecutor()
+ onInitialize()
+ execute()
+ executePlan()
+ cancel()
+ getTrajectoryHistory()
- applyExecutionOptions()
- recordToHistory()
cl_moveit2z::ClJointSpace TrajectoryPlanner
+ ClJointSpaceTrajectoryPlanner()
+ ~ClJointSpaceTrajectoryPlanner()
+ onInitialize()
+ planFromWaypoints()
cl_moveit2z::ClTrajectory Visualizer
+ ClTrajectoryVisualizer()
+ ~ClTrajectoryVisualizer()
+ onInitialize()
+ update()
+ setTrajectory()
+ clearMarkers()
+ setColor()
+ setScale()
+ setEnabled()
+ isEnabled()
-currentState
#stateMachine_
-trClient_
-markersPub_
#cpTrajectoryHistory_
#cpMoveGroup_
#cpMotionPlanner_
#cpTrajectoryExecutor_
#cpJointSpaceTrajectoryPlanner_
#cpTrajectoryVisualizer_
#cpTFListener_
#waypointMarkers_
-autocleanmarkers
-postMotionExecutionFailure Events
cl_moveit2z::ClMoveit2zClient BehaviorBase
+ onStateOrthogonalAllocation()
+ ~ClMoveit2zClientBehavior Base()
# postMotionSuccess()
# postMotionFailure()
optional< std::string >
optional< bool >
vector< geometry_msgs::msg::PoseStamped >
function< void(moveit_msgs::msg::RobotTrajectory &)>
+group_
+tipLink_
+allowInitialTrajectoryState JointDiscontinuity_
#endEffectorTrajectory_
-postIncorrectInitialState Event
-postJointDiscontinuity Event
cl_moveit2z::ClMoveEndEffector Trajectory
+ ClMoveEndEffectorTrajectory()
+ ClMoveEndEffectorTrajectory()
+ onStateOrthogonalAllocation()
+ onEntry()
+ onExit()
# computeJointSpaceTrajectory()
# executeJointSpaceTrajectory()
# generateTrajectory()
# createMarkers()
# getCurrentEndEffectorPose()
- initializeROS()