atomic< bool >

vector< smacc2::ISmaccUpdatable * >

vector< std::vector < smacc2::ISmaccUpdatable * > >

atomic< int64_t >

SmaccFifoScheduler *

processor_handle

thread

ExecutionMode

SharedPtr

double

smacc2::SignalDetector

+ SignalDetector()
+ initialize()
+ setProcessorHandle()
+ runThread()
+ join()
+ stop()
+ terminateScheduler()
+ joinAsyncClientBehaviorThreads()
- pollingLoop()
- postEvent()
+ getNode()
+ getLogger()
+ notifyStateConfigured()
+ notifyStateExited()
+ notifyRosInitialized()
- pollOnce()
- findUpdatableClientsAndComponents()
- findUpdatableStateElements()

map< std::string, std ::pair< std::function< std::string()>, boost ::any > >

vector< smacc2::msg ::msg::SmaccTransitionLogEntry >

SMRunMode

int64_t

vector< smacc2::ISmaccState * >

SmaccStatus

map< std::string, std ::shared_ptr< smacc2 ::ISmaccOrthogonal > >

recursive_mutex

atomic< StateMachineInternal Action >

map< void *, std::shared _ptr< smacc2::CallbackCounterSemaphore > >

smacc2::ISmaccStateMachine

+ ISmaccStateMachine()
+ ~ISmaccStateMachine()
+ reset()
+ stop()
+ eStop()
+ joinAsyncClientBehaviorThreads()
+ getOrthogonal()
+ getClientBehavior()
+ getOrthogonals()
+ requiresComponent()
+ requiresComponent()
+ postEvent()
+ postEvent()
+ getGlobalSMData()
+ setGlobalSMData()
+ getStateMachineName()
+ state_machine_visualization()
+ getCurrentStateInfo()
+ publishTransition()
+ onInitialize()
+ getTransitionLogHistory()
+ createSignalConnection()
+ disconnectSmaccSignalObject()
+ disconnectSmaccSignalObject()
+ notifyOnStateEntryStart()
+ notifyOnStateEntryEnd()
+ notifyOnRuntimeConfigured()
+ notifyOnStateExiting()
+ notifyOnStateExited()
+ notifyOnRuntimeConfiguration Finished()
+ getCurrentStateCounter()
+ getCurrentState()
+ getStateMachineInfo()
+ buildStateMachineInfo()
+ getNode()
+ getLogger()
+ getMutex()
# checkStateMachineConsistence()
# initializeROS()
# onInitialized()
# createOrthogonal()
- lockStateMachine()
- unlockStateMachine()
- propagateEventToStateReactors()
- updateStatusMessage()

SharedPtr

SharedPtr

shared_ptr< smacc2 ::introspection::SmaccState MachineInfo >

shared_ptr< smacc2 ::introspection::SmaccState Info >

vector< smacc2::introspection ::SmaccTransitionInfo >

vector< std::shared _ptr< smacc2::introspection ::SmaccStateInfo > >

type_info *

int

std::enable_shared _from_this< SmaccStateInfo >

map< const std::type _info *, std::vector < smacc2::introspection ::ClientBehaviorInfoEntry > >

map< const std::type _info *, std::vector < std::shared_ptr< smacc2 ::introspection::SmaccStateReactor Info > > >

map< const std::type _info *, std::vector < std::shared_ptr< smacc2 ::introspection::SmaccEventGenerator Info > > >

string

smacc2::introspection ::SmaccStateInfo

+ SmaccStateInfo()
+ getStateLevel()
+ depth()
+ getAncestors()
+ getFullPath()
+ createChildState()
+ declareTransition()
+ toShortName()
+ getDemangledFullName()
+ getNode()
+ getLogger()

vector< std::shared _ptr< smacc2::ISmaccClient > >

vector< std::vector < std::shared_ptr< smacc2 ::ISmaccClientBehavior > > >

vector< std::shared _ptr< smacc2::SmaccEventGenerator > >

shared_ptr< rclcpp ::Logger >

vector< std::shared _ptr< smacc2::SmaccReactor > >

mutex

smacc2::ISmaccOrthogonal

+ setStateMachine()
+ getStateMachine()
+ initState()
+ addClientBehavior()
+ runtimeConfigure()
+ onEntry()
+ onExit()
+ onDispose()
+ getName()
+ requiresComponent()
+ requiresClient()
+ getClients()
+ getClientBehaviors()
+ setGlobalSMData()
+ getGlobalSMData()
+ getClientBehavior()
+ getNode()
+ getLogger()
# onInitialize()
# initializeClients()
# assignClientToOrthogonal()

smacc2::ISmaccState

+ getStateMachine()
+ getName()
+ getParentState()
+ getNode()
+ getLogger()
+ getGlassName()
+ configure()
+ requiresComponent()
+ requiresComponent()
+ requiresClient()
+ getGlobalSMData()
+ setGlobalSMData()
+ createStateReactor()
+ createStateReactor()
+ createEventGenerator()
+ postEvent()
+ postEvent()
+ notifyTransition()
+ notifyTransitionFromTransition TypeInfo()
+ getStateReactors()
+ getEventGenerators()
+ getOrthogonal()
+ getClientBehavior()
+ getEventGenerator()
+ getStateReactor()

boost::signals2::signal < Signature, optional _last_value= typename boost ::function_traits< Signature >::result_type, Group= int, Compare= std ::less< int >, function= Signature >, typename extended_signature< function_traits< Signature >::arity, Signature >::function_type, boost:: signals2::mutex >

map< smacc2::ComponentKey, std::shared_ptr< smacc2 ::ISmaccComponent > >

smacc2::ISmaccClient

+ ISmaccClient()
+ ~ISmaccClient()
+ onInitialize()
+ getName()
+ getComponent()
+ getComponent()
+ getComponent()
+ getType()
+ getStateMachine()
+ connectSignal()
+ requiresClient()
+ getComponents()
+ iterateComponents()
+ postEvent()
+ postEvent()
# onComponentInitialization()
# onStateOrthogonalAllocation()
# createComponent()
# createNamedComponent()
# getNode()
# getLogger()
- initialize()
- setStateMachine()
- setOrthogonal()

smacc2::ISmaccClientBehavior

+ ISmaccClientBehavior()
+ ~ISmaccClientBehavior()
+ getStateMachine()
+ getName()
+ requiresClient()
+ requiresComponent()
+ requiresComponent()
+ onEntry()
+ onExit()
+ executeOnEntry()
+ executeOnExit()
# runtimeConfigure()
# postEvent()
# postEvent()
# getCurrentState()
# dispose()
# getNode()
# getLogger()
- onStateOrthogonalAllocation()

boost::signals2::signal < void(const WrappedResult &), optional_last_value < typename boost::function _traits< void(const WrappedResult &)>::result_type, int, std ::less< int >, function< void(const WrappedResult &)>, typename extended _signature< function_traits< void(const WrappedResult &)>::arity, void(const WrappedResult &)>::function_type, boost::signals2::mutex >

smacc2::SmaccSignal < Signature, Combiner, Group, GroupCompare, SlotFunction, ExtendedSlotFunction, Mutex >

boost::signals2::signal < void(const Feedback &), optional_last_value < typename boost::function _traits< void(const Feedback &)>::result_type, int, std ::less< int >, function< void (const Feedback &)>, typename extended _signature< function_traits< void(const Feedback &)>::arity, void(const Feedback &)>::function_type, boost::signals2::mutex >

boost::signals2::signal < void(), optional_last _value< typename boost:: function_traits< void()>::arity, void()>::function_type, boost::signals2::mutex >

smacc2::ISmaccComponent

+ ISmaccComponent()
+ ~ISmaccComponent()
+ getName()
# onInitialize()
# onComponentInitialization()
# postEvent()
# postEvent()
# onStateOrthogonalAllocation()
# requiresComponent()
# requiresComponent()
# requiresClient()
# createSiblingComponent()
# createSiblingNamedComponent()
# getNode()
# getLogger()
# getStateMachine()
- initialize()
- setStateMachine()

optional< std::shared _future< typename rclcpp ::action::Client< ActionType >::CancelResponse::SharedPtr > >

FeedbackCallback

optional< std::chrono ::milliseconds >

smacc2::SmaccSignal < void() >

optional< std::future < int > >

function< void()>

bool

optional< rclcpp::Time >

optional< rclcpp::Duration >

CpActionClient< ActionType >

optional< std::string >

function< void(const Feedback &)>

function< void(const WrappedResult &)>

smacc2::SmaccSignal < void(const WrappedResult &)>

smacc2::SmaccSignal < void(const Feedback &)>

shared_ptr< ActionClient >

optional< std::shared _future< typename GoalHandle ::SharedPtr > >

cl_nav2z::components ::CpNav2ActionInterface

+ CpNav2ActionInterface()
+ ~CpNav2ActionInterface()
+ sendNavigationGoal()
+ sendGoal()
+ cancelNavigation()
+ isNavigationServerReady()
+ waitForNavigationServer()
+ onComponentInitialization()
+ onInitialize()
+ getActionClient()
+ onNavigationSucceeded()
+ onNavigationAborted()
+ onNavigationAborted()
+ onNavigationCanceled()
+ onNavigationFeedback()
- onNavigationSuccessCallback()
- onNavigationAbortedCallback()
- onNavigationCanceledCallback()
- onNavigationFeedbackCallback()

smacc2::client_core _components::CpActionClient < ActionType >

+ CpActionClient()
+ CpActionClient()
+ ~CpActionClient()
+ sendGoal()
+ cancelGoal()
+ isServerReady()
+ waitForServer()
+ onInitialize()
+ onComponentInitialization()
+ onSucceeded()
+ onAborted()
+ onCanceled()
+ onFeedback()
+ getActionClient()
- onFeedback()
- onResult()
- postResultEvent()

ResultCode

milliseconds

smacc2::client_behavior _bases::CbActionClientBehavior Base< TAction >

+ onStateOrthogonalAllocation()
+ ~CbActionClientBehaviorBase()
+ onExit()
# sendGoal()
# cancelGoal()
# onActionSuccess()
# onActionAborted()
# onActionFeedback()
# setActionClientName()
- dispatchActionSuccess()
- dispatchActionAborted()
- dispatchActionFeedback()

smacc2::client_behavior _bases::CbActionClientBehavior Base< nav2_msgs::action::NavigateToPose >

+ onStateOrthogonalAllocation()
+ ~CbActionClientBehaviorBase()
+ onExit()
# sendGoal()
# cancelGoal()
# onActionSuccess()
# onActionAborted()
# onActionFeedback()
# setActionClientName()
- dispatchActionSuccess()
- dispatchActionAborted()
- dispatchActionFeedback()

cl_nav2z::CbNav2ZClientBehaviorBase

+ ~CbNav2ZClientBehaviorBase()
+ onStateOrthogonalAllocation()
# onNavigationActionSucceed()
# onNavigationActionAborted()
# onActionSucceed()
# onActionAborted()

shared_ptr< tf2_ros ::TransformListener >

weak_ptr< tf2_ros:: Buffer >

weak_ptr< tf2_ros:: TransformListener >

mutex

smacc2::ISmaccUpdatable

+ ISmaccUpdatable()
+ ISmaccUpdatable()
+ executeUpdate()
+ setUpdatePeriod()
# update()

PoseStamped

shared_ptr< tf2_ros ::Buffer >

cl_nav2z::CpPose

+ CpPose()
+ CpPose()
+ oninitialize()
+ update()
+ waitTransformUpdate()
+ toPoseMsg()
+ toPoseStampedMsg()
+ getYaw()
+ getX()
+ getY()
+ getZ()
+ setReferenceFrame()
+ getReferenceFrame()
+ getFrameId()
+ freezeReferenceFrame()
+ unfreezeReferenceFrame()

SharedPtr

Path

WorkingMode

vector< nav_msgs::msg ::Path >

vector< cl_nav2z::odom _tracker::CpOdomTracker ::PathInfo >

OdomTrackerStrategy

optional< geometry_ msgs::msg::PoseStamped >

SharedPtr

cl_nav2z::odom_tracker ::CpOdomTracker

+ CpOdomTracker()
+ processNewPose()
+ odomMessageCallback()
+ update()
+ setWorkingMode()
+ setPublishMessages()
+ pushPath()
+ pushPath()
+ popPath()
+ clearPath()
+ setStartPoint()
+ setStartPoint()
+ setCurrentMotionGoal()
+ setCurrentPathName()
+ getCurrentMotionGoal()
+ getPath()
+ logStateString()
+ updateParameters()
+ setOdomFrame()
# oninitialize()
# rtPublishPaths()
# updateRecordPath()
# updateClearPath()
# updateAggregatedStackPath()
# parametersCallback()

float

optional< float >

cl_nav2z::CbNavigateBackwards

+ CbNavigateBackwards()
+ onEntry()
+ onExit()

smacc2::SignalDetector
smacc2::ISmaccStateMachine
smacc2::ISmaccOrthogonal
smacc2::ISmaccState
smacc2::ISmaccClient
smacc2::ISmaccComponent
smacc2::ISmaccClientBehavior
smacc2::client_core _components::CpActionClient < ActionType >
smacc2::client_behavior _bases::CbActionClientBehavior Base< TAction >
smacc2::client_behavior _bases::CbActionClientBehavior Base< nav2_msgs::action::NavigateToPose >
cl_nav2z::CbNav2ZClientBehaviorBase
cl_nav2z::CbNavigateBackwards