

int
map< const std::type_info *, std::vector< std::shared_ptr< smacc2::introspection::SmaccStateReactorInfo > > >
map< const std::type_info *, std::vector< std::shared_ptr< smacc2::introspection::SmaccEventGeneratorInfo > > >
string
vector< smacc2::introspection::SmaccTransitionInfo >
vector< std::shared_ptr< smacc2::introspection::SmaccStateInfo > >
type_info *
std::enable_shared_from_this< SmaccStateInfo >
map< const std::type_info *, std::vector< smacc2::introspection::ClientBehaviorInfoEntry > >
shared_ptr< smacc2::introspection::SmaccStateMachineInfo >
shared_ptr< smacc2::introspection::SmaccStateInfo >
SharedPtr
map< std::string, std::pair< std::function< std::string()>, boost::any > >
vector< smacc2_msgs::msg::SmaccTransitionLogEntry >
SMRunMode
int64_t
SharedPtr
SharedPtr
SharedPtr
SharedPtr
vector< smacc2::ISmaccState * >
SmaccStatus
map< std::string, std::shared_ptr< smacc2::ISmaccOrthogonal > >
vector< boost::signals2::scoped_connection >
recursive_mutex
StateMachineInternalAction
map< void *, std::shared_ptr< smacc2::CallbackCounterSemaphore > >
SharedPtr
+depth_
+stateIndex_
+stateReactorsInfo_
+eventGeneratorsInfo_
+demangledStateName
+fullStateName_
+transitions_
+children_
+tid_
+staticBehaviorInfo_
+stateMachine_
#stateMachineInfo_
+parentState_
#currentStateInfo_
#n_
+globalData_
transitionLogHistory_
runMode_
stateSeqCounter_
#timer_
#stateMachinePub_
#transitionLogPub_
#transitionHistoryService_
#currentState_
#status_msg_
#orthogonals_
#longLivedSignalConnections_
eventQueueMutex_
m_mutex_
stateMachineCurrentAction_
stateCallbackConnections_
#stateMachineStatusPub_
smacc2::ISmaccStateMachine
+ ISmaccStateMachine()
+ ~ISmaccStateMachine()
+ reset()
+ stop()
+ eStop()
+ getOrthogonal()
+ getClientBehavior()
+ getOrthogonals()
+ requiresComponent()
+ postEvent()
+ postEvent()
+ getGlobalSMData()
+ setGlobalSMData()
+ mapBehavior()
+ getStateMachineName()
+ state_machine_visualization()
+ getCurrentStateInfo()
+ publishTransition()
+ onInitialize()
+ getTransitionLogHistory()
+ createSignalConnection()
+ disconnectSmaccSignalObject()
+ notifyOnStateEntryStart()
+ notifyOnStateEntryEnd()
+ notifyOnRuntimeConfigured()
+ notifyOnStateExitting()
+ notifyOnStateExited()
+ notifyOnRuntimeConfiguration Finished()
+ getCurrentStateCounter()
+ getCurrentState()
+ getStateMachineInfo()
+ buildStateMachineInfo()
+ getNode()
+ getLogger()
+ getMutex()
checkStateMachineConsistence()
initializeROS()
oninitialized()
createOrthogonal()
- lockStateMachine()
- unlockStateMachine()
- propagateEventToStateReactors()
- updateStatusMessage()
smacc2::introspection ::SmaccStateInfo
+ SmaccStateInfo()
+ getStateLevel()
+ depth()
+ getAncestors()
+ getFullPath()
+ createChildState()
+ declareTransition()
+ toShortName()
+ getDemangledFullName()
+ getNode()
+ getLogger()
boost::signals2::signal < Signature, optional _last_value=typename boost ::function_traits< Signature >::result_type >, int, std ::less< int >, function< Signature >, typename extended_signature< function_traits< Signature >::arity, Signature >::function_type, boost:: signals2::mutex >
vector< std::vector < std::shared_ptr< smacc2 ::ISmaccClientBehavior > > >
mutex
vector< std::shared _ptr< smacc2::ISmaccClient > >
vector< std::shared _ptr< smacc2::StateReactor > >
vector< std::shared _ptr< smacc2::SmaccEventGenerator > >
shared_ptr< rclcpp ::Logger >
vector< smacc2::ISmaccUpdatable * >
vector< std::vector < smacc2::ISmaccUpdatable * > >
atomic< int64_t >
double
atomic< bool >
SmaccFifoScheduler *
processor_handle
thread
ExecutionModel
#node_
#statusPub_
-clientBehaviors_
-mutex_
-clients_
#stateInfo_
#stateReactors_
#eventGenerators_
#logger_
-stateMachine_
-smaccStateMachine_
-signalDetector_
-updatableClients_
-updatableStateElements_
-lastState_
-loop_rate_hz_
-end_
-initialized_
-scheduler_
-processorHandle_
-signalDetectorThread_
-executionModel_
smacc2::ISmaccOrthogonal
+ setStateMachine()
+ getStateMachine()
+ initState()
+ addClientBehavior()
+ runtimeConfigure()
+ onEntry()
+ onExit()
+ onDispose()
+ getName()
+ requiresComponent()
+ requiresClient()
+ getClients()
+ getClientBehaviors()
+ setGlobalSMData()
+ getGlobalSMData()
+ getClientBehavior()
+ getNode()
+ getLogger()
onInitialize()
initializeClients()
assignClientToOrthogonal()
smacc2::ISmaccState
+ getStateMachine()
+ getName()
+ getParentState()
+ getNode()
+ getLogger()
+ getClassName()
+ configure()
+ requiresComponent()
+ requiresClient()
+ getGlobalSMData()
+ setGlobalSMData()
+ createStateReactor()
+ createStateReactor()
+ createEventGenerator()
+ postEvent()
+ postEvent()
+ notifyTransition()
+ notifyTransitionFromTransition TypeInfo()
+ getStateReactors()
+ getEventGenerators()
+ getOrthogonal()
+ getClientBehavior()
+ getEventGenerator()
+ getStateReactor()
smacc2::SignalDetector
+ SignalDetector()
+ initialize()
+ setProcessorHandle()
+ runThread()
+ join()
+ stop()
+ pollingLoop()
+ postEvent()
+ getNode()
+ getLogger()
+ notifyStateConfigured()
+ notifyStateExited()
- pollOnce()
- findUpdatableClientsAndComponents()
- findUpdatableStateElements()
boost::signals2::signal < Signature, Combiner, Group, GroupCompare, SlotFunction, ExtendedSlotFunction, Mutex >
boost::signals2::signal < void(const TResponse &), optional_last_value < typename boost::function_traits< void(const TResponse &)>::result_type >, int, std ::less< int >, function< void (const TResponse &)>, typename extended_signature< function_traits < void(const TResponse &)>::arity, void(const TResponse &)>::function_type, boost::signals2::mutex >
map< smacc2::ComponentKey, std::shared_ptr< smacc2 ::ISmaccComponent > >
-timeout_
< void(const TResponse &)>::arity, void(const TResponse &)>::function_type, boost::signals2::mutex >
smacc2::ISmaccClient
+ ISmaccClient()
+ ~ISmaccClient()
+ onInitialize()
+ getName()
+ getComponent()
+ getComponent()
+ getComponent()
+ getType()
+ getStateMachine()
+ connectSignal()
+ requiresClient()
+ getComponents()
+ iterateComponents()
+ postEvent()
+ postEvent()
onComponentInitialization()
onOrthogonalAllocation()
onStateOrthogonalAllocation()
createComponent()
createNamedComponent()
getNode()
getLogger()
- initialize()
- setStateMachine()
- setOrthogonal()
smacc2::ISmaccClientBehavior
+ ISmaccClientBehavior()
+ ~ISmaccClientBehavior()
+ getStateMachine()
+ getName()
+ requiresClient()
+ requiresComponent()
+ onEntry()
+ onExit()
+ executeOnEntry()
+ executeOnExit()
runtimeConfigure()
postEvent()
postEvent()
getCurrentState()
dispose()
getNode()
getLogger()
- onOrthogonalAllocation()
- onStateOrthogonalAllocation()
#components_
-orthogonal_
-currentOrthogonal
-currentState_
< void(const TResponse &)>
bool
SimpleActionServer < odom_tracker::OpOdomTracker Action >
io_context
executor_work_guard < decltype(io_context ...)::executor_type >
thread
context
function< void(TResponse)>
smacc2::SmaccSignal < void(const TResponse &)>
const int
-initialized_
-is_ssl_
-server_
-io_context_
-worker_guard_
-tcp_connection_runner_
-ssl_context_
-callbackHandler_
-onResponseReceived_
-HTTP_VERSION_
cl_http::ClHttp
+ onResponseReceived()
+ ClHttp()
+ ~ClHttp()
+ onInitialize()
+ makeRequest()
kHttpRequestMethod
smacc2::SmaccClientBehavior
+ onEntry()
+ onExit()
-cl_http_
+kRequestType
cl_http::ClbHttpRequestBase
+ ClbHttpRequestBase()
+ onOrthogonalAllocation()
+ onStateOrthogonalAllocation()
+ runtimeConfigure()
+ onResponseReceived()
+ onEntry()
+ onExit()
cl_http::ClbHttpPostRequest
+ ClbHttpPostRequest()