cl_px4_mr::CbSineWaveVertical
+ CbSineWaveVertical()
+ setParams()
+ params()
+ setEndPoint()
# buildPath()
# behaviorName()
cl_px4_mr::CbPx4PathFollowerBase
+ CbPx4PathFollowerBase()
+ ~CbPx4PathFollowerBase()
+ onStateOrthogonalAllocation()
+ setFollowerParams()
+ followerParams()
+ onEntry()
+ onExit()
+ update()
# buildPath()
# behaviorName()
# onPathStarted()
# onPathCompleted()
# totalLength()
# progressFraction()
# carrotVertexIndex()
- commandFor()
- applyCentering()
- tangentYawAt()
cl_px4_mr::CbPx4ClientBehaviorBase
+ onStateOrthogonalAllocation()
+ ~CbPx4ClientBehaviorBase()
+ setTimeout()
+ hasTimeout()
+ update()
# wireCompletionSignals()
# postPx4Success()
# postPx4Failure()
optional< std::chrono::steady_clock::time_point >
-watchdogStart_
-lastUpdateTime_
-lastCmd_
#followerParams_
-path_
#goalChecker_
#offboardKeepAlive_
#tunnelCentering_
#trajectorySetpoint_
#localPosition_
#vehicleStatus_
#vehicleCommand_
cl_px4_mr::CpTunnelCentering
+ CpTunnelCentering()
+ ~CpTunnelCentering()
+ onInitialize()
+ lateralOffsetM()
+ verticalOffsetM()
+ valid()
+ leftWallM()
+ rightWallM()
+ floorM()
+ ceilingM()
+ params()
- onCloud()
- onAttitude()
array< float, 4 >
atomic< float >
-subscriber_
-attitudeQ_
-ceiling_
-floor_
-lateral_
-left_
-right_
-vertical_
-params_
cl_px4_mr::TunnelCenteringParams
+ minRangeM
+ wallBandHalfHeightM
+ verticalSearchM
+ wallFadeM
+ smoothing
-haveAttitude_
-lastCloudNs_
cl_px4_mr::FlightPatternSineWaveVerticalParams
cl_px4_mr::CpVehicleCommand
+ CpVehicleCommand()
+ ~CpVehicleCommand()
+ onInitialize()
+ sendCommand()
+ arm()
+ forceArm()
+ disarm()
+ setOffboardMode()
+ land()
+ takeoff()
cl_px4_mr::CpVehicleStatus
+ CpVehicleStatus()
+ ~CpVehicleStatus()
+ onInitialize()
+ isArmed()
+ isLanded()
+ getNavState()
+ getArmingState()
- onStatusMessage()
-hasPublished_
-armingState_
-navState_
-prevArmingState_
-prevNavState_
-xyResetCounter_
-zResetCounter_
+onArmed_
+onDisarmed_
+onLanded_
+onModeChanged_
+amplitude
+baseAltitudeAgl
+endX
+endY
+sampleSpacing
+wavelength
+onLocalPositionReset
+onPositionReceived_
TrajectorySetpoint
cl_px4_mr::CpTrajectorySetpoint
+ CpTrajectorySetpoint()
+ ~CpTrajectorySetpoint()
+ onInitialize()
+ setPositionNED()
+ hold()
+ republishLast()
+ getLastSetpoint()
-lastSetpoint_
-lastLog_
-trajectorySetpoint_
-enabled_
cl_px4_mr::CpOffboardKeepAlive
+ CpOffboardKeepAlive()
+ ~CpOffboardKeepAlive()
+ onInitialize()
+ update()
+ enable()
+ disable()
+ isEnabled()
cl_px4_mr::CpVehicleLocalPosition
+ CpVehicleLocalPosition()
+ ~CpVehicleLocalPosition()
+ onInitialize()
+ getX()
+ getY()
+ getZ()
+ getHeading()
+ isValid()
+ isHeadingGoodForControl()
+ isVelocityValid()
+ globalRefValid()
+ getRefLat()
+ getRefLon()
+ getRefAlt()
+ getRefTimestamp()
+ getXyResetCounter()
+ getZResetCounter()
+ projectToNed()
+ reprojectFromNed()
- onPositionMessage()
-localPosition_
cl_px4_mr::CpGoalChecker
+ CpGoalChecker()
+ ~CpGoalChecker()
+ onInitialize()
+ update()
+ setGoal()
+ clearGoal()
+ isGoalActive()
-goalActive_
-onFailure_
-onFinished_
-onSuccess_
-projection_
+onGoalReached_
-firstMessage_
-initialized_
smacc2::ISmaccStateMachine
smacc2::ISmaccOrthogonal
smacc2::ISmaccClient
smacc2::ISmaccComponent
smacc2::ISmaccState
smacc2::ISmaccClientBehavior
smacc2::SmaccAsyncClientBehavior
smacc2::SignalDetector
smacc2::ISmaccUpdatable
smacc2::introspection::SmaccStateInfo
cl_px4_mr::MapProjection
cl_px4_mr::PathFollowerParams
cl_px4_mr::NedPoint
smacc2::client_core_components::CpTopicSubscriber< MessageType >
smacc2::client_core_components::CpTopicSubscriber< sensor_msgs::msg::PointCloud2 >
smacc2::SmaccSignal< void()>
SharedPtr
string
mutex
bool
double
float
int
uint8_t
uint64_t