
map< void *, std::shared_ptr< smacc2::CallbackCounterSemaphore > >
map< std::string, std::pair< std::function< std::string()>, boost::any > >
vector< smacc2_msgs::msg::SmaccTransitionLogEntry >
SMRunMode
int64_t
SharedPtr
SharedPtr
vector< smacc2::ISmaccState * >
shared_ptr< smacc2::introspection::SmaccStateInfo >
SmaccStatus
map< std::string, std::shared_ptr< smacc2::ISmaccOrthogonal > >
shared_ptr< smacc2::introspection::SmaccStateMachineInfo >
recursive_mutex
StateMachineInternalAction
SharedPtr
-stateCallbackConnections
-globalData_
-transitionLogHistory_
-runMode_
-stateSeqCounter_
#hh_
#timer_
#currentState_
#currentStateInfo_
#status_msg_
#orthogonals_
#stateMachineInfo_
-eventQueueMutex_
-m_mutex_
-stateMachineCurrentAction
#eventsLogPub_
#stateMachinePub
#stateMachineStatusPub_
#transitionHistoryService_
#transitionLogPub_
smacc2::ISmaccStateMachine
+ ISmaccStateMachine()
+ ~ISmaccStateMachine()
+ reset()
+ stop()
+ eStop()
+ getOrthogonal()
+ getClientBehavior()
+ getOrthogonals()
+ requiresComponent()
+ requiresComponent()
+ postEvent()
+ postEvent()
+ getGlobalSMData()
+ setGlobalSMData()
+ getStateMachineName()
+ state_machine_visualization()
+ getCurrentStateInfo()
+ publishTransition()
+ onInitialize()
+ getTransitionLogHistory()
+ createSignalConnection()
+ disconnectSmaccSignalObject()
+ notifyOnStateEntryStart()
+ notifyOnStateEntryEnd()
+ notifyOnRuntimeConfigured()
+ notifyOnStateExiting()
+ notifyOnStateExited()
+ notifyOnRuntimeConfiguration Finished()
+ getCurrentStateCounter()
+ getCurrentState()
+ getStateMachineInfo()
+ buildStateMachineInfo()
+ getNode()
+ getLogger()
+ getMutex()
# checkStateMachineConsistence()
# initializeROS()
# onInitialized()
# createOrthogonal()
- lockStateMachine()
- unlockStateMachine()
- propagateEventToStateReactors()
- updateStatusMessage()
mutex
vector< std::vector< std::shared_ptr< smacc2::ISmaccClientBehavior > > >
vector< std::shared_ptr< smacc2::ISmaccClient > >
-mutex_
-clientBehaviors_
#clients_
-stateMachine_
double
atomic< bool >
processor_handle
thread
ExecutionModel
vector< smacc2::ISmaccUpdatable * >
vector< std::vector< smacc2::ISmaccUpdatable * > >
atomic< int64_t >
SmaccFifoScheduler *
-statusPub_
-smaccStateMachine_
-signalDetector_
-loop_rate_hz_
-end_initialized_rosInitialized_
-processorHandle_
-signalDetectorThread_
-executionModel_
-updatableClients_
-updatableStateElements_
-lastState_
-scheduler_
smacc2::ISmaccOrthogonal
+ setStateMachine()
+ getStateMachine()
+ initState()
+ addClientBehavior()
+ runtimeConfigure()
+ onEntry()
+ onExit()
+ onDispose()
+ getName()
+ requiresComponent()
+ requiresClient()
+ getClients()
+ getClientBehaviors()
+ setGlobalSMData()
+ getGlobalSMData()
+ getClientBehavior()
+ getNode()
+ getLogger()
# onInitialize()
# initializeClients()
# assignClientToOrthogonal()
smacc2::SignalDetector
+ SignalDetector()
+ initialize()
+ setProcessorHandle()
+ runThread()
+ join()
+ stop()
+ terminateScheduler()
+ pollingLoop()
+ postEvent()
+ getNode()
+ getLogger()
+ notifyStateConfigured()
+ notifyStateExited()
+ notifyRosInitialized()
- pollOnce()
- findUpdatableClientsAndComponents()
- findUpdatableStateElements()
boost::signals2::signal
< Signature, optional
_last_value< typename boost
::function_traits< Signature
>::result_type >, int, std
::less< int >, function< Signature
>, typename extended_signature<
function_traits< Signature >::arity,
Signature >::function_type, boost::
signals2::mutex >
-orthogonal_
map< smacc2::ComponentKey,
std::shared_ptr< smacc2
::ISmaccComponent > >
-stateMachine_
#components_
#stateMachine_
smacc2::ISmaccClient
+ ISmaccClient()
+ ~ISmaccClient()
+ onInitialize()
+ getName()
+ getComponent()
+ getComponent()
+ getComponent()
+ getType()
+ getStateMachine()
+ connectSignal()
+ requiresClient()
+ getComponents()
+ iterateComponents()
+ postEvent()
+ postEvent()
# onComponentInitialization()
# onStateOrthogonalAllocation()
# createComponent()
# createNamedComponent()
# getNode()
# getLogger()
- initialize()
- setStateMachine()
- setOrthogonal()
-sub_
boost::signals2::signal
< void(), optional_last
_value< typename boost::
function_traits< void()>
::result_type >, int, std
::less< int >, function< void
()>, typename extended_signature
< function_traits< void()>::arity,
void()>::function_type, boost::signals2::mutex >
smacc2::SmaccSignal
< Signature, Combiner,
Group, GroupCompare,
SlotFunction, ExtendedSlotFunction,
Mutex >
boost::signals2::signal
< void(const sensor_msgs
::msg::PointCloud2 &), optional
_last_value< typename boost::
function_traits< void(const sensor
_msgs::msg::PointCloud2 &)>::result
_type >, int, std::less< int >, function
< void(const sensor_msgs::msg::PointCloud2
&)>, typename extended_signature< function
_traits< void(const sensor_msgs::msg::PointCloud2
&)>::arity, void(const sensor_msgs::msg::PointCloud2
&)>::function_type, boost::signals2::mutex >
boost::signals2::signal
< void(const MessageType
&), optional_last_value
< typename boost::function
_traits< void(const MessageType
&)>::result_type >, int, std
::less< int >, function< void(const
MessageType &)>, typename extended
_signature< function_traits< void(const
MessageType &)>::arity, void(const MessageType
&)>::function_type, boost::signals2::mutex >
< void()>
< void(const sensor
_msgs::msg::PointCloud2 &)>
< void(const MessageType &)>
-attitudeSub_
-lastYaw_
-tooClose_
-attitudeMutex_
smacc2::SmaccSignal
< void()>
bool
smacc2::SmaccSignal
< void(const sensor
_msgs::msg::PointCloud2 &)>
optional< int >
string
smacc2::SmaccSignal
< void(const MessageType &)>
function< void(const
MessageType &)>
SharedPtr
smacc2::ISmaccComponent
+ ISmaccComponent()
+ ~ISmaccComponent()
+ getName()
# onInitialize()
# onComponentInitialization()
# postEvent()
# postEvent()
# onStateOrthogonalAllocation()
# requiresComponent()
# requiresComponent()
# requiresClient()
# createSiblingComponent()
# createSiblingNamedComponent()
# getNode()
# getLogger()
# getStateMachine()
- initialize()
- setStateMachine()
-firstMessage_
-initialized_
+queueSize_
-topicName_
+onFirstMessageReceived_
+onMessageReceived_
+postInitialMessageEvent
+postMessageEvent
-sub_
smacc2::client_core
_components::CpTopicSubscriber
< MessageType >
+ CpTopicSubscriber()
+ CpTopicSubscriber()
+ ~CpTopicSubscriber()
+ onMessageReceived()
+ onFirstMessageReceived()
+ onStateOrthogonalAllocation()
+ onInitialize()
- messageCallback()
float
int
+levelFrame
-firstMessage_
-initialized_
+onFirstMessageReceived_
+onMessageReceived_
function< void(const
sensor_msgs::msg::PointCloud2 &)>
+queueSize
-topicName_
+onObstacleCleared
+onObstacleTooClose_
-haveAttitude_
+clearRangeM
-floorCutoffM
+halfAngleRad
+maxYawRateRadS
+minRangeM
+triggerRangeM
+clearClouds
+minHits
+triggerClouds
+postInitialMessageEvent
+postMessageEvent
< sensor_msgs::msg
::PointCloud2 >
smacc2::client_core
_components::CpTopicSubscriber
< sensor_msgs::msg::PointCloud2 >
+ CpTopicSubscriber()
+ CpTopicSubscriber()
+ ~CpTopicSubscriber()
+ onMessageReceived()
+ onFirstMessageReceived()
+ onStateOrthogonalAllocation()
+ onInitialize()
- messageCallback()
cl_px4_mr::ForwardObstacle
GuardParams
-cosHalfAngle_
-clearStreak_
-gatedClouds_
-triggerStreak_
-params_
-subscriber_
uint64_t
array< float, 4 >
atomic< float >
atomic< int >
-lastYawStampUs_
-attitudeQ_
-lastMinRange_
-yawRate_
-lastHits_
cl_px4_mr::CpForwardObstacle
Guard
+ CpForwardObstacleGuard()
+ ~CpForwardObstacleGuard()
+ onInitialize()
+ onObstacleTooClose()
+ onObstacleCleared()
+ reset()
+ isTooClose()
+ lastYawRate()
+ lastMinRange()
+ lastHits()
+ params()
- onCloud()
- onAttitude()
- levelRotation()