
string
weak_ptr< smacc2::introspection ::SmaccStateMachineInfo >
weak_ptr< smacc2::introspection ::SmaccStateInfo >
vector< smacc2::introspection ::SmaccTransitionInfo >
vector< std::shared _ptr< smacc2::introspection ::SmaccStateInfo > >
type_info *
std::enable_shared _from_this< SmaccStateInfo >
map< const std::type _info *, std::vector < smacc2::introspection ::ClientBehaviorInfoEntry > >
map< const std::type _info *, std::vector < std::shared_ptr< smacc2 ::introspection::SmaccStateReactor Info > > >
map< const std::type _info *, std::vector < std::shared_ptr< smacc2 ::introspection::SmaccEventGenerator Info > > >
int
SharedPtr
SharedPtr
deque< smacc2_msgs ::msg::SmaccTransitionLogEntry >
size_t
SMRuntimeMode
int64_t
SharedPtr
vector< smacc2::ISmaccState * >
shared_ptr< smacc2 ::introspection::SmaccState Info >
SmaccStatus
map< std::string, std ::shared_ptr< smacc2 ::ISmaccOrthogonal > >
shared_ptr< smacc2 ::introspection::SmaccState MachineInfo >
recursive_mutex
atomic< StateMachineInternal Action >
map< void *, std::shared _ptr< smacc2::CallbackCounterSemaphore > >
map< std::string, std ::pair< std::function < void(std::string) >, boost ::any > >
mutex
demangledStateName
fullStateName
stateMachine_
parentState_
transitions_
children_
info_
staticBehaviorInfo
stateReactorsInfo
eventGeneratorsInfo
depth_
staticIndex_
reactorWalkDepth_
#eventLogPub_
#stateMachinePub_
#stateMachineStatus Pub_
#transitionHistory Subscriber_
#transitionLogPub_
transitionLogHistory_
transitionLogHistorySize_
runMode_
stateSeqCounter_
#timer_
currentState_
currentStateInfo_
#status_msg_
orthogonals_
stateMachineInfo_
eventQueueMutex_
m_mutex_
stateMachineCurrentAction
stateCallbackConnections
globalData_
transitionLogMutex_
smacc2::ISmaccStateMachine
+ ISmaccStateMachine()
+ ~ISmaccStateMachine()
+ reset()
+ stop()
+ eStop()
+ joinAsyncClientBehaviorThreads()
+ getOrthogonal()
+ getClientBehavior()
+ getOrthogonals()
+ requiresComponents()
+ requiresComponent()
+ postEvent()
+ postEvent()
+ getGlobalSMData()
+ setGlobalSMData()
+ getStateMachineName()
+ state_machine_visualization()
+ getCurrentStateInfo()
+ publishTransition()
+ onInitialize()
+ getTransitionLogHistory()
+ createSignalConnection()
+ disconnectSmaccSignalObject()
+ disconnectSmaccSignalObject()
+ notifyOnStateEntryStart()
+ notifyOnStateEntryEnd()
+ notifyOnRuntimeConfigured()
+ notifyOnStateExiting()
+ notifyOnStateExited()
+ notifyOnRuntimeConfiguration Finished()
+ getCurrentStateCounter()
+ getCurrentState()
+ getStateMachineInfo()
+ buildStateMachineInfo()
+ getNode()
+ getLogger()
+ getMutex()
# checkStateMachineConsistence()
# initialiseROS()
# onInitialized()
# createOrthogonal()
- lockStateMachine()
- unlockStateMachine()
- propagateEventToStateReactors()
- updateStatusMessage()
smacc2::introspection ::SmaccStateInfo
+ SmaccStateInfo()
+ getStateLevel()
+ getStateMachineInfo()
+ getParentState()
+ depth()
+ getAncestors()
+ getFullPath()
+ createChildState()
+ declareTransition()
+ toShortName()
+ getDemangledFullName()
+ getNode()
+ getLogger()
shared_ptr< rclcpp ::Logger >
vector< std::shared _ptr< smacc2::IStateReactor > >
vector< std::shared _ptr< smacc2::SmaccEventGenerator > >
#node_
atomic< bool >
#_initialized _isInitialized_
vector< smacc2::ISmaccUpdatable * >
vector< std::vector < smacc2::ISmaccUpdatable * > >
SmaccFifoScheduler *
processor_handle
thread
ExecutionModel
#statePub_
#_initialized _
#updatableClients_
#updatableStateElements_
#scheduler_
#processorHandle_
#signalDetectorThread_
#executionModel_
#signalDetector_
#smaccStateMachine_
vector< std::shared _ptr< smacc2::ISmaccClient > >
vector< std::vector < std::shared_ptr< smacc2 ::ISmaccClientBehavior > > >
#mutex_
double
stateInfo_
logger_
stateReactors_
eventGenerators_
smacc2::ISmaccState
+ ~ISmaccState()
+ getStateMachine()
+ getName()
+ getParentState()
+ getNode()
+ getLogger()
+ getClassName()
+ configure()
+ requiresComponent()
+ requiresComponent()
+ requiresClient()
+ getGlobalSMData()
+ setGlobalSMData()
+ createStateReactor()
+ createStateReactor()
+ createEventGenerator()
+ postEvent()
+ postEvent()
+ notifyTransition()
+ notifyTransitionFromTransition TypeInfo()
+ getStateReactors()
+ getEventGenerators()
+ getOrthogonal()
+ getClientBehavior()
+ getEventGenerator()
+ getStateReactor()
parentState_
smacc2::SignalDetector
+ SignalDetector()
+ initialize()
+ setProcessorHandle()
+ runThread()
+ join()
+ stop()
+ terminateScheduler()
+ joinAsyncClientBehaviorThreads()
+ pollingLoop()
+ postEvent()
+ queueWorkItem()
+ getNode()
+ getLogger()
+ notifyStateConfigured()
+ notifyStateExited()
+ notifyRosInitialized()
+ pollOnce()
- findUpdatableClientsAndComponents()
- findUpdatableStateElements()
stateMachine_
boost::signals2::signal < Signature, optional _last_value< typename boost ::function_traits< Signature >::result_type >, int, std ::less< int >, function< Signature >, typename extended_signature< function_traits< Signature >::arity, Signature > ::function_type, boost:: signals2::mutex >
map< smacc2::ComponentKey, std::shared_ptr< smacc2 ::ISmaccComponent > >
smacc2::ISmaccOrthogonal
+ ~ISmaccOrthogonal()
+ setStateMachine()
+ getStateMachine()
+ initState()
+ addClientBehavior()
+ runtimeConfigure()
+ onEntry()
+ onExit()
+ onDispose()
+ getName()
+ requiresComponent()
+ requiresClient()
+ getClients()
+ getClientBehaviors()
+ setGlobalSMData()
+ getGlobalSMData()
+ getClientBehavior()
+ getNode()
+ getLogger()
# onInitialize()
# initializeClients()
# assignClientToOrthogonal()
- currentClientBehaviorsIdx()
loop_rate_hz_
stateMachine_
clients_
clientBehaviors_
smacc2::ISmaccClientBehavior
+ ISmaccClientBehavior()
+ ~ISmaccClientBehavior()
+ getStateMachine()
+ getName()
+ requiresClient()
+ requiresComponent()
+ requiresComponent()
+ onEntry()
+ onExit()
+ getNode()
+ getLogger()
- onStateOrthogonalAllocation()
currentState
currentOrthogonal
stateMachine_
orthogonal_
components_
smacc2::ISmaccClient
+ ISmaccClient()
+ ~ISmaccClient()
+ onInitialize()
+ getName()
+ getComponent()
+ getComponent()
+ getComponent()
+ getType()
+ getStateMachine()
+ connectSignal()
+ requiresClient()
+ getComponents()
+ iterateComponents()
+ postEvent()
+ postEvent()
# onComponentInitialization()
# onStateOrthogonalAllocation()
# createComponent()
# createNamedComponent()
# getNode()
# getLogger()
- initialize()
- setStateMachine()
- setOrthogonal()
owner_
smacc2::SmaccSignal
< void() >
smacc2::SmaccSignal
< Signature, Combiner, Group, GroupCompare, SlotFunction, ExtendedSlotFunction, Mutex >
boost::signals2::signal
< void(), optional_last_value< boost:: function_traits< void()>:: result_type >, int, std ::less< int >, function< void ()>, typename extended_signature < function_traits< void()>::arity, void()>::function_type, boost::signals2::mutex >
smacc2::ISmaccComponent
+ ISmaccComponent()
+ ~ISmaccComponent()
+ getName()
+ onInitialize()
# onComponentInitialization()
# postEvent()
# postEvent()
# onStateOrthogonalAllocation()
# requiresComponent()
# requiresComponent()
# requiresClient()
# createSiblingComponent()
# createSiblingNamedComponent()
# getNode()
# getLogger()
# getStateMachine()
- initialize()
- setStateMachine()
markersMutex_
markerScale_
publishRate_
function< void()>
optional< std::future < int > >
Options
shared_ptr< moveit ::planning_interface ::MoveGroupInterface >
shared_ptr< moveit ::planning_interface ::PlanningSceneInterface >
vector< cl_moveit2z ::TrajectoryHistoryEntry >
#m_mutex_
shared_ptr< tf2_ros ::TransformListener >
weak_ptr< tf2_ros::Buffer >
weak_ptr< tf2_ros ::TransformListener >
mutex
shared_ptr< tf2_ros ::Buffer >
optional< rclcpp::Duration >
optional< rclcpp::Time >
tfListener_
sharedTfBuffer_
sharedTfListener_
tfMutex_
tfBuffer_
periodDuration_
lastUpdate_
postFailureEventFn
postFinishEventFn
postSuccessEventFn
postEventMotionExecution Failed_
postEventMotionExecution Succeeded_
onEntryThread_
onExitThread_
onFailure_
onFinished_
onSucceed_
onFailed_
onSucceeded_
options_
moveGroupClientInterface
planningSceneInterface
smacc2::SmaccAsyncClient Behavior
+ onStateOrthogonalAllocation()
+ ~SmaccAsyncClientBehavior()
+ onSuccess()
+ onFinished()
+ onFailure()
+ requestForceFinish()
+ executeOnEntry()
+ executeOnExit()
+ waitOnEntryThread()
+ onSuccess()
+ onFinished()
+ onFailure()
# postSuccessEvent()
# postFailureEvent()
# dispose()
# isShutdownRequested()
- waitFuturesIfNotFinished()
cl_moveit2z::ClMoveGroup Interface
+ ClMoveGroupInterface()
+ oninitialize()
+ onStateOrthogonalAllocation()
+ postEventMotionExecution Succeeded()
+ postEventMotionExecution Failed()
+ onMotionExecutionSucceeded()
+ onMotionExecutionFailed()
cl_moveit2z::CpTrajectory History
+ getLastTrajectory()
+ getLastTrajectory()
+ pushTrajectory()
trajectoryHistory_
SharedPtr
tfListener_
sharedTfBuffer_
sharedTfListener_
tfMutex_
tfBuffer_
cl_moveit2z::CpTfListener
+ CpTfListener()
+ ~CpTfListener()
+ oninitialize()
+ lookupTransform()
+ transformPose()
+ canTransform()
+ getBuffer()
float
Time
periodDuration_
lastUpdate_
smacc2::ISmaccUpdatable
+ ISmaccUpdatable()
+ ISmaccUpdatable()
+ ~ISmaccUpdatable()
+ execute(Update)
+ setUpdatePeriod()
# update()
MarkerArray
bool
markers_
enabled _markersReady_
cpMoveGroupInterface_
cpMoveGroup_
cpMotionPlanner_
cpTrajectoryExecutor_
cpTrajectoryHistory_
cl_moveit2z::CpMotionPlanner
+ CpMotionPlanner()
+ ~CpMotionPlanner()
+ oninitialize()
+ planToPose()
+ planToJointTarget()
+ planCartesianPath()
+ getCurrentState()
- applyPlanningOptions()
cl_moveit2z::CpTrajectory Executor
+ CpTrajectoryExecutor()
+ ~CpTrajectoryExecutor()
+ oninitialize()
+ execute()
+ executePlan()
+ cancel()
+ getTrajectoryHistory()
- applyExecutionOptions()
- recordToHistory()
cl_moveit2z::CpJointSpace TrajectoryPlanner
+ CpJointSpaceTrajectoryPlanner()
+ ~CpJointSpaceTrajectoryPlanner()
+ oninitialize()
+ planFromWaypoints()
ikClient_
markersPub_
jointSpaceTrajectoryPlanner_
cl_moveit2z::CpTrajectory Visualizer
+ CpTrajectoryVisualizer()
+ ~CpTrajectoryVisualizer()
+ oninitialize()
+ update()
+ setTrajectory()
+ clearMarkers()
+ setColor()
+ setScale()
+ setEnabled()
+ isEnabled()
markerColor_
lastPublishTime_
cpTfListener_
cpTrajectoryVisualizer_
#washoutMarkers_
autoclearmarkers
cl_moveit2z::ClMoveItIkClient BehaviorBase
+ onStateOrthogonalAllocation()
+ ~ClMoveItIkClientBehavior Base()
# postMotionSuccess()
# postMotionFailure()
cl_moveit2z::ClMoveEndEffector Trajectory
+ ClMoveEndEffectorTrajectory()
+ ClMoveEndEffectorTrajectory()
+ onStateOrthogonalAllocation()
+ onEntry()
+ onExit()
+ computeJointSpaceTrajectory()
# executeJointSpaceTrajectory()
# generateTrajectory()
# createMarkers()
# getCurrentEndEffectorPose()
- initialiseROS()
optional< std::string >
optional< bool >
vector< geometry_msgs ::msg::PoseStamped >
function< void(moveit _msgs::msg::RobotTrajectory &)>
group_
jointSpaceVelocity_
allowInitialTrajectoryState JointSpaceVelocity_
endEffectorTrajectory_
postUnsuccessfulInitialState Event
postJointSpaceVelocity Event
isShutdownRequested_
postMotionExecutionFailure Events_