
SharedPtr
vector< smacc2::ISmaccState * >
SmaccStatus
map< std::string, std ::shared_ptr< smacc2 ::ISmaccOrthogonal > >
recursive_mutex
atomic< StateMachineInternal Action >
map< void *, std::shared _ptr< smacc2::CallbackCounterSemaphore > >
map< std::string, std ::pair< std::function < std::string()>, boost ::any > >
vector< smacc2_msgs ::msg::SmaccTransitionLogEntry >
SMRunMode
int64_t
shared_ptr< smacc2 ::introspection::SmaccState MachineInfo >
shared_ptr< smacc2 ::introspection::SmaccState Info >
vector< smacc2::introspection ::SmaccTransitionInfo >
vector< std::shared _ptr< smacc2::introspection ::SmaccStateInfo > >
type_info *
std::enable_shared _from_this< SmaccStateInfo >
map< const std::type _info *, std::vector < std::shared_ptr< smacc2 ::introspection::SmaccStateReactor Info > > >
map< const std::type _info *, std::vector < std::shared_ptr< smacc2 ::introspection::SmaccEventGenerator Info > > >
string
int
#eventsLogPub_
#stateMachinePub_
#stateMachineStatePub_
#transitionHistoryService_
#transitionLogPub_
#rh_
#timer_
#currentState_
#status_msg_
#orthogonals_
-eventQueueMutex_
-m_mutex_
-stateMachineCurrentAction
-stateCallbackConnections
-globalData_
-transitionLogHistory_
-runMode_
-stateSeqCounter_
#stateMachineInfo_
+stateMachine_
#currentStateInfo_
+parentState_
+transitions_
+children_
+tid_
+staticBehaviorInfo
+stateReactorsInfo
+eventGeneratorsInfo
+demangledStateName
+fullStateName
+depth_
+stateIndex_
smacc2::ISmaccStateMachine
+ ISmaccStateMachine()
+ ~ISmaccStateMachine()
+ reset()
+ stop()
+ eStop()
+ joinAsyncClientBehaviorThreads()
+ getOrthogonal()
+ getClientBehavior()
+ getOrthogonals()
+ requiresComponent()
+ requiresComponent()
+ postEvent()
+ postEvent()
+ getGlobalSMData()
+ setGlobalSMData()
+ getStateMachineName()
+ state_machine_visualization()
+ getCurrentStateInfo()
+ publishTransition()
+ onInitialize()
+ getTransitionLogHistory()
+ createSignalConnection()
+ disconnectSmaccSignalObject()
+ disconnectSmaccSignalObject()
+ notifyOnStateEntryStart()
+ notifyOnStateEntryEnd()
+ notifyOnRuntimeConfigured()
+ notifyOnStateExiting()
+ notifyOnStateExited()
+ notifyOnRuntimeConfiguration Finished()
+ getCurrentStateCounter()
+ getCurrentState()
+ getStateMachineInfo()
+ buildStateMachineInfo()
+ getNode()
+ getLogger()
+ getMutex()
# checkStateMachineConsistence()
# initializeROS()
# onInitialized()
# createOrthogonal()
- lockStateMachine()
- unlockStateMachine()
- propagateEventToStateReactors()
- updateStatusMessage()
smacc2::introspection ::SmaccStateInfo
+ SmaccStateInfo()
+ getStateLevel()
+ depth()
+ getAncestors()
+ getFullPath()
+ createChildState()
+ declareTransition()
+ toShortName()
+ getDemangledFullName()
+ getNode()
+ getLogger()
atomic< bool >
SmaccFifoScheduler *
processor_handle
thread
ExecutionModel
vector< smacc2::ISmaccUpdatable * >
vector< std::vector < smacc2::ISmaccUpdatable * > >
atomic< int64_t >
double
-end_
-initialized_
-rosInitialized_
-scheduler_
-processorHandle_
-signalDetectorThread_
-executionMode_
-updatableClients_
-updatableStateElements_
-lastState_
-loop_rate_hz
-smaccStateMachine_
-signalDetector_
#mode_
shared_ptr< rclcpp ::Logger >
vector< std::shared _ptr< smacc2::StateReactor > >
vector< std::shared _ptr< smacc2::SmaccEventGenerator > >
vector< std::vector < std::shared_ptr< smacc2 ::ISmaccClientBehavior > > >
vector< std::shared _ptr< smacc2::ISmaccClient > >
mutex
#logger_
#stateReactors_
#eventGenerators_
#stateInfo_
-clientBehaviors_
#clients_
-mutex_
smacc2::SignalDetector
+ SignalDetector()
+ initialize()
+ setProcessorHandle()
+ runThread()
+ join()
+ stop()
+ terminateScheduler()
+ joinAsyncClientBehaviorThreads()
+ pollingLoop()
+ postEvent()
+ getNode()
+ getLogger()
+ notifyStateConfigured()
+ notifyStateExited()
+ notifyRosInitialized()
- pollOnce()
- findUpdatableClientsAndComponents()
- findUpdatableStateElements()
smacc2::ISmaccState
+ getStateMachine()
+ getName()
+ getParentState()
+ getNode()
+ getLogger()
+ getClassName()
+ configure()
+ requiresComponent()
+ requiresComponent()
+ requiresClient()
+ getGlobalSMData()
+ setGlobalSMData()
+ createStateReactor()
+ createStateReactor()
+ createEventGenerator()
+ postEvent()
+ postEvent()
+ notifyTransition()
+ notifyTransitionFromTransition TypeInfo()
+ getStateReactors()
+ getEventGenerators()
+ getOrthogonal()
+ getClientBehavior()
+ getEventGenerator()
+ getStateReactor()
smacc2::ISmaccOrthogonal
+ setStateMachine()
+ getStateMachine()
+ initState()
+ addClientBehavior()
+ runtimeConfigure()
+ onEntry()
+ onExit()
+ onDispose()
+ getName()
+ requiresComponent()
+ requiresClient()
+ getClients()
+ getClientBehaviors()
+ setGlobalSMData()
+ getGlobalSMData()
+ getClientBehavior()
+ getNode()
+ getLogger()
# onInitialize()
# initializeClients()
# assignClientToOrthogonal()
boost::signals2::signal < Signature, optional _last_value= typename boost ::function_traits< Signature >::result_type >, int, std ::less< int >, function< Signature >, typename extended_signature< sizeof... Signature >::function_type, boost:: signals2::mutex >
-stateMachine_
-stateMachine_
-parentState_
map< smacc2::ComponentKey, std::shared_ptr< smacc2 ::ISmaccComponent > >
#stateMachine_
#components_
-currentState
-orthogonal_
-currentOrthogonal
smacc2::ISmaccClient
+ ISmaccClient()
+ ~ISmaccClient()
+ onInitialize()
+ getName()
+ getComponent()
+ getComponent()
+ getComponent()
+ getType()
+ getStateMachine()
+ connectSignal()
+ requiresClient()
+ getComponents()
+ iterateComponents()
+ postEvent()
+ postEvent()
# onComponentInitialization()
# onStateOrthogonalAllocation()
# createComponent()
# createNamedComponent()
# getNode()
# getLogger()
- initialize()
- setStateMachine()
- setOrthogonal()
smacc2::ISmaccClientBehavior
+ ISmaccClientBehavior()
+ ~ISmaccClientBehavior()
+ getStateMachine()
+ getName()
+ requiresClient()
+ requiresComponent()
+ requiresComponent()
+ onEntry()
+ onExit()
+ executeOnEntry()
+ executeOnExit()
# runtimeConfigure()
# postEvent()
# postEvent()
# getCurrentState()
# dispose()
# getNode()
# getLogger()
- onStateOrthogonalAllocation()
-isShutdownRequested_
#owner_
smacc2::ISmaccComponent
+ ISmaccComponent()
+ ~ISmaccComponent()
+ getName()
# onInitialize()
# onComponentInitialization()
# postEvent()
# postEvent()
# onStateOrthogonalAllocation()
# requiresComponent()
# requiresComponent()
# requiresClient()
# createSiblingComponent()
# createSiblingNamedComponent()
# getNode()
# getLogger()
# getStateMachine()
- initialize()
- setStateMachine()
boost::signals2::signal < void(int channel, const std::string &error), optional _last_value= typename boost:: function_traits< void()> ::result_type >, int, std ::less< int >, function< void (), typename extended_signature < function_traits< void()>::arity, void()>::function_type, boost::signals2::mutex >
boost::signals2::signal < void(int channel, const std::string &error), optional _last_value= typename boost:: function_traits< void(int channel, const std::string &error)> ::result_type >, int, std::less< int >, function < void(int channel, const std::string &error) >::function_type, boost::signals2::mutex >
boost::signals2::signal < void(uint8_t states), optional _last_value= typename boost::function _traits< void(uint8_t states) >::result_type >, int, std:: less< int >, function< void(uint8 _t states)>, typename extended_signature < function_traits< void(uint8_t states) >::arity, void(uint8_t states)>::function _type, boost::signals2::mutex >
smacc2::SmaccSignal < Signature, Combiner, Group, GroupCompare, SlotFunction, ExtendedSlotFunction, Mutex >
-mutex_
boost::signals2::signal < void(const std::string &), optional_last_value < typename boost::function _traits< void(const std::string &)>::result_type >, int, std ::less< int >, function< void(const std::string &)>, typename extended _signature< function_traits< void(const std::string &)>::arity, void(const std ::string &)>::function_type, boost::signals2::mutex >
boost::signals2::signal < void(int channel, bool state), optional_last_value < typename boost::function _traits< void(int channel, bool state)>::result_type >, int, std ::less< int >, function< void(int channel, bool state)>, typename extended _signature< function_traits< void(int channel, bool state)>::arity, void(int channel, bool state)>::function_type, boost::signals2::mutex >
optional< rclcpp::Duration >
optional< rclcpp::Time >
< void()>
< void(int channel, const std::string &error)>
< void(uint8_t states)>
< void(const std::string &)>
< void(int channel, bool state)>
-periodDuration_
-lastUpdate_
+COIL_BASE_ADDRESS
+NUM_CHANNELS
optional< std::future < int > >
smacc2::SmaccSignal < void()>
smacc2::SmaccSignal < void(int channel, const std::string &error)>
smacc2::SmaccSignal < void(uint8_t states)>
modbus_t *
smacc2::SmaccSignal < void(const std::string &)>
function< void()>
bool
smacc2::SmaccSignal < void(int channel, bool state)>
smacc2::ISmaccUpdatable
+ ISmaccUpdatable()
+ ISmaccUpdatable()
+ execute(Update)
+ setUpdatePeriod()
# update()
-onEntryThread_
-onExitThread_
-onFailure_
-onFinished_
-onSuccess_
+onConnectionLost_
+onConnectionRestored_
-ctx_
+onConnectionError_
-postFailureEventFn
-postFinishEventFn
-postSuccessEventFn
-postConnectionLostEvent
-postConnectionRestored Event_
-connect_on_init_
-connected_
smacc2::SmaccAsyncClient Behavior
+ onStateOrthogonalAllocation()
+ ~SmaccAsyncClientBehavior()
+ onSuccess()
+ onFinished()
+ onFailure()
+ requestForceFinish()
+ executeOnEntry()
+ executeOnExit()
+ waitOnEntryThread()
+ onSuccess()
+ onFinished()
+ onFailure()
# postSuccessEvent()
# postFailureEvent()
# dispose()
# isShutdownRequested()
- waitFutureIfNotFinished()
cl_modbus_tcp_relay ::ClpModbusConnection
+ ClpModbusConnection()
+ ~ClpModbusConnection()
+ onInitialize()
+ onStateOrthogonalAllocation()
+ connect()
+ disconnect()
+ reconnect()
+ isConnected()
+ getContext()
+ getMutex()
+ getIpAddress()
+ getPort()
+ getSlaveId()
+ onConnectionLost()
+ onConnectionRestored()
+ onConnectionError()
# update()
- declareAndLoadParam()
+onWriteFailure_
+onReadComplete_
-connectionComponent_
boost::signals2::signal < Signature, optional _last_value< typename boost ::function_traits< Signature >::result_type >, int, std ::less< int >, function< Signature >, typename extended_signature< sizeof... Signature >::arity, Signature >::function_type, boost:: signals2::mutex >
-ip_address_
-heartbeat_interval _ms_
-port_
-slave_id_
postWriteFailureEvent
postWriteSuccessEvent_
+onWriteSuccess_
cl_modbus_tcp_relay ::ClpModbusRelay
+ ClpModbusRelay()
+ ~ClpModbusRelay()
+ onInitialize()
+ onStateOrthogonalAllocation()
+ writeCoil()
+ readCoil()
+ writeAllCoils()
+ writeAllCoils()
+ readAllCoils()
+ onWriteSuccess()
+ onWriteFailure()
+ onReadComplete()
- channelToAddress()
- isValidChannel()
-connectionComponent_
-relayComponent_
cl_modbus_tcp_relay ::ClModbusTcpRelay
+ ClModbusTcpRelay()
+ ~ClModbusTcpRelay()
+ onInitialize()
+ onStateOrthogonalAllocation()
+ getConnectionComponent()
+ getRelayComponent()
-relayComponent_
-client_
cl_modbus_tcp_relay ::CbAllRelaysOff
+ CbAllRelaysOff()
+ ~CbAllRelaysOff()
+ onStateOrthogonalAllocation()
+ onEntry()