smacc2::ISmaccStateMachine
smacc2::introspection::SmaccStateInfo
smacc2::ISmaccOrthogonal
smacc2::ISmaccState
smacc2::ISmaccClient
smacc2::ISmaccClientBehavior
smacc2::ISmaccComponent
smacc2::SmaccAsyncClientBehavior
cl_px4_mr::CpVehicleStatus
cl_px4_mr::MapProjection
cl_px4_mr::CpVehicleLocalPosition
smacc2::ISmaccUpdatable
cl_px4_mr::CpVehicleCommand
cl_px4_mr::PathFollowerParams
cl_px4_mr::TunnelCenteringParams
smacc2::client_core_components::CpTopicSubscriber< MessageType >
smacc2::SignalDetector
cl_px4_mr::NedPoint
cl_px4_mr::CpTrajectorySetpoint
+ setPositionNED()
+ hold()
+ republishLast()
+ getLastSetpoint()
cl_px4_mr::CpGoalChecker
cl_px4_mr::CpOffboardKeepAlive
+ CpOffboardKeepAlive()
+ ~CpOffboardKeepAlive()
+ onInitialize()
+ update()
+ enable()
+ disable()
+ isEnabled()
#localPosition_
-trajectorySetpoint_
#trajectorySetpoint_
#offboardKeepAlive_
cl_px4_mr::CpTunnelCentering
+ valid()
+ leftWallM()
+ rightWallM()
+ floorM()
+ ceilingM()
+ params()
- onCloud()
- onAttitude()
cl_px4_mr::CbPx4ClientBehaviorBase
+ onStateOrthogonalAllocation()
+ ~CbPx4ClientBehaviorBase()
+ setTimeout()
+ hasTimeout()
+ update()
# wireCompletionSignals()
# postPx4Success()
# postPx4Failure()
-lastCmd_
#followerParams_
#tunnelCentering_
vector< cl_px4_mr::NedPoint >
vector< float >
atomic< size_t >
-path_
-cumLen_
-carrotVertex_
cl_px4_mr::CbPx4PathFollowerBase
+ CbPx4PathFollowerBase()
+ ~CbPx4PathFollowerBase()
+ onStateOrthogonalAllocation()
+ setFollowerParams()
+ followerParams()
+ onEntry()
+ onExit()
+ update()
# buildPath()
# behaviorName()
# onPathStarted()
# onPathCompleted()
# totalLength()
# progressFraction()
# carrotVertexIndex()
- commandFor()
- applyCentering()
- tangentYawAt()
cl_px4_mr::CbVSSearch
+ CbVSSearch()
+ setParams()
+ params()
+ setDatum()
# buildPath()
# behaviorName()