cl_nav2z::CbNavigateNext Waypoint
+ CbNavigateNextWaypoint()
+ ~CbNavigateNextWaypoint()
+ onEntry()
+ onExit()
cl_nav2z::CbNav2ZClientBehaviorBase
+ ~CbNav2ZClientBehaviorBase()
+ onStateOrthogonalAllocation()
# onNavigationActionSuccess()
# onNavigationActionAbort()
# onActionSuccess()
# onActionAbort()
#waypointsNavigator_
#navigationResult_
cl_nav2z::NavigateNextWaypoint Options
smacc2::client_behavior _bases::CbActionClientBehavior Base< nav2_msgs::action::NavigateToPose >
< nav2_msgs::action ::NavigateToPose >
smacc2::client_behavior _bases::CbActionClientBehavior Base< TAction >
#actionClient_
#goalResponseTimeout_
-resultConnectionsInitialized_
#actionResult_
milliseconds
bool
ResultCode
smacc2::client_core _components::CpActionClient < ActionType >
cl_nav2z::CpWaypointNavigator
+ CpWaypointNavigator()
+ onInitialize()
+ onStateOrthogonalAllocation()
+ sendNextGoal()
+ stopWaitingResult()
- onNavigationResult()
- onGoalReached()
- onGoalCancelled()
- onGoalAborted()
cl_nav2z::CpWaypointNavigatorBase
cl_nav2z::components ::CpNav2ActionInterface
#nav2ActionInterface_
+nav2ActionInterface_
smacc2::SmaccAsyncClient Behavior
connection
-abortedNav2ZClientConnection_
-cancelledNav2ZClientConnection_
-succeededNav2ZClientConnection_
WaypointEventDispatcher
cl_nav2z::ClNav2Z
smacc2::ISmaccComponent
smacc2::ISmaccClientBehavior
smacc2::ISmaccClient
smacc2::ISmaccOrthogonal
smacc2::ISmaccState
smacc2::ISmaccStateMachine
smacc2::SignalDetector
smacc2::introspection ::SmaccStateInfo
#stateInfo_
-stateMachineCurrentAction
-stateCallbackConnections
-eventQueueMutex_
-m_mutex_