

| smacc2::ISmaccClient                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| # components_<br>- stateMachine_<br>- orthogonal_                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| + ISmaccClient()<br>+ ~ISmaccClient()<br>+ onInitialize()<br>+ getName()<br>+ getComponent()<br>+ getComponent()<br>+ getComponent()<br>+ getType()<br>+ getStateMachine()<br>+ connectSignal()<br>+ requiresClient()<br>+ getComponents()<br>+ iterateComponents()<br>+ postEvent()<br>+ postEvent()<br># onComponentInitialization()<br># onOrthogonalAllocation()<br># onStateOrthogonalAllocation()<br># createComponent()<br># createNamedComponent()<br># getNode()<br># getLogger()<br>- initialize()<br>- setStateMachine()<br>- setOrthogonal() |



| smacc2::client_bases<br>::CIRosLaunch2                                                                          |
|-----------------------------------------------------------------------------------------------------------------|
| + packageName_<br>+ launchFileName_<br>+ launchPid_<br># result_<br># cancellationToken_<br># detached_futures_ |
| + CIRosLaunch2()<br>+ CIRosLaunch2()<br>+ ~CIRosLaunch2()<br>+ launch()<br>+ stop()<br>+ executeRosLaunch()     |