SmaccStatus
map< std::string, std::shared_ptr< smacc2::ISmaccOrthogonal > >
vector< boost::signals2::scoped_connection >
recursive_mutex
StateMachineInternalAction
map< void *, std::shared_ptr< smacc2::CallbackCounterSemaphore > >
map< std::string, std::pair< std::function< std::string()>, boost::any > >
vector< smacc2_msgs::msg::SmaccTransitionLogEntry >
SMRunMode
int64_t
SharedPtr
vector< smacc2::ISmaccState * >
shared_ptr< smacc2::introspection::SmaccStateInfo >
shared_ptr< smacc2::introspection::SmaccStateMachineInfo >
smacc2::ISmaccStateMachine
vector< std::shared_ptr< smacc2::ISmaccClient > >
vector< std::vector< std::shared_ptr< smacc2::ISmaccClientBehavior > > >
smacc2::ISmaccOrthogonal
vector< smacc2::ISmaccUpdatable * >
vector< std::vector< smacc2::ISmaccUpdatable * > >
atomic< int64_t >
double
atomic< bool >
SmaccFifoScheduler *
processor_handle
thread
ExecutionModel
smacc2::SignalDetector
mutex
string
boost::signals2::signal< Signature, optional_last_value< typename boost::function_traits< Signature >::result_type >, int, std::less< int >, function< Signature >, typename extended_signature< function_traits< Signature >::arity, Signature >::function_type, boost::signals2::mutex >
map< smacc2::ComponentKey, std::shared_ptr< smacc2::ISmaccComponent > >
smacc2::ISmaccClient
std::enable_shared_from_this< SmaccStateInfo >
map< const std::type_info *, std::vector< smacc2::introspection::ClientBehaviorInfoEntry > >
map< const std::type_info *, std::vector< std::shared_ptr< smacc2::introspection::SmaccStateReactorInfo > > >
map< const std::type_info *, std::vector< std::shared_ptr< smacc2::introspection::SmaccEventGeneratorInfo > > >
int
vector< smacc2::introspection::SmaccTransitionInfo >
vector< std::shared_ptr< smacc2::introspection::SmaccStateInfo > >
type_info *
smacc2::introspection::SmaccStateInfo
boost::signals2::signal< void(const WrappedResult &), optional_last_value< typename boost::function_traits< void(const WrappedResult &)>::result_type >, int, std::less< int >, function< void(const WrappedResult &)>, typename extended_signature< function_traits< void(const WrappedResult &)>::arity, void(const WrappedResult &)>::function_type, boost::signals2::mutex >
smacc2::SmaccSignal< Signature, Combiner, Group, GroupCompare, SlotFunction, ExtendedSlotFunction, Mutex >
boost::signals2::signal< void(const Feedback &), optional_last_value< typename boost::function_traits< void(const Feedback &)>::result_type >, int, std::less< int >, function< void(const Feedback &)>, typename extended_signature< function_traits< void(const Feedback &)>::arity, void(const Feedback &)>::function_type, boost::signals2::mutex >
boost::signals2::signal< void(), optional_last_value< typename boost::function_traits< void()>::result_type >, int, std::less< int >, function< void()>, typename extended_signature< function_traits< void()>::arity, void()>::function_type, boost::signals2::mutex >
vector< std::shared_ptr< smacc2::StateReactor > >
vector< std::shared_ptr< smacc2::SmaccEventGenerator > >
shared_ptr< rclcpp::Logger >
smacc2::ISmaccState
smacc2::ISmaccComponent
optional< std::shared_future< typename CancelResponse::SharedPtr > >
function< void(WrappedResult)>
FeedbackCallback
smacc2::client_bases::ISmaccActionClient
optional< std::shared_future< typename GoalHandle::SharedPtr > >
function< void(const Feedback &)>
CpActionClient< ActionType > *
smacc2::SmaccSignal< void(const WrappedResult &)>
smacc2::SmaccSignal< void(const Feedback &)>
function< void(const WrappedResult &)>
optional< std::shared_future< typename rclcpp_action::Client< ActionType >::CancelResponse::SharedPtr > >
optional< std::chrono::milliseconds >
shared_ptr< ActionClient >
smacc2::SmaccSignal< void()>
optional< std::string >
smacc2::client_bases::SmaccActionClientBase< ActionType >
cl_nav2z::components::CpNav2ActionInterface
smacc2::client_core_components::CpActionClient< ActionType >
smacc2::ISmaccClientBehavior
ClNav2Z *
function< void()>
optional< std::shared_future< typename rclcpp_action::Client< nav2_msgs::action::NavigateToPose >::CancelResponse::SharedPtr > >
bool
optional< std::future< int > >
cl_nav2z::NavigateNextWaypointOptions
smacc2::client_bases::SmaccActionClientBase< nav2_msgs::action::NavigateToPose >
smacc2::client_core_components::CpActionClient< nav2_msgs::action::NavigateToPose >
smacc2::SmaccAsyncClientBehavior
long
vector< geometry_msgs::msg::Pose >
WaypointEventDispatcher
vector< std::string >
cl_nav2z::CpWaypointNavigatorBase
cl_nav2z::ClNav2Z
connection
SharedPtr
shared_future< std::shared_ptr< rclcpp_action::ClientGoalHandle< nav2_msgs::action::NavigateToPose > > >
ResultCode
cl_nav2z::CpWaypointNavigator
cl_nav2z::CbNav2ZClientBehaviorBase
cl_nav2z::CbNavigateNextWaypoint
cl_nav2z::CbNavigateNamedWaypoint