

smacc2::ISmaccStateMachine
+ ISmaccStateMachine()
+ ~ISmaccStateMachine()
+ reset()
+ stop()
+ eStop()
+ getOrthogonal()
+ getClientBehavior()
+ getOrthogonals()
+ requiresComponent()
+ postEvent()
+ postEvent()
+ getGlobalSMData()
+ setGlobalSMData()
+ mapBehavior()
+ getStateMachineName()
+ state_machine_visualization()
+ getCurrentStateInfo()
+ publishTransition()
+ onInitialize()
+ getTransitionLogHistory()
+ createSignalConnection()
+ disconnectSmaccSignalObject()
+ notifyOnStateEntryStart()
+ notifyOnStateEntryEnd()
+ notifyOnRuntimeConfigured()
+ notifyOnStateExitting()
+ notifyOnStateExited()
+ notifyOnRuntimeConfiguration Finished()
+ getCurrentStateCounter()
+ getCurrentState()
+ getStateMachineInfo()
+ buildStateMachineInfo()
+ getNode()
+ getLogger()
+ getMutex()
checkStateMachineConsistence()
initializeROS()
onInitialized()
createOrthogonal()
- lockStateMachine()
- unlockStateMachine()
- propagateEventToStateReactors()
- updateStatusMessage()
smacc2::SignalDetector
+ SignalDetector()
+ initialize()
+ setProcessorHandle()
+ runThread()
+ join()
+ stop()
+ pollingLoop()
+ postEvent()
+ getNode()
+ getLogger()
+ notifyStateConfigured()
+ notifyStateExited()
- pollOnce()
- findUpdatableClientsAndComponents()
- findUpdatableStateElements()
smacc2::ISmaccOrthogonal
+ setStateMachine()
+ getStateMachine()
+ initState()
+ addClientBehavior()
+ runtimeConfigure()
+ onEntry()
+ onExit()
+ onDispose()
+ getName()
+ requiresComponent()
+ requiresClient()
+ getClients()
+ getClientBehaviors()
+ setGlobalSMData()
+ getGlobalSMData()
+ getClientBehavior()
+ getNode()
+ getLogger()
onInitialize()
initializeClients()
assignClientToOrthogonal()
smacc2::ISmaccState
+ getStateMachine()
+ getName()
+ getParentState()
+ getNode()
+ getLogger()
+ getClassName()
+ configure()
+ requiresComponents()
+ requiresClient()
+ getGlobalSMData()
+ setGlobalSMData()
+ createStateReactor()
+ createStateReactor()
+ createEventGenerator()
+ postEvent()
+ postEvent()
+ notifyTransition()
+ notifyTransitionFromTransition TypeInfo()
+ getStateReactors()
+ getEventGenerators()
+ getOrthogonal()
+ getClientBehavior()
+ getEventGenerator()
+ getStateReactor()
smacc2::ISmaccClient
+ ISmaccClient()
+ ~ISmaccClient()
+ onInitialize()
+ getName()
+ getComponent()
+ getComponent()
+ getComponent()
+ getType()
+ getStateMachine()
+ connectSignal()
+ requiresClient()
+ getComponents()
+ iterateComponents()
+ postEvent()
+ postEvent()
onComponentInitialization()
onOrthogonalAllocation()
onStateOrthogonalAllocation()
createComponent()
createNamedComponent()
getNode()
getLogger()
- initialize()
- setStateMachine()
- setOrthogonal()
smacc2::ISmaccClientBehavior
+ ISmaccClientBehavior()
+ ~ISmaccClientBehavior()
+ getStateMachine()
+ getName()
+ requiresClient()
+ requiresComponent()
+ onEntry()
+ onExit()
+ executeOnEntry()
+ executeOnExit()
runtimeConfigure()
postEvent()
postEvent()
getCurrentState()
dispose()
getNode()
getLogger()
- onOrthogonalAllocation()
- onStateOrthogonalAllocation()
smacc2::SmaccSignal
< Signature, Combiner, Group, GroupCompare, SlotFunction, ExtendedSlotFunction, Mutex >
smacc2::SmaccSignal
< void(const WrappedResult &)>
smacc2::SmaccSignal
< void()>
boost::signals2::signal
< Signature, optional_last_value< typename boost ::function_traits< Signature >::result_type >, int, std ::less< int >, function< Signature >, typename extended_signature< function_traits< Signature >::arity, Signature >::function_type, boost:: signals2::mutex >
boost::signals2::signal
< void(const WrappedResult &), optional_last_ value< typename boost ::function_traits< void(const WrappedResult &)>::result_type>, int, std::less <int>, function<void(const WrappedResult &)>, typename extended_signature<function _traits<void(const WrappedResult &)>::arity, void(const WrappedResult &)>::function_type, boost::signals2::mutex >
boost::signals2::signal
< void(), optional_last _value< typename boost:: function_traits< void()> ::result_type >, int, std ::less< int >, function< void ()>, typename extended_signature < function_traits< void()>::arity, void()>::function_type, boost::signals2::mutex >
smacc2::introspection ::SmaccStateInfo
+ SmaccStateInfo()
+ getStateLevel()
+ depth()
+ getAncestors()
+ getFullPath()
+ createChildState()
+ declareTransition()
+ toShortName()
+ getDemangledFullName()
+ getNode()
+ getLogger()
smacc2::client_bases ::SmaccActionClientBase < ActionType >
+ SmaccActionClientBase()
+ SmaccActionClientBase()
+ ~SmaccActionClientBase()
+ getClientBase()
+ onInitialize()
+ waitForServer()
+ postResultEvent()
+ onOrthogonalAllocation()
+ onSucceeded()
+ onSucceeded()
+ onAborted()
+ onAborted()
+ onCancelled()
+ onCancelled()
+ cancelGoal()
+ sendGoal()
+ getEventLabel()
onFeedback()
onResult()
smacc2::client_bases ::SmaccActionClientBase < nav2_msgs::action::NavigateTo Pose >
+ SmaccActionClientBase()
+ SmaccActionClientBase()
+ ~SmaccActionClientBase()
+ getClientBase()
+ onInitialize()
+ waitForServer()
+ postResultEvent()
+ onOrthogonalAllocation()
+ onSucceeded()
+ onSucceeded()
+ onAborted()
+ onAborted()
+ onCancelled()
+ onCancelled()
+ cancelGoal()
+ sendGoal()
+ getEventLabel()
onFeedback()
onResult()
smacc2::SmaccAsyncClient Behavior
+ onOrthogonalAllocation()
+ onStateOrthogonalAllocation()
+ ~SmaccAsyncClientBehavior()
+ onSuccess()
+ onFinished()
+ onFailure()
+ requestFinish()
+ executeOnEntry()
+ executeOnExit()
+ waitOnEntryThread()
+ onSuccess()
+ onFinished()
+ onFailure()
postSuccessEvent()
postFailureEvent()
dispose()
isShutdownRequested()
- waitFutureIfNotFinished()
cl_nav2z::ClNav2Z
+ ClNav2Z()
+ ~ClNav2Z()
cl_nav2z::ClNav2ZClientBehaviorBase
+ ~ClNav2ZClientBehaviorBase()
+ onOrthogonalAllocation()
+ onStateOrthogonalAllocation()
sendGoal()
cancelGoal()
isOwnActionResponse()
onNavigationResult()
onNavigationActionSuccess()
onNavigationActionAborts()
cl_nav2z::ClRotate
+ ClRotate()
+ ClRotate()
+ onEntry()
double
atomic< bool >
SmaccFifoScheduler *
processor_handle
thread
ExecutionModel
vector< smacc2::ISmaccUpdatable * >
vector< std::vector < smacc2::ISmaccUpdatable * > >
atomic< int64_t >
mutex
vector< std::shared _ptr< smacc2::ISmaccClient > >
vector< std::vector < std::shared_ptr< smacc2 ::ISmaccClientBehavior > > >
shared_ptr< rclcpp ::Logger >
vector< std::shared _ptr< smacc2::StateReactor > >
vector< std::shared _ptr< smacc2::SmaccEventGenerator > >
map< smacc2::ComponentKey, std::shared_ptr< smacc2 ::ISmaccComponent > >
SharedPtr
map< std::string, std ::shared_ptr< smacc2 ::ISmaccOrthogonal > >
vector< boost::signals2 ::scoped_connection >
recursive_mutex
StateMachineInternalAction
map< void *, std::shared _ptr< smacc2::CallbackCounterSemaphore > >
map< std::string, std ::pair< std::function < std::string()>, boost ::any > >
vector< smacc2_msgs ::msg::SmaccTransitionLogEntry >
SMRunMode
int64_t
shared_ptr< smacc2 ::introspection::SmaccState MachineInfo >
shared_ptr< smacc2 ::introspection::SmaccState Info >
string
std::enable_shared _from_this< SmaccStateInfo >
map< const std::type _info *, std::vector < smacc2::introspection ::ClientBehaviorInfoEntry > >
map< const std::type _info *, std::vector < std::shared_ptr< smacc2 ::introspection::SmaccStateReactor Info> > >
map< const std::type _info *, std::vector < std::shared_ptr< smacc2 ::introspection::SmaccEventGenerator Info> > >
int
vector< smacc2::introspection ::SmaccTransitionInfo >
vector< std::shared _ptr< smacc2::introspection ::SmaccStateInfo > >
type_info *
smacc2::client_bases ::SmaccActionClient
+ ISmaccActionClient()
+ ~ISmaccActionClient()
+ getNamespace()
+ cancelGoal()
+ getClientBase()
+ getName()
optional< std::shared _future< typename GoalHandle ::SharedPtr > >
optional< std::shared _future< typename CancelResponse ::SharedPtr > >
function< void(WrappedResult)>
function< void(const Feedback &)>
FeedbackCallback
bool
optional< std::future < int > >
function< void()>
cl_nav2z::ClNav2Z
shared_future< std ::shared_ptr< rclcpp _action::ClientGoalHandle < nav2_msgs::action::NavigateTo Pose > > >
ResultCode
float
optional< std::string >
optional< cl_nav2z ::SpinningPlanner >
shared_ptr< tf2_ros ::Buffer >
#stateMachine_
#mutex_
#clients_
#clientBehaviors_
#stateInfo_
#logger_
#stateReactors_
#eventGenerators_
#components_
#orthogonal_
#action_smacc2
#currentOrthogonal
#currentState
#name_
#parentState_
#action_endpoint_
#client_
#lastRequest_
#lastCancelResponse_
+postAbortedEvent
+postCancelledEvent
+postSuccessEvent
+postFeedbackEvent
+feedback_cb
+onAborted_
+onCancelled_
+onSucceeded_
+nav2_msgs::action ::NavigateToPose >
+navigationCallback_
+navigationResult_
+goalHandleFuture_
+rotateDegree_
+goalChecker_
+spinningPlanner_
-listener
#stateMachine_
#eventQueueMutex _m_mutex_
#stateMachineCurrentAction
#stateCallbackConnections
#globalData_
#transitionLogHistory_
#runMode_
#stateSeqCounter_
#info_
#stateMachineInfo_
#currentStateInfo_
#stateMachine_
#parentState_
#demangledStateName
#fullStateName
#stateBehaviorsInfo
#stateReactorsInfo
#eventGeneratorsInfo
#depth
#stateIndex
#transitions_
#children_
#sid_
#stateMachineStatusPub_
#timer_
#stateMachinePub_
#transitionLogPub_
#transitionHistoryService_
#currentState_
#status_msg_
#orthogonals_
#longLivedSignalConnections_
#loop_rate_hz
#end_ #initialized_
#scheduler_
#processorHandle_
#signalDetectorThread_
#executionModel_
#updatableClients_
#updatableStateElements_
#lastState_
#signalDetector_
#smaccStateMachine_
#statusPub_
+ void()>
+ void(const WrappedResult &)>
- isShutdownRequested_
-onEntryThread_ -onExitThread_
-onFailure_ -onFinished_ -onSuccess_
+postFailureEventFn
+postFinishEventFn
+postSuccessEventFn