
SharedPtr
SharedPtr
vector< smacc2::ISmaccState * >
SmaccStatus
map< std::string, std ::shared_ptr< smacc2 ::ISmaccOrthogonal > >
recursive_mutex
atomic< StateMachineInternal Action >
map< void *, std::shared _ptr< smacc2::CallbackCounterSemaphore > >
map< std::string, std ::pair< std::function < std::string()>, boost ::any* > >
vector< smacc2_msgs :msg::SmaccTransitionLogEntry >
SMRunMode
int64_t
SharedPtr
shared_ptr< smacc2 ::introspection::SmaccState Info >
shared_ptr< smacc2 ::introspection::SmaccState MachineInfo >
string
vector< smacc2::introspection ::SmaccTransitionInfo >
vector< std::shared _ptr< smacc2::introspection ::SmaccStateInfo > >
type_info *
std::enable_shared _from_this< SmaccStateInfo >
map< const std::type _info *, std::vector < smacc2::introspection ::ClientBehaviorInfoEntry > >
map< const std::type _info *, std::vector < std::shared_ptr< smacc2 ::introspection::SmaccStateReactor Info > > >
map< const std::type _info *, std::vector < std::shared_ptr< smacc2 ::introspection::SmaccEventGenerator Info > > >
int
#eventsLogPub_
#stateMachinePub
#stateMachineStatus Pub_
#transitionHistory Service_
#transitionLogPub_
#timer_
#currentState_
#status_msg_
#orthogonals_
-eventQueueMutex _m_mutex_
-stateMachineCurrentAction
-stateCallbackConnections
-globalData_
-transitionLogHistory_
-runMode_
-stateSeqCounter_
#nh_
#currentStateInfo_
#stateMachineInfo_
+parentState_
+stateMachine_
+demangledStateName +fullStateName
+transitions_
+children_
+tid_
+staticBehaviorInfo
+stateReactorsInfo
+eventGeneratorsInfo
+depth_ +stateIndex_
smacc2::ISmaccStateMachine
+ ISmaccStateMachine()
+ ~ISmaccStateMachine()
+ reset()
+ stop()
+ eStop()
+ getOrthogonal()
+ getClientBehavior()
+ getOrthogonals()
+ requiresComponent()
+ requiresComponent()
+ postEvent()
+ postEvent()
+ getGlobalSMData()
+ setGlobalSMData()
+ getStateMachineName()
+ state_machine_visualization()
+ getCurrentStateInfo()
+ publishTransition()
+ onInitialize()
+ getTransitionLogHistory()
+ createSignalConnection()
+ disconnectSmaccSignalObject()
+ disconnectSmaccSignalObject()
+ notifyOnStateEntryStart()
+ notifyOnStateEntryEnd()
+ notifyOnRuntimeConfigured()
+ notifyOnStateExiting()
+ notifyOnStateExited()
+ notifyOnRuntimeConfiguration Finished()
+ getCurrentStateCounter()
+ getCurrentState()
+ getStateMachineInfo()
+ buildStateMachineInfo()
+ getNode()
+ getLogger()
+ getMutex()
# checkStateMachineConsistence()
# initializeROS()
# onInitialized()
# createOrthogonal()
- lockStateMachine()
- unlockStateMachine()
- propagateEventToStateReactors()
- updateStatusMessage()
smacc2::introspection ::SmaccStateInfo
+ SmaccStateInfo()
+ getStateLevel()
+ depth()
+ getAncestors()
+ getFullPath()
+ createChildState()
+ declareTransition()
+ toShortName()
+ getDemangledFullName()
+ getNode()
+ getLogger()
-statePub_
SmaccFifoScheduler *
processor_handle
thread
ExecutionModel
vector< smacc2::ISmaccUpdatable * >
vector< std::vector < smacc2::ISmaccUpdatable * > >
atomic< int64_t >
double
atomic< bool >
mutex
vector< std::shared _ptr< smacc2::ISmaccClient > >
vector< std::vector < std::shared_ptr< smacc2 ::ISmaccClientBehavior > > >
#node_
vector< std::shared _ptr< smacc2::StateReactor > >
vector< std::shared _ptr< smacc2::SmaccEventGenerator > >
shared_ptr< rclcpp ::Logger >
-scheduler_
-processorHandle_
-signalDetectorThread_
-executionModel_
-updatableClients_
-updatableStateElements_
-lastState_
-loop_rate_hz
-end_ -initialized_ -rosInitialized_
-smaccStateMachine_
-signalDetector_
-stateMachine_
-mutex_
#clients_
-clientBehaviors_
#stateReactors_
#eventGenerators_
#stateInfo_
#logger_
smacc2::SignalDetector
+ SignalDetector()
+ initialize()
+ setProcessorHandle()
+ runThread()
+ join()
+ stop()
+ terminateScheduler()
+ pollingLoop()
+ postEvent()
+ getNode()
+ getLogger()
+ notifyStateConfigured()
+ notifyStateExited()
+ notifyRosInitialized()
- pollOnce()
- findUpdatableClientsAndComponents()
- findUpdatableStateElements()
smacc2::ISmaccOrthogonal
+ setStateMachine()
+ getStateMachine()
+ initState()
+ addClientBehavior()
+ runtimeConfigure()
+ onEntry()
+ onExit()
+ onDispose()
+ getName()
+ requiresComponent()
+ requiresClient()
+ getClients()
+ getClientBehaviors()
+ setGlobalSMData()
+ getGlobalSMData()
+ getClientBehavior()
+ getNode()
+ getLogger()
# onInitialize()
# initializeClients()
# assignClientToOrthogonal()
smacc2::ISmaccState
+ getStateMachine()
+ getName()
+ getParentState()
+ getNode()
+ getLogger()
+ getClassName()
+ configure()
+ requiresComponent()
+ requiresClient()
+ getGlobalSMData()
+ setGlobalSMData()
+ createStateReactor()
+ createStateReactor()
+ createEventGenerator()
+ postEvent()
+ postEvent()
+ notifyTransition()
+ notifyTransitionFromTransition TypeInfo()
+ getStateReactors()
+ getEventGenerators()
+ getOrthogonal()
+ getClientBehavior()
+ getEventGenerator()
+ getStateReactor()
map< smacc2::ComponentKey, std::shared_ptr< smacc2 ::ISmaccComponent > >
boost::signals2::signal < Signature, optional _last_value< typename boost ::function_traits< Signature >::result_type >, int, std ::less< int >, function< Signature >, typename extended_signature< function_traits< Signature >::arity, Signature >::function_type, boost:: signals2::mutex >
-stateMachine_
-stateMachine_
-postEventActivate
-postEventActiveShutdown
-postEventCleanup
-postEventConfigure
-postEventDeactivate
-postEventDestroy
-postEventInactive Shutdown_
-postEventOnActivate Error_
-postEventOnActivate Failure_
-postEventOnActivateSuccess_
-postFailureEventFn
-postFinishEventFn
-postSuccessEventFn_
+onTransitionActivate
+onTransitionActiveShutdown
+onTransitionCleanup
+onTransitionConfigure
+onTransitionCreate
+onTransitionDeactivate
+onTransitionDestroy
+onTransitionInactive Shutdown_
+onTransitionOnActivate Error_
+onTransitionOnActivate Failure_
-onFailure_
-onFinished_
-onSuccess_
-onEntryThread_
-onExitThread_
#components_
#stateMachine_
-nodeName_
#orthogonal_
-currentOrthogonal
-currentState
-client_change_state
-client_get_state_
-isShutdownRequested_
-eventMutex_
smacc2::ISmaccClient
+ ISmaccClient()
+ ~ISmaccClient()
+ onInitialize()
+ getName()
+ getComponent()
+ getComponent()
+ getComponent()
+ getType()
+ getStateMachine()
+ connectSignal()
+ requiresClient()
+ getComponents()
+ iterateComponents()
+ postEvent()
+ postEvent()
# onComponentInitialization()
# onStateOrthogonalAllocation()
# createComponent()
# createNamedComponent()
# getNode()
# getLogger()
- initialize()
- setStateMachine()
- setOrthogonal()
smacc2::SmaccSignal < Signature, Combiner, Group, GroupCompare, SlotFunction, ExtendedSlotFunction, Mutex >
boost::signals2::signal < void(), optional_last _value< typename boost:: function_traits< void()> ::result_type >, int, std ::less< int >, function< void ()>, typename extended_signature < function_traits< void()>::arity, void()>::function_type, boost::signals2::mutex >
smacc2::ISmaccClientBehavior
+ ISmaccClientBehavior()
+ ~ISmaccClientBehavior()
+ getStateMachine()
+ getName()
+ requiresClient()
+ requiresComponent()
+ requiresComponent()
+ onEntry()
+ onExit()
+ executeOnEntry()
+ executeOnExit()
# runtimeConfigure()
# postEvent()
# postEvent()
# getCurrentState()
# dispose()
# getNode()
# getLogger()
- onStateOrthogonalAllocation()
-nodeName_
#owner_
< void()>
smacc2::ISmaccComponent
+ ISmaccComponent()
+ ~ISmaccComponent()
+ getName()
# onInitialize()
# onComponentInitialization()
# postEvent()
# postEvent()
# onStateOrthogonalAllocation()
# requiresComponent()
# requiresComponent()
# requiresClient()
# createSiblingComponent()
# createSiblingNamedComponent()
# getNode()
# getLogger()
# getStateMachine()
- initialize()
- setStateMachine()
SharedPtr
function< void()>
smacc2::SmaccSignal < void()>
optional< std::future < int > >
-lastTransitionEvent
-subscription_
cl_lifecycle_node:: CbLifecycleEventMonitor
+ onTransitionUnconfigured Shutdown_
+ onTransitionOnConfigureSuccess_
+ onTransitionOnConfigureFailure_
+ onTransitionOnConfigureError_
+ onTransitionOnActivateSuccess_
+ onTransitionOnDeactivate Success_
+ onTransitionOnDeactivate Failure_
+ onTransitionOnDeactivate Error_
+ onTransitionOnCleanupSuccess_
+ onTransitionOnCleanupFailure_
+ onTransitionOnCleanupError_
+ onTransitionOnShutdownSuccess_
+ onTransitionOnShutdownFailure_
+ onTransitionOnShutdownError_
+ onTransitionOnActiveShutdown Success_
+ onTransitionOnActiveShutdown Failure_
+ onTransitionOnActiveShutdown Error_
+ onTransitionOnErrorSuccess_
+ onTransitionOnErrorFailure_
+ onTransitionOnErrorError_
- postEventUnconfiguredShutdown_
- postEventOnConfigureSuccess_
- postEventOnConfigureFailure_
- postEventOnConfigureError_
- postEventOnDeactivateSuccess_
- postEventOnDeactivateFailure_
- postEventOnDeactivateError_
- postEventOnCleanupSuccess_
- postEventOnCleanupFailure_
- postEventOnCleanupError_
- postEventOnShutdownSuccess_
- postEventOnShutdownFailure_
- postEventOnShutdownError_
- postEventOnErrorSuccess_
- postEventOnErrorFailure_
+ CpLifecycleEventMonitor()
+ ~CpLifecycleEventMonitor()
+ setOwner()
+ getLastTransitionEvent()
+ onInitialize()
+ onStateOrthogonalAllocation()
- onTransitionEvent()
smacc2::SmaccAsyncClient Behavior
+ onStateOrthogonalAllocation()
+ ~SmaccAsyncClientBehavior()
+ onSuccess()
+ onFinished()
+ onFailure()
+ requestForceFinish()
+ executeOnEntry()
+ executeOnExit()
+ waitOnEntryThread()
+ onSuccess()
+ onFinished()
+ onFailure()
# postSuccessEvent()
# postFailureEvent()
# dispose()
# isShutdownRequested()
- waitFutureIfNotFinished()
string
-node_change_state _topic_
-node_get_state _topic_
-eventMonitor_
-eventMonitor_
cl_lifecycle_node:: CLifecycleNode
+ CLifecycleNode()
+ ~CLifecycleNode()
+ onInitialize()
+ changeState()
+ configure()
+ activate()
+ deactivate()
+ cleanup()
+ shutdown()
+ destroy()
+ onStateOrthogonalAllocation()
-lifecycleNodeClient_
cl_lifecycle_node:: CbDeactivateOnExit
+ CbDeactivateOnExit()
+ ~CbDeactivateOnExit()
+ onStateOrthogonalAllocation()
+ onExit()