cl_px4_mr::CbVSSearch
+ CbVSSearch()
+ setParams()
+ params()
+ setDatum()
# buildPath()
# behaviorName()
-params_
cl_px4_mr::CbPx4PathFollowerBase
+ CbPx4PathFollowerBase()
+ ~CbPx4PathFollowerBase()
+ onStateOrthogonalAllocation()
+ setFollowerParams()
+ followerParams()
+ onEntry()
+ onExit()
+ update()
# buildPath()
# behaviorName()
# onPathStarted()
# onPathCompleted()
# totalLength()
# progressFraction()
# carrotVertexIndex()
- commandFor()
- applyCentering()
- tangentYawAt()
vector< cl_px4_mr::NedPoint >
vector< float >
atomic< size_t >
-path_
-cumLen_
-carrotVertex_
cl_px4_mr::CbPx4ClientBehaviorBase
+ onStateOrthogonalAllocation()
+ ~CbPx4ClientBehaviorBase()
+ setTimeout()
+ hasTimeout()
+ update()
# wireCompletionSignals()
# postPx4Success()
# postPx4Failure()
#offboardKeepAlive_
#trajectorySetpoint_
-watchdogStart_
optional< std::chrono::steady_clock::time_point >
cl_px4_mr::CpTunnelCentering
cl_px4_mr::CpOffboardKeepAlive
cl_px4_mr::CpGoalChecker
cl_px4_mr::CpTrajectorySetpoint
cl_px4_mr::CpVehicleLocalPosition
cl_px4_mr::CpVehicleCommand
cl_px4_mr::CpVehicleStatus
cl_px4_mr::MapProjection
cl_px4_mr::NedPoint
cl_px4_mr::FlightPatternVSSearchParams
cl_px4_mr::PathFollowerParams
cl_px4_mr::TunnelCenteringParams
smacc2::client_core_components::CpTopicSubscriber< MessageType >
smacc2::client_core_components::CpTopicSubscriber< sensor_msgs::msg::PointCloud2 >
smacc2::SmaccSignal< void() >
smacc2::ISmaccUpdatable
smacc2::ISmaccComponent
smacc2::ISmaccClient
smacc2::ISmaccOrthogonal
smacc2::ISmaccStateMachine
smacc2::ISmaccState
smacc2::ISmaccClientBehavior
smacc2::SmaccAsyncClientBehavior
smacc2::SignalDetector
smacc2::introspection::SmaccStateInfo
SharedPtr
mutex
bool
int
float
double
string
Turn
YawMode
TrajectorySetpoint
time_point
atomic< int64_t >
atomic< bool >
function< void()>