
map< const std::type_info *, std::vector< smacc2::introspection::ClientBehaviorVmiEntry > >
map< const std::type_info *, std::vector< std::shared_ptr< smacc2::introspection::SmaccStateReactorInfo > > >
map< const std::type_info *, std::vector< std::shared_ptr< smacc2::introspection::SmaccEventGeneratorInfo > > >
weak_ptr< smacc2::introspection::SmaccStateMachineInfo >
weak_ptr< smacc2::introspection::SmaccStateInfo >
vector< smacc2::introspection::SmaccTransitionInfo >
vector< std::shared_ptr< smacc2::introspection::SmaccStateInfo > >
type_info *
std::enable_shared_from_this< SmaccStateInfo >
string
seconds
optional< std::string >
vector< std::string >
int
SharedPtr
shared_ptr< smacc2::introspection::SmaccStateMachineInfo >
recursive_mutex
atomic< StateMachineInternalAction >
map< void *, std::shared_ptr< smacc2::CallbackCounterSemaphore > >
map< std::string, std::pair< std::function< std::string(vector< boost::any > >
vector< smacc2_msgs::msg::SmaccTransitionLogEntry >
SMRuntimeMode
int64_t
SharedPtr
vector< smacc2::ISmaccState * >
shared_ptr< smacc2::introspection::SmaccStateInfo >
SmaccStatus
map< std::string, std::shared_ptr< smacc2::ISmaccOrthogonal > >
SharedPtr
smacc2::introspection::SmaccStateInfo
vector< std::shared_ptr< smacc2::ISmaccEventGenerator > >
shared_ptr< rclcpp::Logger >
vector< std::shared_ptr< smacc2::ISmaccReactor > >
cl_gcalcli::GcalcliConfig
vector< std::vector< std::shared_ptr< smacc2::ISmaccStateReactor > > >
vector< std::shared_ptr< smacc2::ISmaccClient > >
mutex
atomic< bool >
vector< smacc2::ISmaccUpdatable * >
vector< std::vector< smacc2::ISmaccUpdatable * > >
double
SmaccFifoScheduler *
processor_handle
thread
ExecutionModel
smacc2::ISmaccStateMachine
+ ISmaccStateMachine()
+ ~ISmaccStateMachine()
+ reset()
+ stop()
+ eStop()
+ joinAsyncClientBehaviorThreads()
+ getOrthogonal()
+ getClientBehavior()
+ getOrthogonals()
+ requiresComponent()
+ requiresComponent()
+ postEvent()
+ postEvent()
+ getGlobalSMData()
+ setGlobalSMData()
+ getStateMachineName()
+ state_machine_visualization()
+ getCurrentStateInfo()
+ publishTransition()
+ onInitialize()
+ getTransitionLogHistory()
+ createSignalConnection()
+ disconnectSmaccSignalObject()
+ disconnectSmaccSignalObject()
+ notifyOnStateEntryStart()
+ notifyOnStateEntryEnd()
+ notifyOnRuntimeConfigured()
+ notifyOnStateExiting()
+ notifyOnStateExited()
+ notifyOnRuntimeConfiguration Finished()
+ getCurrentStateCounter()
+ getCurrentState()
+ getStateMachineInfo()
+ buildStateMachineInfo()
+ getNode()
+ getLogger()
+ getMutex()
# checkStateMachineConsistence()
# initializeROS()
# onInitialized()
# createOrthogonal()
- lockStateMachine()
- unlockStateMachine()
- propagateEventToStateReactors()
- updateStatusMessage()
smacc2::introspection::SmaccStateInfo
+ SmaccStateInfo()
+ getStateLevel()
+ getStateMachineInfo()
+ getParentState()
+ depth()
+ getAncestors()
+ getFullPath()
+ createChildState()
+ declareTransition()
+ toShortName()
+ getDemangledFullName()
+ getNode()
+ getLogger()
smacc2::ISmaccState
+ ~ISmaccState()
+ getStateMachine()
+ getName()
+ getParentState()
+ getNode()
+ getLogger()
+ getClassName()
+ configure()
+ requiresComponent()
+ requiresComponent()
+ requiresClient()
+ getGlobalSMData()
+ setGlobalSMData()
+ createStateReactor()
+ createStateReactor()
+ createEventGenerator()
+ postEvent()
+ postEvent()
+ notifyTransition()
+ notifyTransitionFromTransition TypeInfo()
+ getStateReactors()
+ getEventGenerators()
+ getOrthogonal()
+ getClientBehavior()
+ getEventGenerator()
+ getStateReactor()
smacc2::ISmaccOrthogonal
+ ~ISmaccOrthogonal()
+ setStateMachine()
+ getStateMachine()
+ initState()
+ addClientBehavior()
+ runtimeConfigure()
+ onEntry()
+ onExit()
+ onDispose()
+ getName()
+ requiresComponent()
+ requiresClient()
+ getClients()
+ getClientBehaviors()
+ setGlobalSMData()
+ getGlobalSMData()
+ getClientBehavior()
+ getNode()
+ getLogger()
# orInitialize()
- initializeClients()
assignClientToOrthogonal()
- currentClientBehaviors()
map< smacc2::ComponentKey, std::shared_ptr< smacc2 ::ISmaccComponent > >
smacc2::ISmaccClientBehavior
+ ISmaccClientBehavior()
+ ~ISmaccClientBehavior()
+ getStateMachine()
+ getName()
+ requiresClient()
+ requiresComponent()
+ requiresComponent()
+ onEntry()
+ onExit()
+ executeOnEntry()
+ executeOnExit()
# runtimeConfigure()
# postEvent()
# postEvent()
# getCurrentState()
# dispose()
# getNode()
# getLogger()
- orStateOrthogonalAllocation()
smacc2::ISmaccClient
+ ISmaccClient()
+ ~ISmaccClient()
+ orInitialize()
+ getName()
+ getComponent()
+ getComponent()
+ getComponent()
+ getType()
+ getStateMachine()
+ connectSignal()
+ requiresClient()
+ getComponents()
+ iterateComponents()
+ postEvent()
+ postEvent()
# onComponentInitialization()
# orStateOrthogonalAllocation()
# createComponent()
# createNamedComponent()
# getNode()
# getLogger()
- initialize()
- setStateMachine()
- setOrthogonal()
smacc2::ISmaccComponent
+ ISmaccComponent()
+ ~ISmaccComponent()
+ getName()
# orInitialize()
# onComponentInitialization()
# postEvent()
# postEvent()
# orStateOrthogonalAllocation()
# requiresComponent()
# requiresComponent()
# requiresClient()
# createSiblingComponent()
# createSiblingNamedComponent()
# getNode()
# getLogger()
# getStateMachine()
- initialize()
- setStateMachine()
smacc2::SignalDetector
+ SignalDetector()
+ initialize()
+ setProcessorHandle()
+ runThread()
+ join()
+ stop()
+ terminateSchedular()
+ joinAsyncClientBehaviorThreads()
+ pollingLoop()
+ postEvent()
+ queueWorkItem()
+ getNode()
+ getLogger()
+ notifyStateConfigured()
+ notifyStateExited()
+ notifyRosInitialized()
- pollOnce()
- findUpdatableClientsAndComponents()
- findUpdatableStateElements()
smacc2::SmaccSignal
< Signature, Combiner, Group, GroupCompare, SlotFunction, ExtendedSlotFunction, Mutex >
boost::signals2::signal
< Signature, optional last_value= typename boost ::function_traits< Signature >::result_type >, int, std ::less< int >, function< Signature >, typename extended_signature< function_traits< Signature >::arity, Signature >::function_type, boost::signals2::mutex >
boost::signals2::signal
< void(const std::string &error), optional_last_value< typename boost::function_traits< void(const std::string &error)>::result_type >, int, std ::less< int >, function< void(const std::string &error)>, typename extended _signature< function_traits< void(const std::string &error)>::arity, void(const std::string &error)>::function_type, boost ::signals2::mutex >
boost::signals2::signal
< void(int exit_code, const std::string &output), optional_last_value< typename boost::function_traits< void (int exit_code, const std::string &output)>::result_type >, int, std ::less< int >, function< void(int exit _code, const std::string &output)>, typename extended_signature< function_traits< void (int exit_code, const std::string &output)>::arity, void(int exit_code, const std::string &output)>::function_type, boost::signals2::mutex >
boost::signals2::signal
< void(const std::vector < cl_gcalcli::CalendarEvent > &), optional_last_value< typename boost::function_traits< void(const std::vector< cl_gcalcli::CalendarEvent > &)>::result_type >, int, std::less< int >, function< void(const std::vector< cl_gcalcli ::CalendarEvent > &)>, typename extended _signature< function_traits< void(const std::vector< cl_gcalcli::CalendarEvent > &)>::arity, void(const std::vector< cl_gcalcli ::CalendarEvent > &)>::function_type, boost::signals2::mutex >
boost::signals2::signal
< void(const cl_gcalcli ::CalendarEvent &), optional _last_value< typename boost ::function_traits< void(const cl_gcalcli::CalendarEvent &)>::result_type >, int, std::less< int >, function< void(const cl_gcalcli ::CalendarEvent &)>, typename extended_signature< function_traits < void(const cl_gcalcli::CalendarEvent &)>::arity, void(const cl_gcalcli::CalendarEvent &)>::function_type, boost::signals2::mutex >
boost::signals2::signal
< void(const cl_gcalcli ::CalendarEvent &, const std::string &), optional _last_value< typename boost ::function_traits< void(const cl_gcalcli::CalendarEvent &, const std::string &)>::result _type >, int, std::less< int >, function< void(const cl_gcalcli ::CalendarEvent &, const std::string &)>, typename extended_signature< function _traits< void(const cl_gcalcli::CalendarEvent &, const std::string &)>::arity, void(const cl_gcalcli::CalendarEvent &, const std::string &)>::function_type, boost::signals2::mutex >
boost::signals2::signal
< void(const cl_gcalcli ::CalendarEvent &), optional _last_value< typename boost ::function_traits< void(const cl_gcalcli::CalendarEvent &)>::result_type >, int, std::less< int >, function< void(const cl_gcalcli ::CalendarEvent &)>, typename extended_signature< function_traits < void(const cl_gcalcli::CalendarEvent &)>::arity, void(const cl_gcalcli::CalendarEvent &)>::function_type, boost::signals2::mutex >
cl_gcalcli::CGcalcli
+ CGcalcli()
+ ~CGcalcli()
+ ~CGcalcli()
+ configure()
+ getConfig()
+ onComponentInitialization()
+ getConnection()
+ getPoller()
+ getEventListener()
optional< std::future < int > >
function< void()>
smacc2::SmaccSignal < void()>
bool
smacc2::SmaccSignal < void(const std::string &error)>
smacc2::SmaccSignal < void(int exit_code, const std::string &output)>
smacc2::SmaccComponent
+ ISmaccComponent()
+ ~ISmaccComponent()
+ getName()
# orInitialize()
# onComponentInitialization()
# postEvent()
# postEvent()
# orStateOrthogonalAllocation()
# requiresComponent()
# requiresComponent()
# requiresClient()
# createSiblingComponent()
# createSiblingNamedComponent()
# getNode()
# getLogger()
# getStateMachine()
- initialize()
- setStateMachine()
optional< rclcpp::Time >
optional< rclcpp::Duration >
smacc2::SmaccSignal < void(const std::vector < cl_gcalcli::CalendarEvent > &)>
smacc2::SmaccSignal < void(const cl_gcalcli ::CalendarEvent &, const std::string &)>
smacc2::SmaccSignal < void(const cl_gcalcli ::CalendarEvent &)>
smacc2::ISmaccUpdatable
+ ISmaccUpdatable()
+ ISmaccUpdatable()
+ ~ISmaccUpdatable()
+ executeUpdate()
- setUpdatePeriod()
update()
smacc2::SmaccAsyncClient Behavior
+ orStateOrthogonalAllocation()
+ ~SmaccAsyncClientBehavior()
+ orSuccess()
+ onFinished()
+ onFailure()
+ requestForceFinish()
+ executeOnEntry()
+ executeOnExit()
+ waitOnEntryThread()
+ orSuccess()
+ onFinished()
+ onFailure()
# postSuccessEvent()
# postFailureEvent()
# dispose()
# isShutdownRequested()
- waitFutureIfNotFinished()
smacc2::client_core _components::CpSubprocessExecutor
+ CpSubprocessExecutor()
+ ~CpSubprocessExecutor()
+ onInitialize()
+ executeCommand()
+ executeCommandAsync()
+ onCommandCompleted()
+ onCommandFailed()
ConnectionState
time_point
cl_gcalcli::CpGcalcliConnection
+ CpGcalcliConnection()
+ ~CpGcalcliConnection()
+ onInitialize()
+ configure()
+ getConnectionState()
+ isConnected()
+ checkConnection()
+ restartConnection()
+ executeGcalcli()
+ getConfig()
+ onConnectionLost()
+ onConnectionRestored()
+ onAuthenticationRequired()
+ onStateOrthogonalAllocation()
# update()
- performHeartbeat()
- handleConnectionStateChange()
- isAuthenticationError()
time_point
function< void(const std::vector< cl_gcalcli ::CalendarEvent > &)>
vector< cl_gcalcli ::CalendarEvent >
cl_gcalcli::CpCalendarPoller
+ CpCalendarPoller()
+ ~CpCalendarPoller()
+ onInitialize()
+ refreshAgenda()
+ getEvents()
+ findEvents()
+ getEventsInWindow()
+ getActiveEvents()
+ getLastPollTime()
+ onAgendaUpdated()
+ onStateOrthogonalAllocation()
# update()
- parseTevOutput()
- parseTevLine()
- parseDateTime()
- generateEventId()
function< void(const cl_gcalcli::CalendarEvent &, const std::string &)>
function< void(const cl_gcalcli::CalendarEvent &)>
vector< cl_gcalcli ::EventWatch >
bst< std::string >
cl_gcalcli::CpCalendarEvent Listener
+ CpCalendarEventListener()
+ ~CpCalendarEventListener()
+ onInitialize()
+ addWatch()
+ clearWatches()
+ getWatches()
+ resetTriggeredEvents()
+ onEventDetected()
+ onEventStarted()
+ onEventEnded()
+ onStateOrthogonalAllocation()
# update()
- onAgendaUpdated()
- matchesPattern()
- shouldTriggerStart()
- shouldTriggerEnd()
- getTriggeredKey()
optional< cl_gcalcli ::CalendarEvent >
cl_gcalcli::ClEventDetect
+ ClEventDetect()
+ ~ClEventDetect()
+ onEntry()
+ onExit()
+ getDetectedEvent()
- onEventStarted()