
smacc2::ISmaccStateMachine
+ ISmaccStateMachine()
+ ~ISmaccStateMachine()
+ reset()
+ stop()
+ eStop()
+ getOrthogonal()
+ getClientBehavior()
+ getOrthogonals()
+ requiresComponent()
+ postEvent()
+ postEvent()
+ getGlobalSMData()
+ setGlobalSMData()
+ getStateMachineName()
+ state_machine_visualization()
+ getCurrentStateInfo()
+ publishTransition()
+ onInitialize()
+ getTransitionLogHistory()
+ createSignalConnection()
+ disconnect(SmaccSignalObject)
+ notifyOnStateEntryStart()
+ notifyOnStateEntryEnd()
+ notifyOnRuntimeConfigured()
+ notifyOnStateExiting()
+ notifyOnStateExited()
+ notifyOnRuntimeConfiguration Finished()
+ getCurrentStateCounter()
+ getCurrentState()
+ getStateMachineInfo()
+ buildStateMachineInfo()
+ getNode()
+ getLogger()
+ getMutex()
# checkStateMachineConsistence()
# initializeROS()
# onInitialized()
# createOrthogonal()
- lockStateMachine()
- unlockStateMachine()
- propagateEventToStateReactors()
- updateStatusMessage()
smacc2::ISmaccOrthogonal
+ setStateMachine()
+ getStateMachine()
+ initState()
+ addClientBehavior()
+ runtimeConfigure()
+ onEntry()
+ onExit()
+ onDispose()
+ getName()
+ requiresComponent()
+ requiresClient()
+ getClients()
+ getClientBehaviors()
+ setGlobalSMData()
+ getGlobalSMData()
+ getClientBehavior()
+ getNode()
+ getLogger()
# onInitialize()
# initializeClients()
# assignClientToOrthogonal()
smacc2::ISmaccClient
+ ISmaccClient()
+ ~ISmaccClient()
+ onInitialize()
+ getName()
+ getComponent()
+ getComponent()
+ getComponent()
+ getType()
+ getStateMachine()
+ connectSignal()
+ requiresClient()
+ getComponents()
+ iterateComponents()
+ postEvent()
+ postEvent()
# onComponentInitialization()
# onStateOrthogonalAllocation()
# createComponent()
# createNamedComponent()
# getNode()
# getLogger()
- initialize()
- setStateMachine()
- setOrthogonal()
smacc2::ISmaccClientBehavior
+ ISmaccClientBehavior()
+ ~ISmaccClientBehavior()
+ getStateMachine()
+ getName()
+ requiresClient()
+ requiresComponent()
+ onEntry()
+ onExit()
+ executeOnEntry()
+ executeOnExit()
# runtimeConfigure()
# postEvent()
# postEvent()
# getCurrentState()
# dispose()
# getNode()
# getLogger()
- onStateOrthogonalAllocation()
smacc2::ISmaccComponent
+ ISmaccComponent()
+ ~ISmaccComponent()
+ getName()
+ onInitialize()
# onComponentInitialization()
# postEvent()
# postEvent()
# onStateOrthogonalAllocation()
# requiresComponent()
# requiresComponent()
# requiresClient()
# createSiblingComponent()
# createSiblingNamedComponent()
# getNode()
# getLogger()
- getStateMachine()
- initialize()
- setStateMachine()
smacc2::ISmaccState
+ getStateMachine()
+ getName()
+ getParentState()
+ getNode()
+ getLogger()
+ getClassName()
+ configure()
+ requiresComponent()
+ requiresClient()
+ getGlobalSMData()
+ setGlobalSMData()
+ createStateReactor()
+ createStateReactor()
+ createEventGenerator()
+ postEvent()
+ postEvent()
+ notifyTransition()
+ notifyTransitionFromTransition TypeInfo()
+ getStateReactors()
+ getEventGenerators()
+ getOrthogonal()
+ getClientBehavior()
+ getEventGenerator()
+ getStateReactor()
smacc2::introspection ::SmaccStateInfo
+ SmaccStateInfo()
+ getStateLevel()
+ depth()
+ getAncestors()
+ getFullPath()
+ createChildState()
+ declareTransition()
+ toShortName()
+ getDemangledFullName()
+ getNode()
+ getLogger()
smacc2::SignalDetector
+ SignalDetector()
+ initialize()
+ setProcessorHandle()
+ runThread()
+ join()
+ stop()
+ terminateScheduler()
+ pollingLoop()
+ postEvent()
+ getNode()
+ getLogger()
+ notifyStateConfigured()
+ notifyStateEveled()
+ notifyRosInitialized()
- pollOnce()
- findUpdatableClientsAndComponents()
- findUpdatableStateElements()
cl_nav2z::CpPose
+ CpPose()
+ CpPose()
+ onInitialize()
+ update()
+ waitTransformUpdate()
+ toPoseMsg()
+ toPoseStampedMsg()
+ getYaw()
+ getX()
+ getY()
+ getZ()
+ setReferenceFrame()
+ getReferenceFrame()
+ getFrameId()
+ freezeReferenceFrame()
+ unfreezeReferenceFrame()
smacc2::ISmaccUpdatable
+ ISmaccUpdatable()
+ ISmaccUpdatable()
+ execute(Update)
+ setUpdatePeriod()
# update()
smacc2::SmaccAsyncClient Behavior
+ onStateOrthogonalAllocation()
+ ~SmaccAsyncClientBehavior()
+ onSuccess()
+ onFinished()
+ onFailure()
+ requestForceFinish()
+ executeOnEntry()
+ executeOnExit()
+ waitOnEntryThread()
+ onSuccess()
+ onFinished()
+ onFailure()
# postSuccessEvent()
# postFailureEvent()
# dispose()
# isShutdownRequested()
- waitFutureIfNotFinished()
cl_nav2z::components ::CpNav2ActionInterface
+ CpNav2ActionInterface()
+ ~CpNav2ActionInterface()
+ sendNavigationGoal()
+ sendGoal()
+ cancelNavigation()
+ isNavigationServerReady()
+ waitForNavigationServer()
+ onComponentInitialization()
+ onInitialize()
+ getActionClient()
+ onNavigationSucceeded()
+ onNavigationAborted()
+ onNavigationCancelled()
+ onNavigationFeedback()
- onNavigationSuccessCallback()
- onNavigationAbortedCallback()
- onNavigationCanceledCallback()
- onNavigationFeedbackCallback()
smacc2::client_core _components::CpActionClient < ActionType >
+ CpActionClient()
+ CpActionClient()
+ ~CpActionClient()
+ sendGoal()
+ cancelGoal()
+ isServerReady()
+ waitForServer()
+ onInitialize()
+ onComponentInitialization()
+ onSucceeded()
+ onAborted()
+ onCancelled()
+ onFeedback()
+ getActionClient()
- onFeedback()
- onResult()
- postResultEvent()
smacc2::client_core _components::CpActionClient < nav2_msgs::action::NavigateToPose >
+ CpActionClient()
+ CpActionClient()
+ ~CpActionClient()
+ sendGoal()
+ cancelGoal()
+ isServerReady()
+ waitForServer()
+ onInitialize()
+ onComponentInitialization()
+ onSucceeded()
+ onAborted()
+ onCancelled()
+ onFeedback()
+ getActionClient()
- onFeedback()
- onResult()
- postResultEvent()
cl_nav2z::CbNav2ZClientBehaviorBase
+ ~CbNav2ZClientBehaviorBase()
+ onStateOrthogonalAllocation()
# sendGoal()
# cancelGoal()
# onNavigationSucceeded()
# onNavigationAborted()
# onNavigationCancelled()
# onNavigationResult()
# onNavigationActionSuccess()
# onNavigationActionAborted()
cl_nav2z::CbUndoPathBackwards
+ CbUndoPathBackwards()
+ onEntry()
+ onExit()
cl_nav2z::odom_tracker ::CpOdomTracker
+ CpOdomTracker()
+ processNewPose()
+ odomMessageCallback()
+ update()
+ setWorkingMode()
+ setPublishMessages()
+ pushPath()
+ pushPath()
+ popPath()
+ clearPath()
+ setStartPoint()
+ setStartPoint()
+ setCurrentMotionGoal()
+ setCurrentPathName()
+ getCurrentMotionGoal()
+ getPath()
+ logStateString()
+ updateParameters()
+ setOdomFrame()
# onInitialize()
# updateConfigurations()
# rtPublishPath()
# updateRecordPath()
# updateClearPath()
# updateAggregatedStackPath()
# parametersCallback()
boost::signals2::signal < void(const Feedback &)>
boost::signals2::signal < void(const WrappedResult &)>
boost::signals2::signal < void(), optional_last_value< typename boost::function_traits< void()>::result_type >, int, std::less< int >, function< void() >, typename extended_signature< function_traits< void()>::arity, void()>::function_type, boost::signals2::mutex >
smacc2::SmaccSignal < void(const Feedback &)>
smacc2::SmaccSignal < void(const WrappedResult &)>
smacc2::SmaccSignal < void()>
function< void(const Feedback &)>
function< void(const WrappedResult &)>
function< void()>
optional< std::shared _future< typename rclcpp _action::Client< nav2_msgs ::action::NavigateToPose > ::CancelResponse::SharedPtr > >
optional< std::shared _future< typename rclcpp ::action::Client< ActionType > ::CancelResponse::SharedPtr > >
optional< std::shared _ptr< GoalHandle ::SharedPtr > >
optional< std::chrono ::milliseconds >
FeedbackCallback
shared_ptr< ActionClient >
optional< std::string >
optional< std::future < int > >
optional< rclcpp::Duration >
optional< rclcpp::Time >
shared_ptr< tf2_ros ::Buffer >
optional< cl_nav2z ::CbUndoPathBackwardsOptions >
ResultCode
PoseStamped
shared_ptr< tf2_ros ::Buffer >
shared_ptr< tf2_ros ::TransformListener >
mutex
SharedPtr
Path
WorkingMode
vector< nav_msgs::msg ::Path >
vector< cl_nav2z::odom _tracker::CpOdomTracker ::PathInfo >
OdomTrackerStrategy
optional< geometry _msgs::msg::PoseStamped >
vector< std::shared _ptr< smacc2::introspection ::SmaccStateInfo > >
type_info *
string
vector< std::shared _ptr< smacc2::ISmaccClient > >
vector< std::vector < std::shared_ptr< smacc2 ::ISmaccClientBehavior > > >
mutex
vector< std::shared _ptr< smacc2::StateReactor > >
vector< std::shared _ptr< smacc2::EventGenerator > >
shared_ptr< rclcpp ::Logger >
vector< std::vector < smacc2::ISmaccUpdatable * > >
atomic< int64_t >
vector< smacc2::ISmaccUpdatable * >
atomic< bool >
SmaccFifoScheduler *
processor_handle
thread
ExecutionModel
double
map< std::string, std ::shared_ptr< smacc2 ::ISmaccComponent > >
map< std::string, std ::pair< std::function < void(string)>, boost ::any > >
map< void *, std::shared _ptr< smacc2::CallbackCounterSemaphore > >
map< std::string, std ::shared_ptr< smacc2 ::introspection::SmaccState Info > >
map< const std::type _info *, std::vector < std::shared_ptr< smacc2 ::introspection::SmaccStateReactor Info > > >
map< const std::type _info *, std::vector < std::shared_ptr< smacc2 ::introspection::SmaccEventGenerator Info > > >
map< const std::type _info *, std::vector < std::shared_ptr< smacc2 ::introspection ::ISmaccClientBehaviorInfoEntry > > >
vector< smacc2::ISmaccState * >
vector< smacc2::ISmaccComponent * >
vector< smacc2::ISmaccStateReactor * >
vector< smacc2::ISmaccEventGenerator * >
vector< smacc2::ISmaccClientBehavior * >
vector< smacc2::introspection ::SmaccTransitionInfo >
vector< smacc2::ISmaccUpdatable * >
vector< nav_msgs::msg ::Path >
vector< cl_nav2z::odom _tracker::CpOdomTracker ::PathInfo >
vector< std::shared _ptr< smacc2::introspection ::SmaccStateInfo > >
vector< std::shared _ptr< smacc2::ISmaccClient > >
vector< std::vector < std::shared_ptr< smacc2 ::ISmaccClientBehavior > > >
vector< std::shared _ptr< smacc2::StateReactor > >
vector< std::shared _ptr< smacc2::EventGenerator > >
vector< std::vector < smacc2::ISmaccUpdatable * > >
vector< smacc2::ISmaccUpdatable * >
vector< nav_msgs::msg ::Path >
vector< cl_nav2z::odom _tracker::CpOdomTracker ::PathInfo >
vector< std::shared _ptr< smacc2::introspection ::SmaccStateInfo > >
#currentState_
#status_msg_
#orthogonals_
#eventQueueMutex_ m_mutex_
#stateMachineCurrentAction
#stateCallbackConnections
#globalData_
#transitionLogHistory_
#onMode_
#stateSeqCounter_
#m_
#eventInfo_logPub #stateMachineInfoPub_
#stateMachineStatus Pub_ #transitionHistory _service #transitionLogPub_
#currentStateInfo_
#stateMachineInfo_
#timer_
#parentState_
#stateMachine_
#staticBehaviorInfo
#stateReactorsInfo
#eventGeneratorsInfo
#depth_ #stateIndex_
#transitions_
#children_
#id_
+demangledStateName +fullStateName
#node_
#statusPub_
#clientBehaviors_
#mutex_
#stateMachine_
#stateReactors_
#smaccStateMachine_
#eventGenerators_
#logger_
#stateInfo_
#signalDetector_
#updatableStateElements_
#getState_
#updatableClients_
#end_ #initialized_ #startInitialized_
#scheduler_
#processorHandle_
#signalDetectorThread_
#executionModel_
#loop_rate_hz_
boost::signals2::signal < void(), optional_last _value< typename boost ::function_traits< Signature >::result_type >, int, std ::less< int >, function< Signature >, typename extended_signature< function_traits< Signature >::arity, Signature>::function_type, boost: :signals2::mutex >
boost::signals2::signal < void(const Feedback &), optional_last_value < typename boost::function _traits< void(const Feedback &)>::result_type >, int, std ::less< int >, function< void (const Feedback &)>, typename extended _signature< function_traits< void(const Feedback &)>::arity, void(const Feedback &)>::function_type, boost::signals2::mutex >
boost::signals2::signal < void(const WrappedResult &)>, optional_last_value < typename boost::function _traits< void(const WrappedResult &)>::result_type >, int, std ::less< int >, function< void(const WrappedResult &)>, typename extended _signature< function_traits< void(const WrappedResult &)>::arity, void(const WrappedResult &)>::function_type, boost::signals2::mutex >
boost::signals2::signal < void(), optional_last _value< typename boost:: function_traits< void()>::result_type >, int, std ::less< int >, function< void ()>, typename extended_signature < function_traits< void()>::arity, void()>::function_type, boost::signals2::mutex >
smacc2::SmaccSignal < void(const Feedback &)>
smacc2::SmaccSignal < void(const WrappedResult &)>
smacc2::SmaccSignal < void()>
optional< std::shared _future< typename rclcpp _action::Client< nav2_msgs ::action::NavigateToPose > ::CancelResponse::SharedPtr > >
optional< std::shared _future< typename rclcpp ::action::Client< ActionType > ::CancelResponse::SharedPtr > >
optional< std::shared _ptr< GoalHandle ::SharedPtr > >
optional< std::chrono ::milliseconds >
FeedbackCallback
shared_ptr< ActionClient >
optional< std::string >
optional< std::future < int > >
function< void()>
optional< rclcpp::Duration >
optional< rclcpp::Time >
shared_ptr< tf2_ros ::Buffer >
optional< cl_nav2z ::CbUndoPathBackwardsOptions >
ResultCode
PoseStamped
shared_ptr< tf2_ros ::Buffer >
shared_ptr< tf2_ros ::TransformListener >
mutex
SharedPtr
Path
WorkingMode
vector< nav_msgs::msg ::Path >
vector< cl_nav2z::odom _tracker::CpOdomTracker ::PathInfo >
OdomTrackerStrategy
optional< geometry _msgs::msg::PoseStamped >
SharedPtr
string
#actionMutex_
#owner_
#m_mutex_
#navigationClient_
#navigationResult_
#actionClient_
#navigationInterface_
#lastCancelResponse_
#lastRequest_
#serverTimeout
#feedbackCallback_
#client_
#actionServerName
#onGoalAccepted_ #onGoalRejected_
#onFailure_ #onFinished_ #onSuccess_
#postFailureEventPtr
#postFinishEventPtr
#postSuccessEventPtr
#isShutdownRequested_
#periodDuration_
#lastUpdate_
#isInitialized
#odomSub_ #robotBasePathPub_ #robotBasePathStacked Pub_
#robotPose_
#aggregatedStackPathMsg
#baseTrajectory_
#workingMode_
#pathStack_
#pathInfos_
#strategy_
#currentMotionGoal_
#param_callback_handle_
#closeAngularDistanceThreshold
#closePointDistanceThreshold
#recordAngularDistanceThreshold
#recordPointDistanceThreshold_
#robotPoseTimer_
+demangledTypeName _typeInfoName_ +fullOrTypeName_
#odomTracker_
#listener_
#options_
#close_
#tfBuffer_
#tfListener_
#listenerMutex_
#publishMessages_