cl_isaac_apriltag::
CbDetectAprilTag
+ CbDetectAprilTag()
+ ~CbDetectAprilTag()
+ onOrthogonalAllocation()
+ onEntry()
+ onAprilTagDetected()
-postEvAprilTagDetected_
-tracker_
-missionState_
function< void()>
smacc2::SmaccAsyncClient
Behavior
+ onStateOrthogonalAllocation()
+ ~SmaccAsyncClientBehavior()
+ onSuccess()
+ onFinished()
+ onFailure()
+ requestForceFinish()
+ executeOnEntry()
+ executeOnExit()
+ waitOnEntryThread()
+ onSuccess()
+ onFinished()
+ onFailure()
# postSuccessEvent()
# postFailureEvent()
# dispose()
# isShutdownRequested()
- waitFutureIfNotFinished()
-postFailureEventFn
-postFinishEventFn
-postSuccessEventFn_
optional< std::future
< int > >
-onEntryThread_
-onExitThread_
smacc2::SmaccSignal
< void()>
-onFailure_
-onFinished_
-onSuccess_
smacc2::ISmaccClientBehavior
+ ISmaccClientBehavior()
+ ~ISmaccClientBehavior()
+ getStateMachine()
+ getName()
+ requiresClient()
+ requiresComponent()
+ requiresComponent()
+ onEntry()
+ onExit()
+ executeOnEntry()
+ executeOnExit()
# runtimeConfigure()
# postEvent()
# postEvent()
# getCurrentState()
# dispose()
# getNode()
# getLogger()
- onStateOrthogonalAllocation()
-currentState
-sub_
-currentOrthogonal
boost::signals2::signal
< void(), optional_last
_value< typename boost::
function_traits< void()>
::result_type >, int, std
::less< int >, function< void
()>, typename extended_signature
< function_traits< void()>::arity,
void()>::function_type, boost::signals2::mutex >
smacc2::SmaccSignal
< Signature, Combiner,
Group, GroupCompare,
SlotFunction, ExtendedSlotFunction,
Mutex >
boost::signals2::signal
< Signature, optional
_last_value< typename boost
::function_traits< Signature
>::result_type >, int, std
::less< int >, function< Signature
>, typename extended_signature<
function_traits< Signature >::arity,
Signature >::function_type, boost::
signals2::mutex >
< void()>
< void(const AprilTagDetection
Array::SharedPtr &)>
< void(const AprilTagDetection
Array &)>
< void(const MessageType &)>
boost::signals2::signal
< void(const AprilTagDetection
Array::SharedPtr &), optional
_last_value< typename boost::
function_traits< void(const AprilTagDetection
Array::SharedPtr &)>::result_type >, int,
std::less< int >, function< void(const
AprilTagDetectionArray::SharedPtr &)>, typename
extended_signature< function_traits< void(const
AprilTagDetectionArray::SharedPtr &)>::arity, void
(const AprilTagDetectionArray::SharedPtr &)>::function
_type, boost::signals2::mutex >
smacc2::SmaccSignal
< void(const AprilTagDetection
Array::SharedPtr &)>
+onAprilTagDetection_
boost::signals2::signal
< void(const AprilTagDetection
Array &), optional_last_value
< typename boost::function_traits
< void(const AprilTagDetectionArray
&)>::result_type >, int, std::less
< int >, function< void(const AprilTagDetection
Array &)>, typename extended_signature< function
_traits< void(const AprilTagDetectionArray &)>
::arity, void(const AprilTagDetectionArray &)>
::function_type, boost::signals2::mutex >
smacc2::SmaccSignal
< void(const AprilTagDetection
Array &)>
+onFirstMessageReceived
+onMessageReceived_
boost::signals2::signal
< void(const MessageType
&), optional_last_value
< typename boost::function
_traits< void(const MessageType
&)>::result_type >, int, std
::less< int >, function< void(const
MessageType &)>, typename extended
_signature< function_traits< void(const
MessageType &)>::arity, void(const MessageType
&)>::function_type, boost::signals2::mutex >
smacc2::SmaccSignal
< void(const MessageType &)>
function< void(const
MessageType &)>
optional< int >
+queueSize
+onFirstMessageReceived
+onMessageReceived_
+postInitialMessageEvent
+postMessageEvent
smacc2::client_core
_components::CpTopicSubscriber
< MessageType >
+ CpTopicSubscriber()
+ CpTopicSubscriber()
+ ~CpTopicSubscriber()
+ onMessageReceived()
+ onFirstMessageReceived()
+ onStateOrthogonalAllocation()
+ onInitialize()
- messageCallback()
< AprilTagDetectionArray >
function< void(const
AprilTagDetectionArray &)>
smacc2::client_core
_components::CpTopicSubscriber
< AprilTagDetectionArray >
+ CpTopicSubscriber()
+ CpTopicSubscriber()
+ ~CpTopicSubscriber()
+ onMessageReceived()
+ onFirstMessageReceived()
+ onStateOrthogonalAllocation()
+ onInitialize()
- messageCallback()
-topicSubscriber_
-topicName_
-targetFrame_
string
cl_isaac_apriltag::
CpAprilTagTracker
+ CpAprilTagTracker()
+ ~CpAprilTagTracker()
+ onInitialize()
+ onComponentInitialization()
+ getTagsWithinTime()
+ getTagPose()
+ onAprilTagDetected()
- onAprilTagMessage()
shared_ptr< tf2_ros
::Buffer >
-tfBuffer_
shared_ptr< tf2_ros
::TransformListener >
-tfListener_
map< std::string, geometry
_msgs::msg::PoseStamped >
-detectedAprilTagsMapPose_
SharedPtr
-sub_
bool
-firstMessage_
-initialized_
smacc2::ISmaccComponent
+ ISmaccComponent()
+ ~ISmaccComponent()
+ getName()
# onInitialize()
# onComponentInitialization()
# postEvent()
# postEvent()
# onStateOrthogonalAllocation()
# requiresComponent()
# requiresComponent()
# requiresClient()
# createSiblingComponent()
# createSiblingNamedComponent()
# getNode()
# getLogger()
# getStateMachine()
- initialize()
- setStateMachine()
#owner_
cl_isaac_apriltag::
CpAprilTagMissionState
+ CpAprilTagMissionState()
+ ~CpAprilTagMissionState()
+ onInitialize()
+ isTagVisited()
+ markTagVisited()
+ clearVisitedTags()
+ getVisitedTags()
+ selectTag()
+ getSelectedTag()
+ clearSelectedTag()
optional< std::string >
-selectedVisitTagId_
vector< std::string >
-visitedWorkingAreas_
-mutex_
-isShutdownRequested_
smacc2::ISmaccClient
+ ISmaccClient()
+ ~ISmaccClient()
+ onInitialize()
+ getName()
+ getComponent()
+ getComponent()
+ getComponent()
+ getType()
+ getStateMachine()
+ connectSignal()
+ requiresClient()
+ getComponents()
+ iterateComponents()
+ postEvent()
+ postEvent()
# onComponentInitialization()
# onStateOrthogonalAllocation()
# createComponent()
# createNamedComponent()
# getNode()
# getLogger()
- initialize()
- setStateMachine()
- setOrthogonal()
map< smacc2::ComponentKey,
std::shared_ptr< smacc2
::ISmaccComponent > >
#components_
-stateMachine_
-orthogonal_
#stateMachine_
smacc2::ISmaccOrthogonal
+ ~ISmaccOrthogonal()
+ setStateMachine()
+ getStateMachine()
+ initState()
+ addClientBehavior()
+ runtimeConfigure()
+ onEntry()
+ onExit()
+ onDispose()
+ getName()
+ requiresComponent()
+ requiresClient()
+ getClients()
+ getClientBehaviors()
+ setGlobalSMData()
+ getGlobalSMData()
+ getClientBehavior()
+ getNode()
+ getLogger()
# onInitialize()
# initializeClients()
# assignClientToOrthogonal()
- currentClientBehaviors()
vector< std::shared
_ptr< smacc2::ISmaccClient > >
#clients_
vector< std::vector
< std::shared_ptr< smacc2
::ISmaccClientBehavior > > >
-clientBehaviors_
-stateMachine_
smacc2::ISmaccStateMachine
+ ISmaccStateMachine()
+ ~ISmaccStateMachine()
+ reset()
+ stop()
+ eStop()
+ joinAsyncClientBehaviorThreads()
+ getOrthogonal()
+ getClientBehavior()
+ getOrthogonals()
+ requiresComponent()
+ requiresComponent()
+ postEvent()
+ postEvent()
+ getGlobalSMData()
+ setGlobalSMData()
+ getStateMachineName()
+ state_machine_visualization()
+ getCurrentStateInfo()
+ publishTransition()
+ onInitialize()
+ getTransitionLogHistory()
+ createSignalConnection()
+ disconnectSmaccSignalObject()
+ disconnectSmaccSignalObject()
+ notifyOnStateEntryStart()
+ notifyOnStateEntryEnd()
+ notifyOnRuntimeConfigured()
+ notifyOnStateExiting()
+ notifyOnStateExited()
+ notifyOnRuntimeConfiguration
Finished()
+ getCurrentStateCounter()
+ getCurrentState()
+ getStateMachineInfo()
+ buildStateMachineInfo()
+ getNode()
+ getLogger()
+ getMutex()
# checkStateMachineConsistence()
# initializeROS()
# onInitialized()
# createOrthogonal()
- lockStateMachine()
- unlockStateMachine()
- propagateEventToStateReactors()
- updateStatusMessage()
SharedPtr
#nh_
SharedPtr
#timer_
shared_ptr< smacc2
::introspection::SmaccState
MachineInfo >
#stateMachineInfo_
recursive_mutex
-eventQueueMutex_
-m_mutex_
atomic< StateMachineInternal
Action >
-stateMachineCurrentAction
map< void *, std::shared
_ptr< smacc2::CallbackCounterSemaphore > >
-stateCallbackConnections
map< std::string, std
::pair< std::function
< std::string()>, boost
::any > >
-globalData_
vector< smacc2_msgs
::msg::SmaccTransitionLogEntry >
-transitionLogHistory_
SMRunMode
-runMode_
int64_t
-stateSeqCounter_
vector< smacc2::ISmaccState * >
#currentState_
shared_ptr< smacc2
::introspection::SmaccState
Info >
#currentStateInfo_
SmaccStatus
#status_msg_
map< std::string, std
::shared_ptr< smacc2
::ISmaccOrthogonal > >
#orthogonals_
SharedPtr
#eventsLogPub_
#stateMachinePub
#stateMachineStatus
Pub_
#transitionHistory
Service_
#transitionLogPub_
-statusPub_
mutex
-mutex_
-smaccStateMachine_
-signalDetector_
atomic< bool >
-end_
-initialized_
-rosInitialized_
vector< smacc2::ISmaccUpdatable * >
-updatableClients_
vector< std::vector
< smacc2::ISmaccUpdatable * > >
-updatableStateElements_
atomic< int64_t >
-lastState_
double
-loop_rate_hz
SmaccFifoScheduler *
-scheduler_
processor_handle
-processorHandle_
thread
-signalDetectorThread_
ExecutionModel
-executionModel_
smacc2::SignalDetector
+ SignalDetector()
+ initialize()
+ setProcessorHandle()
+ runThread()
+ join()
+ stop()
+ terminateScheduler()
+ joinAsyncClientBehaviorThreads()
+ pollingLoop()
+ postEvent()
+ getNode()
+ getLogger()
+ notifyStateConfigured()
+ notifyStateExited()
+ notifyRosInitialized()
- pollOnce()
- findUpdatableClientsAndComponents()
- findUpdatableStateElements()
SharedPtr
#node_
smacc2::ISmaccState
+ ~ISmaccState()
+ getStateMachine()
+ getName()
+ getParentState()
+ getNode()
+ getLogger()
+ getClassName()
+ configure()
+ requiresComponent()
+ requiresComponent()
+ requiresClient()
+ getGlobalSMData()
+ setGlobalSMData()
+ createStateReactor()
+ createStateReactor()
+ createEventGenerator()
+ postEvent()
+ postEvent()
+ notifyTransition()
+ notifyTransitionFromTransition
TypeInfo()
+ getStateReactors()
+ getEventGenerators()
+ getOrthogonal()
+ getClientBehavior()
+ getEventGenerator()
+ getStateReactor()
#parentState_
shared_ptr< rclcpp
::Logger >
#logger_
vector< std::shared
_ptr< smacc2::StateReactor > >
#stateReactors_
vector< std::shared
_ptr< smacc2::SmaccEventGenerator > >
#eventGenerators_
#stateInfo_
smacc2::introspection
::SmaccStateInfo
+ SmaccStateInfo()
+ getStateLevel()
+ getStateMachineInfo()
+ getParentState()
+ depth()
+ getAncestors()
+ getFullPath()
+ createChildState()
+ declareTransition()
+ toShortName()
+ getDemangledFullName()
+ getNode()
+ getLogger()
int
+depth_
+stateIndex_
weak_ptr< smacc2::introspection
::SmaccStateMachineInfo >
+stateMachine_
weak_ptr< smacc2::introspection
::SmaccStateInfo >
+parentState_
vector< smacc2::introspection
::SmaccTransitionInfo >
+transitions_
vector< std::shared
_ptr< smacc2::introspection
::SmaccStateInfo > >
+children_
type_info *
+tid_
std::enable_shared
_from_this< SmaccStateInfo >
map< const std::type
_info *, std::vector
< smacc2::introspection
::ClientBehaviorInfoEntry > >
+staticBehaviorInfo
map< const std::type
_info *, std::vector
< std::shared_ptr< smacc2
::introspection::SmaccStateReactor
Info > > >
+stateReactorsInfo
map< const std::type
_info *, std::vector
< std::shared_ptr< smacc2
::introspection::SmaccEventGenerator
Info > > >
+eventGeneratorsInfo
+demangledStateName
+fullStateName