

string
std::enable_shared
_from_this< SmaccStateInfo >
map< const std::type
_info *, std::vector
< smacc2::introspection
::ClientBehaviorInfoEntry > >
map< const std::type
_info *, std::vector
< std::shared_ptr< smacc2
::introspection::SmaccStateReactor
Info > > >
map< const std::type
_info *, std::vector
< std::shared_ptr< smacc2
::introspection::SmaccEventGenerator
Info > > >
int
vector< smacc2::introspection
::SmaccTransitionInfo >
vector< std::shared
_ptr< smacc2::introspection
::SmaccStateInfo > >
type_info *
shared_ptr< smacc2
::introspection::SmaccState
MachineInfo >
shared_ptr< smacc2
::introspection::SmaccState
Info >
SharedPtr
StateMachineInternalAction
map< void *, std::shared
_ptr< smacc2::CallbackCounterSemaphore > >
map< std::string, std
::pair< std::function
< std::string()>, boost
::any > >
vector< smacc2_msgs
::msg::SmaccTransitionLogEntry >
SMRunMode
int64_t
SharedPtr
vector< smacc2::ISmaccState * >
SmaccStatus
map< std::string, std
::shared_ptr< smacc2
::ISmaccOrthogonal > >
vector< boost::signals2
::scoped_connection >
recursive_mutex
SharedPtr
+demangledStateName
+fullStateName
+staticBehaviorInfo
+staticReactorInfo
+eventGeneratorInfo
+depth
+stateIndex_
+transitions_
+children_
+id_
+stateMachine_
+parentState_
#stateMachineInfo_
#currentStateInfo_
#hh_
-stateMachineCurrentAction
-stateCallbackConnections
-globalData_
-transitionLogHistory_
+runMode_
-stateSeqCounter_
#mtx_
#currentState_
-status_msg_
#orthogonals_
#orngLiveSignalConnections_
-eventQueueMutex_
m_mutex_
#eventsLogPub_
#stateMachinePub_
#stateMachineStatus
Pub_
#transitionHistory
Service_
#transitionLogPub_
smacc2::ISmaccStateMachine
+ ISmaccStateMachine()
+ ~ISmaccStateMachine()
+ reset()
+ stop()
+ eStop()
+ getOrthogonal()
+ getClientBehavior()
+ getOrthogonals()
+ requiresComponent()
+ postEvent()
+ postEvent()
+ getGlobalSMData()
+ setGlobalSMData()
+ getStateMachineName()
+ state_machine_visualization()
+ getCurrentStateInfo()
+ publishTransition()
+ onInitialize()
+ getTransitionLogHistory()
+ createSignalConnection()
+ disconnectSmaccSignalObjects()
+ notifyOnStateEntryStart()
+ notifyOnStateEntryEnd()
+ notifyOnRuntimeConfigured()
+ notifyOnStateExiting()
+ notifyOnStateExited()
+ notifyOnRuntimeConfiguration
Finished()
+ getCurrentStateCounter()
+ getCurrentState()
+ getStateMachineInfo()
+ buildStateMachineInfo()
+ getNode()
+ getLogger()
+ getMutex()
checkStateMachineConsistence()
initializeROS()
onInitialized()
createOrthogonal()
- lockStateMachine()
- unlockStateMachine()
- propagateEventToStateReactors()
- updateStatusMessage()
boost::signals2::signal
< Signature, optional
_last_value< typename boost
::function_traits
< Signature
::result_type >, int, std
::less< int >, function< Signature
>, typename extended_signature<
function_traits< Signature >::arity,
Signature >::function_type, boost::
signals2::mutex >
smacc2::introspection
::SmaccStateInfo
+ SmaccStateInfo()
+ getStateLevel()
+ depth()
+ getAncestors()
+ getFullPath()
+ createChildState()
+ declareTransition()
+ toShortName()
+ getDemangledFullName()
+ getNode()
+ getLogger()
vector< std::shared
_ptr< smacc2::SmaccEventGenerator > >
shared_ptr< rclcpp
::Logger >
vector< std::shared
_ptr< smacc2::StateReactor > >
#eventGenerators_
#logger_
#stateReactors_
#stateInfo_
#node_
vector< std::shared
_ptr< smacc2::ISmaccClient > >
vector< std::vector
< std::shared_ptr< smacc2
::ISmaccClientBehavior > > >
mutex
#clients_
#clientBehaviors_
#mutex_
#stateMachine_
-smaccStateMachine_
-signalDetector_
vector< smacc2::ISmaccUpdatable * >
vector< std::vector
< smacc2::ISmaccUpdatable * > >
atomic< int64_t >
double
atomic< bool >
SmaccFifoScheduler *
processor_handle
thread
ExecutionModel
-statusPub_
-updatableClients_
-updatableStateElements_
-lastState_
-loop_rate_hz_
-end_
initialized_
-scheduler_
-processorHandle_
-signalDetectorThread_
-executionMode_
smacc2::SignalDetector
+ SignalDetector()
+ initialize()
+ setProcessorHandle()
+ runThread()
+ join()
+ stop()
+ terminateScheduler()
+ pollingLoop()
+ postEvent()
+ getNode()
+ getLogger()
+ notifyStateConfigured()
+ notifyStateExited()
- pollOnce()
- findUpdatableClientsAndComponents()
- findUpdatableStateElements()
smacc2::ISmaccStateSmacc
+ getStateMachine()
+ getName()
+ getParentState()
+ getNode()
+ getLogger()
+ getClassName()
+ configure()
+ requiresComponent()
+ requiresClient()
+ getGlobalSMData()
+ setGlobalSMData()
+ createStateReactor()
+ createStateReactor()
+ createEventGenerator()
+ postEvent()
+ postEvent()
+ notifyTransition()
+ notifyTransitionFromTransition
TypeInfo()
+ getStateReactors()
+ getEventGenerators()
+ getOrthogonal()
+ getClientBehavior()
+ getEventGenerator()
+ getStateReactor()
#eventGenerators_
#logger_
#stateReactors_
#stateInfo_
#eventStates_
#clients_
#clientBehaviors_
#mutex_
#stateMachine_
-stateMachine_
smacc2::ISmaccOrthogonal
+ setStateMachine()
+ getStateMachine()
+ initState()
+ addClientBehavior()
+ runtimeConfigure()
+ onEntry()
+ onExit()
+ onDispose()
+ getName()
+ requiresComponent()
+ requiresClient()
+ getClients()
+ getClientBehaviors()
+ setGlobalSMData()
+ getGlobalSMData()
+ getClientBehavior()
+ getNode()
+ getLogger()
onInitialize()
initializeClients()
assignClientToOrthogonal()
smacc2::ISmaccClientBehavior
+ ISmaccClientBehavior()
+ ~ISmaccClientBehavior()
+ getStateMachine()
+ getName()
+ requiresClient()
+ requiresComponent()
+ requiresComponent()
+ onEntry()
+ onExit()
+ executeOnEntry()
+ executeOnExit()
runtimeConfigure()
postEvent()
postEvent()
getCurrentState()
dispose()
getNode()
getLogger()
- onOrthogonalAllocation()
- onStateOrthogonalAllocation()
boost::signals2::signal
< void(), optional_last
_value< typename boost::
result_of< Combiner(
InputIterator, InputIterator)
>::type >, int, std
::less< int >, function< void
()>, typename extended_signature
< function_traits< void()>::arity,
void()>::function_type, boost::signals2::mutex >
smacc2::SmaccSignal
< void, optional_last
_value< typename boost::
result_of< Combiner(
InputIterator, InputIterator)
>::type >, int, std
::less< int >, function< void
()>, typename extended_signature
< function_traits< void()>::arity,
void()>::function_type, boost::signals2::mutex >
smacc2::SmaccSignal
< Signature, Combiner,
Group, GroupCompare,
SlotFunction, ExtendedSlotFunction,
Mutex >
void()>
#nodeName_
currentState
currentOrthogonal
-stateMachine_
optional< std::future
< int > >
function< void()>
smacc2::SmaccSignal
< void()>
bool
-onEntryThread_
-onExitThread_
postFailureEvent()
postFinishEvent()
postSuccessEvent()
-onFailure_
-onFinished_
-onSuccess_
isShutdownRequested_
smacc2::SmaccAsyncClient
Behavior
+ onOrthogonalAllocation()
+ onStateOrthogonalAllocation()
+ ~SmaccAsyncClientBehavior()
+ onSuccess()
+ onFinished()
+ onFailure()
+ requestForceFinish()
+ executeOnEntry()
+ executeOnExit()
+ waitOnEntryThread()
+ onSuccess()
+ onFinished()
+ onFailure()
postSuccessEvent()
postFailureEvent()
dispose()
isShutdownRequested()
- waitFutureIsNotFinished()
Rate
sleep_
smacc2::client_behaviors
::CbWaitNode
+ CbWaitNode()
+ onEntry()