

KUKA


Robots

KUKA Deutschland GmbH

KR AGILUS sixx CR

With W and C Variants

Operating Instructions



Issued: 15.05.2018

Version: BA KR AGILUS sixx CR V5



© Copyright 2018

KUKA Deutschland GmbH
Zugspitzstraße 140
D-86165 Augsburg
Germany

This documentation or excerpts therefrom may not be reproduced or disclosed to third parties without the express permission of KUKA Deutschland GmbH.

Other functions not described in this documentation may be operable in the controller. The user has no claims to these functions, however, in the case of a replacement or service work.

We have checked the content of this documentation for conformity with the hardware and software described. Nevertheless, discrepancies cannot be precluded, for which reason we are not able to guarantee total conformity. The information in this documentation is checked on a regular basis, however, and necessary corrections will be incorporated in the subsequent edition.

Subject to technical alterations without an effect on the function.

KIM-PS5-DOC

Translation of the original documentation

Publication:	Pub BA KR AGILUS sixx CR (PDF) en
Book structure:	BA KR AGILUS sixx CR V4.4
Version:	BA KR AGILUS sixx CR V5

Contents

1	Introduction	7
1.1	Industrial robot documentation	7
1.2	Representation of warnings and notes	7
1.3	Terms used	7
2	Purpose	9
2.1	Target group	9
2.2	Intended use	9
3	Product description	11
3.1	Overview of the robot system	11
3.2	Description of the manipulator	12
4	Technical data	15
4.1	Technical data, KR 6 R700 sixx CR	18
4.1.1	Basic data, KR 6 R700 sixx CR	18
4.1.2	Axis data, KR 6 R700 sixx CR	19
4.1.3	Payloads, KR 6 R700 sixx CR	21
4.1.4	Loads acting on the foundation, KR 6 R700 sixx CR	24
4.2	Technical data, KR 6 R700 sixx W-CR	26
4.2.1	Basic data, KR 6 R700 sixx W-CR	26
4.2.2	Axis data, KR 6 R700 sixx W-CR	27
4.2.3	Payloads, KR 6 R700 sixx W-CR	29
4.2.4	Loads acting on the foundation, KR 6 R700 sixx W-CR	32
4.3	Technical data, KR 6 R700 sixx C-CR	33
4.3.1	Basic data, KR 6 R700 sixx C-CR	33
4.3.2	Axis data, KR 6 R700 sixx C-CR	34
4.3.3	Payloads, KR 6 R700 sixx C-CR	37
4.3.4	Loads acting on the foundation, KR 6 R700 sixx C-CR	39
4.4	Technical data, KR 6 R900 sixx CR	40
4.4.1	Basic data, KR 6 R900 sixx CR	40
4.4.2	Axis data, KR 6 R900 sixx CR	42
4.4.3	Payloads, KR 6 R900 sixx CR	44
4.4.4	Loads acting on the foundation, KR 6 R900 sixx CR	47
4.5	Technical data, KR 6 R900 sixx W-CR	49
4.5.1	Basic data, KR 6 R900 sixx W-CR	49
4.5.2	Axis data, KR 6 R900 sixx W-CR	50
4.5.3	Payloads, KR 6 R900 sixx W-CR	53
4.5.4	Loads acting on the foundation, KR 6 R900 sixx W-CR	55
4.6	Technical data, KR 6 R900 sixx C-CR	56
4.6.1	Basic data, KR 6 R900 sixx C-CR	56
4.6.2	Axis data, KR 6 R900 sixx C-CR	58
4.6.3	Payloads, KR 6 R900 sixx C-CR	60
4.6.4	Loads acting on the foundation, KR 6 R900 sixx C-CR	63
4.7	Technical data, KR 10 R900 sixx CR	64
4.7.1	Basic data, KR 10 R900 sixx CR	64
4.7.2	Axis data, KR 10 R900 sixx CR	65

4.7.3	Payloads, KR 10 R900 sixx CR	68
4.7.4	Loads acting on the foundation, KR 10 R900 sixx CR	70
4.8	Technical data, KR 10 R900 sixx W-CR	72
4.8.1	Basic data, KR 10 R900 sixx W-CR	72
4.8.2	Axis data, KR 10 R900 sixx W-CR	73
4.8.3	Payloads, KR 10 R900 sixx W-CR	76
4.8.4	Loads acting on the foundation, KR 10 R900 sixx W-CR	78
4.9	Technical data, KR 10 R900 sixx C-CR	79
4.9.1	Basic data, KR 10 R900 sixx C-CR	79
4.9.2	Axis data, KR 10 R900 sixx C-CR	81
4.9.3	Payloads, KR 10 R900 sixx C-CR	83
4.9.4	Loads acting on the foundation, KR 10 R900 sixx C-CR	86
4.10	Technical data, KR 10 R1100 sixx CR	87
4.10.1	Basic data, KR 10 R1100 sixx CR	87
4.10.2	Axis data, KR 10 R1100 sixx CR	88
4.10.3	Payloads, KR 10 R1100 sixx CR	91
4.10.4	Loads acting on the foundation, KR 10 R1100 sixx CR	93
4.11	Technical data, KR 10 R1100 sixx W-CR	95
4.11.1	Basic data, KR 10 R1100 sixx W-CR	95
4.11.2	Axis data, KR 10 R1100 sixx W-CR	96
4.11.3	Payloads, KR 10 R1100 sixx W-CR	99
4.11.4	Loads acting on the foundation, KR 10 R1100 sixx W-CR	101
4.12	Technical data, KR 10 R1100 sixx C-CR	102
4.12.1	Basic data, KR 10 R1100 sixx C-CR	102
4.12.2	Axis data, KR 10 R1100 sixx C-CR	104
4.12.3	Payloads, KR 10 R1100 sixx C-CR	106
4.12.4	Loads acting on the foundation, KR 10 R1100 sixx C-CR	109
4.13	Supplementary load	110
4.13.1	Supplementary load, reach R700	111
4.13.2	Supplementary load, reach R900	112
4.13.3	Supplementary load, reach R1100	113
4.14	Plates and labels	114
4.15	Stopping distances and times	116
4.15.1	General information	116
4.15.2	Terms used	117
4.15.3	Stopping distances and times, KR 6 R700 sixx CR and KR 6 R700 sixx C-CR ..	118
4.15.3.1	Stopping distances and stopping times for STOP 0, axis 1 to axis 3	118
4.15.3.2	Stopping distances and stopping times for STOP 1, axis 1	119
4.15.3.3	Stopping distances and stopping times for STOP 1, axis 2	121
4.15.3.4	Stopping distances and stopping times for STOP 1, axis 3	123
4.15.4	Stopping distances and times, KR 6 R700 sixx W-CR	123
4.15.4.1	Stopping distances and stopping times for STOP 0, axis 1 to axis 3	123
4.15.4.2	Stopping distances and stopping times for STOP 1, axis 1	125
4.15.4.3	Stopping distances and stopping times for STOP 1, axis 2	127
4.15.4.4	Stopping distances and stopping times for STOP 1, axis 2	129
4.15.5	Stopping distances and times, KR 6 R900 sixx CR and KR 6 R900 sixx C-CR ..	129
4.15.5.1	Stopping distances and stopping times for STOP 0, axis 1 to axis 3	129
4.15.5.2	Stopping distances and stopping times for STOP 1, axis 1	131
4.15.5.3	Stopping distances and stopping times for STOP 1, axis 2	133

4.15.5.4	Stopping distances and stopping times for STOP 1, axis 3	135
4.15.6	Stopping distances and times, KR 6 R900 sixx W-CR	135
4.15.6.1	Stopping distances and stopping times for STOP 0, axis 1 to axis 3	135
4.15.6.2	Stopping distances and stopping times for STOP 1, axis 1	137
4.15.6.3	Stopping distances and stopping times for STOP 1, axis 2	139
4.15.6.4	Stopping distances and stopping times for STOP 1, axis 3	141
4.15.7	Stopping distances and times, KR 10 R900 sixx CR and KR 10 R1100 sixx CR (with C variant)	141
4.15.7.1	Stopping distances and stopping times for STOP 0, axis 1 to axis 3	141
4.15.7.2	Stopping distances and stopping times for STOP 1, axis 1	143
4.15.7.3	Stopping distances and stopping times for STOP 1, axis 2	145
4.15.7.4	Stopping distances and stopping times for STOP 1, axis 3	147
4.15.8	Stopping distances and times, KR 10 R900 sixx W-CR and KR 10 R1100 sixx W-CR	147
4.15.8.1	Stopping distances and stopping times for STOP 0, axis 1 to axis 3	147
4.15.8.2	Stopping distances and stopping times for STOP 1, axis 1	149
4.15.8.3	Stopping distances and stopping times for STOP 1, axis 2	151
4.15.8.4	Stopping distances and stopping times for STOP 1, axis 3	153
5	Safety	155
5.1	General	155
5.1.1	Liability	155
5.1.2	Intended use of the industrial robot	156
5.1.3	EC declaration of conformity and declaration of incorporation	156
5.1.4	Terms used	157
5.2	Personnel	158
5.3	Workspace, safety zone and danger zone	159
5.4	Overview of protective equipment	159
5.4.1	Mechanical end stops	159
5.4.2	Mechanical axis limitation (optional)	159
5.4.3	Options for moving the manipulator without drive energy	160
5.4.4	Labeling on the industrial robot	160
5.5	Safety measures	161
5.5.1	General safety measures	161
5.5.2	Transportation	162
5.5.3	Start-up and recommissioning	162
5.5.4	Manual mode	163
5.5.5	Automatic mode	164
5.5.6	Maintenance and repair	164
5.5.7	Decommissioning, storage and disposal	166
5.6	Applied norms and regulations	166
6	Planning	169
6.1	Information for planning	169
6.2	Mounting base	169
6.3	Machine frame mounting	172
6.4	Connecting cables and interfaces	173
6.5	Customer interfaces	175
7	Transportation	181
7.1	Transporting the manipulator	181

8 Start-up and recommissioning	187
8.1 Installing the mounting base	187
8.2 Installing the machine frame mounting assembly	188
8.3 Installing a floor-mounted robot	188
8.4 Installing a wall-mounted robot	190
8.5 Installing a ceiling-mounted robot	195
8.6 Description of the connecting cables	199
8.7 Moving the manipulator without drive energy	205
9 Maintenance	207
9.1 Maintenance overview	207
9.1.1 Maintenance table	207
9.2 Checking the screws, side section of link arm	210
9.3 Checking the screws, in-line wrist torque bridge	211
9.4 Greasing the inside of covers A2 and A3	211
9.5 Exchanging the toothed belts	213
9.6 Cleaning the robot	214
10 Repair	217
10.1 Measuring and adjusting the toothed belt tension	217
11 Decommissioning, storage and disposal	221
11.1 Decommissioning, floor-mounted robot	221
11.2 Decommissioning, wall-mounted robot	222
11.3 Decommissioning, ceiling-mounted robot	225
11.4 Storage	228
11.5 Disposal	229
12 Appendix	231
12.1 Tightening torques	231
12.2 Tightening torque for stainless steel screws	231
12.3 Auxiliary and operating materials used	232
13 KUKA Service	233
13.1 Requesting support	233
13.2 KUKA Customer Support	233
Index	241

1 Introduction

1.1 Industrial robot documentation

The industrial robot documentation consists of the following parts:

- Documentation for the manipulator
- Documentation for the robot controller
- Operating and programming instructions for the System Software
- Instructions for options and accessories
- Parts catalog on storage medium

Each of these sets of instructions is a separate document.

1.2 Representation of warnings and notes

Safety

These warnings are relevant to safety and **must** be observed.



DANGER These warnings mean that it is certain or highly probable that death or severe injuries **will** occur, if no precautions are taken.



WARNING These warnings mean that death or severe injuries **may** occur, if no precautions are taken.



CAUTION These warnings mean that minor injuries **may** occur, if no precautions are taken.



NOTICE These warnings mean that damage to property **may** occur, if no precautions are taken.



These warnings contain references to safety-relevant information or general safety measures.

These warnings do not refer to individual hazards or individual precautionary measures.

This warning draws attention to procedures which serve to prevent or remedy emergencies or malfunctions:



SAFETY INSTRUCTIONS The following procedure must be followed exactly!

Procedures marked with this warning **must** be followed exactly.

Notices

These notices serve to make your work easier or contain references to further information.



Tip to make your work easier or reference to further information.

1.3 Terms used

Term	Description
CR	Cleanroom
MEMD	Micro Electronic Mastering Device
KL	KUKA linear unit

Term	Description
RDC	Resolver Digital Converter
smartPAD	The smartPAD teach pendant has all the operator control and display functions required for operating and programming the industrial robot.

2 Purpose

2.1 Target group

This documentation is aimed at users with the following knowledge and skills:

- Advanced knowledge of mechanical engineering
- Advanced knowledge of electrical and electronic systems
- Knowledge of the robot controller system



For optimal use of our products, we recommend that our customers take part in a course of training at KUKA College. Information about the training program can be found at www.kuka.com or can be obtained directly from our subsidiaries.

2.2 Intended use

Use

The industrial robot is intended for handling tools and fixtures or for processing and transferring components or products. Use is only permitted under the specified environmental conditions.

Misuse

Any use or application deviating from the intended use is deemed to be misuse and is not allowed. This includes e.g.:

- Use as a climbing aid
- Operation outside the specified operating parameters
- Operation without the required safety equipment

NOTICE

Changing the structure of the robot, e.g. by drilling holes, can result in damage to the components. This is considered improper use and leads to loss of guarantee and liability entitlements.

NOTICE

Deviations from the operating conditions specified in the technical data or the use of special functions or applications can lead to premature wear. KUKA Deutschland GmbH must be consulted.



The robot system is an integral part of a complete system and may only be operated in a CE-compliant system.

3 Product description

3.1 Overview of the robot system

A robot system (**>>> Fig. 3-1**) comprises all the assemblies of an industrial robot, including the manipulator (mechanical system and electrical installations), control cabinet, connecting cables, end effector (tool) and other equipment. The KR AGILUS sixx CR product family consists of the following types:

- KR 6 R700 sixx CR
- KR 6 R900 sixx CR
- KR 10 R900 sixx CR
- KR 10 R1100 sixx CR

The robots are also available as W and C variants (wall-mounted and ceiling-mounted versions).

An industrial robot of this type comprises the following components:

- Manipulator
- Robot controller
- smartPAD teach pendant
- Connecting cables
- Software
- Options, accessories




Fig. 3-1: Example of an industrial robot

- 1 Manipulator
- 2 smartPAD teach pendant
- 3 Connecting cable, smartPAD
- 4 Robot controller
- 5 Connecting cable, data cable
- 6 Connecting cable, motor cable
- 7 Device connection cable

3.2 Description of the manipulator

Overview

The manipulators (= robot arm and electrical installations) of the variants are designed as 6-axis jointed-arm kinematic systems made of cast light alloy. Each axis is fitted with a brake. All motor units and current-carrying cables are protected against dirt and moisture beneath screwed-on cover plates.

The manipulators consist of the following main assemblies:

- In-line wrist
- Arm
- Link arm
- Rotating column
- Base frame
- Electrical installations




Fig. 3-2: Principal components

- | | | | |
|---|---------------|---|--------------------------|
| 1 | In-line wrist | 4 | Rotating column |
| 2 | Arm | 5 | Electrical installations |
| 3 | Link arm | 6 | Base frame |

In-line wrist A4, A5, A6

The robot is fitted with a 3-axis in-line wrist. The in-line wrist consists of axes 4, 5 and 6.

There are three 5/2-way solenoid valves and a CAT5 data cable in the in-line wrist that can be used for controlling tools.

The in-line wrist also accommodates the 10-contact circular connector of the wrist I/O cable and interface A4 for the energy supply system.

Arm A3

The arm is the link between the in-line wrist and the link arm. The arm is driven by the motor of axis 3.

Link arm A2

The link arm is the assembly located between the arm and the rotating column. It houses the motor and gear unit of axis 2. The supply lines of the energy supply system and the cable set for axes 2 to 6 are routed through the link arm.

Rotating column A1

The rotating column houses the motors of axes 1 and 2. The rotational motion of axis 1 is performed by the rotating column. This is screwed to the base frame via the gear unit of axis 1 and is driven by a motor in the rotating column. The link arm is also mounted in the rotating column.

Base frame	The base frame is the base of the robot. Interface A1 is located at the rear of the base frame. It constitutes the interface for the connecting cables between the robot, the controller and the energy supply system.
Electrical installations	The electrical installations include all the motor and data cables for the motors of axes 1 to 6, as well as the connections for the internal energy supply system and external axes A7 and A8. All connections are pluggable. The electrical installations also include the RDC, which is integrated into the robot. The connectors for the motor and data cables are mounted on the robot base frame. The connecting cables from the robot controller are connected here by means of connectors. The electrical installations also include a protective circuit.
Options	The robot can be fitted and operated with various options, e.g. working range limitation A1 or brake release device. The option is described in separate documentation.

4 Technical data

The technical data for the individual robot types can be found in the following sections:

Robot	Technical data
KR 6 sixx CR	
KR 6 R700 sixx CR	<ul style="list-style-type: none"> ■ Technical data (>>> 4.1 "Technical data, KR 6 R700 sixx CR" Page 18) ■ Supplementary loads (>>> 4.13.1 "Supplementary load, reach R700" Page 111) ■ Plates and labels (>>> 4.14 "Plates and labels" Page 114) ■ Stopping distances and times (>>> 4.15.3 "Stopping distances and times, KR 6 R700 sixx CR and KR 6 R700 sixx C-CR" Page 118)
KR 6 R700 sixx W-CR	<ul style="list-style-type: none"> ■ Technical data (>>> 4.2 "Technical data, KR 6 R700 sixx W-CR" Page 26) ■ Supplementary loads (>>> 4.13.1 "Supplementary load, reach R700" Page 111) ■ Plates and labels (>>> 4.14 "Plates and labels" Page 114) ■ Stopping distances and times (>>> 4.15.4 "Stopping distances and times, KR 6 R700 sixx W-CR" Page 123)
KR 6 R700 sixx C-CR	<ul style="list-style-type: none"> ■ Technical data (>>> 4.3 "Technical data, KR 6 R700 sixx C-CR" Page 33) ■ Supplementary loads (>>> 4.13.1 "Supplementary load, reach R700" Page 111) ■ Plates and labels (>>> 4.14 "Plates and labels" Page 114) ■ Stopping distances and times (>>> 4.15.3 "Stopping distances and times, KR 6 R700 sixx CR and KR 6 R700 sixx C-CR" Page 118)
KR 6 R900 sixx CR	<ul style="list-style-type: none"> ■ Technical data (>>> 4.4 "Technical data, KR 6 R900 sixx CR" Page 40) ■ Supplementary loads (>>> 4.13.2 "Supplementary load, reach R900" Page 112) ■ Plates and labels (>>> 4.14 "Plates and labels" Page 114) ■ Stopping distances and times (>>> 4.15.5 "Stopping distances and times, KR 6 R900 sixx CR and KR 6 R900 sixx C-CR" Page 129)

Robot	Technical data
KR 6 sixx CR	
KR 6 R900 sixx W-CR	<ul style="list-style-type: none"> ■ Technical data (>>> 4.5 "Technical data, KR 6 R900 sixx W-CR" Page 49) ■ Supplementary loads (>>> 4.13.2 "Supplementary load, reach R900" Page 112) ■ Plates and labels (>>> 4.14 "Plates and labels" Page 114) ■ Stopping distances and times (>>> 4.15.6 "Stopping distances and times, KR 6 R900 sixx W-CR" Page 135)
KR 6 R900 sixx C-CR	<ul style="list-style-type: none"> ■ Technical data (>>> 4.6 "Technical data, KR 6 R900 sixx C-CR" Page 56) ■ Supplementary loads (>>> 4.13.2 "Supplementary load, reach R900" Page 112) ■ Plates and labels (>>> 4.14 "Plates and labels" Page 114) ■ Stopping distances and times (>>> 4.15.5 "Stopping distances and times, KR 6 R900 sixx CR and KR 6 R900 sixx C-CR" Page 129)

Robot	Technical data
KR 10 sixx CR	
KR 10 R900 sixx CR	<ul style="list-style-type: none"> ■ Technical data (>>> 4.7 "Technical data, KR 10 R900 sixx CR" Page 64) ■ Supplementary loads (>>> 4.13.2 "Supplementary load, reach R900" Page 112) ■ Plates and labels (>>> 4.14 "Plates and labels" Page 114) ■ Stopping distances and times (>>> 4.15.7 "Stopping distances and times, KR 10 R900 sixx CR and KR 10 R1100 sixx CR (with C variant)" Page 141)
KR 10 R900 sixx W-CR	<ul style="list-style-type: none"> ■ Technical data (>>> 4.8 "Technical data, KR 10 R900 sixx W-CR" Page 72) ■ Supplementary loads (>>> 4.13.2 "Supplementary load, reach R900" Page 112) ■ Plates and labels (>>> 4.14 "Plates and labels" Page 114) ■ Stopping distances and times (>>> 4.15.8 "Stopping distances and times, KR 10 R900 sixx W-CR and KR 10 R1100 sixx W-CR" Page 147)

Robot	Technical data
KR 10 sixx CR	
KR 10 R900 sixx C-CR	<ul style="list-style-type: none"> ■ Technical data (>>> 4.9 "Technical data, KR 10 R900 sixx C-CR" Page 79) ■ Supplementary loads (>>> 4.13.2 "Supplementary load, reach R900" Page 112) ■ Plates and labels (>>> 4.14 "Plates and labels" Page 114) ■ Stopping distances and times (>>> 4.15.7 "Stopping distances and times, KR 10 R900 sixx CR and KR 10 R1100 sixx CR (with C vari- ant)" Page 141)
KR 10 R1100 sixx CR	<ul style="list-style-type: none"> ■ Technical data (>>> 4.10 "Technical data, KR 10 R1100 sixx CR" Page 87) ■ Supplementary loads (>>> 4.13.2 "Supplementary load, reach R900" Page 112) ■ Plates and labels (>>> 4.14 "Plates and labels" Page 114) ■ Stopping distances and times (>>> 4.15.7 "Stopping distances and times, KR 10 R900 sixx CR and KR 10 R1100 sixx CR (with C vari- ant)" Page 141)
KR 10 R1100 sixx W-CR	<ul style="list-style-type: none"> ■ Technical data (>>> 4.11 "Technical data, KR 10 R1100 sixx W-CR" Page 95) ■ Supplementary loads (>>> 4.13.2 "Supplementary load, reach R900" Page 112) ■ Plates and labels (>>> 4.14 "Plates and labels" Page 114) ■ Stopping distances and times (>>> 4.15.7 "Stopping distances and times, KR 10 R900 sixx CR and KR 10 R1100 sixx CR (with C vari- ant)" Page 141)
KR 10 R1100 sixx C-CR	<ul style="list-style-type: none"> ■ Technical data (>>> 4.12 "Technical data, KR 10 R1100 sixx C-CR" Page 102) ■ Supplementary loads (>>> 4.13.2 "Supplementary load, reach R900" Page 112) ■ Plates and labels (>>> 4.14 "Plates and labels" Page 114) ■ Stopping distances and times (>>> 4.15.7 "Stopping distances and times, KR 10 R900 sixx CR and KR 10 R1100 sixx CR (with C vari- ant)" Page 141)

4.1 Technical data, KR 6 R700 sixx CR

4.1.1 Basic data, KR 6 R700 sixx CR

Basic data

	KR 6 R700 sixx CR
Number of axes	6
Number of controlled axes	6
Volume of working envelope	1.36 m ³
Pose repeatability (ISO 9283)	± 0.03 mm
Weight	approx. 50 kg
Rated payload	3 kg
Maximum reach	706.7 mm
Protection rating (IEC 60529)	IP54
Protection rating, in-line wrist (IEC 60529)	IP54
Sound level	< 70 dB (A)
Mounting position	Floor
Footprint	320 mm x 320 mm
Hole pattern: mounting surface for kinematic system	C246
Permissible angle of inclination	-
Default color	Base frame: traffic white (RAL 9016); Moving parts: traffic white (RAL 9016); Protective cover: traffic white (RAL 9016)
Controller	KR C4 smallsize-2; KR C4 compact
Transformation name	KR C4: KR6R700 C4SR FLR

Ambient conditions

Humidity class (EN 60204)	-
Classification of environmental conditions (EN 60721-3-3)	3K3
Cleanroom class (ISO 14644-1)	Class 2 at 40% override; Class 2 at 80% override
Ambient temperature	
During operation	5 °C to 45 °C (278 K to 318 K)
During storage/transportation	-40 °C to 60 °C (233 K to 333 K)

The manipulator may not be used under the following ambient conditions:

- High-pressure component washing systems
- Continuous submersion
- Acidic or alkaline environments
- Vacuum applications

Connecting cables

Cable designation	Connector designation robot controller - robot	Interface with robot
Motor cable	X20 - X30	Han Yellock 30
Data cable	X21 - X31	Han Q12

Cable designation	Connector designation robot controller - robot	Interface with robot
Data cable CAT5 (can be ordered as an option)	X65/X66 - XPN1	M12 connector
Connecting cable, external axes A7 and A8 (can be ordered as an option)	XP7 - XP7.1 XP8 - XP8.1	Connector M17 in each case
Ground conductor, equipotential bonding (can be ordered as an option)		M4 ring cable lug

Only resolvers can be connected to the connections XP7.1 and XP8.1.

	Cable lengths
Standard	4 m
Option	1 m, 7 m, 15 m, 25 m

For detailed specifications of the connecting cables, see "Description of the connecting cables".

4.1.2 Axis data, KR 6 R700 sixx CR

Axis data

Motion range	
A1	±170 °
A2	-190 ° / 45 °
A3	-120 ° / 156 °
A4	±185 °
A5	±120 °
A6	±350 °
Speed with rated payload	
A1	360 °/s
A2	300 °/s
A3	360 °/s
A4	381 °/s
A5	388 °/s
A6	615 °/s



In the case of manipulators with a payload of 6 kg and a reach of R700, not every angle for axis A4 can be reached in the end position.

The direction of motion and the arrangement of the individual axes may be noted from the diagram ([>>> Fig. 4-1](#)).




Fig. 4-1: Direction of rotation of robot axes

Mastering position

Mastering position	
A1	0 °
A2	-90 °
A3	90 °
A4	0 °
A5	0 °
A6	0 °

Working envelope

The following diagrams ([>>> Fig. 4-2](#)) and ([>>> Fig. 4-3](#)) show the load center of gravity and the shape and size of the working envelope.




Fig. 4-2: KR 6 R700 sixx CR working envelope, side view




Fig. 4-3: KR 6 R700 sixx CR working envelope, top view

Distance to flange

The distance to the flange varies according to the position of the robot ([>>> Fig. 4-4](#)).




Fig. 4-4: Distance to flange, KR 6 R700 sixx CR (with W and C variant)

4.1.3 Payloads, KR 6 R700 sixx CR

Payloads

Rated payload	3 kg
Maximum payload	6 kg
Rated mass moment of inertia	0.045 kgm ²
Rated supplementary load, base frame	0 kg
Maximum supplementary load, base frame	6 kg
Rated supplementary load, rotating column	0 kg
Maximum supplementary load, rotating column	6 kg
Rated supplementary load, link arm	0 kg
Maximum supplementary load, link arm	6 kg
Rated supplementary load, arm	0 kg

Maximum supplementary load, arm	6 kg
Maximum total load	6 kg
Nominal distance to load center of gravity	
Lxy	60 mm
Lz	80 mm

! The sum of all loads mounted on the robot must not exceed the maximum total load.

Load center of gravity

For all payloads, the load center of gravity refers to the distance from the face of the mounting flange on axis 6. Refer to the payload diagram for the nominal distance.




Fig. 4-5: Load center of gravity

Payload diagram




Fig. 4-6: Payload diagram, payload 6 kg

NOTICE

This loading curve corresponds to the maximum load capacity. Both values (payload and mass moment of inertia) must be checked in all cases. Exceeding this capacity will reduce the service life of the robot and overload the motors and the gears; in any such case KUKA Deutschland GmbH must be consulted beforehand.

The values determined here are necessary for planning the robot application. For commissioning the robot, additional input data are required in accordance with the operating and programming instructions of the KUKA System Software.

The mass inertia must be verified using KUKA.Load. It is imperative for the load data to be entered in the robot controller!

In-line wrist

In-line wrist type	ZH6 R700 CR
Mounting flange	see drawing

Mounting flange

Mounting flange (hole circle)	31.5 mm
Screw grade	12.9
Screw size	M5
Number of fastening screws	7
Grip length	min. 1.5 x nominal diameter
Depth of engagement	min. 5.5 mm, max. 7 mm
Locating element	5 H7
Standard	See illustration

The mounting flange is depicted with axis 6 in the zero position. The symbol X_m indicates the position of the locating element in the zero position.

Dimensions: mm




Fig. 4-7: Mounting flange

4.1.4 Loads acting on the foundation, KR 6 R700 sixx CR

Foundation loads The specified forces and moments already include the maximum payload and the inertia force (weight) of the robot.




Fig. 4-8: Loads acting on the foundation, floor mounting

Vertical force $F(v)$	
$F(v \text{ normal})$	697 N
$F(v \text{ max})$	1297 N
Horizontal force $F(h)$	
$F(h \text{ normal})$	1223 N
$F(h \text{ max})$	1362 N
Tilting moment $M(k)$	
$M(k \text{ normal})$	788 Nm
$M(k \text{ max})$	1152 Nm
Torque about axis 1 $M(r)$	
$M(r \text{ normal})$	367 Nm
$M(r \text{ max})$	880 Nm

Vertical force $F(v)$, horizontal force $F(h)$, tilting torque $M(k)$, torque about axis 1 $M(r)$

WARNING

Normal loads and maximum loads for the foundations are specified in the table.

The maximum loads must be referred to when dimensioning the foundations and must be adhered to for safety reasons. Failure to observe this can result in personal injury and damage to property.

The normal loads are average expected foundation loads. The actual loads are dependent on the program and on the robot loads and may therefore be greater or less than the normal loads.

The supplementary loads (A1 and A2) are not taken into consideration in the calculation of the mounting base load. These supplementary loads must be taken into consideration for F_v .

4.2 Technical data, KR 6 R700 sixx W-CR

4.2.1 Basic data, KR 6 R700 sixx W-CR

Basic data

	KR 6 R700 sixx W-CR
Number of axes	6
Number of controlled axes	6
Volume of working envelope	1.36 m ³
Pose repeatability (ISO 9283)	± 0.03 mm
Weight	approx. 50 kg
Rated payload	3 kg
Maximum reach	706.7 mm
Protection rating (IEC 60529)	IP54
Protection rating, in-line wrist (IEC 60529)	IP54
Sound level	< 70 dB (A)
Mounting position	Wall
Footprint	320 mm x 320 mm
Hole pattern: mounting surface for kinematic system	C246
Permissible angle of inclination	-
Default color	Base frame: traffic white (RAL 9016); Moving parts: traffic white (RAL 9016); Protective cover: traffic white (RAL 9016)
Controller	KR C4 smallsize-2; KR C4 compact
Transformation name	KR C4: KR6R700 C4SR WLL

Ambient conditions

Humidity class (EN 60204)	-
Classification of environmental conditions (EN 60721-3-3)	3K3
Cleanroom class (ISO 14644-1)	Class 2 at 40% override; Class 2 at 80% override
Ambient temperature	
During operation	5 °C to 45 °C (278 K to 318 K)
During storage/transportation	-40 °C to 60 °C (233 K to 333 K)

The manipulator may not be used under the following ambient conditions:

- High-pressure component washing systems
- Continuous submersion
- Acidic or alkaline environments
- Vacuum applications

Connecting cables

Cable designation	Connector designation robot controller - robot	Interface with robot
Motor cable	X20 - X30	Han Yellock 30
Data cable	X21 - X31	Han Q12

Cable designation	Connector designation robot controller - robot	Interface with robot
Data cable CAT5 (can be ordered as an option)	X65/X66 - XPN1	M12 connector
Connecting cable, external axes A7 and A8 (can be ordered as an option)	XP7 - XP7.1 XP8 - XP8.1	Connector M17 in each case
Ground conductor, equipotential bonding (can be ordered as an option)		M4 ring cable lug

Only resolvers can be connected to the connections XP7.1 and XP8.1.

	Cable lengths
Standard	4 m
Option	1 m, 7 m, 15 m, 25 m

For detailed specifications of the connecting cables, see "Description of the connecting cables".

4.2.2 Axis data, KR 6 R700 sixx W-CR

Axis data

Motion range	
A1	±170 °
A2	-190 ° / 45 °
A3	-120 ° / 156 °
A4	±185 °
A5	±120 °
A6	±350 °
Speed with rated payload	
A1	360 °/s
A2	300 °/s
A3	360 °/s
A4	381 °/s
A5	388 °/s
A6	615 °/s



In the case of manipulators with a payload of 6 kg and a reach of R700, not every angle for axis A4 can be reached in the end position.

The direction of motion and the arrangement of the individual axes may be noted from the diagram ([>>> Fig. 4-9](#)).




Fig. 4-9: Direction of rotation of robot axes

Mastering position

Mastering position	
A1	0 °
A2	-90 °
A3	90 °
A4	0 °
A5	0 °
A6	0 °

Working envelope

The following diagrams ([Fig. 4-10](#)) and ([Fig. 4-11](#)) show the load center of gravity and the shape and size of the working envelope.




Fig. 4-10: KR 6 R700 sixx W-CR, working envelope, side view




Fig. 4-11: KR 6 R700 sixx W-CR, working envelope, top view

Distance to flange

The distance to the flange varies according to the position of the robot (=> Fig. 4-12).




Fig. 4-12: Distance to flange, KR 6 R700 sixx CR (with W and C variant)

4.2.3 Payloads, KR 6 R700 sixx W-CR

Payloads

Rated payload	3 kg
Maximum payload	6 kg
Rated mass moment of inertia	0.045 kgm ²
Rated supplementary load, base frame	0 kg
Maximum supplementary load, base frame	6 kg
Rated supplementary load, rotating column	0 kg
Maximum supplementary load, rotating column	6 kg
Rated supplementary load, link arm	0 kg
Maximum supplementary load, link arm	6 kg
Rated supplementary load, arm	0 kg

Maximum supplementary load, arm	6 kg
Maximum total load	6 kg
Nominal distance to load center of gravity	
Lxy	60 mm
Lz	80 mm

! The sum of all loads mounted on the robot must not exceed the maximum total load.

Load center of gravity

For all payloads, the load center of gravity refers to the distance from the face of the mounting flange on axis 6. Refer to the payload diagram for the nominal distance.




Fig. 4-13: Load center of gravity

Payload diagram




Fig. 4-14: Payload diagram, payload 6 kg

NOTICE

This loading curve corresponds to the maximum load capacity. Both values (payload and mass moment of inertia) must be checked in all cases. Exceeding this capacity will reduce the service life of the robot and overload the motors and the gears; in any such case KUKA Deutschland GmbH must be consulted beforehand.

The values determined here are necessary for planning the robot application. For commissioning the robot, additional input data are required in accordance with the operating and programming instructions of the KUKA System Software.

The mass inertia must be verified using KUKA.Load. It is imperative for the load data to be entered in the robot controller!

In-line wrist

In-line wrist type	ZH6 R700 CR
Mounting flange	see drawing

Mounting flange

Mounting flange (hole circle)	31.5 mm
Screw grade	12.9
Screw size	M5
Number of fastening screws	7
Grip length	min. 1.5 x nominal diameter
Depth of engagement	min. 5.5 mm, max. 7 mm
Locating element	5 H7
Standard	See illustration

The mounting flange is depicted with axis 6 in the zero position. The symbol X_m indicates the position of the locating element in the zero position.

Dimensions: mm




Fig. 4-15: Mounting flange

4.2.4 Loads acting on the foundation, KR 6 R700 sixx W-CR

Foundation loads The specified forces and moments already include the maximum payload and the inertia force (weight) of the robot.




Fig. 4-16: Loads acting on the foundation, wall mounting

Vertical force F(v)	
F(v normal)	697 N
F(v max)	1297 N

Horizontal force F(h)	
F(h normal)	1223 N
F(h max)	1362 N
Tilting moment M(k)	
M(k normal)	788 Nm
M(k max)	1152 Nm
Torque about axis 1 M(r)	
M(r normal)	367 Nm
M(r max)	880 Nm

Vertical force F(v), horizontal force F(h), tilting torque M(k), torque about axis 1 M(r)



Normal loads and maximum loads for the foundations are specified in the table.

The maximum loads must be referred to when dimensioning the foundations and must be adhered to for safety reasons. Failure to observe this can result in personal injury and damage to property.

The normal loads are average expected foundation loads. The actual loads are dependent on the program and on the robot loads and may therefore be greater or less than the normal loads.

The supplementary loads (A1 and A2) are not taken into consideration in the calculation of the mounting base load. These supplementary loads must be taken into consideration for F_v .

4.3 Technical data, KR 6 R700 sixx C-CR

4.3.1 Basic data, KR 6 R700 sixx C-CR

Basic data

	KR 6 R700 sixx C-CR
Number of axes	6
Number of controlled axes	6
Volume of working envelope	1.36 m ³
Pose repeatability (ISO 9283)	± 0.03 mm
Weight	approx. 50 kg
Rated payload	3 kg
Maximum reach	706.7 mm
Protection rating (IEC 60529)	IP54
Protection rating, in-line wrist (IEC 60529)	IP54
Sound level	< 70 dB (A)
Mounting position	Ceiling
Footprint	320 mm x 320 mm
Hole pattern: mounting surface for kinematic system	C246
Permissible angle of inclination	-
Default color	Base frame: traffic white (RAL 9016); Moving parts: traffic white (RAL 9016); Protective cover: traffic white (RAL 9016)

	KR 6 R700 sixx C-CR
Controller	KR C4 smallsize-2; KR C4 compact
Transformation name	KR C4: KR6R700 C4SR CLG

Ambient conditions

Humidity class (EN 60204)	-
Classification of environmental conditions (EN 60721-3-3)	3K3
Cleanroom class (ISO 14644-1)	Class 2 at 40% override; Class 2 at 80% override
Ambient temperature	
During operation	5 °C to 45 °C (278 K to 318 K)
During storage/transportation	-40 °C to 60 °C (233 K to 333 K)

The manipulator may not be used under the following ambient conditions:

- High-pressure component washing systems
- Continuous submersion
- Acidic or alkaline environments
- Vacuum applications

Connecting cables

Cable designation	Connector designation robot controller - robot	Interface with robot
Motor cable	X20 - X30	Han Yellock 30
Data cable	X21 - X31	Han Q12
Data cable CAT5 (can be ordered as an option)	X65/X66 - XPN1	M12 connector
Connecting cable, external axes A7 and A8 (can be ordered as an option)	XP7 - XP7.1 XP8 - XP8.1	Connector M17 in each case
Ground conductor, equi-potential bonding (can be ordered as an option)		M4 ring cable lug

Only resolvers can be connected to the connections XP7.1 and XP8.1.

	Cable lengths
Standard	4 m
Option	1 m, 7 m, 15 m, 25 m

For detailed specifications of the connecting cables, see "Description of the connecting cables".

4.3.2 Axis data, KR 6 R700 sixx C-CR**Axis data**

Motion range
A1
A2
A3

A4	$\pm 185^\circ$
A5	$\pm 120^\circ$
A6	$\pm 350^\circ$
Speed with rated payload	
A1	360 °/s
A2	300 °/s
A3	360 °/s
A4	381 °/s
A5	388 °/s
A6	615 °/s



In the case of manipulators with a payload of 6 kg and a reach of R700, not every angle for axis A4 can be reached in the end position.

The direction of motion and the arrangement of the individual axes may be noted from the diagram ([>>> Fig. 4-17](#)).




Fig. 4-17: Direction of rotation of robot axes

Mastering position

Mastering position	
A1	0 °
A2	-90 °
A3	90 °
A4	0 °
A5	0 °
A6	0 °

Working envelope

The following diagrams ([>>> Fig. 4-18](#)) and ([>>> Fig. 4-19](#)) show the load center of gravity and the shape and size of the working envelope.




Fig. 4-18: KR 6 R700 sixx C-CR, working envelope, side view




Fig. 4-19: KR 6 R700 sixx C-CR, working envelope, top view

Distance to flange

The distance to the flange varies according to the position of the robot ([>>> Fig. 4-20](#)).




Fig. 4-20: Distance to flange, KR 6 R700 sixx CR (with W and C variant)

4.3.3 Payloads, KR 6 R700 sixx C-CR

Payloads

Rated payload	3 kg
Maximum payload	6 kg
Rated mass moment of inertia	0.045 kgm ²
Rated supplementary load, base frame	0 kg
Maximum supplementary load, base frame	6 kg
Rated supplementary load, rotating column	0 kg
Maximum supplementary load, rotating column	6 kg
Rated supplementary load, link arm	0 kg
Maximum supplementary load, link arm	6 kg
Rated supplementary load, arm	0 kg
Maximum supplementary load, arm	6 kg
Maximum total load	6 kg
Nominal distance to load center of gravity	
L _{xy}	60 mm
L _z	80 mm



The sum of all loads mounted on the robot must not exceed the maximum total load.

Load center of gravity

For all payloads, the load center of gravity refers to the distance from the face of the mounting flange on axis 6. Refer to the payload diagram for the nominal distance.




Fig. 4-21: Load center of gravity

Payload diagram




Fig. 4-22: Payload diagram, payload 6 kg

NOTICE

This loading curve corresponds to the maximum load capacity. Both values (payload and mass moment of inertia) must be checked in all cases. Exceeding this capacity will reduce the service life of the robot and overload the motors and the gears; in any such case KUKA Deutschland GmbH must be consulted beforehand.

The values determined here are necessary for planning the robot application. For commissioning the robot, additional input data are required in accordance with the operating and programming instructions of the KUKA System Software.

The mass inertia must be verified using KUKA.Load. It is imperative for the load data to be entered in the robot controller!

In-line wrist

In-line wrist type	ZH6 R700 CR
Mounting flange	see drawing

Mounting flange

Mounting flange (hole circle)	31.5 mm
Screw grade	12.9
Screw size	M5
Number of fastening screws	7
Grip length	min. 1.5 x nominal diameter

Depth of engagement	min. 5.5 mm, max. 7 mm
Locating element	5 H7
Standard	See illustration

The mounting flange is depicted with axis 6 in the zero position. The symbol X_m indicates the position of the locating element in the zero position.




Fig. 4-23: Mounting flange

4.3.4 Loads acting on the foundation, KR 6 R700 sixx C-CR

Foundation loads The specified forces and moments already include the maximum payload and the inertia force (weight) of the robot.




Fig. 4-24: Loads acting on the foundation, ceiling mounting

Vertical force $F(v)$	
$F(v \text{ normal})$	697 N
$F(v \text{ max})$	1297 N
Horizontal force $F(h)$	
$F(h \text{ normal})$	1223 N
$F(h \text{ max})$	1362 N
Tilting moment $M(k)$	
$M(k \text{ normal})$	788 Nm
$M(k \text{ max})$	1152 Nm
Torque about axis 1 $M(r)$	
$M(r \text{ normal})$	367 Nm
$M(r \text{ max})$	880 Nm

Vertical force $F(v)$, horizontal force $F(h)$, tilting moment $M(k)$, torque about axis 1 $M(r)$

WARNING

Normal loads and maximum loads for the foundations are specified in the table.

The maximum loads must be referred to when dimensioning the foundations and must be adhered to for safety reasons. Failure to observe this can result in personal injury and damage to property.

The normal loads are average expected foundation loads. The actual loads are dependent on the program and on the robot loads and may therefore be greater or less than the normal loads.

The supplementary loads (A1 and A2) are not taken into consideration in the calculation of the mounting base load. These supplementary loads must be taken into consideration for F_v .

4.4 Technical data, KR 6 R900 sixx CR

4.4.1 Basic data, KR 6 R900 sixx CR

Basic data

Basic data	KR 6 R900 sixx CR
Number of axes	6
Number of controlled axes	6
Volume of working envelope	2.85 m ³
Pose repeatability (ISO 9283)	± 0.03 mm
Weight	approx. 52 kg

KR 6 R900 sixx CR	
Rated payload	3 kg
Maximum reach	901.5 mm
Protection rating (IEC 60529)	IP54
Protection rating, in-line wrist (IEC 60529)	IP54
Sound level	< 70 dB (A)
Mounting position	Floor
Footprint	320 mm x 320 mm
Hole pattern: mounting surface for kinematic system	C246
Permissible angle of inclination	-
Default color	Base frame: traffic white (RAL 9016); Moving parts: traffic white (RAL 9016); Protective cover: traffic white (RAL 9016)
Controller	KR C4 smallsize-2; KR C4 compact
Transformation name	KR C4: KR6R900 C4SR FLR

Ambient conditions

Humidity class (EN 60204)	-
Classification of environmental conditions (EN 60721-3-3)	3K3
Cleanroom class (ISO 14644-1)	Class 2 at 40% override; Class 2 at 80% override
Ambient temperature	
During operation	5 °C to 45 °C (278 K to 318 K)
During storage/transportation	-40 °C to 60 °C (233 K to 333 K)

The manipulator may not be used under the following ambient conditions:

- High-pressure component washing systems
- Continuous submersion
- Acidic or alkaline environments
- Vacuum applications

Connecting cables

Cable designation	Connector designation robot controller - robot	Interface with robot
Motor cable	X20 - X30	Han Yellock 30
Data cable	X21 - X31	Han Q12
Data cable CAT5 (can be ordered as an option)	X65/X66 - XPN1	M12 connector

Cable designation	Connector designation robot controller - robot	Interface with robot
Connecting cable, external axes A7 and A8 (can be ordered as an option)	XP7 - XP7.1 XP8 - XP8.1	Connector M17 in each case
Ground conductor, equipotential bonding (can be ordered as an option)		M4 ring cable lug

Only resolvers can be connected to the connections XP7.1 and XP8.1.

	Cable lengths
Standard	4 m
Option	1 m, 7 m, 15 m, 25 m

For detailed specifications of the connecting cables, see "Description of the connecting cables".

4.4.2 Axis data, KR 6 R900 sixx CR

Axis data

Motion range	
A1	±170 °
A2	-190 ° / 45 °
A3	-120 ° / 156 °
A4	±185 °
A5	±120 °
A6	±350 °
Speed with rated payload	
A1	360 °/s
A2	300 °/s
A3	360 °/s
A4	381 °/s
A5	388 °/s
A6	615 °/s

The direction of motion and the arrangement of the individual axes may be noted from the diagram ([>>> Fig. 4-25](#)).




Fig. 4-25: Direction of rotation of robot axes

Mastering position

Mastering position	
A1	0 °
A2	-90 °
A3	90 °
A4	0 °
A5	0 °
A6	0 °

Working envelope

The following diagrams ([>>> Fig. 4-26](#)) and ([>>> Fig. 4-27](#)) show the load center of gravity and the shape and size of the working envelope.




Fig. 4-26: KR 6 R900 sixx CR working envelope, side view




Fig. 4-27: KR 6 R900 sixx CR working envelope, top view

Distance to flange

The distance to the flange varies according to the position of the robot ([>>> Fig. 4-28](#)).




Fig. 4-28: Distance to flange, KR 6 R900 sixx CR (with W and C variants)

4.4.3 Payloads, KR 6 R900 sixx CR

Payloads

Rated payload	3 kg
Maximum payload	6 kg
Rated mass moment of inertia	0.045 kgm ²
Rated supplementary load, base frame	0 kg
Maximum supplementary load, base frame	6 kg

Rated supplementary load, rotating column	0 kg
Maximum supplementary load, rotating column	6 kg
Rated supplementary load, link arm	0 kg
Maximum supplementary load, link arm	6 kg
Rated supplementary load, arm	0 kg
Maximum supplementary load, arm	6 kg
Maximum total load	6 kg
Nominal distance to load center of gravity	
L _{xy}	60 mm
L _z	80 mm



The sum of all loads mounted on the robot must not exceed the maximum total load.

Load center of gravity

For all payloads, the load center of gravity refers to the distance from the face of the mounting flange on axis 6. Refer to the payload diagram for the nominal distance.





Fig. 4-29: Load center of gravity

Payload diagram**Fig. 4-30: Payload diagram, payload 6 kg****NOTICE**

This loading curve corresponds to the maximum load capacity. Both values (payload and mass moment of inertia) must be checked in all cases. Exceeding this capacity will reduce the service life of the robot and overload the motors and the gears; in any such case KUKA Deutschland GmbH must be consulted beforehand.

The values determined here are necessary for planning the robot application. For commissioning the robot, additional input data are required in accordance with the operating and programming instructions of the KUKA System Software.

The mass inertia must be verified using KUKA.Load. It is imperative for the load data to be entered in the robot controller!

In-line wrist


In-line wrist type	ZH6 R900 CR
Mounting flange	see drawing

Mounting flange

Mounting flange (hole circle)	31.5 mm
Screw grade	12.9
Screw size	M5
Number of fastening screws	7
Grip length	min. 1.5 x nominal diameter
Depth of engagement	min. 5.5 mm, max. 7 mm
Locating element	5 H7
Standard	See illustration

The mounting flange is depicted with axis 6 in the zero position. The symbol X_m indicates the position of the locating element in the zero position.

Dimensions: mm

**Fig. 4-31: Mounting flange**

4.4.4 Loads acting on the foundation, KR 6 R900 sixx CR

Foundation loads The specified forces and moments already include the maximum payload and the inertia force (weight) of the robot.




Fig. 4-32: Loads acting on the foundation, floor mounting

Vertical force $F(v)$	
$F(v \text{ normal})$	697 N
$F(v \text{ max})$	1297 N
Horizontal force $F(h)$	
$F(h \text{ normal})$	1223 N
$F(h \text{ max})$	1362 N
Tilting moment $M(k)$	
$M(k \text{ normal})$	788 Nm
$M(k \text{ max})$	1152 Nm
Torque about axis 1 $M(r)$	
$M(r \text{ normal})$	367 Nm
$M(r \text{ max})$	880 Nm

Vertical force $F(v)$, horizontal force $F(h)$, tilting torque $M(k)$, torque about axis 1 $M(r)$

WARNING

Normal loads and maximum loads for the foundations are specified in the table.

The maximum loads must be referred to when dimensioning the foundations and must be adhered to for safety reasons. Failure to observe this can result in personal injury and damage to property.

The normal loads are average expected foundation loads. The actual loads are dependent on the program and on the robot loads and may therefore be greater or less than the normal loads.

The supplementary loads (A1 and A2) are not taken into consideration in the calculation of the mounting base load. These supplementary loads must be taken into consideration for F_v .

4.5 Technical data, KR 6 R900 sixx W-CR

4.5.1 Basic data, KR 6 R900 sixx W-CR

Basic data

	KR 6 R900 sixx W-CR
Number of axes	6
Number of controlled axes	6
Volume of working envelope	2.85 m ³
Pose repeatability (ISO 9283)	± 0.03 mm
Weight	approx. 52 kg
Rated payload	3 kg
Maximum reach	901.5 mm
Protection rating (IEC 60529)	IP54
Protection rating, in-line wrist (IEC 60529)	IP54
Sound level	< 70 dB (A)
Mounting position	Wall
Footprint	320 mm x 320 mm
Hole pattern: mounting surface for kinematic system	C246
Permissible angle of inclination	-
Default color	Base frame: traffic white (RAL 9016); Moving parts: traffic white (RAL 9016); Protective cover: traffic white (RAL 9016)
Controller	KR C4 smallsize-2; KR C4 compact
Transformation name	KR C4: KR6R900 C4SR WLL

Ambient conditions

Humidity class (EN 60204)	-
Classification of environmental conditions (EN 60721-3-3)	3K3
Cleanroom class (ISO 14644-1)	Class 2 at 40% override; Class 2 at 80% override
Ambient temperature	
During operation	5 °C to 45 °C (278 K to 318 K)
During storage/transportation	-40 °C to 60 °C (233 K to 333 K)

The manipulator may not be used under the following ambient conditions:

- High-pressure component washing systems
- Continuous submersion
- Acidic or alkaline environments
- Vacuum applications

Connecting cables

Cable designation	Connector designation robot controller - robot	Interface with robot
Motor cable	X20 - X30	Han Yellock 30
Data cable	X21 - X31	Han Q12

Cable designation	Connector designation robot controller - robot	Interface with robot
Data cable CAT5 (can be ordered as an option)	X65/X66 - XPN1	M12 connector
Connecting cable, external axes A7 and A8 (can be ordered as an option)	XP7 - XP7.1 XP8 - XP8.1	Connector M17 in each case
Ground conductor, equipotential bonding (can be ordered as an option)		M4 ring cable lug

Only resolvers can be connected to the connections XP7.1 and XP8.1.

	Cable lengths
Standard	4 m
Option	1 m, 7 m, 15 m, 25 m

For detailed specifications of the connecting cables, see "Description of the connecting cables".

4.5.2 Axis data, KR 6 R900 sixx W-CR

Axis data	Motion range
A1	±170 °
A2	-190 ° / 45 °
A3	-120 ° / 156 °
A4	±185 °
A5	±120 °
A6	±350 °
Speed with rated payload	
A1	360 °/s
A2	300 °/s
A3	360 °/s
A4	381 °/s
A5	388 °/s
A6	615 °/s

The direction of motion and the arrangement of the individual axes may be noted from the diagram ([>>> Fig. 4-33](#)).




Fig. 4-33: Direction of rotation of robot axes

Mastering position

Mastering position	
A1	0 °
A2	-90 °
A3	90 °
A4	0 °
A5	0 °
A6	0 °

Working envelope

The following diagrams ([>>> Fig. 4-34](#)) and ([>>> Fig. 4-35](#)) show the load center of gravity and the shape and size of the working envelope.




Fig. 4-34: KR 6 R900 sixx W-CR, working envelope, side view




Fig. 4-35: KR 6 R900 sixx W-CR, working envelope, top view

Distance to flange The distance to the flange varies according to the position of the robot ([>> Fig. 4-36](#)).




Fig. 4-36: Distance to flange, KR 6 R900 sixx CR (with W and C variants)

4.5.3 Payloads, KR 6 R900 sixx W-CR

Payloads

Rated payload	3 kg
Maximum payload	6 kg
Rated mass moment of inertia	0.045 kgm ²
Rated supplementary load, base frame	0 kg
Maximum supplementary load, base frame	6 kg
Rated supplementary load, rotating column	0 kg
Maximum supplementary load, rotating column	6 kg
Rated supplementary load, link arm	0 kg
Maximum supplementary load, link arm	6 kg
Rated supplementary load, arm	0 kg
Maximum supplementary load, arm	6 kg
Maximum total load	6 kg
Nominal distance to load center of gravity	
L _{xy}	60 mm
L _z	80 mm



The sum of all loads mounted on the robot must not exceed the maximum total load.

Load center of gravity

For all payloads, the load center of gravity refers to the distance from the face of the mounting flange on axis 6. Refer to the payload diagram for the nominal distance.




Fig. 4-37: Load center of gravity

Payload diagram




Fig. 4-38: Payload diagram, payload 6 kg

NOTICE

This loading curve corresponds to the maximum load capacity. Both values (payload and mass moment of inertia) must be checked in all cases. Exceeding this capacity will reduce the service life of the robot and overload the motors and the gears; in any such case KUKA Deutschland GmbH must be consulted beforehand.

The values determined here are necessary for planning the robot application. For commissioning the robot, additional input data are required in accordance with the operating and programming instructions of the KUKA System Software.

The mass inertia must be verified using KUKA.Load. It is imperative for the load data to be entered in the robot controller!

In-line wrist

In-line wrist type	ZH6 R900 CR
Mounting flange	see drawing

Mounting flange

Mounting flange (hole circle)	31.5 mm
Screw grade	12.9
Screw size	M5
Number of fastening screws	7
Grip length	min. 1.5 x nominal diameter

Depth of engagement	min. 5.5 mm, max. 7 mm
Locating element	5 H7
Standard	See illustration

The mounting flange is depicted with axis 6 in the zero position. The symbol X_m indicates the position of the locating element in the zero position.




Fig. 4-39: Mounting flange

4.5.4 Loads acting on the foundation, KR 6 R900 sixx W-CR

Foundation loads The specified forces and moments already include the maximum payload and the inertia force (weight) of the robot.




Fig. 4-40: Loads acting on the foundation, wall mounting

Vertical force F(v)	
F(v normal)	697 N
F(v max)	1297 N
Horizontal force F(h)	
F(h normal)	1223 N
F(h max)	1362 N
Tilting moment M(k)	
M(k normal)	788 Nm
M(k max)	1152 Nm
Torque about axis 1 M(r)	
M(r normal)	367 Nm
M(r max)	880 Nm

Vertical force F(v), horizontal force F(h), tilting torque M(k), torque about axis 1 M(r)

⚠ WARNING

Normal loads and maximum loads for the foundations are specified in the table.

The maximum loads must be referred to when dimensioning the foundations and must be adhered to for safety reasons. Failure to observe this can result in personal injury and damage to property.

The normal loads are average expected foundation loads. The actual loads are dependent on the program and on the robot loads and may therefore be greater or less than the normal loads.

The supplementary loads (A1 and A2) are not taken into consideration in the calculation of the mounting base load. These supplementary loads must be taken into consideration for F_v.

4.6 Technical data, KR 6 R900 sixx C-CR

4.6.1 Basic data, KR 6 R900 sixx C-CR

Basic data

	KR 6 R900 sixx C-CR
Number of axes	6
Number of controlled axes	6
Volume of working envelope	2.85 m ³
Pose repeatability (ISO 9283)	± 0.03 mm

KR 6 R900 sixx C-CR	
Weight	approx. 52 kg
Rated payload	3 kg
Maximum reach	901.5 mm
Protection rating (IEC 60529)	IP54
Protection rating, in-line wrist (IEC 60529)	IP54
Sound level	< 70 dB (A)
Mounting position	Ceiling
Footprint	320 mm x 320 mm
Hole pattern: mounting surface for kinematic system	C246
Permissible angle of inclination	-
Default color	Base frame: traffic white (RAL 9016); Moving parts: traffic white (RAL 9016); Protective cover: traffic white (RAL 9016)
Controller	KR C4 smallsize-2; KR C4 compact
Transformation name	KR C4: KR6R900 C4SR CLG

Ambient conditions

Humidity class (EN 60204)	-
Classification of environmental conditions (EN 60721-3-3)	3K3
Cleanroom class (ISO 14644-1)	Class 2 at 40% override; Class 2 at 80% override
Ambient temperature	
During operation	5 °C to 45 °C (278 K to 318 K)
During storage/transportation	-40 °C to 60 °C (233 K to 333 K)

The manipulator may not be used under the following ambient conditions:

- High-pressure component washing systems
- Continuous submersion
- Acidic or alkaline environments
- Vacuum applications

Connecting cables

Cable designation	Connector designation robot controller - robot	Interface with robot
Motor cable	X20 - X30	Han Yellock 30
Data cable	X21 - X31	Han Q12
Data cable CAT5 (can be ordered as an option)	X65/X66 - XPN1	M12 connector

Cable designation	Connector designation robot controller - robot	Interface with robot
Connecting cable, external axes A7 and A8 (can be ordered as an option)	XP7 - XP7.1 XP8 - XP8.1	Connector M17 in each case
Ground conductor, equipotential bonding (can be ordered as an option)		M4 ring cable lug

Only resolvers can be connected to the connections XP7.1 and XP8.1.

	Cable lengths
Standard	4 m
Option	1 m, 7 m, 15 m, 25 m

For detailed specifications of the connecting cables, see "Description of the connecting cables".

4.6.2 Axis data, KR 6 R900 sixx C-CR

Axis data

Motion range	
A1	±170 °
A2	-190 ° / 45 °
A3	-120 ° / 156 °
A4	±185 °
A5	±120 °
A6	±350 °
Speed with rated payload	
A1	360 °/s
A2	300 °/s
A3	360 °/s
A4	381 °/s
A5	388 °/s
A6	615 °/s

The direction of motion and the arrangement of the individual axes may be noted from the diagram ([>>> Fig. 4-41](#)).




Fig. 4-41: Direction of rotation of robot axes

Mastering position

Mastering position	
A1	0 °
A2	-90 °
A3	90 °
A4	0 °
A5	0 °
A6	0 °

Working envelope

The following diagrams ([>>> Fig. 4-42](#)) and ([>>> Fig. 4-43](#)) show the load center of gravity and the shape and size of the working envelope.




Fig. 4-42: Working envelope, KR 6 R900 sixx C-CR, working envelope, side view




Fig. 4-43: KR 6 R900 sixx C-CR, working envelope, top view

Distance to flange

The distance to the flange varies according to the position of the robot ([>> Fig. 4-44](#)).




Fig. 4-44: Distance to flange, KR 6 R900 sixx CR (with W and C variants)

4.6.3 Payloads, KR 6 R900 sixx C-CR

Payloads

Rated payload	3 kg
Maximum payload	6 kg
Rated mass moment of inertia	0.045 kgm ²
Rated supplementary load, base frame	0 kg
Maximum supplementary load, base frame	6 kg

Rated supplementary load, rotating column	0 kg
Maximum supplementary load, rotating column	6 kg
Rated supplementary load, link arm	0 kg
Maximum supplementary load, link arm	6 kg
Rated supplementary load, arm	0 kg
Maximum supplementary load, arm	6 kg
Maximum total load	6 kg
Nominal distance to load center of gravity	
L _{xy}	60 mm
L _z	80 mm



The sum of all loads mounted on the robot must not exceed the maximum total load.

Load center of gravity

For all payloads, the load center of gravity refers to the distance from the face of the mounting flange on axis 6. Refer to the payload diagram for the nominal distance.





Fig. 4-45: Load center of gravity

Payload diagram**Fig. 4-46: Payload diagram, payload 6 kg****NOTICE**

This loading curve corresponds to the maximum load capacity. Both values (payload and mass moment of inertia) must be checked in all cases. Exceeding this capacity will reduce the service life of the robot and overload the motors and the gears; in any such case KUKA Deutschland GmbH must be consulted beforehand.

The values determined here are necessary for planning the robot application. For commissioning the robot, additional input data are required in accordance with the operating and programming instructions of the KUKA System Software.

The mass inertia must be verified using KUKA.Load. It is imperative for the load data to be entered in the robot controller!

In-line wrist

In-line wrist type	ZH6 R900 CR
Mounting flange	see drawing

Mounting flange

Mounting flange (hole circle)	31.5 mm
Screw grade	12.9
Screw size	M5
Number of fastening screws	7
Grip length	min. 1.5 x nominal diameter
Depth of engagement	min. 5.5 mm, max. 7 mm
Locating element	5 H7
Standard	See illustration

The mounting flange is depicted with axis 6 in the zero position. The symbol X_m indicates the position of the locating element in the zero position.




Fig. 4-47: Mounting flange

4.6.4 Loads acting on the foundation, KR 6 R900 sixx C-CR

Foundation loads The specified forces and moments already include the maximum payload and the inertia force (weight) of the robot.




Fig. 4-48: Loads acting on the foundation, ceiling mounting

Vertical force F(v)	
F(v normal)	697 N
F(v max)	1297 N

Horizontal force F(h)	
F(h normal)	1223 N
F(h max)	1362 N
Tilting moment M(k)	
M(k normal)	788 Nm
M(k max)	1152 Nm
Torque about axis 1 M(r)	
M(r normal)	367 Nm
M(r max)	880 Nm

Vertical force F(v), horizontal force F(h), tilting torque M(k), torque about axis 1 M(r)



Normal loads and maximum loads for the foundations are specified in the table.

The maximum loads must be referred to when dimensioning the foundations and must be adhered to for safety reasons. Failure to observe this can result in personal injury and damage to property.

The normal loads are average expected foundation loads. The actual loads are dependent on the program and on the robot loads and may therefore be greater or less than the normal loads.

The supplementary loads (A1 and A2) are not taken into consideration in the calculation of the mounting base load. These supplementary loads must be taken into consideration for F_v .

4.7 Technical data, KR 10 R900 sixx CR

4.7.1 Basic data, KR 10 R900 sixx CR

Basic data

	KR 10 R900 sixx CR
Number of axes	6
Number of controlled axes	6
Volume of working envelope	2.85 m ³
Pose repeatability (ISO 9283)	± 0.03 mm
Weight	approx. 52 kg
Rated payload	5 kg
Maximum reach	901.5 mm
Protection rating (IEC 60529)	IP54
Protection rating, in-line wrist (IEC 60529)	IP54
Sound level	< 70 dB (A)
Mounting position	Floor
Footprint	320 mm x 320 mm
Hole pattern: mounting surface for kinematic system	C246
Permissible angle of inclination	-
Default color	Base frame: traffic white (RAL 9016); Moving parts: traffic white (RAL 9016); Protective cover: traffic white (RAL 9016)

	KR 10 R900 sixx CR
Controller	KR C4 smallsize-2; KR C4 compact
Transformation name	KR C4: KR10R900 C4SR FLR

Ambient conditions

Humidity class (EN 60204)	-
Classification of environmental conditions (EN 60721-3-3)	3K3
Cleanroom class (ISO 14644-1)	Class 2 at 40% override; Class 2 at 80% override
Ambient temperature	
During operation	5 °C to 45 °C (278 K to 318 K)
During storage/transportation	-40 °C to 60 °C (233 K to 333 K)

The manipulator may not be used under the following ambient conditions:

- High-pressure component washing systems
- Continuous submersion
- Acidic or alkaline environments
- Vacuum applications

Connecting cables

Cable designation	Connector designation robot controller - robot	Interface with robot
Motor cable	X20 - X30	Han Yellock 30
Data cable	X21 - X31	Han Q12
Data cable CAT5 (can be ordered as an option)	X65/X66 - XPN1	M12 connector
Connecting cable, external axes A7 and A8 (can be ordered as an option)	XP7 - XP7.1 XP8 - XP8.1	Connector M17 in each case
Ground conductor, equi-potential bonding (can be ordered as an option)		M4 ring cable lug

Only resolvers can be connected to the connections XP7.1 and XP8.1.

	Cable lengths
Standard	4 m
Option	1 m, 7 m, 15 m, 25 m

For detailed specifications of the connecting cables, see "Description of the connecting cables".

4.7.2 Axis data, KR 10 R900 sixx CR**Axis data**

Motion range	
A1	±170 °
A2	-190 ° / 45 °
A3	-120 ° / 156 °

A4	$\pm 185^\circ$
A5	$\pm 120^\circ$
A6	$\pm 350^\circ$
Speed with rated payload	
A1	300 °/s
A2	225 °/s
A3	225 °/s
A4	381 °/s
A5	311 °/s
A6	492 °/s

The direction of motion and the arrangement of the individual axes may be noted from the diagram ([>>> Fig. 4-49](#)).




Fig. 4-49: Direction of rotation of robot axes

Mastering position

Mastering position	
A1	0 °
A2	-90 °
A3	90 °
A4	0 °
A5	0 °
A6	0 °

Working envelope

The following diagrams ([>>> Fig. 4-50](#)) and ([>>> Fig. 4-51](#)) show the load center of gravity and the shape and size of the working envelope.




Fig. 4-50: KR 10 R900 sixx CR working envelope, side view




Fig. 4-51: KR 10 R900 sixx CR working envelope, top view

Distance to flange

The distance to the flange varies according to the position of the robot ([>>> Fig. 4-52](#)).




Fig. 4-52: Distance to flange, KR 10 R900 sixx CR (with W and C variant)

4.7.3 Payloads, KR 10 R900 sixx CR

Payloads

Rated payload	5 kg
Maximum payload	10 kg
Rated mass moment of inertia	0.045 kgm ²
Rated supplementary load, base frame	0 kg
Maximum supplementary load, base frame	10 kg
Rated supplementary load, rotating column	0 kg
Maximum supplementary load, rotating column	10 kg
Rated supplementary load, link arm	0 kg
Maximum supplementary load, link arm	10 kg
Rated supplementary load, arm	0 kg
Maximum supplementary load, arm	10 kg
Maximum total load	10 kg
Nominal distance to load center of gravity	
L _{xy}	100 mm
L _z	80 mm



The sum of all loads mounted on the robot must not exceed the maximum total load.

Load center of gravity

For all payloads, the load center of gravity refers to the distance from the face of the mounting flange on axis 6. Refer to the payload diagram for the nominal distance.




Fig. 4-53: Load center of gravity

Payload diagram




Fig. 4-54: Payload diagram, payload 10 kg

NOTICE

This loading curve corresponds to the maximum load capacity. Both values (payload and mass moment of inertia) must be checked in all cases. Exceeding this capacity will reduce the service life of the robot and overload the motors and the gears; in any such case KUKA Deutschland GmbH must be consulted beforehand. The values determined here are necessary for planning the robot application. For commissioning the robot, additional input data are required in accordance with the operating and programming instructions of the KUKA System Software. The mass inertia must be verified using KUKA.Load. It is imperative for the load data to be entered in the robot controller!

In-line wrist

In-line wrist type	ZH10 R900 CR
Mounting flange	see drawing

Mounting flange

Mounting flange (hole circle)	31.5 mm
Screw grade	12.9
Screw size	M5
Number of fastening screws	7
Grip length	min. 1.5 x nominal diameter
Depth of engagement	min. 5.5 mm, max. 7 mm
Locating element	5 H7
Standard	See illustration

The mounting flange is depicted with axis 6 in the zero position. The symbol X_m indicates the position of the locating element in the zero position.

Dimensions: mm




Fig. 4-55: Mounting flange

4.7.4 Loads acting on the foundation, KR 10 R900 sixx CR

Foundation loads The specified forces and moments already include the maximum payload and the inertia force (weight) of the robot.




Fig. 4-56: Loads acting on the foundation, floor mounting

Vertical force $F(v)$	
$F(v \text{ normal})$	697 N
$F(v \text{ max})$	1297 N
Horizontal force $F(h)$	
$F(h \text{ normal})$	1223 N
$F(h \text{ max})$	1362 N
Tilting moment $M(k)$	
$M(k \text{ normal})$	788 Nm
$M(k \text{ max})$	1152 Nm
Torque about axis 1 $M(r)$	
$M(r \text{ normal})$	367 Nm
$M(r \text{ max})$	880 Nm

Vertical force $F(v)$, horizontal force $F(h)$, tilting torque $M(k)$, torque about axis 1 $M(r)$

WARNING

Normal loads and maximum loads for the foundations are specified in the table.

The maximum loads must be referred to when dimensioning the foundations and must be adhered to for safety reasons. Failure to observe this can result in personal injury and damage to property.

The normal loads are average expected foundation loads. The actual loads are dependent on the program and on the robot loads and may therefore be greater or less than the normal loads.

The supplementary loads (A1 and A2) are not taken into consideration in the calculation of the mounting base load. These supplementary loads must be taken into consideration for F_v .

4.8 Technical data, KR 10 R900 sixx W-CR

4.8.1 Basic data, KR 10 R900 sixx W-CR

Basic data

	KR 10 R900 sixx W-CR
Number of axes	6
Number of controlled axes	6
Volume of working envelope	2.85 m ³
Pose repeatability (ISO 9283)	± 0.03 mm
Weight	approx. 52 kg
Rated payload	5 kg
Maximum reach	901.5 mm
Protection rating (IEC 60529)	IP54
Protection rating, in-line wrist (IEC 60529)	IP54
Sound level	< 70 dB (A)
Mounting position	Wall
Footprint	320 mm x 320 mm
Hole pattern: mounting surface for kinematic system	C246
Permissible angle of inclination	-
Default color	Base frame: traffic white (RAL 9016); Moving parts: traffic white (RAL 9016); Protective cover: traffic white (RAL 9016)
Controller	KR C4 smallsize-2; KR C4 compact
Transformation name	KR C4: KR10R900 C4SR WLL

Ambient conditions

Humidity class (EN 60204)	-
Classification of environmental conditions (EN 60721-3-3)	3K3
Cleanroom class (ISO 14644-1)	Class 2 at 40% override; Class 2 at 80% override
Ambient temperature	
During operation	5 °C to 45 °C (278 K to 318 K)
During storage/transportation	-40 °C to 60 °C (233 K to 333 K)

The manipulator may not be used under the following ambient conditions:

- High-pressure component washing systems
- Continuous submersion
- Acidic or alkaline environments
- Vacuum applications

Connecting cables

Cable designation	Connector designation robot controller - robot	Interface with robot
Motor cable	X20 - X30	Han Yellock 30
Data cable	X21 - X31	Han Q12

Cable designation	Connector designation robot controller - robot	Interface with robot
Data cable CAT5 (can be ordered as an option)	X65/X66 - XPN1	M12 connector
Connecting cable, external axes A7 and A8 (can be ordered as an option)	XP7 - XP7.1 XP8 - XP8.1	Connector M17 in each case
Ground conductor, equipotential bonding (can be ordered as an option)		M4 ring cable lug

Only resolvers can be connected to the connections XP7.1 and XP8.1.

	Cable lengths
Standard	4 m
Option	1 m, 7 m, 15 m, 25 m

For detailed specifications of the connecting cables, see "Description of the connecting cables".

4.8.2 Axis data, KR 10 R900 sixx W-CR

Axis data

Motion range	
A1	±170 °
A2	-190 ° / 45 °
A3	-120 ° / 156 °
A4	±185 °
A5	±120 °
A6	±350 °
Speed with rated payload	
A1	300 °/s
A2	225 °/s
A3	225 °/s
A4	381 °/s
A5	311 °/s
A6	492 °/s

The direction of motion and the arrangement of the individual axes may be noted from the diagram ([>>> Fig. 4-57](#)).




Fig. 4-57: Direction of rotation of robot axes

**Mastering
position**

Mastering position	
A1	0 °
A2	-90 °
A3	90 °
A4	0 °
A5	0 °
A6	0 °

**Working
envelope**

The following diagrams ([>>> Fig. 4-58](#)) and ([>>> Fig. 4-59](#)) show the load center of gravity and the shape and size of the working envelope.




Fig. 4-58: KR 10 R900 sixx W-CR, working envelope, side view




Fig. 4-59: KR 10 R900 sixx W-CR, working envelope, top view

Distance to flange

The distance to the flange varies according to the position of the robot ([>>> Fig. 4-60](#)).




Fig. 4-60: Distance to flange, KR 10 R900 sixx CR (with W and C variant)

4.8.3 Payloads, KR 10 R900 sixx W-CR

Payloads

Rated payload	5 kg
Maximum payload	10 kg
Rated mass moment of inertia	0.045 kgm ²
Rated supplementary load, base frame	0 kg
Maximum supplementary load, base frame	10 kg
Rated supplementary load, rotating column	0 kg
Maximum supplementary load, rotating column	10 kg
Rated supplementary load, link arm	0 kg
Maximum supplementary load, link arm	10 kg
Rated supplementary load, arm	0 kg
Maximum supplementary load, arm	10 kg
Maximum total load	10 kg
Nominal distance to load center of gravity	
L _{xy}	100 mm
L _z	80 mm



The sum of all loads mounted on the robot must not exceed the maximum total load.

Load center of gravity

For all payloads, the load center of gravity refers to the distance from the face of the mounting flange on axis 6. Refer to the payload diagram for the nominal distance.




Fig. 4-61: Load center of gravity

Payload diagram




Fig. 4-62: Payload diagram, payload 10 kg

NOTICE

This loading curve corresponds to the maximum load capacity. Both values (payload and mass moment of inertia) must be checked in all cases. Exceeding this capacity will reduce the service life of the robot and overload the motors and the gears; in any such case KUKA Deutschland GmbH must be consulted beforehand. The values determined here are necessary for planning the robot application. For commissioning the robot, additional input data are required in accordance with the operating and programming instructions of the KUKA System Software. The mass inertia must be verified using KUKA.Load. It is imperative for the load data to be entered in the robot controller!

In-line wrist

In-line wrist type	ZH10 R900 CR
Mounting flange	see drawing

Mounting flange

Mounting flange (hole circle)	31.5 mm
Screw grade	12.9
Screw size	M5
Number of fastening screws	7
Grip length	min. 1.5 x nominal diameter
Depth of engagement	min. 5.5 mm, max. 7 mm
Locating element	5 H7
Standard	See illustration

The mounting flange is depicted with axis 6 in the zero position. The symbol X_m indicates the position of the locating element in the zero position.

Dimensions: mm




Fig. 4-63: Mounting flange

4.8.4 Loads acting on the foundation, KR 10 R900 sixx W-CR

Foundation loads The specified forces and moments already include the maximum payload and the inertia force (weight) of the robot.




Fig. 4-64: Loads acting on the foundation, wall mounting

Vertical force F(v)	
F(v normal)	697 N
F(v max)	1297 N
Horizontal force F(h)	
F(h normal)	1223 N
F(h max)	1362 N
Tilting moment M(k)	
M(k normal)	788 Nm
M(k max)	1152 Nm
Torque about axis 1 M(r)	
M(r normal)	367 Nm
M(r max)	880 Nm

Vertical force F(v), horizontal force F(h), tilting torque M(k), torque about axis 1 M(r)

WARNING

Normal loads and maximum loads for the foundations are specified in the table.

The maximum loads must be referred to when dimensioning the foundations and must be adhered to for safety reasons. Failure to observe this can result in personal injury and damage to property.

The normal loads are average expected foundation loads. The actual loads are dependent on the program and on the robot loads and may therefore be greater or less than the normal loads.

The supplementary loads (A1 and A2) are not taken into consideration in the calculation of the mounting base load. These supplementary loads must be taken into consideration for F_v.

4.9 Technical data, KR 10 R900 sixx C-CR

4.9.1 Basic data, KR 10 R900 sixx C-CR

Basic data

	KR 10 R900 sixx C-CR
Number of axes	6
Number of controlled axes	6
Volume of working envelope	2.85 m ³
Pose repeatability (ISO 9283)	± 0.03 mm

KR 10 R900 sixx C-CR	
Weight	approx. 52 kg
Rated payload	5 kg
Maximum reach	901.5 mm
Protection rating (IEC 60529)	IP54
Protection rating, in-line wrist (IEC 60529)	IP54
Sound level	< 70 dB (A)
Mounting position	Ceiling
Footprint	320 mm x 320 mm
Hole pattern: mounting surface for kinematic system	C246
Permissible angle of inclination	-
Default color	Base frame: traffic white (RAL 9016); Moving parts: traffic white (RAL 9016); Protective cover: traffic white (RAL 9016)
Controller	KR C4 smallsize-2; KR C4 compact
Transformation name	KR C4: KR10R900 C4SR CLG

Ambient conditions

Humidity class (EN 60204)	-
Classification of environmental conditions (EN 60721-3-3)	3K3
Cleanroom class (ISO 14644-1)	Class 2 at 40% override; Class 2 at 80% override
Ambient temperature	
During operation	5 °C to 45 °C (278 K to 318 K)
During storage/transportation	-40 °C to 60 °C (233 K to 333 K)

The manipulator may not be used under the following ambient conditions:

- High-pressure component washing systems
- Continuous submersion
- Acidic or alkaline environments
- Vacuum applications

Connecting cables

Cable designation	Connector designation robot controller - robot	Interface with robot
Motor cable	X20 - X30	Han Yellock 30
Data cable	X21 - X31	Han Q12
Data cable CAT5 (can be ordered as an option)	X65/X66 - XPN1	M12 connector

Cable designation	Connector designation robot controller - robot	Interface with robot
Connecting cable, external axes A7 and A8 (can be ordered as an option)	XP7 - XP7.1 XP8 - XP8.1	Connector M17 in each case
Ground conductor, equipotential bonding (can be ordered as an option)		M4 ring cable lug

Only resolvers can be connected to the connections XP7.1 and XP8.1.

	Cable lengths
Standard	4 m
Option	1 m, 7 m, 15 m, 25 m

For detailed specifications of the connecting cables, see "Description of the connecting cables".

4.9.2 Axis data, KR 10 R900 sixx C-CR

Axis data

Motion range	
A1	±170 °
A2	-190 ° / 45 °
A3	-120 ° / 156 °
A4	±185 °
A5	±120 °
A6	±350 °
Speed with rated payload	
A1	300 °/s
A2	225 °/s
A3	225 °/s
A4	381 °/s
A5	311 °/s
A6	492 °/s

The direction of motion and the arrangement of the individual axes may be noted from the diagram ([>>>](#) Fig. 4-65).




Fig. 4-65: Direction of rotation of robot axes

Mastering position

Mastering position	
A1	0 °
A2	-90 °
A3	90 °
A4	0 °
A5	0 °
A6	0 °

Working envelope

The following diagrams ([Fig. 4-66](#)) and ([Fig. 4-67](#)) show the load center of gravity and the shape and size of the working envelope.




Fig. 4-66: KR 10 R900 sixx C-CR, working envelope, side view




Fig. 4-67: KR 10 R900 sixx C-CR, working envelope, top view

Distance to flange

The distance to the flange varies according to the position of the robot ([>>> Fig. 4-68](#)).




Fig. 4-68: Distance to flange, KR 10 R900 sixx CR (with W and C variant)

4.9.3 Payloads, KR 10 R900 sixx C-CR

Payloads

Rated payload	5 kg
Maximum payload	10 kg
Rated mass moment of inertia	0.045 kgm ²
Rated supplementary load, base frame	0 kg
Maximum supplementary load, base frame	10 kg

Rated supplementary load, rotating column	0 kg
Maximum supplementary load, rotating column	10 kg
Rated supplementary load, link arm	0 kg
Maximum supplementary load, link arm	10 kg
Rated supplementary load, arm	0 kg
Maximum supplementary load, arm	10 kg
Maximum total load	10 kg
Nominal distance to load center of gravity	
L _{xy}	100 mm
L _z	80 mm



The sum of all loads mounted on the robot must not exceed the maximum total load.

Load center of gravity

For all payloads, the load center of gravity refers to the distance from the face of the mounting flange on axis 6. Refer to the payload diagram for the nominal distance.





Fig. 4-69: Load center of gravity

Payload diagram**Fig. 4-70: Payload diagram, payload 10 kg****NOTICE**

This loading curve corresponds to the maximum load capacity. Both values (payload and mass moment of inertia) must be checked in all cases. Exceeding this capacity will reduce the service life of the robot and overload the motors and the gears; in any such case KUKA Deutschland GmbH must be consulted beforehand.

The values determined here are necessary for planning the robot application. For commissioning the robot, additional input data are required in accordance with the operating and programming instructions of the KUKA System Software.

The mass inertia must be verified using KUKA.Load. It is imperative for the load data to be entered in the robot controller!

In-line wrist

In-line wrist type	ZH10 R900 CR
Mounting flange	see drawing

Mounting flange

Mounting flange (hole circle)	31.5 mm
Screw grade	12.9
Screw size	M5
Number of fastening screws	7
Grip length	min. 1.5 x nominal diameter
Depth of engagement	min. 5.5 mm, max. 7 mm
Locating element	5 H7
Standard	See illustration

The mounting flange is depicted with axis 6 in the zero position. The symbol X_m indicates the position of the locating element in the zero position.

Dimensions: mm




Fig. 4-71: Mounting flange

4.9.4 Loads acting on the foundation, KR 10 R900 sixx C-CR

Foundation loads The specified forces and moments already include the maximum payload and the inertia force (weight) of the robot.




Fig. 4-72: Loads acting on the foundation, ceiling mounting

Vertical force F(v)	
F(v normal)	697 N
F(v max)	1297 N

Horizontal force F(h)	
F(h normal)	1223 N
F(h max)	1362 N
Tilting moment M(k)	
M(k normal)	788 Nm
M(k max)	1152 Nm
Torque about axis 1 M(r)	
M(r normal)	367 Nm
M(r max)	880 Nm

Vertical force F(v), horizontal force F(h), tilting torque M(k), torque about axis 1 M(r)



Normal loads and maximum loads for the foundations are specified in the table.

The maximum loads must be referred to when dimensioning the foundations and must be adhered to for safety reasons. Failure to observe this can result in personal injury and damage to property.

The normal loads are average expected foundation loads. The actual loads are dependent on the program and on the robot loads and may therefore be greater or less than the normal loads.

The supplementary loads (A1 and A2) are not taken into consideration in the calculation of the mounting base load. These supplementary loads must be taken into consideration for F_v .

4.10 Technical data, KR 10 R1100 sixx CR

4.10.1 Basic data, KR 10 R1100 sixx CR

Basic data

	KR 10 R1100 sixx CR
Number of axes	6
Number of controlled axes	6
Volume of working envelope	5.2 m ³
Pose repeatability (ISO 9283)	± 0.03 mm
Weight	approx. 55 kg
Rated payload	5 kg
Maximum reach	1101 mm
Protection rating (IEC 60529)	IP54
Protection rating, in-line wrist (IEC 60529)	IP54
Sound level	< 70 dB (A)
Mounting position	Floor
Footprint	320 mm x 320 mm
Hole pattern: mounting surface for kinematic system	C246
Permissible angle of inclination	-
Default color	Base frame: traffic white (RAL 9016); Moving parts: traffic white (RAL 9016); Protective cover: traffic white (RAL 9016)

	KR 10 R1100 sixx CR
Controller	KR C4 smallsize-2; KR C4 compact
Transformation name	KR C4: KR10R1100 C4SR FLR

Ambient conditions

Humidity class (EN 60204)	-
Classification of environmental conditions (EN 60721-3-3)	3K3
Cleanroom class (ISO 14644-1)	Class 2 at 40% override; Class 2 at 80% override
Ambient temperature	
During operation	5 °C to 45 °C (278 K to 318 K)
During storage/transportation	-40 °C to 60 °C (233 K to 333 K)

The manipulator may not be used under the following ambient conditions:

- High-pressure component washing systems
- Continuous submersion
- Acidic or alkaline environments
- Vacuum applications

Connecting cables

Cable designation	Connector designation robot controller - robot	Interface with robot
Motor cable	X20 - X30	Han Yellock 30
Data cable	X21 - X31	Han Q12
Data cable CAT5 (can be ordered as an option)	X65/X66 - XPN1	M12 connector
Connecting cable, external axes A7 and A8 (can be ordered as an option)	XP7 - XP7.1 XP8 - XP8.1	Connector M17 in each case
Ground conductor, equi-potential bonding (can be ordered as an option)		M4 ring cable lug

Only resolvers can be connected to the connections XP7.1 and XP8.1.

	Cable lengths
Standard	4 m
Option	1 m, 7 m, 15 m, 25 m

For detailed specifications of the connecting cables, see "Description of the connecting cables".

4.10.2 Axis data, KR 10 R1100 sixx CR**Axis data**

Motion range	
A1	±170 °
A2	-190 ° / 45 °
A3	-120 ° / 156 °

A4	$\pm 185^\circ$
A5	$\pm 120^\circ$
A6	$\pm 350^\circ$
Speed with rated payload	
A1	300 °/s
A2	225 °/s
A3	225 °/s
A4	381 °/s
A5	311 °/s
A6	492 °/s

The direction of motion and the arrangement of the individual axes may be noted from the diagram ([>>> Fig. 4-73](#)).




Fig. 4-73: Direction of rotation of robot axes

Mastering position

Mastering position	
A1	0 °
A2	-90 °
A3	90 °
A4	0 °
A5	0 °
A6	0 °

Working envelope

The following diagrams ([>>> Fig. 4-74](#)) and ([>>> Fig. 4-75](#)) show the load center of gravity and the shape and size of the working envelope.




Fig. 4-74: KR 10 R1100 sixx CR working envelope, side view




Fig. 4-75: KR 10 R1100 sixx CR working envelope, top view

Distance to flange The distance to the flange varies according to the position of the robot ([>> Fig. 4-76](#)).




Fig. 4-76: Distance to flange, KR 10 R1100 sixx CR (with W and C variant)

4.10.3 Payloads, KR 10 R1100 sixx CR

Payloads

Rated payload	5 kg
Maximum payload	10 kg
Rated mass moment of inertia	0.045 kgm ²
Rated supplementary load, base frame	0 kg
Maximum supplementary load, base frame	10 kg
Rated supplementary load, rotating column	0 kg
Maximum supplementary load, rotating column	10 kg
Rated supplementary load, link arm	0 kg
Maximum supplementary load, link arm	10 kg
Rated supplementary load, arm	0 kg
Maximum supplementary load, arm	10 kg
Maximum total load	10 kg
Nominal distance to load center of gravity	
L _{xy}	100 mm
L _z	80 mm



The sum of all loads mounted on the robot must not exceed the maximum total load.

Load center of gravity

For all payloads, the load center of gravity refers to the distance from the face of the mounting flange on axis 6. Refer to the payload diagram for the nominal distance.




Fig. 4-77: Load center of gravity


Payload diagram

Fig. 4-78: Payload diagram, payload 10 kg

NOTICE

This loading curve corresponds to the maximum load capacity. Both values (payload and mass moment of inertia) must be checked in all cases. Exceeding this capacity will reduce the service life of the robot and overload the motors and the gears; in any such case KUKA Deutschland GmbH must be consulted beforehand. The values determined here are necessary for planning the robot application. For commissioning the robot, additional input data are required in accordance with the operating and programming instructions of the KUKA System Software. The mass inertia must be verified using KUKA.Load. It is imperative for the load data to be entered in the robot controller!

In-line wrist

In-line wrist type	ZH10 R1100 CR
Mounting flange	see drawing

Mounting flange

Mounting flange (hole circle)	31.5 mm
Screw grade	12.9
Screw size	M5
Number of fastening screws	7
Grip length	min. 1.5 x nominal diameter
Depth of engagement	min. 5.5 mm, max. 7 mm
Locating element	5 H7
Standard	See illustration

The mounting flange is depicted with axis 6 in the zero position. The symbol X_m indicates the position of the locating element in the zero position.




Fig. 4-79: Mounting flange

4.10.4 Loads acting on the foundation, KR 10 R1100 sixx CR

Foundation loads The specified forces and moments already include the maximum payload and the inertia force (weight) of the robot.




Fig. 4-80: Loads acting on the foundation, floor mounting

Vertical force $F(v)$	
$F(v \text{ normal})$	697 N
$F(v \text{ max})$	1297 N
Horizontal force $F(h)$	
$F(h \text{ normal})$	1223 N
$F(h \text{ max})$	1362 N
Tilting moment $M(k)$	
$M(k \text{ normal})$	788 Nm
$M(k \text{ max})$	1152 Nm
Torque about axis 1 $M(r)$	
$M(r \text{ normal})$	367 Nm
$M(r \text{ max})$	880 Nm

Vertical force $F(v)$, horizontal force $F(h)$, tilting torque $M(k)$, torque about axis 1 $M(r)$

 **WARNING**

Normal loads and maximum loads for the foundations are specified in the table.

The maximum loads must be referred to when dimensioning the foundations and must be adhered to for safety reasons. Failure to observe this can result in personal injury and damage to property.

The normal loads are average expected foundation loads. The actual loads are dependent on the program and on the robot loads and may therefore be greater or less than the normal loads.

The supplementary loads (A_1 and A_2) are not taken into consideration in the calculation of the mounting base load. These supplementary loads must be taken into consideration for F_v .

4.11 Technical data, KR 10 R1100 sixx W-CR

4.11.1 Basic data, KR 10 R1100 sixx W-CR

Basic data

	KR 10 R1100 sixx W-CR
Number of axes	6
Number of controlled axes	6
Volume of working envelope	5.2 m ³
Pose repeatability (ISO 9283)	± 0.03 mm
Weight	approx. 55 kg
Rated payload	5 kg
Maximum reach	1101 mm
Protection rating (IEC 60529)	IP54
Protection rating, in-line wrist (IEC 60529)	IP54
Sound level	< 70 dB (A)
Mounting position	Wall
Footprint	320 mm x 320 mm
Hole pattern: mounting surface for kinematic system	C246
Permissible angle of inclination	-
Default color	Base frame: traffic white (RAL 9016); Moving parts: traffic white (RAL 9016); Protective cover: traffic white (RAL 9016)
Controller	KR C4 smallsize-2; KR C4 compact
Transformation name	KR C4: KR10R1100 C4SR WLL

Ambient conditions

Humidity class (EN 60204)	-
Classification of environmental conditions (EN 60721-3-3)	3K3
Cleanroom class (ISO 14644-1)	Class 2 at 40% override; Class 2 at 80% override
Ambient temperature	
During operation	5 °C to 45 °C (278 K to 318 K)
During storage/transportation	-40 °C to 60 °C (233 K to 333 K)

The manipulator may not be used under the following ambient conditions:

- High-pressure component washing systems
- Continuous submersion
- Acidic or alkaline environments
- Vacuum applications

Connecting cables

Cable designation	Connector designation robot controller - robot	Interface with robot
Motor cable	X20 - X30	Han Yellock 30
Data cable	X21 - X31	Han Q12

Cable designation	Connector designation robot controller - robot	Interface with robot
Data cable CAT5 (can be ordered as an option)	X65/X66 - XPN1	M12 connector
Connecting cable, external axes A7 and A8 (can be ordered as an option)	XP7 - XP7.1 XP8 - XP8.1	Connector M17 in each case
Ground conductor, equipotential bonding (can be ordered as an option)		M4 ring cable lug

Only resolvers can be connected to the connections XP7.1 and XP8.1.

	Cable lengths
Standard	4 m
Option	1 m, 7 m, 15 m, 25 m

For detailed specifications of the connecting cables, see "Description of the connecting cables".

4.11.2 Axis data, KR 10 R1100 sixx W-CR

Axis data	Motion range
A1	±170 °
A2	-190 ° / 45 °
A3	-120 ° / 156 °
A4	±185 °
A5	±120 °
A6	±350 °
Speed with rated payload	
A1	300 °/s
A2	225 °/s
A3	225 °/s
A4	381 °/s
A5	311 °/s
A6	492 °/s

The direction of motion and the arrangement of the individual axes may be noted from the diagram ([>>> Fig. 4-81](#)).




Fig. 4-81: Direction of rotation of robot axes

**Mastering
position**

Mastering position	
A1	0 °
A2	-90 °
A3	90 °
A4	0 °
A5	0 °
A6	0 °

**Working
envelope**

The following diagrams ([>>> Fig. 4-82](#)) and ([>>> Fig. 4-83](#)) show the load center of gravity and the shape and size of the working envelope.




Fig. 4-82: KR 10 R1100 sixx W-CR, working envelope, side view




Fig. 4-83: KR 10 R1100 sixx W-CR, working envelope, top view

Distance to flange The distance to the flange varies according to the position of the robot ([>>> Fig. 4-84](#)).




Fig. 4-84: Distance to flange, KR 10 R1100 sixx CR (with W and C variant)

4.11.3 Payloads, KR 10 R1100 sixx W-CR

Payloads

Rated payload	5 kg
Maximum payload	10 kg
Rated mass moment of inertia	0.045 kgm ²
Rated supplementary load, base frame	0 kg
Maximum supplementary load, base frame	10 kg
Rated supplementary load, rotating column	0 kg
Maximum supplementary load, rotating column	10 kg
Rated supplementary load, link arm	0 kg
Maximum supplementary load, link arm	10 kg
Rated supplementary load, arm	0 kg
Maximum supplementary load, arm	10 kg
Maximum total load	10 kg
Nominal distance to load center of gravity	
L _{xy}	100 mm
L _z	80 mm



The sum of all loads mounted on the robot must not exceed the maximum total load.

Load center of gravity

For all payloads, the load center of gravity refers to the distance from the face of the mounting flange on axis 6. Refer to the payload diagram for the nominal distance.




Fig. 4-85: Load center of gravity


Payload diagram

Fig. 4-86: Payload diagram, payload 10 kg

NOTICE

This loading curve corresponds to the maximum load capacity. Both values (payload and mass moment of inertia) must be checked in all cases. Exceeding this capacity will reduce the service life of the robot and overload the motors and the gears; in any such case KUKA Deutschland GmbH must be consulted beforehand. The values determined here are necessary for planning the robot application. For commissioning the robot, additional input data are required in accordance with the operating and programming instructions of the KUKA System Software. The mass inertia must be verified using KUKA.Load. It is imperative for the load data to be entered in the robot controller!

In-line wrist

In-line wrist type	ZH10 R1100 CR
Mounting flange	see drawing

Mounting flange

Mounting flange (hole circle)	31.5 mm
Screw grade	12.9
Screw size	M5
Number of fastening screws	7
Grip length	min. 1.5 x nominal diameter
Depth of engagement	min. 5.5 mm, max. 7 mm
Locating element	5 H7
Standard	See illustration

The mounting flange is depicted with axis 6 in the zero position. The symbol X_m indicates the position of the locating element in the zero position.




Fig. 4-87: Mounting flange

4.11.4 Loads acting on the foundation, KR 10 R1100 sixx W-CR

Foundation loads The specified forces and moments already include the maximum payload and the inertia force (weight) of the robot.




Fig. 4-88: Loads acting on the foundation, wall mounting

Vertical force F(v)	
F(v normal)	697 N
F(v max)	1297 N
Horizontal force F(h)	
F(h normal)	1223 N
F(h max)	1362 N
Tilting moment M(k)	
M(k normal)	788 Nm
M(k max)	1152 Nm
Torque about axis 1 M(r)	
M(r normal)	367 Nm
M(r max)	880 Nm

Vertical force F(v), horizontal force F(h), tilting torque M(k), torque about axis 1 M(r)

WARNING

Normal loads and maximum loads for the foundations are specified in the table.

The maximum loads must be referred to when dimensioning the foundations and must be adhered to for safety reasons. Failure to observe this can result in personal injury and damage to property.

The normal loads are average expected foundation loads. The actual loads are dependent on the program and on the robot loads and may therefore be greater or less than the normal loads.

The supplementary loads (A1 and A2) are not taken into consideration in the calculation of the mounting base load. These supplementary loads must be taken into consideration for F_v.

4.12 Technical data, KR 10 R1100 sixx C-CR

4.12.1 Basic data, KR 10 R1100 sixx C-CR

Basic data

	KR 10 R1100 sixx C-CR
Number of axes	6
Number of controlled axes	6
Volume of working envelope	5.2 m ³
Pose repeatability (ISO 9283)	± 0.03 mm

KR 10 R1100 sixx C-CR	
Weight	approx. 55 kg
Rated payload	5 kg
Maximum reach	1101 mm
Protection rating (IEC 60529)	IP54
Protection rating, in-line wrist (IEC 60529)	IP54
Sound level	< 70 dB (A)
Mounting position	Ceiling
Footprint	320 mm x 320 mm
Hole pattern: mounting surface for kinematic system	C246
Permissible angle of inclination	-
Default color	Base frame: traffic white (RAL 9016); Moving parts: traffic white (RAL 9016); Protective cover: traffic white (RAL 9016)
Controller	KR C4 smallsize-2; KR C4 compact
Transformation name	KR C4: KR10R1100 C4SR CLG

Ambient conditions

Humidity class (EN 60204)	-
Classification of environmental conditions (EN 60721-3-3)	3K3
Cleanroom class (ISO 14644-1)	Class 2 at 40% override; Class 2 at 80% override
Ambient temperature	
During operation	5 °C to 45 °C (278 K to 318 K)
During storage/transportation	-40 °C to 60 °C (233 K to 333 K)

The manipulator may not be used under the following ambient conditions:

- High-pressure component washing systems
- Continuous submersion
- Acidic or alkaline environments
- Vacuum applications

Connecting cables

Cable designation	Connector designation robot controller - robot	Interface with robot
Motor cable	X20 - X30	Han Yellock 30
Data cable	X21 - X31	Han Q12
Data cable CAT5 (can be ordered as an option)	X65/X66 - XPN1	M12 connector

Cable designation	Connector designation robot controller - robot	Interface with robot
Connecting cable, external axes A7 and A8 (can be ordered as an option)	XP7 - XP7.1 XP8 - XP8.1	Connector M17 in each case
Ground conductor, equipotential bonding (can be ordered as an option)		M4 ring cable lug

Only resolvers can be connected to the connections XP7.1 and XP8.1.

	Cable lengths
Standard	4 m
Option	1 m, 7 m, 15 m, 25 m

For detailed specifications of the connecting cables, see "Description of the connecting cables".

4.12.2 Axis data, KR 10 R1100 sixx C-CR

Axis data

Motion range	
A1	±170 °
A2	-190 ° / 45 °
A3	-120 ° / 156 °
A4	±185 °
A5	±120 °
A6	±350 °
Speed with rated payload	
A1	300 °/s
A2	225 °/s
A3	225 °/s
A4	381 °/s
A5	311 °/s
A6	492 °/s

The direction of motion and the arrangement of the individual axes may be noted from the diagram ([>>> Fig. 4-89](#)).




Fig. 4-89: Direction of rotation of robot axes

Mastering position

Mastering position	
A1	0 °
A2	-90 °
A3	90 °
A4	0 °
A5	0 °
A6	0 °

Working envelope

The following diagrams ([>>> Fig. 4-90](#)) and ([>>> Fig. 4-91](#)) show the load center of gravity and the shape and size of the working envelope.




Fig. 4-90: KR 10 R1100 sixx C-CR, working envelope, side view




Fig. 4-91: KR 10 R1100 sixx C-CR, working envelope, top view

Distance to flange

The distance to the flange varies according to the position of the robot ([>>> Fig. 4-92](#)).




Fig. 4-92: Distance to flange, KR 10 R1100 sixx CR (with W and C variant)

4.12.3 Payloads, KR 10 R1100 sixx C-CR

Payloads

Rated payload	5 kg
Maximum payload	10 kg
Rated mass moment of inertia	0.045 kgm ²
Rated supplementary load, base frame	0 kg
Maximum supplementary load, base frame	10 kg

Rated supplementary load, rotating column	0 kg
Maximum supplementary load, rotating column	10 kg
Rated supplementary load, link arm	0 kg
Maximum supplementary load, link arm	10 kg
Rated supplementary load, arm	0 kg
Maximum supplementary load, arm	10 kg
Maximum total load	10 kg
Nominal distance to load center of gravity	
L _{xy}	100 mm
L _z	80 mm



The sum of all loads mounted on the robot must not exceed the maximum total load.

Load center of gravity

For all payloads, the load center of gravity refers to the distance from the face of the mounting flange on axis 6. Refer to the payload diagram for the nominal distance.





Fig. 4-93: Load center of gravity

Payload diagram**Fig. 4-94: Payload diagram, payload 10 kg****NOTICE**

This loading curve corresponds to the maximum load capacity. Both values (payload and mass moment of inertia) must be checked in all cases. Exceeding this capacity will reduce the service life of the robot and overload the motors and the gears; in any such case KUKA Deutschland GmbH must be consulted beforehand. The values determined here are necessary for planning the robot application. For commissioning the robot, additional input data are required in accordance with the operating and programming instructions of the KUKA System Software. The mass inertia must be verified using KUKA.Load. It is imperative for the load data to be entered in the robot controller!

In-line wrist

In-line wrist type	ZH10 R1100 CR
Mounting flange	see drawing

Mounting flange

Mounting flange (hole circle)	31.5 mm
Screw grade	12.9
Screw size	M5
Number of fastening screws	7
Grip length	min. 1.5 x nominal diameter
Depth of engagement	min. 5.5 mm, max. 7 mm
Locating element	5 H7
Standard	See illustration

The mounting flange is depicted with axis 6 in the zero position. The symbol X_m indicates the position of the locating element in the zero position.

Dimensions: mm




Fig. 4-95: Mounting flange

4.12.4 Loads acting on the foundation, KR 10 R1100 sixx C-CR

Foundation loads The specified forces and moments already include the maximum payload and the inertia force (weight) of the robot.




Fig. 4-96: Loads acting on the foundation, ceiling mounting

Vertical force F(v)	
F(v normal)	697 N
F(v max)	1297 N

Horizontal force F(h)	
F(h normal)	1223 N
F(h max)	1362 N
Tilting moment M(k)	
M(k normal)	788 Nm
M(k max)	1152 Nm
Torque about axis 1 M(r)	
M(r normal)	367 Nm
M(r max)	880 Nm

Vertical force F(v), horizontal force F(h), tilting torque M(k), torque about axis 1 M(r)



WARNING Normal loads and maximum loads for the foundations are specified in the table.

The maximum loads must be referred to when dimensioning the foundations and must be adhered to for safety reasons. Failure to observe this can result in personal injury and damage to property.

The normal loads are average expected foundation loads. The actual loads are dependent on the program and on the robot loads and may therefore be greater or less than the normal loads.

The supplementary loads (A1 and A2) are not taken into consideration in the calculation of the mounting base load. These supplementary loads must be taken into consideration for F_v .

4.13 Supplementary load

The robot can carry supplementary loads on the arm, on the in-line wrist, on the link arm and on the rotating column. The fastening holes on the arm, link arm and rotating column are used for fastening the covers or external energy supply systems. Parts of the energy supply system (e.g. holders for compressed air hose) are fastened to the in-line wrist using the fastening holes. When mounting the supplementary loads, be careful to observe the maximum permissible total load. The dimensions and positions of the installation options can be seen in the following diagram.



The sum of all loads mounted on the robot must not exceed the maximum total load.

Further information about the supplementary load on the robot can be found in the following sections.

Robot	Description
<ul style="list-style-type: none"> ■ KR 6 R700 sixx CR ■ KR 6 R700 sixx W-CR ■ KR 6 R700 sixx C-CR 	(>>> 4.13.1 "Supplementary load, reach R700" Page 111)

Robot	Description
<ul style="list-style-type: none"> ■ KR 6 R900 sixx CR ■ KR 6 R900 sixx W-CR ■ KR 6 R900 sixx C-CR 	
<ul style="list-style-type: none"> ■ KR 10 R900 sixx CR ■ KR 10 R900 sixx W-CR ■ KR 10 R900 sixx C-CR 	(>>> 4.13.2 "Supplementary load, reach R900" Page 112)
<ul style="list-style-type: none"> ■ KR 10 R1100 sixx CR ■ KR 10 R1100 sixx W-CR ■ KR 10 R1100 sixx C-CR 	(>>> 4.13.3 "Supplementary load, reach R1100" Page 113)

4.13.1 Supplementary load, reach R700

The following diagrams (>>> Fig. 4-97) and (>>> Fig. 4-98) show the dimensions and position of the installation options on the arm, in-line wrist, link arm and rotating column.




Fig. 4-97: Supplementary load on arm and in-line wrist

1 Support bracket for supplementary load




Fig. 4-98: Supplementary load on link arm and rotating column

1 Support bracket for supplementary load

4.13.2 Supplementary load, reach R900

The following diagrams ([>>> Fig. 4-99](#)) and ([>>> Fig. 4-100](#)) show the dimensions and position of the installation options on the arm, in-line wrist, link arm and rotating column.




Fig. 4-99: Supplementary load on arm and in-line wrist

1 Support bracket for supplementary load




Fig. 4-100: Supplementary load on link arm and rotating column

1 Support bracket for supplementary load

4.13.3 Supplementary load, reach R1100

The following diagrams ([>>> Fig. 4-101](#)) and ([>>> Fig. 4-102](#)) show the dimensions and position of the installation options on the arm, in-line wrist, link arm and rotating column.




Fig. 4-101: Supplementary load on arm and in-line wrist

1 Support bracket for supplementary load




Fig. 4-102: Supplementary load on link arm and rotating column

1 Support bracket for supplementary load

4.14 Plates and labels

Plates and labels The following plates and labels are attached to the robot. They must not be removed or rendered illegible. Illegible plates and labels must be replaced.







Fig. 4-103: Plates and labels

Item	Description												
1	 <p>Secure the axes Before exchanging any motor, secure the corresponding axis through safeguarding by suitable means/devices to protect against possible movement. The axis can move. Risk of crushing!</p>												
2	 <table border="1"> <tr> <td>A1</td> <td>A2</td> <td>A3</td> <td>A4</td> <td>A5</td> <td>A6</td> </tr> <tr> <td>0°</td> <td>-105°</td> <td>+156°</td> <td>0°</td> <td>+120°</td> <td>0°</td> </tr> </table> <p>CAUTION Move the robot into its transport position before removing the mounting base!</p> <p>ATTENTION Amener le robot en position de transport avant de défaire la fixation aux fondations!</p> <p>VORSICHT Roboter vor Lösen der Fundamentbefestigung in Transportstellung bringen!</p> <p>Transport position Before loosening the bolts of the mounting base, the robot must be in the transport position as indicated in the table. Risk of toppling!</p>	A1	A2	A3	A4	A5	A6	0°	-105°	+156°	0°	+120°	0°
A1	A2	A3	A4	A5	A6								
0°	-105°	+156°	0°	+120°	0°								
3	 <p>Danger zone Entering the danger zone of the robot is prohibited if the robot is in operation or ready for operation. Risk of injury!</p>												

Item	Description																																				
4	   <p>00-259-735</p> <table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td style="padding: 5px; background-color: yellow;">CAUTION</td> <td style="padding: 5px;">Secure the system before beginning work on the robot. Read and observe the safety instructions!</td> </tr> <tr> <td style="padding: 5px; background-color: yellow;">ATTENTION</td> <td style="padding: 5px;">Bloquer le système avant d'effectuer des travaux sur le robot. Lire et respecter les remarques relatives à la sécurité!</td> </tr> <tr> <td style="padding: 5px; background-color: yellow;">VORSICHT</td> <td style="padding: 5px;">Vor Arbeiten am Roboter, System sichern. Sicherheitshinweise lesen und beachten!</td> </tr> </table> <p>Work on the robot Before start-up, transportation or maintenance, read and follow the assembly and operating instructions.</p>	CAUTION	Secure the system before beginning work on the robot. Read and observe the safety instructions!	ATTENTION	Bloquer le système avant d'effectuer des travaux sur le robot. Lire et respecter les remarques relatives à la sécurité!	VORSICHT	Vor Arbeiten am Roboter, System sichern. Sicherheitshinweise lesen und beachten!																														
CAUTION	Secure the system before beginning work on the robot. Read and observe the safety instructions!																																				
ATTENTION	Bloquer le système avant d'effectuer des travaux sur le robot. Lire et respecter les remarques relatives à la sécurité!																																				
VORSICHT	Vor Arbeiten am Roboter, System sichern. Sicherheitshinweise lesen und beachten!																																				
5	 <p>KUKA Deutschland GmbH Zugspitzstraße 140 86165 Augsburg Germany Country of Origin Germany</p> <table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td>Typ</td> <td>Type</td> <td>Type</td> <td>XXXXXXXXXXXXXXXXXXXXXXXXXXXXXX</td> </tr> <tr> <td>Artikel-Nr.</td> <td>Article No.</td> <td>No. d'article</td> <td>XXXXXXXXXX</td> </tr> <tr> <td>Serie-Nr.</td> <td>Serial No.</td> <td>No. Série#</td> <td>XXXXXX</td> </tr> <tr> <td>Baujahr</td> <td>Date</td> <td>Année de fabric.</td> <td>XXXX-XX</td> </tr> <tr> <td>Gewicht</td> <td>Weight</td> <td>Poids</td> <td>XXXX kg</td> </tr> <tr> <td>Traglast</td> <td>Load</td> <td>Charge</td> <td>XXX kg</td> </tr> <tr> <td>Reichweite Range</td> <td></td> <td>Portée</td> <td>XXXX MM</td> </tr> <tr> <td colspan="2">STRAFONAME[]="#...."</td> <td></td> <td>XXXXXXXXXXXXXXXXXXXXXXXXXXXXXX</td> </tr> <tr> <td colspan="2">...IMADA</td> <td></td> <td>XXXXXXXXXXXXXXXXXXXXXXXXXXXXXX</td> </tr> </table> <p>de/en/fr</p> <p>Identification plate Content according to Machinery Directive.</p>	Typ	Type	Type	XXXXXXXXXXXXXXXXXXXXXXXXXXXXXX	Artikel-Nr.	Article No.	No. d'article	XXXXXXXXXX	Serie-Nr.	Serial No.	No. Série#	XXXXXX	Baujahr	Date	Année de fabric.	XXXX-XX	Gewicht	Weight	Poids	XXXX kg	Traglast	Load	Charge	XXX kg	Reichweite Range		Portée	XXXX MM	STRAFONAME[]="#...."			XXXXXXXXXXXXXXXXXXXXXXXXXXXXXX	...IMADA			XXXXXXXXXXXXXXXXXXXXXXXXXXXXXX
Typ	Type	Type	XXXXXXXXXXXXXXXXXXXXXXXXXXXXXX																																		
Artikel-Nr.	Article No.	No. d'article	XXXXXXXXXX																																		
Serie-Nr.	Serial No.	No. Série#	XXXXXX																																		
Baujahr	Date	Année de fabric.	XXXX-XX																																		
Gewicht	Weight	Poids	XXXX kg																																		
Traglast	Load	Charge	XXX kg																																		
Reichweite Range		Portée	XXXX MM																																		
STRAFONAME[]="#...."			XXXXXXXXXXXXXXXXXXXXXXXXXXXXXX																																		
...IMADA			XXXXXXXXXXXXXXXXXXXXXXXXXXXXXX																																		

4.15 Stopping distances and times

4.15.1 General information

Information concerning the data:

- The stopping distance is the angle traveled by the robot from the moment the stop signal is triggered until the robot comes to a complete standstill.
- The stopping time is the time that elapses from the moment the stop signal is triggered until the robot comes to a complete standstill.
- The data are given for the main axes A1, A2 and A3. The main axes are the axes with the greatest deflection.
- Superposed axis motions can result in longer stopping distances.
- Stopping distances and stopping times in accordance with DIN EN ISO 10218-1, Annex B.
- Stop categories:
 - Stop category 0 » STOP 0
 - Stop category 1 » STOP 1

according to IEC 60204-1
- The values specified for Stop 0 are guide values determined by means of tests and simulation. They are average values which conform to the requirements of DIN EN ISO 10218-1. The actual stopping distances and stopping times may differ due to internal and external influences on the braking torque. It is therefore advisable to determine the exact stopping

distances and stopping times where necessary under the real conditions of the actual robot application.

■ Measuring technique

The stopping distances were measured using the robot-internal measuring technique.

■ The wear on the brakes varies depending on the operating mode, robot application and the number of STOP 0 stops triggered. It is therefore advisable to check the stopping distance at least once a year.

4.15.2 Terms used

Term	Description
m	Mass of the rated load and the supplementary load on the arm.
Phi	Angle of rotation (°) about the corresponding axis. This value can be entered in the controller via the KCP/smartPAD and can be displayed on the KCP/smartPAD.
POV	Program override (%) = velocity of the robot motion. This value can be entered in the controller via the KCP/smartPAD and can be displayed on the KCP/smartPAD.
Extension	Distance (l in %) (>>> Fig. 4-104) between axis 1 and the intersection of axes 4 and 5. With parallelogram robots, the distance between axis 1 and the intersection of axis 6 and the mounting flange.
KCP	KUKA Control Panel Teach pendant for the KR C2/KR C2 edition2005 The KCP has all the operator control and display functions required for operating and programming the industrial robot.
smartPAD	Teach pendant for the KR C4 The smartPAD has all the operator control and display functions required for operating and programming the industrial robot.




Fig. 4-104: Extension

4.15.3 Stopping distances and times, KR 6 R700 sixx CR and KR 6 R700 sixx C-CR

The following values are preliminary values and are valid for the following robots.


- KR 6 R700 sixx CR
- KR 6 R700 sixx C-CR

4.15.3.1 Stopping distances and stopping times for STOP 0, axis 1 to axis 3

The table shows the stopping distances and stopping times after a STOP 0 (category 0 stop) is triggered. The values refer to the following configuration:

- Extension $I = 100\%$
- Program override POV = 100%
- Mass m = maximum load (rated load + supplementary load on arm)

	Stopping distance (°)	Stopping time (s)
Axis 1	133.67	0.494
Axis 2	122.43	0.556
Axis 3	79.29	0.371

4.15.3.2 Stopping distances and stopping times for STOP 1, axis 1**Fig. 4-105: Stopping distances for STOP 1, axis 1**




Fig. 4-106: Stopping times for STOP 1, axis 1

4.15.3.3 Stopping distances and stopping times for STOP 1, axis 2




Fig. 4-107: Stopping distances for STOP 1, axis 2




Fig. 4-108: Stopping times for STOP 1, axis 2

4.15.3.4 Stopping distances and stopping times for STOP 1, axis 3




Fig. 4-109: Stopping distances for STOP 1, axis 3




Fig. 4-110: Stopping times for STOP 1, axis 3

4.15.4 Stopping distances and times, KR 6 R700 sixx W-CR

The following values are preliminary values and are valid for the following robots.


- KR 6 R700 sixx W-CR

4.15.4.1 Stopping distances and stopping times for STOP 0, axis 1 to axis 3

The table shows the stopping distances and stopping times after a STOP 0 (category 0 stop) is triggered. The values refer to the following configuration:

- Extension I = 100%
- Program override POV = 100%
- Mass m = maximum load (rated load + supplementary load on arm)

	Stopping distance (°)	Stopping time (s)
Axis 1	182.04	0.665
Axis 2	68.31	0.377
Axis 3	63.48	0.379

4.15.4.2 Stopping distances and stopping times for STOP 1, axis 1**Fig. 4-111: Stopping distances for STOP 1, axis 1**





Fig. 4-112: Stopping times for STOP 1, axis 1

4.15.4.3 Stopping distances and stopping times for STOP 1, axis 2**Fig. 4-113: Stopping distances for STOP 1, axis 1**




Fig. 4-114: Stopping times for STOP 1, axis 1

4.15.4.4 Stopping distances and stopping times for STOP 1, axis 2




Fig. 4-115: Stopping distances for STOP 1, axis 1




Fig. 4-116: Stopping times for STOP 1, axis 1

4.15.5 Stopping distances and times, KR 6 R900 sixx CR and KR 6 R900 sixx C-CR

The following values are valid for the following robots:

- KR 6 R900 sixx CR
- KR 6 R900 sixx C-CR

4.15.5.1 Stopping distances and stopping times for STOP 0, axis 1 to axis 3

The table shows the stopping distances and stopping times after a STOP 0 (category 0 stop) is triggered. The values refer to the following configuration:

- Extension I = 100%
- Program override POV = 100%
- Mass m = maximum load (rated load + supplementary load on arm)

	Stopping distance (°)	Stopping time (s)
Axis 1	113.59	0.507
Axis 2	126.76	0.684
Axis 3	68.10	0.370

4.15.5.2 Stopping distances and stopping times for STOP 1, axis 1




Fig. 4-117: Stopping distances for STOP 1, axis 1





Fig. 4-118: Stopping times for STOP 1, axis 1

4.15.5.3 Stopping distances and stopping times for STOP 1, axis 2**Fig. 4-119: Stopping distances for STOP 1, axis 2**




Fig. 4-120: Stopping times for STOP 1, axis 2

4.15.5.4 Stopping distances and stopping times for STOP 1, axis 3




Fig. 4-121: Stopping distances for STOP 1, axis 3




Fig. 4-122: Stopping times for STOP 1, axis 3

4.15.6 Stopping distances and times, KR 6 R900 sixx W-CR

The following values are valid for the following robots:

- KR 6 R900 sixx W-CR

4.15.6.1 Stopping distances and stopping times for STOP 0, axis 1 to axis 3

The table shows the stopping distances and stopping times after a STOP 0 (category 0 stop) is triggered. The values refer to the following configuration:

- Extension I = 100 %
- Program override POV = 100 %
- Mass m = maximum load (rated load + supplementary load on arm)

	Stopping distance (°)	Stopping time (s)
Axis 1	163.11	0.745
Axis 2	67.78	0.404
Axis 3	60.96	0.387

4.15.6.2 Stopping distances and stopping times for STOP 1, axis 1




Fig. 4-123: Stopping distances for STOP 1, axis 1





Fig. 4-124: Stopping times for STOP 1, axis 1

4.15.6.3 Stopping distances and stopping times for STOP 1, axis 2**Fig. 4-125: Stopping distances for STOP 1, axis 2**




Fig. 4-126: Stopping times for STOP 1, axis 2

4.15.6.4 Stopping distances and stopping times for STOP 1, axis 3




Fig. 4-127: Stopping distances for STOP 1, axis 3




Fig. 4-128: Stopping times for STOP 1, axis 3

4.15.7 Stopping distances and times, KR 10 R900 sixx CR and KR 10 R1100 sixx CR (with C variant)

The following values are preliminary values and are valid for the following robots.

- KR 10 R900 sixx CR
- KR 10 R900 sixx C-CR
- KR 10 R1100 sixx CR
- KR 10 R1100 sixx C-CR


4.15.7.1 Stopping distances and stopping times for STOP 0, axis 1 to axis 3

The table shows the stopping distances and stopping times after a STOP 0 (category 0 stop) is triggered. The values refer to the following configuration:

- Extension I = 100 %

- Program override POV = 100 %
- Mass m = maximum load (rated load + supplementary load on arm)

	Stopping distance (°)	Stopping time (s)
Axis 1	106.21	0.536
Axis 2	96.06	0.647
Axis 3	46.99	0.373

4.15.7.2 Stopping distances and stopping times for STOP 1, axis 1**Fig. 4-129: Stopping distances for STOP 1, axis 1**





Fig. 4-130: Stopping times for STOP 1, axis 1

4.15.7.3 Stopping distances and stopping times for STOP 1, axis 2**Fig. 4-131: Stopping distances for STOP 1, axis 2**




Fig. 4-132: Stopping times for STOP 1, axis 2

4.15.7.4 Stopping distances and stopping times for STOP 1, axis 3




Fig. 4-133: Stopping distances for STOP 1, axis 3




Fig. 4-134: Stopping times for STOP 1, axis 3

4.15.8 Stopping distances and times, KR 10 R900 sixx W-CR and KR 10 R1100 sixx W-CR

The following values are preliminary values and are valid for the following robots.


- KR 10 R900 sixx W-CR
- KR 10 R1100 sixx W-CR

4.15.8.1 Stopping distances and stopping times for STOP 0, axis 1 to axis 3

The table shows the stopping distances and stopping times after a STOP 0 (category 0 stop) is triggered. The values refer to the following configuration:

- Extension I = 100 %
- Program override POV = 100 %
- Mass m = maximum load (rated load + supplementary load on arm)

	Stopping distance (°)	Stopping time (s)
Axis 1	163.11	0.745
Axis 2	67.78	0.404
Axis 3	60.96	0.387

4.15.8.2 Stopping distances and stopping times for STOP 1, axis 1**Fig. 4-135: Stopping distances for STOP 1, axis 1**





Fig. 4-136: Stopping times for STOP 1, axis 1

4.15.8.3 Stopping distances and stopping times for STOP 1, axis 2**Fig. 4-137: Stopping distances for STOP 1, axis 2**






Fig. 4-138: Stopping times for STOP 1, axis 2

4.15.8.4 Stopping distances and stopping times for STOP 1, axis 3**Fig. 4-139: Stopping distances for STOP 1, axis 3****Fig. 4-140: Stopping times for STOP 1, axis 3**

5 Safety

5.1 General



- This "Safety" chapter refers to a mechanical component of an industrial robot.
- If the mechanical component is used together with a KUKA robot controller, the "Safety" chapter of the operating instructions or assembly instructions of the robot controller must be used!
- This contains all the information provided in this "Safety" chapter. It also contains additional safety information relating to the robot controller which must be observed.
- Where this "Safety" chapter uses the term "industrial robot", this also refers to the individual mechanical component if applicable.

5.1.1 Liability

The device described in this document is either an industrial robot or a component thereof.

Components of the industrial robot:

- Manipulator
- Robot controller
- Teach pendant
- Connecting cables
- External axes (optional)
e.g. linear unit, turn-tilt table, positioner
- Software
- Options, accessories

The industrial robot is built using state-of-the-art technology and in accordance with the recognized safety rules. Nevertheless, misuse of the industrial robot may constitute a risk to life and limb or cause damage to the industrial robot and to other material property.

The industrial robot may only be used in perfect technical condition in accordance with its designated use and only by safety-conscious persons who are fully aware of the risks involved in its operation. Use of the industrial robot is subject to compliance with this document and with the declaration of incorporation supplied together with the industrial robot. Any functional disorders affecting safety must be rectified immediately.

Safety information

Information about safety may not be construed against KUKA Deutschland GmbH. Even if all safety instructions are followed, this is not a guarantee that the industrial robot will not cause personal injuries or material damage.

No modifications may be carried out to the industrial robot without the authorization of KUKA Deutschland GmbH. Additional components (tools, software, etc.), not supplied by KUKA Deutschland GmbH, may be integrated into the industrial robot. The user is liable for any damage these components may cause to the industrial robot or to other material property.

In addition to the Safety chapter, this document contains further safety instructions. These must also be observed.

5.1.2 Intended use of the industrial robot

The industrial robot is intended exclusively for the use designated in the "Purpose" chapter of the operating instructions or assembly instructions.

Any use or application deviating from the intended use is deemed to be misuse and is not allowed. The manufacturer is not liable for any damage resulting from such misuse. The risk lies entirely with the user.

Operation of the industrial robot in accordance with its intended use also requires compliance with the operating and assembly instructions for the individual components, with particular reference to the maintenance specifications.

Misuse

Any use or application deviating from the intended use is deemed to be misuse and is not allowed. This includes e.g.:

- Use as a climbing aid
- Operation outside the specified operating parameters
- Operation without the required safety equipment

5.1.3 EC declaration of conformity and declaration of incorporation

The industrial robot constitutes partly completed machinery as defined by the EC Machinery Directive. The industrial robot may only be put into operation if the following preconditions are met:

- The industrial robot is integrated into a complete system.
or: The industrial robot, together with other machinery, constitutes a complete system.
or: All safety functions and safeguards required for operation in the complete machine as defined by the EC Machinery Directive have been added to the industrial robot.
- The complete system complies with the EC Machinery Directive. This has been confirmed by means of a conformity assessment procedure.

EC declaration of conformity

The system integrator must issue an EC declaration of conformity for the complete system in accordance with the Machinery Directive. The EC declaration of conformity forms the basis for the CE mark for the system. The industrial robot must always be operated in accordance with the applicable national laws, regulations and standards.

The robot controller has a CE mark in accordance with the EMC Directive and the Low Voltage Directive.

Declaration of incorporation

The partly completed machinery is supplied with a declaration of incorporation in accordance with Annex II B of the EC Machinery Directive 2006/42/EC. The assembly instructions and a list of essential requirements complied with in accordance with Annex I are integral parts of this declaration of incorporation.

The declaration of incorporation declares that the start-up of the partly completed machinery is not allowed until the partly completed machinery has been incorporated into machinery, or has been assembled with other parts to form machinery, and this machinery complies with the terms of the EC Machinery Directive, and the EC declaration of conformity is present in accordance with Annex II A.

5.1.4 Terms used

Term	Description
Axis range	Range of each axis, in degrees or millimeters, within which it may move. The axis range must be defined for each axis.
Stopping distance	Stopping distance = reaction distance + braking distance The stopping distance is part of the danger zone.
Workspace	The manipulator is allowed to move within its workspace. The workspace is derived from the individual axis ranges.
Operator (User)	The user of the industrial robot can be the management, employer or delegated person responsible for use of the industrial robot.
Danger zone	The danger zone consists of the workspace and the stopping distances.
Service life	The service life of a safety-relevant component begins at the time of delivery of the component to the customer. The service life is not affected by whether the component is used in a controller or elsewhere or not, as safety-relevant components are also subject to aging during storage
KCP	KUKA Control Panel Teach pendant for the KR C2/KR C2 edition2005 The KCP has all the operator control and display functions required for operating and programming the industrial robot.
KUKA smartPAD	see "smartPAD"
Manipulator	The robot arm and the associated electrical installations
Safety zone	The safety zone is situated outside the danger zone.
Safety options	Generic term for options which make it possible to configure additional safe monitoring functions in addition to the standard safety functions. Example: SafeOperation
smartPAD	Teach pendant for the KR C4 The smartPAD has all the operator control and display functions required for operating and programming the industrial robot.
Stop category 0	The drives are deactivated immediately and the brakes are applied. The manipulator and any external axes (optional) perform path-oriented braking. Note: This stop category is called STOP 0 in this document.
Stop category 1	The manipulator and any external axes (optional) perform path-maintaining braking. The drives are deactivated after 1 s and the brakes are applied. Note: This stop category is called STOP 1 in this document.
Stop category 2	The drives are not deactivated and the brakes are not applied. The manipulator and any external axes (optional) are braked with a normal braking ramp. Note: This stop category is called STOP 2 in this document.
System integrator (plant integrator)	System integrators are people who safely integrate the industrial robot into a complete system and commission it.
T1	Test mode, Manual Reduced Velocity (<= 250 mm/s)
T2	Test mode, Manual High Velocity (> 250 mm/s permissible)
External axis	Axis of motion that does not belong to the manipulator, yet is controlled with the same controller. e.g. KUKA linear unit, turn-tilt table, Posiflex

5.2 Personnel

The following persons or groups of persons are defined for the industrial robot:

- User
- Personnel



All persons working with the industrial robot must have read and understood the industrial robot documentation, including the safety chapter.

User

The user must observe the labor laws and regulations. This includes e.g.:

- The user must comply with his monitoring obligations.
- The user must carry out briefing at defined intervals.

Personnel

Personnel must be instructed, before any work is commenced, in the type of work involved and what exactly it entails as well as any hazards which may exist. Instruction must be carried out regularly. Instruction is also required after particular incidents or technical modifications.

Personnel includes:

- System integrator
- Operators, subdivided into:
 - Start-up, maintenance and service personnel
 - Operating personnel
 - Cleaning personnel



Installation, exchange, adjustment, operation, maintenance and repair must be performed only as specified in the operating or assembly instructions for the relevant component of the industrial robot and only by personnel specially trained for this purpose.

System integrator

The industrial robot is safely integrated into a complete system by the system integrator.

The system integrator is responsible for the following tasks:

- Installing the industrial robot
- Connecting the industrial robot
- Performing risk assessment
- Implementing the required safety functions and safeguards
- Issuing the EC declaration of conformity
- Attaching the CE mark
- Creating the operating instructions for the system

Operators

The operator must meet the following preconditions:

- The operator must be trained for the work to be carried out.
- Work on the system must only be carried out by qualified personnel. These are people who, due to their specialist training, knowledge and experience, and their familiarization with the relevant standards, are able to assess the work to be carried out and detect any potential hazards.



Work on the electrical and mechanical equipment of the industrial robot may only be carried out by specially trained personnel.

5.3 Workspace, safety zone and danger zone

Workspaces are to be restricted to the necessary minimum size. A workspace must be safeguarded using appropriate safeguards.

The safeguards (e.g. safety gate) must be situated inside the safety zone. In the case of a stop, the manipulator and external axes (optional) are braked and come to a stop within the danger zone.

The danger zone consists of the workspace and the stopping distances of the manipulator and external axes (optional). It must be safeguarded by means of physical safeguards to prevent danger to persons or the risk of material damage.

5.4 Overview of protective equipment

The protective equipment of the mechanical component may include:

- Mechanical end stops
- Mechanical axis limitation (optional)
- Release device (optional)
- Brake release device (optional)
- Labeling of danger areas

Not all equipment is relevant for every mechanical component.

5.4.1 Mechanical end stops

Depending on the robot variant, the axis ranges of the main and wrist axes of the manipulator are partially limited by mechanical end stops.

Additional mechanical end stops can be installed on the external axes.



If the manipulator or an external axis hits an obstruction or a mechanical end stop or mechanical axis limitation, the manipulator can no longer be operated safely. The manipulator must be taken out of operation and KUKA Deutschland GmbH must be consulted before it is put back into operation.

5.4.2 Mechanical axis limitation (optional)

Some manipulators can be fitted with mechanical axis limitation systems in axes A1 to A3. The axis limitation systems restrict the working range to the required minimum. This increases personal safety and protection of the system.

In the case of manipulators that are not designed to be fitted with mechanical axis limitation, the workspace must be laid out in such a way that there is no danger to persons or material property, even in the absence of mechanical axis limitation.

If this is not possible, the workspace must be limited by means of photoelectric barriers, photoelectric curtains or obstacles on the system side. There must be no shearing or crushing hazards at the loading and transfer areas.



This option is not available for all robot models. Information on specific robot models can be obtained from KUKA Deutschland GmbH.

5.4.3 Options for moving the manipulator without drive energy



The system user is responsible for ensuring that the training of personnel with regard to the response to emergencies or exceptional situations also includes how the manipulator can be moved without drive energy.

Description

The following options are available for moving the manipulator without drive energy after an accident or malfunction:

- Release device (optional)

The release device can be used for the main axis drive motors and, depending on the robot variant, also for the wrist axis drive motors.

- Brake release device (option)

The brake release device is designed for robot variants whose motors are not freely accessible.

- Moving the wrist axes directly by hand

There is no release device available for the wrist axes of variants in the low payload category. This is not necessary because the wrist axes can be moved directly by hand.



Information about the options available for the various robot models and about how to use them can be found in the assembly and operating instructions for the robot or requested from KUKA Deutschland GmbH.

NOTICE

Moving the manipulator without drive energy can damage the motor brakes of the axes concerned. The motor must be replaced if the brake has been damaged. The manipulator may therefore be moved without drive energy only in emergencies, e.g. for rescuing persons.

5.4.4 Labeling on the industrial robot

All plates, labels, symbols and marks constitute safety-relevant parts of the industrial robot. They must not be modified or removed.

Labeling on the industrial robot consists of:

- Identification plates
- Warning signs
- Safety symbols
- Designation labels
- Cable markings
- Rating plates



Further information is contained in the technical data of the operating instructions or assembly instructions of the components of the industrial robot.

5.5 Safety measures

5.5.1 General safety measures

The industrial robot may only be used in perfect technical condition in accordance with its intended use and only by safety-conscious persons. Operator errors can result in personal injury and damage to property.

It is important to be prepared for possible movements of the industrial robot even after the robot controller has been switched off and locked out. Incorrect installation (e.g. overload) or mechanical defects (e.g. brake defect) can cause the manipulator or external axes to sag. If work is to be carried out on a switched-off industrial robot, the manipulator and external axes must first be moved into a position in which they are unable to move on their own, whether the payload is mounted or not. If this is not possible, the manipulator and external axes must be secured by appropriate means.



DANGER In the absence of operational safety functions and safeguards, the industrial robot can cause personal injury or material damage. If safety functions or safeguards are dismantled or deactivated, the industrial robot may not be operated.



DANGER Standing underneath the robot arm can cause death or injuries. For this reason, standing underneath the robot arm is prohibited!



CAUTION The motors reach temperatures during operation which can cause burns to the skin. Contact must be avoided. Appropriate safety precautions must be taken, e.g. protective gloves must be worn.

KCP/smartPAD

The user must ensure that the industrial robot is only operated with the KCP/smartPAD by authorized persons.

If more than one KCP/smartPAD is used in the overall system, it must be ensured that each device is unambiguously assigned to the corresponding industrial robot. They must not be interchanged.



WARNING The operator must ensure that decoupled KCPs/smart-PADs are immediately removed from the system and stored out of sight and reach of personnel working on the industrial robot. This serves to prevent operational and non-operational EMERGENCY STOP devices from becoming interchanged. Failure to observe this precaution may result in death, severe injuries or considerable damage to property.

External keyboard, external mouse

An external keyboard and/or external mouse may only be used if the following conditions are met:

- Start-up or maintenance work is being carried out.
- The drives are switched off.
- There are no persons in the danger zone.

The KCP/smartPAD must not be used as long as an external keyboard and/or external mouse are connected to the control cabinet.

The external keyboard and/or external mouse must be removed from the control cabinet as soon as the start-up or maintenance work is completed or the KCP/smartPAD is connected.

Modifications	<p>After modifications to the industrial robot, checks must be carried out to ensure the required safety level. The valid national or regional work safety regulations must be observed for this check. The correct functioning of all safety functions must also be tested.</p> <p>New or modified programs must always be tested first in Manual Reduced Velocity mode (T1).</p> <p>After modifications to the industrial robot, existing programs must always be tested first in Manual Reduced Velocity mode (T1). This applies to all components of the industrial robot and includes e.g. modifications of the external axes or to the software and configuration settings.</p>
Faults	<p>The following tasks must be carried out in the case of faults in the industrial robot:</p> <ul style="list-style-type: none">■ Switch off the robot controller and secure it (e.g. with a padlock) to prevent unauthorized persons from switching it on again.■ Indicate the fault by means of a label with a corresponding warning (tag-out).■ Keep a record of the faults.■ Eliminate the fault and carry out a function test.

5.5.2 Transportation

Manipulator	<p>The prescribed transport position of the manipulator must be observed. Transportation must be carried out in accordance with the operating instructions or assembly instructions of the robot.</p> <p>Avoid vibrations and impacts during transportation in order to prevent damage to the manipulator.</p>
Robot controller	<p>The prescribed transport position of the robot controller must be observed. Transportation must be carried out in accordance with the operating instructions or assembly instructions of the robot controller.</p> <p>Avoid vibrations and impacts during transportation in order to prevent damage to the robot controller.</p>
External axis (optional)	<p>The prescribed transport position of the external axis (e.g. KUKA linear unit, turn-tilt table, positioner) must be observed. Transportation must be carried out in accordance with the operating instructions or assembly instructions of the external axis.</p>

5.5.3 Start-up and recommissioning

Before starting up systems and devices for the first time, a check must be carried out to ensure that the systems and devices are complete and operational, that they can be operated safely and that any damage is detected.

The valid national or regional work safety regulations must be observed for this check. The correct functioning of all safety circuits must also be tested.



The passwords for logging onto the KUKA System Software as "Expert" and "Administrator" must be changed before start-up and must only be communicated to authorized personnel.

WARNING

The robot controller is preconfigured for the specific industrial robot. If cables are interchanged, the manipulator and the external axes (optional) may receive incorrect data and can thus cause personal injury or material damage. If a system consists of more than one manipulator, always connect the connecting cables to the manipulators and their corresponding robot controllers.



If additional components (e.g. cables), which are not part of the scope of supply of KUKA Deutschland GmbH, are integrated into the industrial robot, the user is responsible for ensuring that these components do not adversely affect or disable safety functions.

NOTICE

If the internal cabinet temperature of the robot controller differs greatly from the ambient temperature, condensation can form, which may cause damage to the electrical components. Do not put the robot controller into operation until the internal temperature of the cabinet has adjusted to the ambient temperature.

Function test

The following tests must be carried out before start-up and recommissioning:

It must be ensured that:

- The industrial robot is correctly installed and fastened in accordance with the specifications in the documentation.
- There is no damage to the robot that could be attributed to external forces. Example: Dents or abrasion that could be caused by an impact or collision.

WARNING

In the case of such damage, the affected components must be exchanged. In particular, the motor and counterbalancing system must be checked carefully. External forces can cause non-visible damage. For example, it can lead to a gradual loss of drive power from the motor, resulting in unintended movements of the manipulator. Death, injuries or considerable damage to property may otherwise result.

- There are no foreign bodies or loose parts on the industrial robot.
- All required safety equipment is correctly installed and operational.
- The power supply ratings of the industrial robot correspond to the local supply voltage and mains type.
- The ground conductor and the equipotential bonding cable are sufficiently rated and correctly connected.
- The connecting cables are correctly connected and the connectors are locked.

5.5.4 Manual mode

Manual mode is the mode for setup work. Setup work is all the tasks that have to be carried out on the industrial robot to enable automatic operation. Setup work includes:

- Jog mode
- Teaching
- Programming
- Program verification

The following must be taken into consideration in manual mode:

- If the drives are not required, they must be switched off to prevent the manipulator or the external axes (optional) from being moved unintentionally.

- New or modified programs must always be tested first in Manual Reduced Velocity mode (T1).
- The manipulator, tooling or external axes (optional) must never touch or project beyond the safety fence.
- Workpieces, tooling and other objects must not become jammed as a result of the industrial robot motion, nor must they lead to short-circuits or be liable to fall off.
- All setup work must be carried out, where possible, from outside the safeguarded area.

If the setup work has to be carried out inside the safeguarded area, the following must be taken into consideration:

In Manual Reduced Velocity mode (T1):

- If it can be avoided, there must be no other persons inside the safeguarded area.
- If it is necessary for there to be several persons inside the safeguarded area, the following must be observed:
- Each person must have an enabling device.
 - All persons must have an unimpeded view of the industrial robot.
 - Eye-contact between all persons must be possible at all times.
- The operator must be so positioned that he can see into the danger area and get out of harm's way.

In Manual High Velocity mode (T2):

- This mode may only be used if the application requires a test at a velocity higher than possible in T1 mode.
- Teaching and programming are not permissible in this operating mode.
- Before commencing the test, the operator must ensure that the enabling devices are operational.
- The operator must be positioned outside the danger zone.
- There must be no other persons inside the safeguarded area. It is the responsibility of the operator to ensure this.

5.5.5 Automatic mode

Automatic mode is only permissible in compliance with the following safety measures:

- All safety equipment and safeguards are present and operational.
- There are no persons in the system.
- The defined working procedures are adhered to.

If the manipulator or an external axis (optional) comes to a standstill for no apparent reason, the danger zone must not be entered until an EMERGENCY STOP has been triggered.

5.5.6 Maintenance and repair

After maintenance and repair work, checks must be carried out to ensure the required safety level. The valid national or regional work safety regulations must be observed for this check. The correct functioning of all safety functions must also be tested.

The purpose of maintenance and repair work is to ensure that the system is kept operational or, in the event of a fault, to return the system to an operational state. Repair work includes troubleshooting in addition to the actual repair itself.

The following safety measures must be carried out when working on the industrial robot:

- Carry out work outside the danger zone. If work inside the danger zone is necessary, the user must define additional safety measures to ensure the safe protection of personnel.
- Switch off the industrial robot and secure it (e.g. with a padlock) to prevent it from being switched on again. If it is necessary to carry out work with the robot controller switched on, the user must define additional safety measures to ensure the safe protection of personnel.
- If it is necessary to carry out work with the robot controller switched on, this may only be done in operating mode T1.
- Label the system with a sign indicating that work is in progress. This sign must remain in place, even during temporary interruptions to the work.
- The EMERGENCY STOP devices must remain active. If safety functions or safeguards are deactivated during maintenance or repair work, they must be reactivated immediately after the work is completed.



DANGER Before work is commenced on live parts of the robot system, the main switch must be turned off and secured against being switched on again. The system must then be checked to ensure that it is deenergized.
It is not sufficient, before commencing work on live parts, to execute an EMERGENCY STOP or a safety stop, or to switch off the drives, as this does not disconnect the robot system from the mains power supply. Parts remain energized. Death or severe injuries may result.

Faulty components must be replaced using new components with the same article numbers or equivalent components approved by KUKA Deutschland GmbH for this purpose.

Cleaning and preventive maintenance work is to be carried out in accordance with the operating instructions.

Robot controller

Even when the robot controller is switched off, parts connected to peripheral devices may still carry voltage. The external power sources must therefore be switched off if work is to be carried out on the robot controller.

The ESD regulations must be adhered to when working on components in the robot controller.

Voltages in excess of 50 V (up to 600 V) can be present in various components for several minutes after the robot controller has been switched off! To prevent life-threatening injuries, no work may be carried out on the industrial robot in this time.

Water and dust must be prevented from entering the robot controller.

Counterbalancing system

Some robot variants are equipped with a hydropneumatic, spring or gas cylinder counterbalancing system.

The hydropneumatic and gas cylinder counterbalancing systems are pressure equipment and, as such, are subject to obligatory equipment monitoring and the provisions of the Pressure Equipment Directive.

The user must comply with the applicable national laws, regulations and standards pertaining to pressure equipment.

Inspection intervals in Germany in accordance with Industrial Safety Order, Sections 14 and 15. Inspection by the user before commissioning at the installation site.

The following safety measures must be carried out when working on the counterbalancing system:

- The manipulator assemblies supported by the counterbalancing systems must be secured.
- Work on the counterbalancing systems must only be carried out by qualified personnel.

Hazardous substances

The following safety measures must be carried out when handling hazardous substances:

- Avoid prolonged and repeated intensive contact with the skin.
- Avoid breathing in oil spray or vapors.
- Clean skin and apply skin cream.



To ensure safe use of our products, we recommend regularly requesting up-to-date safety data sheets for hazardous substances.

5.5.7 Decommissioning, storage and disposal

The industrial robot must be decommissioned, stored and disposed of in accordance with the applicable national laws, regulations and standards.

5.6 Applied norms and regulations

Name/Edition	Definition
2006/42/EU:2006	Machinery Directive: Directive 2006/42/EC of the European Parliament and of the Council of 17 May 2006 on machinery, and amending Directive 95/16/EC (recast)
2014/68/EU:2014	Pressure Equipment Directive: Directive 2014/68/EU of the European Parliament and of the Council dated 15 May 2014 on the approximation of the laws of the Member States concerning pressure equipment (Only applicable for robots with hydropneumatic counterbalancing system.)
EN ISO 13850:2015	Safety of machinery: Emergency stop - Principles for design
EN ISO 13849-1:2015	Safety of machinery: Safety-related parts of control systems - Part 1: General principles of design
EN ISO 13849-2:2012	Safety of machinery: Safety-related parts of control systems - Part 2: Validation
EN ISO 12100:2010	Safety of machinery: General principles of design, risk assessment and risk reduction
EN ISO 10218-1:2011	Industrial robots – Safety requirements: Part 1: Robots Note: Content equivalent to ANSI/RIA R.15.06-2012, Part 1

EN 614-1:2006+A1:2009	Safety of machinery: Ergonomic design principles - Part 1: Terms and general principles
EN 61000-6-2:2005	Electromagnetic compatibility (EMC): Part 6-2: Generic standards; Immunity for industrial environments
EN 61000-6-4:2007 + A1:2011	Electromagnetic compatibility (EMC): Part 6-4: Generic standards; Emission standard for industrial environments
EN 60204-1:2006/A1:2009	Safety of machinery: Electrical equipment of machines - Part 1: General requirements

6 Planning

6.1 Information for planning

In the planning and design phase, care must be taken regarding the functions or applications to be executed by the kinematic system. The following conditions can lead to premature wear. They necessitate shorter maintenance intervals and/or earlier exchange of components. In addition, the permissible operating parameters specified in the technical data must be taken into account and observed during planning.

- Continuous operation near temperature limits or in abrasive environments
- Continuous operation close to the performance limits, e.g. high rpm of an axis
- High duty cycle of individual axes
- Monotonous motion profiles, e.g. short, frequently recurring axis motions
- Static axis positions, e.g. continuous vertical position of a wrist axis
- External forces (process forces) acting on the robot

If one or more of these conditions are to apply during operation of the kinematic system, KUKA Deutschland GmbH must be consulted.

If the robot reaches its corresponding operation limit or if it is operated near the limit for a period of time, the built-in monitoring functions come into effect and the robot is automatically switched off.

This protective function can limit the availability of the robot system.

6.2 Mounting base

Description

The mounting base with centering is used when the robot is fastened to the floor, i.e. directly on a concrete foundation.

The mounting base with centering consists of:

- Bedplate
- Resin-bonded anchors (chemical anchors)
- Fastening elements

This mounting variant requires a level and smooth surface on a concrete foundation with adequate load bearing capacity. The concrete foundation must be able to accommodate the forces occurring during operation. There must be no layers of insulation or screed between the bedplate and the concrete foundation.

The minimum dimensions must be observed.




Fig. 6-1: Mounting base

- | | |
|-----------------------------|----------------------------|
| 1 Robot base frame | 4 Hexagon bolt |
| 2 Locating pin, cylindrical | 5 Bedplate |
| 3 Resin-bonded anchor | 6 Locating pin, flat-sided |

**Grade of concrete
for foundations**

When producing foundations from concrete, observe the load-bearing capacity of the ground and the country-specific construction regulations. There must be no layers of insulation or screed between the bedplate/bedplates and the concrete foundation. The quality of the concrete must meet the requirements of the following standard:

- C20/25 according to DIN EN 206-1:2001/DIN 1045-2:2008

**Dimensioned
drawing**

The following illustration ([>>> Fig. 6-2](#)) provides all the necessary information on the mounting base, together with the required foundation data. The specified foundation dimensions refer to the safe transmission of the foundation loads into the foundation and not to the stability of the foundation.

Dimensions: mm




Fig. 6-2: Mounting base, dimensioned drawing

To ensure that the anchor forces are safely transmitted to the foundation, observe the dimensions for concrete foundations specified in the following illustration ([>>> Fig. 6-3](#)).

NOTICE

The dimensions specified for the distance to the edge are valid for non-reinforced or normally reinforced concrete without verification of concrete edge failure. For safety against concrete edge failure in accordance with ETAG 001 Annex C, the concrete foundation must be provided with an appropriate edge reinforcement.




Fig. 6-3: Cross-section of foundations

6.3 Machine frame mounting

Description

The machine frame mounting assembly is used when the robot is fastened on a steel structure, a booster frame (pedestal) or a KUKA linear unit. This assembly is also used if the robot is installed on the wall or ceiling. It must be ensured that the substructure is able to withstand safely the forces occurring during operation (foundation loads). The following diagram contains all the necessary information that must be observed when preparing the mounting surface (>>> Fig. 6-4).

The machine frame mounting assembly consists of:

- Locating pin
- Hexagon bolts with conical spring washers




Fig. 6-4: Machine frame mounting

- 1 Hexagon bolt
- 2 Locating pin, cylindrical
- 3 Locating pin, flat-sided

Dimensioned drawing

The following illustration ([>>> Fig. 6-5](#)) provides all the necessary information on machine frame mounting, together with the required foundation data.




Fig. 6-5: Machine frame mounting, dimensioned drawing

- | | |
|-----------------------------|----------------------------|
| 1 Hexagon bolt (4x) | 4 Locating pin, flat-sided |
| 2 Locating pin, cylindrical | 5 Steel structure |
| 3 Mounting surface | |

6.4 Connecting cables and interfaces

Connecting cables

The connecting cables comprise all the cables for transferring energy and signals between the robot and the robot controller. They are connected to the robot junction boxes with connectors. The set of connecting cables comprises:

- Motor cable
- Data cable
- CAT5 data cable (optional)
- Connecting cable, external axes A7 and A8 (optional)
- Ground conductor (optional)

Depending on the specification of the robot, various connecting cables are used. The standard cable length is 4 m. Cable lengths of 1 m, 7 m, 15 m and 25 m are available as an option. The maximum length of the connecting cables must not exceed 25 m. Thus if the robot is operated on a linear unit which has its own energy supply chain these cables must also be taken into account.



For the connecting cables, a ground conductor is always required to provide a low-resistance connection between the robot and the control cabinet in accordance with DIN EN 60204. The ground conductor is not part of the scope of supply and can be ordered as an option. The connection must be made by the customer. The tapped holes for connecting the ground conductor are located on the base frame of the robot.

The following points must be observed when planning and routing the connecting cables:

- The bending radius for fixed routing must not be less than 50 mm for motor cables and 30 mm for control cables.
- Protect cables against exposure to mechanical stress.
- Route the cables without mechanical stress – no tensile forces on the connectors
- Cables are only to be installed indoors.
- Observe the permissible temperature range (fixed installation) of 263 K (-10 °C) to 343 K (+70 °C).
- Route the motor cables and the data cables separately in metal ducts; if necessary, additional measures must be taken to ensure electromagnetic compatibility (EMC).

Interface A1

Interface A1 is located at the rear of the base frame. The connections for the motor and data cables are shown in the following illustration.




Fig. 6-6: Interface A1

- 1 Motor cable connection X30
- 2 Data cable connection X31

6.5 Customer interfaces

Interface A1 Interface A1 is located at the rear of the base frame.




Fig. 6-7: Customer interface A1

- 1 MEMD connection X32
- 2 CAT5 data cable connection XPN1
- 3 Air line connection AIR2
Outside diameter: 6 mm
- 4 Air line connection AIR1
Outside diameter: 6 mm
- 5 Pressurization connection
Max. pressure: 0.3 bar
Air, oil-free, dry, filtered
according to: ISO 8573.1-1, 1.2 to 16.2
- 6 Connection for external axis A8 (XP8.1)
- 7 Connection for external axis A7 (XP7.1)

Interface A4 Interface A4 is located on top of the in-line wrist.




Fig. 6-8: Interface A4, example

- | | |
|--------------------|-------------------|
| 1 Connection X41 | 4 In-line wrist |
| 2 Connection XPN41 | 5 Air connections |
| 3 Air line AIR2 | |

The optional connector bypass is required for use of the air connections. This option contains a silencer and several plug-in couplings (=> Fig. 6-9).




Fig. 6-9: Connections for connector bypass option

- | | |
|------------|-------------------|
| 1 Silencer | 2 Push-in fitting |
|------------|-------------------|

The robot has three bistable 5/2-way solenoid valves integrated into the in-line wrist. The valve unit is activated via the internal energy supply system:

Designation	Limit values
Valve type	5/2-way solenoid valve
Max. pressure	7 bar
Switching frequency	10 Hz
Operating temperature	+5 °C to +45 °C (278 K to 318 K)
Threaded union	M5
Medium	Air, oil-free, dry, filtered according to: ISO 8573.1-1, 1.2 to 16.2 Degree of filtration: max. 5 µm

Designation	Limit values
Operating voltage	24 V DC
Current	25 mA




Fig. 6-10: Valve diagram

Valve activation

Designation	Values
Digital outputs (for valve activation)	6 (DO7 to DO12): <ul style="list-style-type: none"> ■ Valve 1: DO7/DO10 ■ Valve 2: DO8/DO11 ■ Valve 3: DO9/DO12 not short circuit proof
	Rated voltage 24 V DC (-15%/+20%)
	Output current max. 25 mA



The inputs and outputs are not preconfigured and must be configured in WorkVisual.
Further information about mapping inputs and outputs can be found in the **WorkVisual** documentation.

Connection X41

Designation	Values
Digital outputs (for customer interface X41)	2 (DO13, DO14) short-circuit proof
Rated voltage	24 V DC (-15%/+20%)
Output current	max. 0.5 A
Short-circuit current	max. 2 A
Load type	Ohmic, inductive Lamp load
Digital inputs (for customer interface X41)	6 (DI1 to DI6)
Signal voltage "0"	-3 V ... +5 V EN 61131-2, type 3
Signal voltage "1"	15 V ... 30 V EN 61131-2, type 3
Input current	typically 3 mA EN 61131-2, type 3
Input filter	typically 0.3 ms
Power supply	24 V / 3 A

A 615springtec® connector, 12-pole EMC enclosure E-part from Intercontec is required for connection X41.

When using the power supply, the customer must protect this against overload and short circuit with a 3 A fuse downstream of connector X41.

For the connector bypack option, the pin assignments on the connector insert are to be noted.




Fig. 6-11: Wiring diagram, connection X41


**Connection
XPN41**


Fig. 6-12: Wiring diagram, connection XPN41

A SAISM-4/8S-M12 4P D-ZF connector from Weidmüller is required for connection XPN41.

Connection AIR2

Customer-specific air connection with the following values:

Designation	Limit values
Max. pressure	7 bar
Vacuum	Atmospheric pressure minus 0.95 bar

7 Transportation

7.1 Transporting the manipulator

Description Move the robot into its transport position each time it is transported. It must be ensured that the robot is stable while it is being transported. The robot must remain in its transport position until it has been fastened to the foundation. Before the robot is lifted, it must be ensured that it is free from obstructions. Remove all transport safeguards, such as nails and screws, in advance. First remove any corrosion or glue on contact surfaces.

Transport position The robot must be in the transport position before it can be transported ([>>> Fig. 7-1](#)). The robot is in the transport position when the axes are in the following positions:

Axis	A1	A2	A3	A4	A5	A6
Angle	0°	-105°	+156°	0°	+120°	0°




Fig. 7-1: Transport position

Transport dimensions The transport dimensions for the robot can be noted from the following figures. The position of the center of gravity and the weight vary according to the specific configuration. The specified dimensions refer to the robot without equipment.

The following transport dimensions ([>>> Fig. 7-2](#)) are valid for the robots:

- KR 6 R700 sixx CR
- KR 6 R700 sixx W-CR
- KR 6 R700 sixx C-CR




Fig. 7-2: Transport dimensions, R700

1 Robot

2 Center of gravity

The following transport dimensions (>>> Fig. 7-3) are valid for the robots:

- KR 6 R900 sixx CR
- KR 6 R900 sixx W-CR
- KR 6 R900 sixx C-CR
- KR 10 R900 sixx CR
- KR 10 R900 sixx W-CR
- KR 10 R900 sixx C-CR




Fig. 7-3: Transport dimensions, R900

1 Robot

2 Center of gravity

- KR 10 R1100 sixx CR
 - KR 10 R1100 sixx W-CR
 - KR 10 R1100 sixx C-CR




Fig. 7-4: Transport dimensions, R1100

1 Robot

2 Center of gravity

Transportation using lifting tackle

WARNING Use of unsuitable handling equipment may result in damage to the robot or injury to persons. Only use authorized handling equipment with a sufficient load-bearing capacity. Only transport the robot in the manner specified here.

The robot is transported using lifting tackle (=> Fig. 7-5). For this, it must be in the transport position. The loops of the lifting tackle are passed around the link arm and rotating column. All ropes must be long enough and must be routed in such a way that the robot is not damaged. Installed tools and items of equipment can cause undesirable shifts in the center of gravity.

WARNING The robot may tip during transportation. Risk of personal injury and damage to property.
If the robot is being transported using lifting tackle, special care must be exercised to prevent it from tipping. Additional safeguarding measures must be taken. It is forbidden to pick up the robot in any other way using a crane!




Fig. 7-5: Transportation using lifting tackle

- | | | | |
|---|----------------|---|-----------------|
| 1 | Crane | 3 | Link arm |
| 2 | Lifting tackle | 4 | Rotating column |

8 Start-up and recommissioning

CAUTION For screwed connections, the fastening screws (standard, strength class 8.8) are to be tightened with the tightening torques specified in the appendix ([>>> 12 "Appendix" Page 231](#)). Tightening torques deviating from these values are specified directly. The specified screw sizes and strength classes are those valid at the copy deadline. The specifications contained in the Parts Catalog are, however, always to be taken as the most up-to-date information. Screws of strength class 10.9 and higher may only be tightened once with the rated tightening torque. When the screws are first slackened they must be replaced with new ones.

8.1 Installing the mounting base

Description	<p>These instructions apply to the variant “mounting base with centering (resin cartridge)”. The robot is fastened to an appropriate concrete foundation using one or more bedplates and resin-bonded anchors.</p> <p>If the surface of the concrete foundation is not sufficiently smooth and even, the differences must be evened out with a suitable leveling compound.</p> <p>When using resin-bonded anchors, use only resin cartridges and anchors from the same manufacturer. No diamond tools or core drills may be used for drilling the anchor holes; for preference, drilling tools supplied by the anchor manufacturer are to be used. The manufacturer’s instructions for the use of resin-bonded anchors must also be observed.</p>
Precondition	<ul style="list-style-type: none"> ■ The concrete foundation must have the required dimensions and cross-section. ■ The surface of the foundation must be smooth and even. ■ The mounting base assembly must be complete. ■ Have the leveling compound readily at hand.
Special tools	<p>The following special tools are required:</p> <ul style="list-style-type: none"> ■ Drill with a Ø 14 mm bit ■ Setting tool approved by the anchor manufacturer
Procedure	<ol style="list-style-type: none"> 1. Determine the position of the plate on the foundation in relation to the working envelope. 2. Set the bedplate down on the foundation in its installation position. <p>NOTICE If the bedplate is not fully seated on the concrete ceiling, this can cause strain or result in loosening of the mounting base. Fill the gap with leveling compound. To do this, lift the bedplate again and apply sufficient leveling compound to the underside (toothed spatula). Then set the bedplate down again and align it, removing any excess leveling compound. The maximum height of the leveling compound must not be exceeded.</p> <p>The area under the hexagon bolt for robot fastening must be kept free from leveling compound.</p> <p>Allow the leveling compound to cure for about 3 hours. The curing time is longer at temperatures below 293 K (20 °C).</p> <ol style="list-style-type: none"> 3. Check that the bedplate is horizontal. The maximum permissible deviation is 3°. 4. Drill 4 anchor holes in accordance with the manufacturer’s specifications and fit the anchors as specified in the instructions for use.

The instructions for use are enclosed with the anchors and must be followed precisely.

5. Allow the resin to cure. See table provided by manufacturer.

8.2 Installing the machine frame mounting assembly

Description The machine frame mounting is used for installing robots on a steel structure prepared by the customer.

Precondition

- The mounting surface has been prepared as shown in the diagram ([>>> Fig. 6-5](#)).
- The substructure has been checked for sufficient safety.
- The machine frame mounting assembly is complete.

Procedure

1. Clean the mounting surface of the robot ([>>> Fig. 8-1](#)).
2. Check the hole pattern.
3. Insert 2 locating pins into the hole pattern.
4. Prepare 4 M10x35 hexagon bolts together with conical spring washers.




Fig. 8-1: Installing the machine frame mounting assembly

- 1 M10x35-8.8 hexagon bolt (4x)
- 2 Locating pin, cylindrical
- 3 Mounting surface
- 4 Locating pin, flat-sided

The mounting base is now ready for the robot to be installed.

8.3 Installing a floor-mounted robot

Description This description is valid for the installation of floor-mounted robots.

4 hexagon bolts with conical spring washers are used for fastening to the bed-plate or to a machine frame. A cylindrical stepped pin and a flat-sided locating pin are provided to ensure correct positioning.

The installation and start-up of the robot controller, the tools mounted and the applications are not described here.

NOTICE

The robot may only be operated with a functioning compressed air supply. The compressed air must be oil-free, dry and filtered. Damage to property may otherwise result.



During start-up and recommissioning, compliance with the cleanroom class requirements cannot be assured. Before the manipulator is put into operation, cleaning must be carried out in accordance with the requirements of the application.

Precondition

- The mounting base is installed.
- The installation site is accessible with a crane.
- Any tools or other system components which would hinder the work have been removed.
- The robot is in the transport position.
- The connecting cables and ground conductors are routed to the robot and installed.
- There is a compressed air supply to the robot.

Procedure

1. Clean the robot ([>>> 9.6 "Cleaning the robot" Page 214](#)).
 2. Check that the locating pins are undamaged and fitted securely ([>>> Fig. 8-2](#)).
 3. Bring the robot to the installation site with the crane.
 4. Carefully lower the robot vertically onto the mounting surface. Ensure that an entirely vertical position is maintained in order to prevent damage to the locating pins.
 5. Insert 4 M10x35 hexagon bolts together with conical spring washers.
 6. Tighten 4 M10x35 hexagon bolts with a torque wrench in diagonally opposite sequence. Gradually increase the tightening torque to 45.0 Nm.
 7. Remove the lifting tackle.
 8. Connect motor cable X30 and data cable X31.
- When connecting the motor cable connectors, it must be ensured that the connectors on the controller and on the robot are locked correctly. Correct locking is indicated by an audible click. It is indicated optically by the fact that the red rings on each of the locking buttons are not visible and are pushed in completely.
9. Connect the PURGE compressed air line with max. 0.3 bar.
 10. Connect the ground conductor between the robot controller and the robot to the ground conductor connection.
 11. Connect the ground conductor between the system component and the robot to the ground conductor connection.
 12. Check the equipotential bonding in accordance with VDE 0100 and EN 60204-1.



Further information is contained in the operating and assembly instructions of the robot controller.

13. Mount tooling, if present.
14. Perform cleaning ([>>> 9.6 "Cleaning the robot" Page 214](#)).
15. Retighten the 4 M10x35 hexagon bolts with a torque wrench after 100 hours of operation.




Fig. 8-2: Installing a floor-mounted robot

- | | |
|----------------------------|-----------------------------|
| 1 Motor cable | 5 Mounting surface |
| 2 Data cable | 6 Locating pin, cylindrical |
| 3 Compressed air line | 7 Ground conductor |
| 4 Locating pin, flat-sided | 8 Hexagon bolt |

Put the robot into operation in accordance with the "Start-up" chapter of the operating and programming instructions for the System Software and/or the assembly instructions or operating instructions for the robot controller.

NOTICE

Incorrectly adjusted pressure regulators or operation with no pressure regulator may result in damage to the robot. For this reason, the robot may only be operated with a correctly adjusted pressure regulator and with the compressed air supply connected.

8.4 Installing a wall-mounted robot

Description

This description is valid for the installation of wall-mounted robots with the mounting variant "Machine frame mounting". For installation on the wall, the robot must be fastened to the Load Lifting Attachment. The robot is fastened to the wall using the Load Lifting Attachment. The Load Lifting Attachment must then be removed.

The installation and start-up of the robot controller, the tools mounted and the applications are not described here.

NOTICE

The robot may only be operated with a functioning compressed air supply. The compressed air must be oil-free, dry and filtered. Damage to property may otherwise result.



During start-up and recommissioning, compliance with the cleanroom class requirements cannot be assured. Before the manipulator is put into operation, cleaning must be carried out in accordance with the requirements of the application.

Precondition

- The machine frame mounting assembly is installed.
- The installation site is accessible with a crane and fork lift truck.
- Any tools or other system components which would hinder the work have been removed.

- The robot is in the transport position.
- 2 instructed persons are required for performing this task.
- There is a compressed air supply to the robot.

Procedure

1. Clean the robot.
2. Bring the robot to the installation site with the crane and set it down.
3. Carefully push the Load Lifting Attachment onto the base frame of the robot from the front (**>>> Fig. 8-3**).
4. Remove the lifting tackle.
5. Fasten the robot to the front of the Load Lifting Attachment with 2 M12x30 Allen screws and washers; $M_A = 40 \text{ Nm}$.




Fig. 8-3: Pushing on the Load Lifting Attachment and fastening it at the front

- 1 Base frame
- 2 Load lifting attachment
- 3 M12x30 Allen screw (front)
6. Position swivel holders on base frame (**>>> Fig. 8-4**).
7. Fasten the swivel holders to the rear of the base frame with 2 M12x30 Allen screws and washers; $M_A = 40 \text{ Nm}$.
8. Lock the swivel holders to the Load Lifting Attachment with 2 M12x30 Allen screws and washers.




Fig. 8-4: Positioning and fastening the swivel holders

- 1 Swivel holder
 - 2 M12x30 Allen screw (rear)
 - 3 M12x30 Allen screw (locking screw)
9. Attach lifting tackle to the 2 rotating swivel eyebolts on the Load Lifting Attachment and to the crane.
10. Person 1:
Slowly and carefully lift the robot with the crane.
Person 2:
Secure the robot against toppling during the lifting operation.

WARNING Ensure that the robot does not topple during the lifting operation. Serious injuries and damage to property may otherwise result.

11. Slowly rotate the robot through 90°. The arm must point downward.
12. Lift the Load Lifting Attachment with a fork lift truck ([>>> Fig. 8-5](#)).
The fork lift truck must remain in the fork slots of the Load Lifting Attachment during installation in order to prevent slipping.

NOTICE When picking up the Load Lifting Attachment with the fork lift truck, the width of the fork slots (140 mm) must be taken into consideration. Damage to property may otherwise result.




Fig. 8-5: Lifting the Load Lifting Attachment with a fork lift truck

13. Position the robot on the wall using the fork lift truck. Ensure that an entirely horizontal position is maintained in order to prevent damage to the locating pins.

14. Unscrew 2 M12x30 Allen screws (top Allen screws) and washers from the top of the base frame (**>>> Fig. 8-6**).
15. Unscrew 2 M12x30 Allen screws (locking screws) and washers from the Load Lifting Attachment.




Fig. 8-6: Removing the top screws

- 1 M12x30 Allen screw (top)
 - 2 M12x30 Allen screw (locking screw)
16. Rotate the swivel holders outwards (**>>> Fig. 8-7**).
 17. Fasten the robot to the wall with 2 M10x35 hexagon bolts (top hexagon bolts) and washers at the top.
Tighten the hexagon bolts alternately with the torque wrench. Gradually increase the tightening torque to 45 Nm.




Fig. 8-7: Rotating the swivel holders outwards

- 1 Swivel holder
- 2 M10x35 hexagon bolt (top)
18. Unscrew 2 M12x30 Allen screws (bottom Allen screws) and washers from the bottom of the base frame.
19. Carefully separate the Load Lifting Attachment from the bottom of the base frame with the fork lift truck.
20. Fasten the robot to the wall with 2 M10x35 hexagon bolts and washers on the bottom of the base frame.
Tighten the hexagon bolts alternately with the torque wrench. Gradually increase the tightening torque to 45 Nm.
21. Connect motor cable X30 and data cable X31 ([>>> Fig. 8-8](#)).
When connecting the motor cable connectors, it must be ensured that the connectors on the controller and on the robot are locked correctly. Correct locking is indicated by an audible click. It is indicated optically by the fact that the red rings on each of the locking buttons are not visible and are pushed in completely.
22. Connect the PURGE compressed air line with max. 0.3 bar.
23. Connect the ground conductor between the robot controller and the robot to the ground conductor connection.




Fig. 8-8: Connecting the cables

- | | | | |
|---|------------------|---|---------------------|
| 1 | Ground conductor | 3 | Compressed air line |
| 2 | Motor cable | 4 | Data cable |
24. Check the equipotential bonding in accordance with VDE 0100 and EN 60204-1.
 25. Connect the ground conductor between the system component and the robot to the ground conductor connection.
 26. Mount tooling, if present.
 27. Retighten the 4 hexagon bolts with a torque wrench after 100 hours of operation.



Further information is contained in the operating and assembly instructions of the robot controller.

Put the robot into operation in accordance with the “Start-up” chapter of the operating and programming instructions for the System Software and/or the assembly instructions or operating instructions for the robot controller.

NOTICE

Incorrectly adjusted pressure regulators or operation with no pressure regulator may result in damage to the robot. For this reason, the robot may only be operated with a correctly adjusted pressure regulator and with the compressed air supply connected.

8.5 Installing a ceiling-mounted robot

Description

This description is valid for the installation of ceiling-mounted robots. The mounting base or machine frame mounting assembly is used for this purpose. For installation on the ceiling, the robot must be fastened to the Load Lifting Attachment. The robot is fastened to the ceiling using the Load Lifting Attachment. The Load Lifting Attachment must then be removed.

The installation and start-up of the robot controller, the tools mounted and the applications are not described here.

NOTICE

The robot may only be operated with a functioning compressed air supply. The compressed air must be oil-free, dry and filtered. Damage to property may otherwise result.



During start-up and recommissioning, compliance with the cleanroom class requirements cannot be assured. Before the manipulator is put into operation, cleaning must be carried out in accordance with the requirements of the application.

Precondition

- The machine frame mounting assembly is installed.
- The installation site is accessible with a crane and fork lift truck.
- Any tools or other system components which would hinder the work have been removed.
- The robot is in the transport position.
- 2 instructed persons are required for performing this task.
- There is a compressed air supply to the robot.

Procedure

1. Clean the robot.
2. Bring the robot to the installation site with the crane and set it down.
3. Carefully push the Load Lifting Attachment onto the base frame of the robot from the front (**>>> Fig. 8-9**).
4. Remove the lifting tackle.
5. Fasten the robot to the front of the Load Lifting Attachment with 2 M12x30 Allen screws and washers; $M_A = 40.0 \text{ Nm}$.




Fig. 8-9: Pushing on the Load Lifting Attachment and fastening it at the front

- 1 Base frame
- 2 Load lifting attachment
- 3 M12x30 Allen screw (front)
6. Position swivel holders on base frame ([>>> Fig. 8-10](#)).
7. Fasten the swivel holders to the rear of the base frame with 2 M12x30 Allen screws and washers; $M_A = 40.0 \text{ Nm}$.
8. Lock the swivel holders to the Load Lifting Attachment with 2 M12x30 Allen screws and washers.




Fig. 8-10: Positioning and fastening the swivel holders

- 1 Swivel holder
- 2 M12x30 Allen screw (rear)
- 3 M12x30 Allen screw (locking screw)
9. Attach lifting tackle to the 2 rotating swivel eyebolts on the Load Lifting Attachment and to the crane.
10. Person 1:
Slowly and carefully lift the robot with the crane.

Person 2:

Secure the robot against toppling during the lifting operation.

WARNING Ensure that the robot does not topple during the lifting operation. Serious injuries and damage to property may otherwise result.

11. Slowly rotate the robot through 180° and lower it.
12. Lift the Load Lifting Attachment with a fork lift truck (**>>>** Fig. 8-11).
The fork lift truck must remain in the fork slots of the Load Lifting Attachment during installation in order to prevent slipping.

NOTICE When picking up the Load Lifting Attachment with the fork lift truck, the width of the fork slots (140 mm) must be taken into consideration. Damage to property may otherwise result.




Fig. 8-11: Lifting the Load Lifting Attachment with a fork lift truck

13. Position the robot on the ceiling using the fork lift truck. Ensure that an entirely vertical position is maintained in order to prevent damage to the locating pins.
14. Unscrew 2 M12x30 Allen screws (rear Allen screws) and washers from the rear of the base frame (**>>>** Fig. 8-12).
15. Unscrew 2 M12x30 Allen screws (locking screws) and washers from the Load Lifting Attachment.




Fig. 8-12: Removing screws from the rear

- 1 M12x30 Allen screw (rear)
- 2 M12x30 Allen screw (locking screw)

16. Rotate the swivel holders outwards (**>>>** Fig. 8-13).
17. Fasten the robot to the ceiling with 2 M10x35 hexagon bolts (rear hexagon bolts) and washers at the rear.
Tighten the hexagon bolts alternately with the torque wrench. Gradually increase the tightening torque to 45.0 Nm.




Fig. 8-13: Rotating the swivel holders outwards

- 1 Swivel holder
- 2 M10x35 hexagon bolt (rear)

18. Unscrew 2 M12x30 Allen screws (front Allen screws) and washers from the front of the base frame.
19. Carefully push the Load Lifting Attachment down from the rear of the base frame with the fork lift truck.
20. Fasten the robot to the ceiling with 2 M10x35 hexagon bolts and washers at the front of the base frame.
Tighten the hexagon bolts alternately with the torque wrench. Gradually increase the tightening torque to 45.0 Nm.
21. To ensure that no fluids and/or solids can collect between the mounting surface and base frame of the robot, it is advisable to fill or seal this area.
22. Connect motor cable X30 and data cable X31 ([>>> Fig. 8-14](#)).
When connecting the motor cable connectors, it must be ensured that the connectors on the controller and on the robot are locked correctly. Correct locking is indicated by an audible click. It is indicated optically by the fact that the red rings on each of the locking buttons are not visible and are pushed in completely.
23. Connect the PURGE compressed air line with max. 0.3 bar.
24. Connect the ground conductor between the robot controller and the robot to the ground conductor connection.




Fig. 8-14: Connecting the cables

- | | |
|--------------------|-----------------------|
| 1 Ground conductor | 3 Compressed air line |
| 2 Motor cable | 4 Data cable |
25. Check the equipotential bonding in accordance with VDE 0100 and EN 60204-1.



Further information is contained in the operating and assembly instructions of the robot controller.

26. Connect the ground conductor between the system component and the robot to the ground conductor connection.
27. Mount tooling, if present.
28. Retighten the 4 M10x35 hexagon bolts with a torque wrench after 100 hours of operation.

Put the robot into operation in accordance with the "Start-up" chapter of the operating and programming instructions for the System Software and/or the assembly instructions or operating instructions for the robot controller.

NOTICE

Incorrectly adjusted pressure regulators or operation with no pressure regulator may result in damage to the robot. For this reason, the robot may only be operated with a correctly adjusted pressure regulator and with the compressed air supply connected.

8.6 Description of the connecting cables

Setup

The connecting cables are used to transfer power and signals between the robot controller and the robot.

The connecting cables comprise:

- Motor cable
- Data cable
- CAT5 data cable (optional)
- Connecting cable, external axes A7 and A8 (optional)
- Ground conductor (optional)

Interface

For connection of the connecting cables between the robot controller and the robot, the following connectors are available at the interfaces:

Cable designation	Connector designation robot controller - robot	Interface with robot
Motor cable	X20 - X30	Han Yellock 30
Data cable	X21 - X31	Han Q12
Data cable CAT5 (can be ordered as an option)	X65/X66 - XPN1	M12 connector
Connecting cable, exter- nal axes A7 and A8 (can be ordered as an option)	XP7 - XP7.1 XP8 - XP8.1	Connector M17 in each case
Ground conductor, equi- potential bonding (can be ordered as an option)		M4 ring cable lug

Only resolvers can be connected to the connections XP7.1 and XP8.1.



For the connecting cables, a ground conductor is always required to provide a low-resistance connection between the robot and the control cabinet in accordance with DIN EN 60204. The ground conductor is not part of the scope of supply and can be ordered as an option. The connection must be made by the customer. The tapped holes for connecting the ground conductor are located on the base frame of the robot.

**Standard
connecting cable**





Fig. 8-15: Connecting cables, overview



Wiring diagram




Fig. 8-16: Connecting cable, motor cable, X20 - X30




Fig. 8-17: Connecting cable, data cable X21 - X31




Fig. 8-18: Connecting cable, data cable CAT5 X65/X66 - XPN1




Fig. 8-19: Connecting cable, external axes A7 and A8




Fig. 8-20: Connecting cable, ground conductor

1	Ground conductor	6	Conical spring washer
2	Hexagon nut	7	Robot
3	Conical spring washer	8	Setscrew, M4
4	Plain washer 2x	9	Ground conductor connection, M4 ring cable lug
5	Hexagon nut	10	Ground sign

8.7 Moving the manipulator without drive energy

Description The brake release device (optional) can be used for moving the manipulator after an accident or malfunction without drive energy.

This option is only for use in exceptional circumstances and emergencies, e.g. for freeing people.

Precondition

- The robot controller must be switched off and secured (e.g. with a padlock) to prevent unauthorized persons from switching it on again.

Procedure



WARNING Use of the brake release device may result in unexpected robot motions, especially sagging of the axes. During use of the brake release device, attention must be paid to motion of this kind in order to be able to prevent physical injuries or damage to property. Standing under moving axes is not permitted.



The following procedure must be followed exactly!

1. Unplug motor cable X30 on the robot.
2. Plug connector X20 into the brake release device and connector X30 into the robot.
3. Plug connector X1 of the hand-held device into the brake release device.
4. Select the brakes to be released (main axes, wrist axes) via the selection switch on the brake release device.
5. Press the button on the hand-held device.

The brakes of the main axes or wrist axes are released and the robot can be moved manually.



Further information about the brake release device can be found in the documentation for the brake release device.

9 Maintenance

CAUTION For screwed connections, the fastening screws (standard, strength class 8.8) are to be tightened with the tightening torques specified in the appendix ([>>> 12 "Appendix" Page 231](#)). Tightening torques deviating from these values are specified directly. The specified screw sizes and strength classes are those valid at the copy deadline. The specifications contained in the Parts Catalog are, however, always to be taken as the most up-to-date information. Screws of strength class 10.9 and higher may only be tightened once with the rated tightening torque. When the screws are first slackened they must be replaced with new ones.

9.1 Maintenance overview

Description The table provides an overview of the maintenance work (maintenance intervals, activities, lubrication work) and required lubricants applicable to this robot.

The maintenance intervals given in the table are valid for the operating conditions specified in the technical data. KUKA Deutschland GmbH must be consulted in the case of discrepancies!



Further information can be found in the section "Information for planning" ([>>> 6.1 "Information for planning" Page 169](#)).

Precondition

- The maintenance points must be freely accessible.
- Remove the tools and any additional items of equipment if they impede maintenance work.



WARNING Unintentional robot motions can cause injuries and damage to property. If work is carried out on an operational robot, the robot must be secured by activating the EMERGENCY STOP device.

Warn all persons concerned before starting to put it back into operation.



During maintenance and repair work, the ISO Class 2 cleanroom cannot be guaranteed.

9.1.1 Maintenance table

Maintenance symbols



The overview may contain maintenance symbols that are not relevant for the maintenance work on this product. The maintenance illustrations provide an overview of the relevant maintenance work.



Oil change



Lubricate with grease gun



Lubricate with brush



Lubricate with spray grease



Tighten screw/nut



Check component, visual inspection



Clean component



Exchange battery



Exchanging the toothed belt



Check toothed belt tension




Fig. 9-1: Maintenance work

Interval	Item	Activity	Lubricant
100 h*	5	<p>Check the tightening torque of the 4 holding-down bolts on the mounting base.</p> <p>$M_A = 45.0 \text{ Nm}$</p> <p>* Once only, after initial start-up or recommissioning.</p>	-
100 h*	2	<p>Check the tightening torque of the 4 fastening screws on the side section of the link arm.</p> <p>$M_A = 23.0 \text{ Nm}$</p> <p>* Once only, after initial start-up or recommissioning.</p> <p>(>>> 9.2 "Checking the screws, side section of link arm" Page 210)</p>	-
100 h*	4	<p>Check the tightening torque of the 10 fastening screws on the torque bridge.</p> <p>$2x M_A = 0.8 \text{ Nm}$</p> <p>$8x M_A = 9.0 \text{ Nm}$</p> <p>* Once only, after initial start-up or recommissioning.</p> <p>(>>> 9.3 "Checking the screws, in-line wrist torque bridge" Page 211)</p>	-
1 week	-	<p>Check that all plug connections are undamaged and fitted securely.</p> <p>Secure any loose cables and connectors. Exchange any damaged components.</p>	-
1 week	-	Perform a visual inspection of the sealing points for damage. In the case of damage, inform KUKA Service.	-
1 year	5	<p>If using a mounting base, check the tightening torque of the 4 holding-down bolts.</p> <p>$M_A = 45 \text{ Nm}$</p>	-
5,000 h or 1 year at the latest	1	<p>Grease the inside of covers A2 and A3.</p> <p>(>>> 9.4 "Greasing the inside of covers A2 and A3" Page 211)</p>	Grease RB 2 Art. no. 00-101-456 10 g

Interval	Item	Activity	Lubricant
5,000 h or 1 year at the latest	3	Exchange toothed belts on A5 and A6. (>>> 9.5 "Exchanging the toothed belts" Page 213)	-
5,000 h or 1 year at the latest*	-	Depending on installation conditions and degree of clogging, clean the robot. (>>> 9.6 "Cleaning the robot" Page 214)	-

9.2 Checking the screws, side section of link arm

Description The tightening torques of the fastening screws of the side section of the link arm must be checked once 100 h following initial start-up or recommissioning.

Precondition

- The robot is in the mechanical zero position.

WARNING Unintentional robot motions can cause injuries and damage to property. If work is carried out on an operational robot, the robot must be secured by activating the EMERGENCY STOP device.
Warn all persons concerned before starting to put it back into operation.

CAUTION The motors reach temperatures during operation which can cause burns to the skin. Contact must be avoided. Appropriate safety precautions must be taken, e.g. protective gloves must be worn.

Procedure

1. Check the following 4 fastening screws with the torque wrench and retighten with the tightening torques indicated if necessary (>>> Fig. 9-2).
Exchange damaged screws and washers.
 - 2x M8x40 Allen screw: $M_A = 23.0 \text{ Nm}$
 - 2x M8x20 Allen screw: $M_A = 23.0 \text{ Nm}$




Fig. 9-2: Checking the screws, side section of the link arm

- 1 M8x40 Allen screw
- 2 M8x20 Allen screw
2. Clean the robot.

9.3 Checking the screws, in-line wrist torque bridge

Description The tightening torques of the fastening screws of the torque bridge on the in-line wrist must be checked once 100 h following initial start-up or recommissioning.

Precondition

- The robot is in the mechanical zero position.

WARNING Unintentional robot motions can cause injuries and damage to property. If work is carried out on an operational robot, the robot must be secured by activating the EMERGENCY STOP device.
Warn all persons concerned before starting to put it back into operation.

CAUTION The motors reach temperatures during operation which can cause burns to the skin. Contact must be avoided. Appropriate safety precautions must be taken, e.g. protective gloves must be worn.

Procedure

1. Check the following 10 fastening screws with the torque wrench and retighten with the tightening torques indicated if necessary ([>>> Fig. 9-3](#)). Exchange damaged screws and washers.
 - 8x M5x20 Allen screw: $M_A = 9.0 \text{ Nm}$
 - 2x M3x10 round head screw: $M_A = 0.8 \text{ Nm}$




Fig. 9-3: Checking the screws, in-line wrist torque bridge

- 1 M5x20 Allen screw
- 2 M3x10 round head screw
- 2. Clean the robot.

9.4 Greasing the inside of covers A2 and A3

Description The inside of covers must be greased with Optitemp RB 2.

Precondition

- Arm and in-line wrist are horizontal.

WARNING Unintentional robot motions can cause injuries and damage to property. If work is carried out on an operational robot, the robot must be secured by activating the EMERGENCY STOP device.
Warn all persons concerned before starting to put it back into operation.

CAUTION

The motors reach temperatures during operation which can cause burns to the skin. Contact must be avoided. Appropriate safety precautions must be taken, e.g. protective gloves must be worn.

Procedure

1. Remove the following round head screws from cover A2 and take off cover A2 together with the seal (>>> Fig. 9-4):
 - 3 M4x16-10.9 round head screws
 - 2 M4x25-10.9 round head screws
 - 5 M4x35-10.9 round head screws
2. Remove 7 M3x12-10.9 round head screws from cover A3 and take off cover A3 together with the seal.




Fig. 9-4: Removing covers A2 and A3

- 1 Cover A2
 - 2 M4x35-10.9 round head screws
 - 3 M4x25-10.9 round head screws
 - 4 M4x16-10.9 round head screws
 - 5 Cover A3
 - 6 M3x12-10.9 round head screws
3. Remove the seals from the covers and dispose of them in accordance with the pertinent regulations.
 4. Clean the sealing surfaces of the cover and housing and check them for damage. In the case of damage, inform KUKA Service.
 5. Grease the inside of both covers with Optitemp RB 2.
 6. Mount a new seal in each cover.
 7. Fit cover A2 and fasten it with the following new screws:
 - 3 M4x16-10.9 round head screws; $M_A = 1.9 \text{ Nm}$
 - 2 M4x25-10.9 round head screws; $M_A = 1.9 \text{ Nm}$
 - 5 M4x35-10.9 round head screws; $M_A = 1.9 \text{ Nm}$
 8. Mount cover A3 and fasten it with 7 new M3x12-10.9 round head screws; $M_A = 0.8 \text{ Nm}$.
 9. Clean the robot.

9.5 Exchanging the toothed belts

Description The toothed belts of axes 5 and 6 may only be removed and installed together.

Precondition

- The arm is in the horizontal position.
- The wrist axes are in their zero positions.
- No tools are installed on axis 6.

WARNING Unintentional robot motions can cause injuries and damage to property. If work is carried out on an operational robot, the robot must be secured by activating the EMERGENCY STOP device.
Warn all persons concerned before starting to put it back into operation.

CAUTION If the toothed belt is removed and installed immediately after the robot has stopped operating, surface temperatures are likely to be high and could result in burn injuries; there is also a risk of hands and fingers being pinched or crushed.
Protective gloves must be worn.

Procedure

1. Remove 7 M3x10-10.9 fillister head screws from the cover and take off the cover together with the seal ([>>> Fig. 9-5](#)).




Fig. 9-5: Removing the cover from the in-line wrist – example

- | | |
|-----------------|------------------------|
| 1 In-line wrist | 3 Cover |
| 2 Seal | 4 Fillister head screw |
2. Slacken 2 M4x10-10.9 fillister head screws on motor A5 and motor A6 ([>>> Fig. 9-6](#)).
 3. Take the old toothed belts A5 and A6 off the pulleys.




Fig. 9-6: Removing the toothed belt – example

- | | |
|------------------------|-------------------|
| 1 Fillister head screw | 3 Toothed belt A5 |
| 2 Toothed belt pulley | 4 Toothed belt A6 |
4. Fit new toothed belts A5 and A6 in the in-line wrist. Ensure that the toothed belts mesh properly with the toothed belt pinions (**>>>** Fig. 9-7).




Fig. 9-7: Toothed belt and toothed belt pinion

- | | |
|----------------|-----------------------|
| 1 Toothed belt | 2 Toothed belt pinion |
|----------------|-----------------------|
5. Measure and adjust the toothed belt tension.
(**>>>** 10.1 "Measuring and adjusting the toothed belt tension" Page 217)
 6. Clean the sealing surfaces of the cover and housing and check them for damage. In the case of damage, inform KUKA Service.
 7. Insert a new seal into the cover.
 8. Mount the cover and fasten it with 7 new M3x10-10.9 fillister head screws; $M_A = 0.8 \text{ Nm}$.
 9. Carry out mastering of axes 5 and 6.



Detailed information about mastering is contained in the operating and programming instructions for end users or system integrators.

10. Clean the robot.

9.6 Cleaning the robot

Description

The robot must be cleaned in compliance with the instructions given here in order to prevent damage. These instructions only refer to the robot. System components, tools and the robot controller must be cleaned in accordance with the cleaning instructions relevant to them.

The following must be taken into consideration when using cleaning agents and carrying out cleaning work:

- Only use solvent-free, water-soluble cleaning agents.
- Do not use flammable cleaning agents.
- Do not use aggressive cleaning agents.
- Use cloths with isopropanol.
- Do not use steam or refrigerants for cleaning.
- Use ionized clean air with 6 bar and a distance of 30 cm.
- Do not use high-pressure cleaners.
- It must be ensured that no cleaning agent enters electrical or mechanical system components.
- Personnel protection measures must be taken.

Precondition

⚠ WARNING Unintentional robot motions can cause injuries and damage to property. If work is carried out on an operational robot, the robot must be secured by activating the EMERGENCY STOP device.
Warn all persons concerned before starting to put it back into operation.

⚠ WARNING Unintentional robot motions can cause injuries and damage to property. If work is carried out on an operational robot, the robot must be secured by activating the EMERGENCY STOP device.
Warn all persons concerned before starting to put it back into operation.

Procedure

1. Shut down the robot.
2. If necessary, shut adjacent system components down and lock them.
3. Remove enclosures if this is necessary in order to carry out the cleaning work.
4. Clean the robot.
5. Fully remove all cleaning agents from the robot.
6. Remove cleaning agents and equipment from the workspace of the robot.
7. Dispose of cleaning agents in accordance with the pertinent regulations.
8. Install any safety equipment that has been removed and check that it is functioning correctly.
9. Replace any damaged or illegible plates and covers.
10. Put back in place any enclosures that have been removed.
11. Only put fully functional robots and systems back into operation.

10 Repair

CAUTION For screwed connections, the fastening screws (standard, strength class 8.8) are to be tightened with the tightening torques specified in the appendix ([>>> 12 "Appendix" Page 231](#)). Tightening torques deviating from these values are specified directly. The specified screw sizes and strength classes are those valid at the copy deadline. The specifications contained in the Parts Catalog are, however, always to be taken as the most up-to-date information. Screws of strength class 10.9 and higher may only be tightened once with the rated tightening torque. When the screws are first slackened they must be replaced with new ones.

10.1 Measuring and adjusting the toothed belt tension

Description The toothed belt tension on A5 and A6 is measured and adjusted in the same way. The following description deals with the toothed belt tension for A5.

Precondition

- Axis 5 is horizontal.
- No tools are installed on axis 6.

WARNING Unintentional robot motions can cause injuries and damage to property. If work is carried out on an operational robot, the robot must be secured by activating the EMERGENCY STOP device.
Warn all persons concerned before starting to put it back into operation.

CAUTION If the toothed belt tension is measured and adjusted immediately after the robot has stopped operating, surface temperatures are likely to be high and could result in burn injuries. Protective gloves must be worn.

i During maintenance and repair work, the ISO Class 2 cleanroom cannot be guaranteed.

Procedure

1. Remove 7 M3x10-10.9 fillister head screws from the cover and take off the cover together with the seal ([>>> Fig. 10-1](#)).




Fig. 10-1: Removing the cover from the in-line wrist – example

- 1 In-line wrist
2 Seal
3 Cover
4 Fillister head screw
2. Slacken 2 M4x10-10.9 fillister head screws on motor A5 (**>>>** Fig. 10-2).
 3. Insert a suitable tool (e.g. screwdriver) into the corresponding aperture in the motor mount and carefully press motor A5 to the left in order to tension toothed belt A5.




Fig. 10-2: Tensioning the toothed belt – example

- 1 Fillister head screw
2 Aperture in motor mount A5
3 Toothed belt A5
4 Tothod belt A6
5 Aperture in motor mount A6
4. Lightly tighten 2 M4x10-10.9 fillister head screws on motor A5.
 5. Switch on the belt tension measuring device (**>>>** Fig. 10-3).
 6. Pluck toothed belt A5 and hold the sensor near its center at a distance of 2 to 3 mm from the vibrating toothed belt. Read the measurement on the belt tension measuring device.




Fig. 10-3: Belt tension measuring device

- 1 Belt tension measuring device
2 Sensor

Toothed belt tension

In-line wrist	Axis	Toothed belt	Frequency
ZH6 R700 CR	5	AT3/267	305 ± 5 Hz
	6		
ZH6 R900 CR ZH10 R900 CR	5	AT3/351	205 ± 5 Hz
	6		

In-line wrist	Axis	Toothed belt	Frequency
ZH10 R1100 CR	5	AT3/351	205 ± 5 Hz
	6		

7. Tighten 2 M4x10-10.9 fillister head screws on motor A5, $M_A = 1.9$ Nm.
8. Put the robot into operation and move A5 in both directions.
9. Secure the robot by pressing the E-STOP device.
10. Measure the tension of the toothed belt again.
If the value obtained does not correspond to the value in the table, repeat steps 2 to 10.
11. Carry out steps 2 to 10 for toothed belt A6.
12. Clean the sealing surfaces of the cover and housing and check them for damage. In the case of damage, inform KUKA Service.
13. Insert a new seal into the cover.
14. Mount the cover and fasten it with 7 new M3x10-10.9 fillister head screws; $M_A = 0.8$ Nm.
15. Clean the robot.

11 Decommissioning, storage and disposal

11.1 Decommissioning, floor-mounted robot

Description This section describes all the work required for decommissioning the robot if the robot is to be removed from the system. After decommissioning, it is prepared for storage or for transportation to a different location.

Following its removal, the robot can be transported by means of round slings and a crane ([>>> 7 "Transportation" Page 181](#)).

Precondition

- The removal site is accessible for transportation with a crane.
- There is no hazard posed by system components.



WARNING When carrying out the following work, the robot must be moved several times between the individual work steps. While work is being carried out on the robot, it must always be secured by activating the EMERGENCY STOP device. Unintentional robot motions can cause injuries and damage to property. If work is carried out on an operational robot that is switched on, the robot must only be moved at reduced velocity. It must be possible to stop the robot at any time by activating an EMERGENCY STOP device. Operation must be limited to what is absolutely necessary.
Warn all persons concerned before switching on and moving the robot.

Procedure

1. Secure the robot.
2. Remove tools and equipment.
3. Put the robot into operation and move it into the transport position ([>>> Fig. 11-1](#)).




Fig. 11-1: Transport position

4. Secure the robot by activating the E-STOP device and then shut down the robot ([>>> Fig. 11-2](#)).
 5. Release and unplug all peripheral connections.
 6. Release and unplug the motor cable and data cable connectors.
 7. Release and unplug the compressed air connector.
 8. Release and unplug the ground conductor.
 9. Attach the lifting tackle.
 10. Unscrew and remove the 4 hexagon bolts and conical spring washers.
 11. Lift the robot vertically off the mounting surface and transport it away.
- Take care not to damage the two locating pins when lifting.

CAUTION

If the robot is caught on the mounting surface, it may come free abruptly, endangering persons and property. The robot must stand loosely on the mounting surface; completely remove all fastening materials and any adhesives.

12. Prepare the robot for storage.




Fig. 11-2: Removing a floor-mounted robot

- | | |
|-----------------------|--------------------|
| 1 Lifting tackle | 5 Mounting surface |
| 2 Motor cable | 6 Hexagon bolt |
| 3 Data cable | 7 Ground conductor |
| 4 Compressed air line | 8 Locating pin |

11.2 Decommissioning, wall-mounted robot

Description

This section describes all the work required for decommissioning the wall-mounted robot if the robot is to be removed from the system. After decommissioning, it is prepared for storage or for transportation to a different location.

Precondition

- The removal site is accessible with a crane and fork lift truck.
- There is no hazard posed by system components.

WARNING

When carrying out the following work, the robot must be moved several times between the individual work steps. While work is being carried out on the robot, it must always be secured by activating the EMERGENCY STOP device. Unintentional robot motions can cause injuries and damage to property. If work is carried out on an operational robot that is switched on, the robot must only be moved at reduced velocity. It must be possible to stop the robot at any time by activating an EMERGENCY STOP device. Operation must be limited to what is absolutely necessary. Warn all persons concerned before switching on and moving the robot.

Procedure

1. Secure the robot.
2. Remove tools and equipment.

3. Put the robot into operation and move it into the transport position (**>>> Fig. 11-3**).




Fig. 11-3: Transport position

4. Secure the robot by activating the E-STOP device and then shut down the robot.
5. Release and unplug all peripheral connections.
6. Release and unplug the motor cable and data cable connectors.
7. Release and unplug the compressed air connector.
8. Release and unplug the ground conductor.
9. Rotate the Load Lifting Attachment so that it can be screwed to the wall-mounted machine.
10. Lift the Load Lifting Attachment with a fork lift truck.

The fork lift truck must remain in the fork slots of the Load Lifting Attachment during removal in order to prevent slipping.

NOTICE

When picking up the Load Lifting Attachment with the fork lift truck, the width of the fork slots (140 mm) must be taken into consideration. Damage to property may otherwise result.

11. Unscrew 2 M10x35 hexagon bolts (bottom hexagon bolts) and washers from the bottom of the base frame.
12. Carefully push the Load Lifting Attachment onto the base frame of the robot from underneath (**>>> Fig. 11-4**).
13. Fasten the robot to the Load Lifting Attachment from underneath with 2 M12x30 Allen screws (bottom Allen screws) and washers; $M_A = 40 \text{ Nm}$.




Fig. 11-4: Fastening the Load Lifting Attachment to the robot

- 1 Base frame
 - 2 M10x35 hexagon bolt (bottom)
 - 3 Load Lifting Attachment
 - 4 M12x30 Allen screw (bottom)
14. Unscrew 2 M10x35 hexagon bolts (top hexagon bolts) and washers from the top of the base frame.
 15. Position swivel holders on base frame ([>>> Fig. 11-5](#)).
 16. Fasten the swivel holders to the top of the base frame with 2 M12x30 Allen screws and washers; $M_A = 40 \text{ Nm}$.
 17. Lock the swivel holders to the Load Lifting Attachment with 2 M12x30 Allen screws (locking screws) and washers.




Fig. 11-5: Positioning and fastening the swivel holders

- 1 Swivel holder
 - 2 M12x30 Allen screw (top)
 - 3 M12x30 Allen screw (locking screw)

 18. Slowly move the robot away from the wall with a fork lift truck.
 19. Attach lifting tackle to the 2 rotating swivel eyebolts on the Load Lifting Attachment and to the crane.
 20. Move the fork lift truck slowly and carefully out of the fork slots of the Load Lifting Attachment.
 21. Person 1:
Slowly and carefully lower the robot with the crane.
Person 2:
Secure the robot against toppling during the lowering operation.
- ⚠️ WARNING** Ensure that the robot does not topple during the lowering operation. Serious injuries and damage to property may otherwise result.
22. Slowly rotate the robot through 90° and carefully set it down.
 23. Unscrew 4 M12x30 Allen screws and washers from the Load Lifting Attachment.
 24. Unscrew 2 M12x30 Allen screws and washers from the swivel holders.
 25. Rotate the swivel holders outwards.
 26. Carefully push the Load Lifting Attachment down from the back of the base frame.
 27. Prepare the robot for storage.

11.3 Decommissioning, ceiling-mounted robot

Description This section describes all the work required for decommissioning the ceiling-mounted robot if the robot is to be removed from the system. After decommissioning, it is prepared for storage or for transportation to a different location.

Precondition

- The removal site is accessible with a crane and fork lift truck.
- There is no hazard posed by system components.

⚠️ WARNING When carrying out the following work, the robot must be moved several times between the individual work steps. While work is being carried out on the robot, it must always be secured by activating the EMERGENCY STOP device. Unintentional robot motions can cause injuries and damage to property. If work is carried out on an operational robot that is switched on, the robot must only be moved at reduced velocity. It must be possible to stop the robot at any time by activating an EMERGENCY STOP device. Operation must be limited to what is absolutely necessary. Warn all persons concerned before switching on and moving the robot.

Procedure

1. Secure the robot.
2. Remove tools and equipment.
3. Put the robot into operation and move it into the transport position (**>>>** Fig. 11-6).




Fig. 11-6: Transport position

4. Secure the robot by activating the E-STOP device and then shut down the robot.
5. Release and unplug all peripheral connections.
6. Release and unplug the motor cable and data cable connectors.
7. Release and unplug the compressed air connector.
8. Release and unplug the ground conductor.
9. Rotate the Load Lifting Attachment so that it can be screwed to the ceiling-mounted machine.
10. Lift the Load Lifting Attachment with a fork lift truck.

The fork lift truck must remain in the fork slots of the Load Lifting Attachment during removal in order to prevent slipping.

NOTICE

When picking up the Load Lifting Attachment with the fork lift truck, the width of the fork slots (140 mm) must be taken into consideration. Damage to property may otherwise result.

11. Unscrew 2 M10x35 hexagon bolts (front hexagon bolts) and washers from the front of the base frame.
12. Carefully push the Load Lifting Attachment onto the base frame of the robot from the front (**>>> Fig. 11-7**).
13. Fasten the robot to the front of the Load Lifting Attachment with 2 M12x30 Allen screws (front Allen screws) and washers; $M_A = 40 \text{ Nm}$.




Fig. 11-7: Fastening the Load Lifting Attachment to the robot

- 1 Base frame
- 2 M10x35 hexagon bolt (front)
- 3 Load Lifting Attachment
- 4 M12x30 Allen screw (front) and washer

14. Unscrew 2 M10x35 hexagon bolts (rear hexagon bolts) and washers from the rear of the base frame.
15. Position swivel holders on base frame (**>>> Fig. 11-8**).
16. Fasten the swivel holders to the rear of the base frame with 2 M12x30 Allen screws and washers; $M_A = 40 \text{ Nm}$.
17. Lock the swivel holders on the Load Lifting Attachment with 2 M12x30 Allen screws.




Fig. 11-8: Positioning and fastening the swivel holders

- 1 M12x30 Allen screw (locking screw)
- 2 M12x30 Allen screw (rear)
- 3 Swivel holder

18. Slowly lower the robot with a fork lift truck.
19. Attach lifting tackle to the 2 rotating swivel eyebolts on the Load Lifting Attachment and to the crane.
20. Move the fork lift truck slowly and carefully out of the fork slots of the Load Lifting Attachment.

21. Person 1:

Slowly and carefully lift the robot with the crane.

Person 2:

Secure the robot against toppling during the lifting operation.



WARNING Ensure that the robot does not topple during the lifting operation. Serious injuries and damage to property may otherwise result.

22. Slowly rotate the robot through 180° and carefully set it down.

23. Unscrew 4 M12x30 Allen screws (front and rear) and washers from the Load Lifting Attachment.

24. Unscrew 2 M12x30 Allen screws (locking screws) and washers from the swivel holders.

25. Rotate the swivel holders outwards.

26. Carefully push the Load Lifting Attachment down from the back of the base frame.

27. Prepare the robot for storage.

11.4 Storage

Description

If the robot is to be put into long-term storage, the following points must be observed:

- The place of storage must be as dry and dust-free as possible.
- Avoid temperature fluctuations.
- Avoid wind and drafts.
- Avoid condensation.
- Use appropriate coverings that cannot detach themselves and which can withstand the expected environmental conditions.
- Do not leave any loose parts on the robot, especially ones that might knock against other parts.
- Do not leave the robot exposed to direct sunlight while in storage.
- Observe and comply with the permissible temperature ranges for storage.
- Select a storage location in which the packaging materials cannot be damaged.

Procedure

1. Remove tools and equipment.
2. Remove the robot.
3. Clean and dry the robot. No dirt or cleaning agent residue may remain on or in the robot.
4. Perform a visual inspection of the robot.
5. Remove any foreign bodies.
6. Remove any corrosion.
7. Attach all covers to the robot and check that the seals are correctly in place.
8. Seal off electrical connections with suitable covers.
9. Seal hose connections by suitable means.
10. Cover the robot with plastic film and seal it at the base frame against dust.
If necessary, add a desiccant beneath the sheeting.

11.5 Disposal

When the manipulator reaches the end of its useful life, it can be removed from the system and dismantled, and the materials can be disposed of properly by type.

The following table provides an overview of the materials used in the manipulator. All plastic components are marked with a material designation and must be disposed of accordingly.

Material	Subassembly, component	Additional information
Metals		
Cast aluminum	Rotating column, arm, link arm, wrist, base frame	
Copper	Cables, wires	
Steel	Gear units, screws, washers	
Electrical components		
	Electronic components, such as RDC, EDS, etc.	Dispose of as electrical scrap without disassembling
	Motors	Dispose of motors without dismantling.
Plastics		
FKM	Seals	
Plastic	Panels, covers	
NBR	Shaft seals, O-rings	
PU	Hoses	
PUR	Cable sheaths	
Auxiliary substances and consumables		
Lubricating grease	Cabling	Optitemp RB 2
Lubricant for Harmonic Drive gear units	Gear units	Flexolub®-A1

Up-to-date safety data sheets must be requested from the manufacturers of auxiliary and operating materials ([>>> 12.3 "Auxiliary and operating materials used"](#) Page 232).

12 Appendix

12.1 Tightening torques

Tightening torques

The following tightening torques (Nm) are valid for screws and nuts where no other specifications are given.

The specified values apply to lightly oiled black (e.g. phosphated) and coated (e.g. mech. galv., zinc flake plating) screws and nuts.

Thread	Strength class		
	8.8	10.9	12.9
M1.6	0.17 Nm	0.24 Nm	0.28 Nm
	0.35 Nm	0.48 Nm	0.56 Nm
M2.5	0.68 Nm	0.93 Nm	1.10 Nm
M3	1.2 Nm	1.6 Nm	2.0 Nm
M4	2.8 Nm	3.8 Nm	4.4 Nm
M5	5.6 Nm	7.5 Nm	9.0 Nm
M6	9.5 Nm	12.5 Nm	15.0 Nm
M8	23.0 Nm	31.0 Nm	36.0 Nm
M10	45.0 Nm	60.0 Nm	70.0 Nm
M12	78.0 Nm	104.0 Nm	125.0 Nm
M14	125.0 Nm	165.0 Nm	195.0 Nm
M16	195.0 Nm	250.0 Nm	305.0 Nm
M20	370.0 Nm	500.0 Nm	600.0 Nm
M24	640.0 Nm	860.0 Nm	1030.0 Nm
M30	1330.0 Nm	1700.0 Nm	2000.0 Nm

Thread	Strength class	
	8.8 ISO7991 Allen screw	10.9 ISO7380, ISO07381 Fillister head screw
M3	0.8 Nm	0.8 Nm
M4	1.9 Nm	1.9 Nm
M5	3.8 Nm	3.8 Nm

Thread	Strength class	
	10.9 DIN7984 pan head screws	
M4	2.8 Nm	

Tighten M5 domed cap nuts with a torque of 4.2 Nm.

12.2 Tightening torque for stainless steel screws

Tightening torques for stainless steel screws

The tightening torques (Nm) specified here are valid for stainless steel screws and nuts where no other specifications are given.

The specified values are valid for lightly oiled screws and nuts.

Screw size	Stainless steel A4-80	Stainless steel A2-70 and A4- 70	Stainless steel A2-50
M3	1.0	0.8	0.4
M4	2.4	1.9	0.9
M5	4.8	3.8	1.9
M6	8.0	6.4	3.1
M8	19.5	15.5	7.5
M10	38.5	30.5	15.0
M12	66.0	52.0	25.5
M14	106.0	84.0	41.0
M16	165.0	130.0	64.0
M20	320.0	253.0	125.0
M24	557.0	441.0	217.0
M30	1107.0	876.0	--

12.3 Auxiliary and operating materials used

Product designation	Use	Manufacturer designation/Address
Optitemp RB 2	Lubricating grease	Deutsche BP Aktiengesellschaft - Industrial Lubricants & Services Erkelenzer Straße 20 D-41179 Mönchengladbach Germany
Flexolub®-A1	Lubricant for Harmonic Drive gear units	Harmonic Drive AG Hoembergstrasse 14 D-65555 Limburg a. d. Lahn Germany



To ensure safe use of our products, we recommend regularly requesting up-to-date safety data sheets from the manufacturers of auxiliary and operating materials.

13 KUKA Service

13.1 Requesting support

Introduction This documentation provides information on operation and operator control, and provides assistance with troubleshooting. For further assistance, please contact your local KUKA subsidiary.

Information **The following information is required for processing a support request:**

- Description of the problem, including information about the duration and frequency of the fault
- As comprehensive information as possible about the hardware and software components of the overall system

The following list gives an indication of the information which is relevant in many cases:

- Model and serial number of the kinematic system, e.g. the manipulator
- Model and serial number of the controller
- Model and serial number of the energy supply system
- Designation and version of the system software
- Designations and versions of other software components or modifications
- Diagnostic package KRCDiag
 - Additionally for KUKA Sunrise: Existing projects including applications
 - For versions of KUKA System Software older than V8: Archive of the software (KRCDiag is not yet available here.)
- Application used
- External axes used

13.2 KUKA Customer Support

Availability KUKA Customer Support is available in many countries. Please do not hesitate to contact us if you have any questions.

Argentina Ruben Costantini S.A. (Agency)
Luis Angel Huergo 13 20
Parque Industrial
2400 San Francisco (CBA)
Argentina
Tel. +54 3564 421033
Fax +54 3564 428877
ventas@costantini-sa.com

Australia KUKA Robotics Australia Pty Ltd
45 Fennell Street
Port Melbourne VIC 3207
Australia
Tel. +61 3 9939 9656
info@kuka-robotics.com.au
www.kuka-robotics.com.au

Belgium	KUKA Automatisering + Robots N.V. Centrum Zuid 1031 3530 Houthalen Belgium Tel. +32 11 516160 Fax +32 11 526794 info@kuka.be www.kuka.be
Brazil	KUKA Roboter do Brasil Ltda. Travessa Claudio Armando, nº 171 Bloco 5 - Galpões 51/52 Bairro Assunção CEP 09861-7630 São Bernardo do Campo - SP Brazil Tel. +55 11 4942-8299 Fax +55 11 2201-7883 info@kuka-roboter.com.br www.kuka-roboter.com.br
Chile	Robotec S.A. (Agency) Santiago de Chile Chile Tel. +56 2 331-5951 Fax +56 2 331-5952 robotec@robotec.cl www.robotec.cl
China	KUKA Robotics China Co., Ltd. No. 889 Kungang Road Xiaokunshan Town Songjiang District 201614 Shanghai P. R. China Tel. +86 21 5707 2688 Fax +86 21 5707 2603 info@kuka-robotics.cn www.kuka-robotics.com
Germany	KUKA Deutschland GmbH Zugspitzstr. 140 86165 Augsburg Germany Tel. +49 821 797-1926 Fax +49 821 797-41 1926 Hotline.robotics.de@kuka.com www.kuka.com

France	KUKA Automatisme + Robotique SAS Techvallée 6, Avenue du Parc 91140 Villebon S/Yvette France Tel. +33 1 6931660-0 Fax +33 1 6931660-1 commercial@kuka.fr www.kuka.fr
India	KUKA Robotics India Pvt. Ltd. Office Number-7, German Centre, Level 12, Building No. - 9B DLF Cyber City Phase III 122 002 Gurgaon Haryana India Tel. +91 124 4635774 Fax +91 124 4635773 info@kuka.in www.kuka.in
Italy	KUKA Roboter Italia S.p.A. Via Pavia 9/a - int.6 10098 Rivoli (TO) Italy Tel. +39 011 959-5013 Fax +39 011 959-5141 kuka@kuka.it www.kuka.it
Japan	KUKA Japan K.K. YBP Technical Center 134 Godo-cho, Hodogaya-ku Yokohama, Kanagawa 240 0005 Japan Tel. +81 45 744 7531 Fax +81 45 744 7541 info@kuka.co.jp
Canada	KUKA Robotics Canada Ltd. 6710 Maritz Drive - Unit 4 Mississauga L5W 0A1 Ontario Canada Tel. +1 905 670-8600 Fax +1 905 670-8604 info@kukarobotics.com www.kuka-robotics.com/canada

Korea	KUKA Robotics Korea Co. Ltd. RIT Center 306, Gyeonggi Technopark 1271-11 Sa 3-dong, Sangnok-gu Ansan City, Gyeonggi Do 426-901 Korea Tel. +82 31 501-1451 Fax +82 31 501-1461 info@kukakorea.com
Malaysia	KUKA Robot Automation (M) Sdn Bhd South East Asia Regional Office No. 7, Jalan TPP 6/6 Taman Perindustrian Puchong 47100 Puchong Selangor Malaysia Tel. +60 (03) 8063-1792 Fax +60 (03) 8060-7386 info@kuka.com.my
Mexico	KUKA de México S. de R.L. de C.V. Progreso #8 Col. Centro Industrial Puente de Vigas Tlalnepantla de Baz 54020 Estado de México Mexico Tel. +52 55 5203-8407 Fax +52 55 5203-8148 info@kuka.com.mx www.kuka-robotics.com/mexico
Norway	KUKA Sveiseanlegg + Roboter Sentrumsvegen 5 2867 Hov Norway Tel. +47 61 18 91 30 Fax +47 61 18 62 00 info@kuka.no
Austria	KUKA Roboter CEE GmbH Gruberstraße 2-4 4020 Linz Austria Tel. +43 7 32 78 47 52 Fax +43 7 32 79 38 80 office@kuka-roboter.at www.kuka.at

Poland	KUKA Roboter CEE GmbH Poland Spółka z ograniczoną odpowiedzialnością Oddział w Polsce Ul. Porcelanowa 10 40-246 Katowice Poland Tel. +48 327 30 32 13 or -14 Fax +48 327 30 32 26 ServicePL@kuka-roboter.de
Portugal	KUKA Robots IBÉRICA, S.A. Rua do Alto da Guerra n° 50 Armazém 04 2910 011 Setúbal Portugal Tel. +351 265 729 780 Fax +351 265 729 782 info.portugal@kukapt.com www.kuka.com
Russia	KUKA Russia OOO 1-y Nagatinskiy pr-d, 2 117105 Moskau Russia Tel. +7 495 665-6241 support.robotics.ru@kuka.com
Sweden	KUKA Svetsanläggningar + Robotar AB A. Odhnars gata 15 421 30 Västra Frölunda Sweden Tel. +46 31 7266-200 Fax +46 31 7266-201 info@kuka.se
Switzerland	KUKA Roboter Schweiz AG Industriestr. 9 5432 Neuenhof Switzerland Tel. +41 44 74490-90 Fax +41 44 74490-91 info@kuka-roboter.ch www.kuka-roboter.ch
Slovakia	KUKA Roboter CEE GmbH organizačná zložka Bojnická 3 831 04 Bratislava Slovakia Tel. +420 226 212 273 support.robotics.cz@kuka.com

Spain	KUKA Iberia, S.A.U. Pol. Industrial Torrent de la Pastera Carrer del Bages s/n 08800 Vilanova i la Geltrú (Barcelona) Spain Tel. +34 93 8142-353 comercial@kukarob.es
South Africa	Jendamark Automation LTD (Agency) 76a York Road North End 6000 Port Elizabeth South Africa Tel. +27 41 391 4700 Fax +27 41 373 3869 www.jendamark.co.za
Taiwan	KUKA Automation Taiwan Co. Ltd. 1F, No. 298 Yangguang ST., Nei Hu Dist., Taipei City, Taiwan 114 Taiwan Tel. +886 2 8978 1188 Fax +886 2 8797 5118 info@kuka.com.tw
Thailand	KUKA (Thailand) Co. Ltd. No 22/11-12 H-Cape Biz Sector Onnut Sukhaphiban 2 road, Prawet Bangkok 10250 Thailand Tel. +66 (0) 90-940-8950 HelpdeskTH@kuka.com
Czech Republic	KUKA Roboter CEE GmbH organizační složka Pražská 239 25066 Zdiby Czech Republic Tel. +420 226 212 273 support.robotics.cz@kuka.com
Hungary	KUKA Robotics Hungaria Kft. Fö út 140 2335 Taksony Hungary Tel. +36 24 501609 Fax +36 24 477031 info@kuka-robotics.hu

USA

KUKA Robotics Corporation
51870 Shelby Parkway
Shelby Township
48315-1787
Michigan
USA
Tel. +1 866 873-5852
Fax +1 866 329-5852
info@kukarobotics.com
www.kukarobotics.com

UK

KUKA Robotics UK Ltd
Great Western Street
Wednesbury West Midlands
WS10 7LL
UK
Tel. +44 121 505 9970
Fax +44 121 505 6589
service@kuka-robotics.co.uk
www.kuka-robotics.co.uk

Index

Symbols

-A1 232
® 232

Numbers

2006/42/EU2006 166
2014/68/EU2014 166
95/16/EC 166

A

Accessories 11, 155
Angle of rotation 117
ANSI/RIA R.15.06-2012 166
Appendix 231
Applied norms and regulations 166
Automatic mode 164
Auxiliary materials used 232
Axis data, KR 10 R1100 sixx C-CR 104
Axis data, KR 10 R1100 sixx CR 88
Axis data, KR 10 R1100 sixx W-CR 96
Axis data, KR 6 R700 sixx C-CR 34
Axis data, KR 6 R700 sixx CR 19
Axis data, KR 6 R700 sixx W-CR 27
Axis data, KR 10 R900 sixx C-CR 81
Axis data, KR 10 R900 sixx CR 65
Axis data, KR 10 R900 sixx W-CR 73
Axis data, KR 6 R900 sixx C-CR 58
Axis data, KR 6 R900 sixx CR 42
Axis data, KR 6 R900 sixx W-CR 50
Axis limitation, mechanical 159
Axis range 157

B

Basic data, KR 10 R1100 sixx C-CR 102
Basic data, KR 10 R1100 sixx CR 87
Basic data, KR 10 R1100 sixx W-CR 95
Basic data, KR 6 R700 sixx C-CR 33
Basic data, KR 6 R700 sixx CR 18
Basic data, KR 6 R700 sixx W-CR 26
Basic data, KR 10 R900 sixx C-CR 79
Basic data, KR 10 R900 sixx CR 64
Basic data, KR 10 R900 sixx W-CR 72
Basic data, KR 6 R900 sixx C-CR 56
Basic data, KR 6 R900 sixx CR 40
Basic data, KR 6 R900 sixx W-CR 49
Brake defect 161
Brake release device 160
Braking distance 157

C

CE mark 156
Ceiling-mounted robot, installing 195
Changing, toothed belts 213
Checking the screws, in-line wrist torque bridge 211
Checking the screws, side section of link arm 210
Cleaning the robot 214

Cleaning work 165
Connecting cable, standard 200
Connecting cables 11, 18, 26, 34, 41, 49, 57, 65, 72, 80, 88, 95, 103, 155, 173, 199
Counterbalancing system 165
Cover A2, greasingCover A3, greasing 211
CR 7
Customer interfaces 175

D

Danger zone 157
Declaration of conformity 156
Declaration of incorporation 155, 156
Decommissioning 166, 221
Decommissioning, ceiling-mounted robot 225
Decommissioning, floor-mounted robot 221
Decommissioning, wall-mounted robot 222
Description, manipulator 12
Disposal 166, 221
Documentation, industrial robot 7

E

EC declaration of conformity 156
Electromagnetic compatibility (EMC) 167
EMC Directive 156
EN 60204-12006/A12009 167
EN 61000-6-22005 167
EN 61000-6-42007 + A12011 167
EN 614-12006+A12009 167
EN ISO 10218-12011 166
EN ISO 121002010 166
EN ISO 13849-12015 166
EN ISO 13849-22012 166
EN ISO 138502015 166
Exchanging, toothed belts 213
Extension 117
External axes 155, 157

F

Faults 162
Flexolub 232
Floor-mounted robot, installing 188
Function test 163

G

General information 116
General safety measures 161

H

Handling equipment 184
Hazardous substances 166

I

In-line wrist 23, 31, 38, 46, 54, 62, 69, 77, 85, 92, 100, 108
Industrial robot 155
Intended use 156
Interface A1 174

Interfaces 173

Introduction 7

K

KCP 117, 157, 161

Keyboard, external 161

KL 7

KUKA Customer Support 233

KUKA Service 233

KUKA smartPAD 157

L

Labeling 160

Liability 155

Linear unit 155

Loads acting on the foundation, KR 10 R1100
sixx C-CR 109

Loads acting on the foundation, KR 10 R1100
sixx CR 93

Loads acting on the foundation, KR 6 R700 sixx
C-CR 39

Loads acting on the foundation, KR 6 R700 sixx
CR 24

Loads acting on the foundation, KR 6 R700 sixx
W-CR 32

Loads acting on the foundation, KR 10 R1100
W-CR 101

Loads acting on the foundation,
KR 10 R900 sixx C-CR 86

Loads acting on the foundation,
KR 10 R900 sixx CR 70

Loads acting on the foundation,
KR 10 R900 sixx W-CR 78

Loads acting on the foundation,
KR 6 R900 sixx C-CR 63

Loads acting on the foundation,
KR 6 R900 sixx CR 47

Loads acting on the foundation,
KR 6 R900 sixx W-CR 55

Low Voltage Directive 156

Lubricants 207

Lubrication work 207

M

Machine frame mounting 172

Machine frame mounting, installing 188

Machinery Directive 156, 166

main axes 116

Maintenance 164, 207

Maintenance intervals 207

Maintenance overview 207

Maintenance symbols 207

Maintenance table 207

Manipulator 11, 155, 157

Manual mode 163

Material designation 229

Mechanical end stops 159

MEMD 7

Mounting base 169

Mounting base with centering 169

Mounting base, installing 187

Mouse, external 161

Moving the robot, without drive energy 205

O

Operating materials used 232

Operator 157

Operators 158

Options 11, 155

Optitemp RB 2 232

Overload 161

Overview of the robot system 11

P

Payload diagram 22, 30, 38, 46, 54, 62, 69, 77,
85, 92, 100, 108

Payloads, KR 10 R1100 sixx C-CR 106

Payloads, KR 10 R1100 sixx CR 91

Payloads, KR 10 R1100 sixx W-CR 99

Payloads, KR 6 R700 sixx C-CR 37

Payloads, KR 6 R700 sixx CR 21

Payloads, KR 6 R700 sixx W-CR 29

Payloads, KR 10 R900 sixx C-CR 83

Payloads, KR 10 R900 sixx CR 68

Payloads, KR 10 R900 sixx W-CR 76

Payloads, KR 6 R900 sixx C-CR 60

Payloads, KR 6 R900 sixx CR 44

Payloads, KR 6 R900 sixx W-CR 53

Personnel 158

Planning 169

Plant integrator 157

Plates and labels 114

Positioner 155

Pressure Equipment Directive 165, 166

Preventive maintenance work 165

Product description 11

Program override, motion velocity 117

Protective equipment, overview 159

Purpose 9

R

RDC 8

Reaction distance 157

Recommissioning 162, 187

Release device 160

Repair 164, 217

Robot controller 11, 155

S

Safety 155

Safety instructions 7

Safety of machinery 166, 167

Safety options 157

Safety zone 157, 159

Safety, general 155

Service life 157

smartPAD 8, 11, 117, 157, 161

Software 11, 155

Start-up 162, 187

STOP 0 116, 157

STOP 1 116, 157

STOP 2 157

- Stop category 0 157
 Stop category 1 157
 Stop category 2 157
 Stop signal 116
 Stopping distance 116, 157
 Stopping distances 116
 Stopping distances, KR 10 R1100 sixx C-CR 141
 Stopping distances, KR 10 R1100 sixx CR 141
 Stopping distances, KR 10 R1100 sixx W-CR 147
 Stopping distances, KR 6 R700 sixx C-CR 118
 Stopping distances, KR 6 R700 sixx CR 118
 Stopping distances, KR 6 R700 sixx W-CR 123
 Stopping distances, KR 10 R900 sixx C-CR 141
 Stopping distances, KR 10 R900 sixx CR 141
 Stopping distances, KR 10 R900 sixx W-CR 147
 Stopping distances, KR 6 R900 sixx C-CR 129
 Stopping distances, KR 6 R900 sixx CR 129
 Stopping distances, KR 6 R900 sixx W-CR 135
 Stopping time 116
 Stopping times 116
 Stopping times, KR 10 R1100 sixx C-CR 141
 Stopping times, KR 10 R1100 sixx CR 141
 Stopping times, KR 10 R1100 sixx W-CR 147
 Stopping times, KR 6 R700 sixx C-CR 118
 Stopping times, KR 6 R700 sixx CR 118
 Stopping times, KR 6 R700 sixx W-CR 123
 Stopping times, KR 10 R900 sixx C-CR 141
 Stopping times, KR 10 R900 sixx CR 141
 Stopping times, KR 10 R900 sixx W-CR 147
 Stopping times, KR 6 R900 sixx C-CR 129
 Stopping times, KR 6 R900 sixx CR 129
 Stopping times, KR 6 R900 sixx W-CR 135
 Storage 166, 221
 Supplementary load 110
 Supplementary load, R1100 113
 Supplementary load, R700 111
 Supplementary load, R900 112
 Support request 233
 System integrator 156, 157, 158

T

- T1 157
 T2 157
 Teach pendant 11, 155
 Technical data 15
 Technical data, KR 10 R1100 sixx C-CR 102
 Technical data, KR 10 R1100 sixx CR 87
 Technical data, KR 10 R1100 sixx W-CR 95
 Technical data, KR 6 R700 sixx C-CR 33
 Technical data, KR 6 R700 sixx CR 18
 Technical data, KR 6 R700 sixx W-CR 26
 Technical data, KR 10 R900 sixx C-CR 79
 Technical data, KR 10 R900 sixx CR 64
 Technical data, KR 10 R900 sixx W-CR 72
 Technical data, KR 6 R900 sixx C-CR 56
 Technical data, KR 6 R900 sixx CR 40
 Technical data, KR 6 R900 sixx W-CR 49
 Terms used 7, 117
 Terms, safety 157
 Tightening torques 231

- Tightening torques, stainless steel screws 231
 Toothed belt tension, adjustment 217
 Toothed belt tension, measurement 217
 Toothed belts, exchanging 213
 Training 9
 Transport position 181
 Transportation 162, 181
 Turn-tilt table 155

U

- Use, contrary to intended use 155
 Use, improper 155
 User 157, 158
 Users 9

W

- Wall-mounted robot, installing 190
 Warnings 7
 Working envelope 20, 28, 35, 43, 51, 59, 66, 74, 82, 89, 97, 105
 Workspace 157, 159

