

```
yarp::dev::ImplementCanBuffer  
Factory< FakeCanMessage,  
FCMSG >
```

```
ICanBus
```

```
yarp::dev::DeviceDriver
```

```
yarp::dev::FakeCan
```

```
classDiagram
    class yarp_dev_FakeCan["yarp::dev::FakeCan"]
    class yarp_dev_DeviceDriver["yarp::dev::DeviceDriver"]
    class yarp_dev_ImplementCanBufferFactory["yarp::dev::ImplementCanBufferFactory< FakeCanMessage, FCMSG >"]
    class ICanBus
    yarp_dev_FakeCan --|> yarp_dev_DeviceDriver
    yarp_dev_FakeCan --|> yarp_dev_ImplementCanBufferFactory
    yarp_dev_FakeCan --|> ICanBus
```

The diagram illustrates the relationships between several classes in the yarp::dev namespace. A central class, `yarp::dev::FakeCan`, is shown with a grey background. It has three blue arrows pointing to it from other classes: `yarp::dev::DeviceDriver` (bottom left), `yarp::dev::ImplementCanBufferFactory< FakeCanMessage, FCMSG >` (top left), and `ICanBus` (middle left). This indicates that `yarp::dev::FakeCan` inherits from or implements these three interfaces or base classes.