```
❯   kubectl apply -f ratelimiting/0-memquota.yaml
memquota "handler" created

~/projects/istio-demo ( master ✓ )
❯   kubectl apply -f ratelimiting/1-quota.yaml
quota "requestcount" created

~/projects/istio-demo ( master ✓ )
❯   kubectl apply -f ratelimiting/2-quotaspec.yaml █
```

```
›  kubectl apply -f ratelimiting/0-memquota.yaml
memquota "handler" created

~/projects/istio-demo ( master ✓ )
›  kubectl apply -f ratelimiting/1-quota.yaml
quota "requestcount" created

~/projects/istio-demo ( master ✓ )
›  kubectl apply -f ratelimiting/2-quotaspec.yaml █
```

```
❯  kubectl apply -f ratelimiting/0-memquota.yaml
memquota "handler" created

~/projects/istio-demo ( master ✓ )
❯  kubectl apply -f ratelimiting/1-quota.yaml
quota "requestcount" created

~/projects/istio-demo ( master ✓ )
❯  kubectl apply -f ratelimiting/2-quotaspec.yaml █
```

```yaml
apiVersion: config.istio.io/v1alpha2
kind: QuotaSpecBinding
metadata:
  name: request-count
  namespace: istio-system
spec:
  quotaSpecs:
  - name: request-count
    namespace: istio-system
  services:
  - name: productpage
    namespace: default
```