```
❯ kubectl get pod -n istio-system -l app=jaeger
NAME                            READY    STATUS     RESTARTS   AGE
istio-tracing-ff94688bb-7pnrs   1/1      Running    0          1h

~/projects/istio-demo ( master ✓ )
❯ kubectl port-forward -n istio-system istio-tracing-ff94688bb-7pnrs 16686
:16686
```

```
>  kubectl get pod -n istio-system -l app=jaeger
NAME                           READY     STATUS    RESTARTS   AGE
istio-tracing-ff94688bb-7pnrs  1/1       Running   0          1h

~/projects/istio-demo ( master ✓ )
>  kubectl port-forward -n istio-system istio-tracing-ff94688bb-7pnrs 16686
:16686█
```

```
> kubectl get pod -n istio-system -l app=jaeger
NAME                            READY      STATUS     RESTARTS    AGE
istio-tracing-ff94688bb-7pnrs   1/1        Running    0           1h

~/projects/istio-demo ( master ✓ )
> kubectl port-forward -n istio-system istio-tracing-ff94688bb-7pnrs 16686
:16686
```

```
❯   kubectl get pod -n istio-system -l app=jaeger
NAME                            READY       STATUS      RESTARTS    AGE
istio-tracing-ff94688bb-7pnrs   1/1         Running     0           1h

~/projects/istio-demo ( master ✓ )
❯   kubectl port-forward -n istio-system istio-tracing-ff94688bb-7pnrs 16686
:16686
Forwarding from 127.0.0.1:16686 -> 16686
Handling connection for 16686
Handling connection for 16686

```