




This is CS50x

OpenCourseWare

Donate  (<https://cs50.harvard.edu/donate>)



David J. Malan (<https://cs.harvard.edu/malan/>)


malan@harvard.edu

 (<https://www.facebook.com/dmalan>)  (<https://github.com/dmalan>) 

(<https://www.instagram.com/davidjmalan/>)  (<https://www.linkedin.com/in/malan/>) 

(<https://orcid.org/0000-0001-5338-2522>)  ([https://www.quora.com/profile/David-J-](https://www.quora.com/profile/David-J-Malan)

Malan)  (<https://www.reddit.com/user/davidjmalan>) 

(<https://www.tiktok.com/@davidjmalan>)  (<https://twitter.com/davidjmalan>)

Plurality

For this program, you'll implement a program that runs a plurality election, per the below.

```
$ ./plurality Alice Bob Charlie
Number of voters: 4
Vote: Alice
Vote: Bob
Vote: Charlie
Vote: Alice
Alice
```

Background

Elections come in all shapes and sizes. In the UK, the [Prime Minister](https://www.parliament.uk/education/about-your-parliament/general-elections/) (<https://www.parliament.uk/education/about-your-parliament/general-elections/>) is officially appointed by the monarch, who generally chooses the leader of the political party that wins the most seats in the House of Commons. The United States uses a multi-step [Electoral College](#)

(<https://www.archives.gov/federal-register/electoral-college/about.html>) process where citizens vote on how each state should allocate Electors who then elect the President.

Perhaps the simplest way to hold an election, though, is via a method commonly known as the “plurality vote” (also known as “first-past-the-post” or “winner take all”). In the plurality vote, every voter gets to vote for one candidate. At the end of the election, whichever candidate has the greatest number of votes is declared the winner of the election.

Getting Started

Log into code.cs50.io (<https://code.cs50.io/>), click on your terminal window, and execute `cd` by itself. You should find that your terminal window’s prompt resembles the below:

```
$
```

Next execute

```
wget https://cdn.cs50.net/2021/fall/psets/3/plurality.zip
```

in order to download a ZIP called `plurality.zip` into your codespace.

Then execute

```
unzip plurality.zip
```

to create a folder called `plurality`. You no longer need the ZIP file, so you can execute

```
rm plurality.zip
```

and respond with “y” followed by Enter at the prompt to remove the ZIP file you downloaded.

Now type

```
cd plurality
```

followed by Enter to move yourself into (i.e., open) that directory. Your prompt should now resemble the below.

```
plurality/ $
```

If all was successful, you should execute

```
ls
```

and see a file named `plurality.c`. Executing `code plurality.c` should open the file where you will type your code for this problem set. If not, retrace your steps and see if you can determine where you went wrong!

Understanding

Let's take a look at `plurality.c` and read through the distribution code that's been provided to you.

The line `#define MAX 9` is some syntax used here to mean that `MAX` is a constant (equal to `9`) that can be used throughout the program. Here, it represents the maximum number of candidates an election can have.

The file then defines a `struct` called a `candidate`. Each `candidate` has two fields: a `string` called `name` representing the candidate's name, and an `int` called `votes` representing the number of votes the candidate has. Next, the file defines a global array of `candidates`, where each element is itself a `candidate`.

Now, take a look at the `main` function itself. See if you can find where the program sets a global variable `candidate_count` representing the number of candidates in the election, copies command-line arguments into the array `candidates`, and asks the user to type in the number of voters. Then, the program lets every voter type in a vote (see how?), calling the `vote` function on each candidate voted for. Finally, `main` makes a call to the `print_winner` function to print out the winner (or winners) of the election.

If you look further down in the file, though, you'll notice that the `vote` and `print_winner` functions have been left blank. This part is up to you to complete!

Specification

Complete the implementation of `plurality.c` in such a way that the program simulates a plurality vote election.

- Complete the `vote` function.
 - `vote` takes a single argument, a `string` called `name`, representing the name of the candidate who was voted for.
 - If `name` matches one of the names of the candidates in the election, then update that candidate's vote total to account for the new vote. The `vote` function in this case

should return `true` to indicate a successful ballot.

- If `name` does not match the name of any of the candidates in the election, no vote totals should change, and the `vote` function should return `false` to indicate an invalid ballot.
- You may assume that no two candidates will have the same name.
- Complete the `print_winner` function.
 - The function should print out the name of the candidate who received the most votes in the election, and then print a newline.
 - It is possible that the election could end in a tie if multiple candidates each have the maximum number of votes. In that case, you should output the names of each of the winning candidates, each on a separate line.

You should not modify anything else in `plurality.c` other than the implementations of the `vote` and `print_winner` functions (and the inclusion of additional header files, if you'd like).

Usage

Your program should behave per the examples below.

```
$ ./plurality Alice Bob
Number of voters: 3
Vote: Alice
Vote: Bob
Vote: Alice
Alice
```

```
$ ./plurality Alice Bob
Number of voters: 3
Vote: Alice
Vote: Charlie
Invalid vote.
Vote: Alice
Alice
```

```
$ ./plurality Alice Bob Charlie
Number of voters: 5
Vote: Alice
Vote: Charlie
Vote: Bob
Vote: Bob
Vote: Alice
```

Alice
Bob

Walkthrough



Testing

Be sure to test your code to make sure it handles...

- An election with any number of candidate (up to the `MAX` of `9`)
- Voting for a candidate by name
- Invalid votes for candidates who are not on the ballot
- Printing the winner of the election if there is only one
- Printing the winner of the election if there are multiple winners

Execute the below to evaluate the correctness of your code using `check50`. But be sure to compile and test it yourself as well!

```
check50 cs50/problems/2022/x/plurality
```

Execute the below to evaluate the style of your code using `style50`.

```
style50 plurality.c
```

How to Submit

In your terminal, execute the below to submit your work.

```
submit50 cs50/problems/2022/x/plurality
```