

# aurel: A Python package for automatic relativistic calculations

Robyn L. Munoz<sup>1</sup>, Christian T. Byrnes<sup>1</sup>, and Will J. Roper<sup>1</sup>

<sup>1</sup> Department of Physics and Astronomy, University of Sussex, Brighton, BN1 9QH, United Kingdom

DOI: [10.xxxxxx/draft](https://doi.org/10.xxxxxx/draft)

## Software

- [Review](#)
- [Repository](#)
- [Archive](#)

Editor: [Open Journals](#)

## Reviewers:

- [@openjournals](#)

Submitted: 01 January 1970

Published: unpublished

## License

Authors of papers retain copyright and release the work under a Creative Commons Attribution 4.0 International License ([CC BY 4.0](#)).

## Summary

aurel is an open-source Python package designed to automatically calculate relativistic quantities. It uses an efficient, flexible and user-friendly caching and dependency-tracking system, ideal for managing the highly nonlinear nature of general relativity. The package supports both symbolic and numerical calculations. The symbolic part extends SymPy with additional tensorial calculations. The numerical part computes a wide range of tensorial quantities, such as curvature, matter kinematics and much more, directly from any spacetime and matter data arrays using finite-difference methods. Inputs can be either generated from analytical expressions or imported from Numerical Relativity (NR) simulations. For users of Einstein Toolkit, aurel also provides utilities to load 3D data generated with Carpet. Given the increasing use of NR, aurel offers a timely post-processing tool to support the popularisation of this field.

## Statement of need

General relativity describes matter as moving according to how distances shrink or expand; likewise, the intervals of space and time evolve depending on the distribution of matter. Handling this dynamic “mesh” of distances and times requires elaborate tensor algebra that, in some cases, can only be managed with symbolic or numerical tools. Naturally, NR has become essential for modern astrophysics, cosmology, and gravitational physics, most notably in the modelling of gravitational-wave signals.

While established computational frameworks focus on solving and evolving Einstein’s field equations, with specific key diagnostics, they leave calculations of the remaining analysis to the discretion of the researchers. Newcomers to the field then face a substantial overhead until they develop their own personal post-processing codes. Established researchers also face the tedious task of handling intermediary variables and indices when calculating new quantities. The field then suffers from this error-prone, time-consuming process and would benefit from an accessible, open-source, standardised framework to automate these steps.

We therefore present aurel, an open-source Python package designed to streamline relativistic calculations. It is hosted on [GitHub](#) and is available on [PyPI](#). The documentation is available through [GitHub Pages](#).

## State of the field

When looking for general relativity Python packages, there are a number of tools that provide symbolic calculations ([Bapat et al., 2020](#); [Czaja, n.d.](#); [Della Monica, 2025](#); [Gourgoulhon et al., 2015](#); [Hackstein & Hackmann, 2025](#); [Martín & Sureda, 2022](#); [Shoshany, 2025](#); [Wittig & Grover, 2017](#)). Or, one may also consider computer algebra systems ([Maplesoft, 2025](#); [Martín-García](#)

39 & others, 2025; Wolfram Research, 2025). However, when non-linearities become too complex  
40 for symbolic packages, NR is used instead.

41 Einstein Toolkit (Löffler & others, 2012; Rizzo et al., 2025) is a large community-driven  
42 software whose tools enable the evolution of Einstein's field equations. Diagnostic and further  
43 analysis calculations are typically performed on the fly, during simulations. To study the  
44 outputs of such simulations, provided by Carpet, there are Python reading packages available  
45 (Bozzola, 2021; Ferguson et al., 2025; Kastaun, n.d.; Radice, n.d.). These extra calculations  
46 can slow down the simulation of the spacetime evolution, and if certain relativistic quantities  
47 are not available in Einstein Toolkit, or in one of the post-processing packages, then the  
48 user needs to code that up themselves.

49 There are a number of other well-established NR codes (Andrade et al., 2021; Barrera-Hinojosa  
50 & Li, 2020; Palenzuela et al., 2025; Wright, 2018; Zhang et al., 2025) that also have their  
51 own diagnostic tools. However, these are typically built-in, so going from one code to another,  
52 to benchmark or to use their different types of applications, requires learning the ecosystem of  
53 each.

54 To improve the community's versatility and limit the repeated implementation of error-prone  
55 calculations, there is a motivation to provide packages for computing relativistic quantities in  
56 an NR-code-agnostic way. Especially in the post-processing sense, where all calculations are  
57 done from a given NR spacetime and matter solution. A couple of notable packages (Grasso  
58 et al., 2021; Pook-Kolb et al., 2019) focus on ray tracing, or apparent-horizon finding, which  
59 are currently beyond the scope of aurel. While others have more overlap (Cranganore et al.,  
60 2025; Munoz & Bruni, 2023) in calculating curvature terms, they differ in scope and workflow.

61 Here, aurel innovates in its automatic design, which is easily extendable and provides flexibility  
62 and robustness with a large and ever-growing catalogue of relativistic quantities. A precursor  
63 to this package was EBWeyl (Munoz & Bruni, 2023), as it provided calculations of gravito-  
64 electromagnetic contributions from base spacetime and matter quantities. aurel now has  
65 a completely different structure (relying on the automatic dependency resolution), provides  
66 calculations of many more terms, over time, and has entirely new features as described in the  
67 following section.

## 68 Software Design

69 aurel provides an intuitive interface for the automatic calculation of general relativistic  
70 quantities, either symbolically (with AurelCoreSymbolic, built on SymPy (Meurer et al., 2017))  
71 or numerically (with AurelCore, which heavily utilises numpy.einsum (Harris et al., 2020) for  
72 efficient operations on array data structures).

73 Both require base quantities such as the spacetime coordinates or the parameters of the  
74 Cartesian numerical grid, as well as the spacetime and matter distributions (the Minkowski  
75 vacuum is otherwise assumed). These inputs can either come from analytical expressions, with  
76 a couple of built-in solutions available, or from output data from any NR simulations; they  
77 just need to be passed as numpy arrays.

78 Specifically, for simulations run with Carpet in the Einstein Toolkit, the reading module  
79 provides helper functions to load and organise the 3D data. These can read the parameter file,  
80 summarise available iterations and variables, and handle data separated across restarts, chunks,  
81 or refinement levels for normal Carpet data files or checkpoint files. To speed up repeated  
82 data reading, read\_data can also split the data per iteration, instead of per variable.

83 Then, once input data is provided, users can directly request a wide range of relativistic  
84 quantities, including: spacetime; matter (Eulerian, Lagrangian, or conserved); BSSNOK  
85 formulation; constraints; fluid covariant kinematics; null ray expansion; 3- and 4-dimensional  
86 curvature; gravito-electromagnetism; Weyl scalars and invariants (including gravitational waves).  
87 To see a full list of available quantities, see: [descriptions](#). Tools are also provided for spatial

88 and spacetime covariant derivatives and Lie derivatives. All spatial derivatives are computed by  
89 the `FiniteDifference` class that provides 2nd, 4th, 6th and 8th order schemes, using periodic,  
90 symmetric or one-sided boundary conditions.

## 91 Automatic Computational Pathway

92 The `aurel` automatic process composes a computational pathway at runtime to evaluate  
93 the requested quantities. This is implemented through a lazy-evaluation memoised property  
94 pattern, where each quantity is defined as a method of the core class that may depend on  
95 other quantities. This design has been chosen for its flexibility and accessibility while remaining  
96 robust under future extensions.

97 Quantities are requested via a user-friendly dictionary-style access, e.g. `rel["s_RicciS"]`,  
98 which triggers the lazy memoised check to see if this is already cached. If yes, then the result is  
99 directly returned. If not, then the corresponding method is called, which recursively triggers the  
100 calculation of dependencies (e.g. `rel["s_Ricci_down3"]`). This continues until the requested  
101 quantities can be calculated and so returned.

102 To avoid redundant computations, each result is cached, which builds up a cache memory that  
103 needs to be efficiently managed. So, inspired by Python's garbage collection, `aurel` uses an  
104 intelligent eviction policy that tracks memory footprint, evaluation counts, and last-access  
105 times. When the configurable thresholds are exceeded, the older and heavier cached quantities  
106 are removed, while safeguarding protected base quantities. Throughout this process, `aurel`  
107 keeps the user informed on progress by providing verbose updates on the computation and  
108 caching workflow.

## 109 Time dependence

110 All calculations within the `AurelCore` class are evaluated at a single fixed time, corresponding  
111 to one slice in time, so that individual time steps can be treated independently. For multiple  
112 time steps, an `AurelCore` object needs to be created and the requested quantities collected for  
113 each.

114 To streamline this process, `aurel` provides the `over_time` function to do exactly this, and  
115 also compute summary statistics over the grid domain (e.g., max/min) at each time step. By  
116 design, it is easily extensible, so `over_time` also accepts custom functions of new relativistic  
117 quantities and summary statistics. This makes `aurel` versatile, supporting an infinite number  
118 of ways to view a problem and develop diagnostic tools.

## 119 Research Impact Statement

120 `aurel` is a specialist tool for general relativity researchers and streamlines numerical relativists'  
121 post-processing workflow. Through conference interactions and collaborations involving the  
122 authors, this package has gradually been disseminated to individual researchers who appreciate  
123 the effortless integration, satisfying dependency resolution and substantial reduction to post-  
124 processing overhead. Indeed, in ongoing studies involving NR simulations of primordial  
125 black hole formation, `aurel` has increased capacity and redirected repetitive and error-prone  
126 development efforts towards exploring a broader range of simulated scenarios. Additionally, for  
127 master students, the straightforward and transparent design has provided an easy gateway for  
128 them to analyse NR simulations and so quickly get results within the duration of their projects.  
129 Going forward, awareness of this code will build upon publication, reaching a wider audience  
130 and supporting the popularisation of NR.

## 131 AI usage disclosure

132 GitHub Copilot Claude Sonnet 4 was used for the development and documentation of this  
 133 package. Autocompletion suggestions were accepted via the VSCode Copilot plugin, and upon  
 134 the developer's request, edits and code snippets were generated via the large language model's  
 135 user interface. The most significant AI contributions came in drafting the docstrings and  
 136 scaffolding the test suite, both of which are essential for the accessibility and robustness of this  
 137 package. Each and every suggestion or contribution was meticulously reviewed and adjusted  
 138 before being included by the authors, who made all core design decisions and innovated the  
 139 original structural concept. Finally, this paper was prepared without the use of generative  
 140 language models, solely with grammar checkers.

## 141 Acknowledgements

142 We thank Nat Kemp for being one of the first testers of aurel. We thank Ian Hawke for  
 143 support and suggestions.

144 RM and WR are supported by an STFC grant ST/X001040/1. CB is supported by STFC  
 145 grants ST/X001040/1 and ST/X000796/1.

146 Andrade, T., Salo, L. A., Aurrekoetxea, J. C., Bamber, J., Clough, K., Croft, R., Jong, E.  
 147 de, Drew, A., Duran, A., Ferreira, P. G., Figueras, P., Finkel, H., França, T., Ge, B.-X.,  
 148 Gu, C., Helfer, T., Jäykkä, J., Joana, C., Kunesch, M., ... Wong, K. (2021). GRChombo:  
 149 An adaptable numerical relativity code for fundamental physics. *Journal of Open Source*  
 150 *Software*, 6(68), 3703. <https://doi.org/10.21105/joss.03703>

151 Bapat, S., Saha, R., Bhatt, B., Jain, S., Jain, A., Vela, S. O., Khandelwal, P., Shivottam, J.,  
 152 Ma, J., Ng, G. S., Kerhalkar, P., Sarode, H. S., Sharma, R., Gupta, M., Gupta, D., Tyagi,  
 153 T., Rustagi, T., Singh, V., Bansal, S., ... Chan, M. Y. (2020). *EinsteinPy: A community*  
 154 *python package for general relativity*. <https://arxiv.org/abs/2005.11288>

155 Barrera-Hinojosa, C., & Li, B. (2020). GRAMES: A new route to general relativistic *N*-body  
 156 simulations in cosmology. Part i. Methodology and code description. *JCAP*, 01, 007.  
 157 <https://doi.org/10.1088/1475-7516/2020/01/007>

158 Bozzola, G. (2021). Kuibit: Analyzing einstein toolkit simulations with python. *Journal of*  
 159 *Open Source Software*, 6(60), 3099. <https://doi.org/10.21105/joss.03099>

160 Cranganore, S. S., Bodnar, A., Berzins, A., & Brandstetter, J. (2025). *Einstein fields: A neural*  
 161 *perspective to computational general relativity*. <https://arxiv.org/abs/2507.11589>

162 Czaja, W. (n.d.). *GraviPy, tensor calculus package for general relativity*. <https://pypi.python.org/pypi/GraviPy>

164 Della Monica, R. (2025). PyGRO: A python integrator for general relativistic orbits. *Astronomy*  
 165 *& Astrophysics*, 698, A193. <https://doi.org/10.1051/0004-6361/202554300>

166 Ferguson, D., Anne, S., Gracia-Linares, M., Iglesias, H., Jan, A., Martinez, E., Lu, L., Meoni, F.,  
 167 Nowicki, R., Trostel, M., Tsao, B.-J., & Valorz, F. (2025). *Mayawaves* (Version v2025.12).  
 168 Zenodo. <https://doi.org/10.5281/zenodo.17981058>

169 Gourgoulhon, E., Beijer, M., & Mancini, M. (2015). Tensor calculus with open-source  
 170 software: The SageManifolds project. *Journal of Physics: Conference Series*, 600(1),  
 171 012002. <https://doi.org/10.1088/1742-6596/600/1/012002>

172 Grasso, M., Villa, E., Korzyński, M., & Matarrese, S. (2021). Isolating nonlinearities of  
 173 light propagation in inhomogeneous cosmologies. *Phys. Rev. D*, 104(4), 043508. <https://doi.org/10.1103/PhysRevD.104.043508>

175 Hackstein, J. P., & Hackmann, E. (2025). GREOPy: A python package for solving the

- emitter-observer problem in general relativity. *Journal of Open Source Software*, 10(112), 8765. <https://doi.org/10.21105/joss.08765>
- Harris, C. R., Millman, K. J., Walt, S. J. van der, Gommers, R., Virtanen, P., Cournapeau, D., Wieser, E., Taylor, J., Berg, S., Smith, N. J., Kern, R., Picus, M., Hoyer, S., Kerkwijk, M. H. van, Brett, M., Haldane, A., Río, J. F. del, Wiebe, M., Peterson, P., ... Oliphant, T. E. (2020). Array programming with NumPy. *Nature*, 585(7825), 357–362. <https://doi.org/10.1038/s41586-020-2649-2>
- Kastaun, W. (n.d.). *PostCactus*. GitHub. <https://github.com/wokast/PyCactus>
- Löffler, F., & others. (2012). The einstein toolkit: A community computational infrastructure for relativistic astrophysics. *Class. Quant. Grav.*, 29, 115001. <https://doi.org/10.1088/0264-9381/29/11/115001>
- Maplesoft, a division of W. M. Inc. (2025). *Maple, version 2025.2*. <https://www.maplesoft.com/products/maple/>
- Martín, M. S., & Sureda, J. (2022). Pytearcats: PYthon TEnsor AlgeBRa calCulATor a python package for general relativity and tensor calculus. *Astronomy and Computing*, 100572. <https://doi.org/10.1016/j.ascom.2022.100572>
- Martín-García, J. M., & others. (2025). *xAct: Efficient tensor computer algebra for the wolfram language*. <https://www.xact.es/>
- Meurer, A., Smith, C. P., Paprocki, M., Čertík, O., Kirpichev, S. B., Rocklin, M., Kumar, A., Ivanov, S., Moore, J. K., Singh, S., Rathnayake, T., Vig, S., Granger, B. E., Muller, R. P., Bonazzi, F., Gupta, H., Vats, S., Johansson, F., Pedregosa, F., ... Scopatz, A. (2017). SymPy: Symbolic computing in Python. *PeerJ Computer Science*, 3, e103. <https://doi.org/10.7717/peerj-cs.103>
- Munoz, R. L., & Bruni, M. (2023). EBWeyl: A code to invariantly characterize numerical spacetimes. *Classical and Quantum Gravity*, 40(13), 135010. <https://doi.org/10.1088/1361-6382/acd6cf>
- Palenzuela, C., Bezares, M., Liebling, S., Schianchi, F., Abalos, J. F., Aguilera-Miret, R., Bona, C., Carretero, J. A., Massò, J., Smith, M. P., Amponsah, K., Kornet, K., Miñano, B., Pareek, S., & Radia, M. (2025). *MHDuet : A high-order general relativistic radiation MHD code for CPU and GPU architectures*. <https://arxiv.org/abs/2510.13965>
- Pook-Kolb, D., Birnholtz, O., Krishnan, B., & Schnetter, E. (2019). Existence and stability of marginally trapped surfaces in black-hole spacetimes. *Phys. Rev. D*, 99(6), 064005. <https://doi.org/10.1103/PhysRevD.99.064005>
- Radice, D. (n.d.). *Scidata*. Bitbucket. <https://bitbucket.org/dradice/scidata/src/master/>
- Rizzo, M., Haas, R., Brandt, S. R., Etienne, Z., Ferguson, D., Sanches, L. T., Tsao, B.-J., Werneck, L., Boyer, D., Bozzola, G., Cheng, C.-H., Cupp, S., Diener, P., Jacques, T. P., Ji, L., Macpherson, H., Markin, I., Schnetter, E., Tichy, W., ... Zink, B. (2025). *The einstein toolkit* (The "Martin D. Kruskal" release, ET\_2025\_05). Zenodo. <https://doi.org/10.5281/zenodo.15520463>
- Shoshany, B. (2025). OGREPy: An object-oriented general relativity package for python. *Journal of Open Research Software*, 13. <https://doi.org/10.5334/jors.558>
- Wittig, A. N., & Grover, J. (2017). *PyHole: General relativity ray tracing and analysis tool*. <https://eprints.soton.ac.uk/453123/>
- Wolfram Research, Inc. (2025). *Mathematica, version 14.3*. <https://www.wolfram.com/mathematica>
- Wright, A. (2018). *AlexJamesWright/METHOD: Initial public release* (Version 1.0). Zenodo. <https://doi.org/10.5281/zenodo.1404697>

- 223 Zhang, H., Li, B., Weinzierl, T., & Barrera-Hinojosa, C. (2025). ExaGRyPE: Numerical general  
224 relativity solvers based upon the hyperbolic PDEs solver engine ExaHyPE. *Comput. Phys.*  
225 *Commun.*, 307, 109435. <https://doi.org/10.1016/j.cpc.2024.109435>

DRAFT