SYSTEM ENTERED VALUES

By RLF

AHU - Variable Volume Reheat (30% Min Flow Default)

Design Air Conditions   **Max**   **Min**

Cooling supply:	Supply duct temperature diff: 0.0 °F	Design humidity ratio diff:
Leaving cooling coil:	Reheat Temperature diff: 0.0 °F	Min room relative humidity:
Heating supply:		

Advanced Options

Cooling coil sizing method: Block	Supply fan motor location: Supply	Night purge schedule: Off (0%)
Cooling coil location: System	Return fan motor location: Return	Optimum start schedule: Off (0%)
Block cooling airflow:	Supply fan cofiguration: Draw Thru	Optimum stop schedule: Off (0%)
Ventilation deck location: Return/Outdoor Deck	Supply fan sizing: Block	
Supply duct location: Return Air	Fan mechanical efficiency : 75%	CO2-based DCV: None
Return air path: PLENUM	Apply Std62 People Avg: No	
	Std62 Max Vent (Z) Ratio:	System ventilation flag: Sum Room OA Reqs

Reset per worst case room schedule: Off (0%)	Supply air path / duct location: Return Air
Max reset:	Space convective gains to occupied layer: 100 %
Use system default outside air reset: Yes	Underfloor plenum height:
	Conductive resistance of raised floor: 0.8 hr·ft²·°F/Btu
	Upstream nominal leakage fraction: 0 %
	Downstream constant leakage fraction: 0 %
	Aux cooling coil losses to plenum: 0 %

	Control Method	Control Type
Auxiliary cooling coil	Activate After Primary System	None
Auxiliary heating coil	Activate After Primary System	None
Auxiliary fan	No Fan	

Coils   **Capacity**   **Schedule**   **Diversity**

	Capacity	Schedule	Diversity	
Main cooling:	100.0 % of Design Capacity by adjusting a	Available (100%)	People	100%
Aux cooling:		Available (100%)	Lights	100%
Main heating:	100.0 % of Design Capacity	Available (100%)	Misc loads	100%
Aux heating:		Available (100%)		
Preheat:	100.0% of Design Capacity	Available (100%)		
Reheat:	100.0 % of Design Capacity	Available (100%)		
Humidification:	100.0 % of Design Capacity	Available (100%)		

Fans

	Type	Static Press.	90.1 SP Adj	Full Load Energy Rate	Schedule	Efficiency	Priority
Primary	None	0.0 in. wg	0.0 in. wg	0.00000 kW	Available (100%)	90	
Secondary	None	0.0 in. wg	NA	0.00000 kW	Available (100%)	85	
Return	None	0.0 in. wg	0.0 in. wg	0.00000 kW	Available (100%)	90	
System Exhaust	None	0.0 in. wg	0.0 in. wg	0.00000 kW	Available (100%)	90	
Room Exhaust	None	0.0 in. wg	0.0 in. wg	0.00000 kW	Available (100%)	85	
Optional ventilation	None	0.0 in. wg	NA	0.00000 kW	Available (100%)	90	
Auxiliary	None	0.0 in. wg	NA	0.00000 kW	Available (100%)	85	
Fan Cycling					Cycle with occupancy 0.0 ft		