ROAM Systems rear seat system: installation handover record

To be completed by the installer and given to the vehicle owner with the copies of test summaries VO00269 and VO00270. See installation guide Revision A, section 11.

Vehicle

Registration	
Make, model and year	
Wheelbase (SWB / LWB)	
Rear doors (tailgate / barn doors)	

Installation

Seat position: distance from the ski heels to the lip of the van (mm, not less than 80)	
Seat belt reels at least 20mm clear of the rear window, doors closed (Y / N)	
Height of the tallest occupant checked for head clearance	
Head clear of the D pillar, roof and fittings for that occupant (Y / N)	
All 12 M12 fixings fitted, grade 8.8 or better (Y / N)	
A plate fitted under every fixing (Y / N)	
At least two full threads showing through every nyloc nut (Y / N)	
"Not for use when travelling" label fitted to each side bench (Y / N)	

Installer

Company	
Name	
Signature	
Date	

500 mile fixing check

All 12 seat fixings must be checked for tightness after the first 500 miles.

Date	
Mileage	
Checked by	

For the vehicle owner

- The side bench sections are for stationary use only. Passengers must not travel on them.
- Anyone taller than the occupant recorded above must not travel in the rear seat until head clearance has been checked for them.
- The rear travel seat was independently pull tested for seat belt anchorage strength on a steel test structure. The tests were not carried out in a vehicle and are not crash tests. They do not cover the vehicle floor or the installation.