ROAM Systems rear seat: installation trial sheet, VW Transporter T6

Fill in one sheet for each seat position: 80mm, 115mm and 215mm (heel to lip of van). Measure, do not estimate. Take a photo for every row marked (photo). Results go into the revised installation guide.

1. Vehicle and position

Reg	Model / year	Wheelbase (SWB / LWB)	Rear doors (tailgate / barn)	Frame (Standard / Full Width)

Floor build-up (ply mm / insulation)	Seat position, heel to lip (mm)	Date	Completed by
	80 / 115 / 215 / other: ____		

2. Checks at this position (rear doors or tailgate closed)

Check	Left	Right	Notes
Gap between seat belt reel and rear window or door (mm) (photo)			
Do the rear doors / tailgate close without clashing? (Y / N)			
Height of person seated for the head check (m or ft/in)			
Is their head clear of the D pillar, roof and fittings? (Y / N) (photo)			
Gap from head to D pillar (mm)			

3. The 12 fixings at this position

The frame has two ski bases with 6 holes each. L = left ski, R = right ski (as seated, facing forward). Number each ski 1 to 6 from the front of the van to the rear. Look from underneath before drilling.

Hole	Comes out through: chassis section / floor rib / flat floor	Obstruction underneath? (what)	Plate: LH or RH chassis plate / 100 x 100	Plate sits flat? (Y / N / folded)	Total thickness clamped, head to nut face (mm)	Bolt length needed (mm)
L1						
L2						
L3						
L4						
L5						
L6						
R1						
R2						
R3						
R4						
R5						
R6						

4. Drilling and bolts

Drill size used for the M12 holes (mm)	Bolt fit in hole (free / tight)	Bolt grade marked on head	Thread showing below the nut with the bolt length above (mm)

5. Torque trial (torque wrench, tighten in steps, stop at first sign of movement)

Fixing type	Hole no. tried	Torque at which ply, floor or section starts to deform (Nm)	What deformed	Proposed torque (Nm)
Through flat floor or floor rib, with 100 x 100 plate				
Through the hollow rear chassis section (no anti-crush tube)				

6. Problems, anything that did not fit, photos taken
