

ABS Interlocking Boxwall Flood Barriers

TB-BW series · freestanding L-profile · no fixing to the building · factory-direct from China

Tucsenberg
2026.07
TB-BW-SPEC · v1

50–85

cm heights · 4 models

4–5

mm wall (±0.5)

3 yr

materials warranty

12 h

standard-item quote

A freestanding flood barrier that needs no bolts, no rails, and no preparation on the building. Each ABS unit locks into the next; rising water presses the L-shaped base down and **seals it harder against the ground**. Straight, curved and gable-end units at every height, so the wall actually closes around real sites.

Specifications weights ±5% · confirmed with quotation

Model	Protection height	Straight unit	Curve units (in / out)	Wall thickness
TB-BW50	50 cm	3.8 kg	2.8 / 2.7 kg	4 mm
TB-BW60	60 cm	7.4 kg	3.3 / 3.3 kg	4–5 mm
TB-BW75	75 cm	9.8 kg	3.2 / 3.2 kg	4–5 mm
TB-BW85	85 cm (with handle)	9.8 kg	5 / 5 kg	5 mm

TB-BW85 effective stop height is 75 cm — the handle section sits above the waterline. Straight-unit footprint at 75 cm: 100 cm W × 85 cm D. Gable-end units available at every height.

System

- Freestanding L-profile — water load improves the ground seal; no anchors, no drilling
- Tool-free mechanical locking-and-coupling joints between units
- Curve and gable-end units follow driveways, entrances and property lines
- Anti-slip seals on bottom and edges; ground sheet recommended on rough surfaces
- Stack flat for storage; spare joints and seals sold separately

Material & testing

- UV-stabilised ABS with anti-slip seals on bottom and edges
- Working temperature −40 °C to +95 °C
- Designed for repeated seasonal deployment — rinse, dry, restack
- Custom colours and moulded-in logos from moulded-batch quantities

Ordering

- **Minimum order:** one carton / small pallet lot — no single retail units
- **Samples:** paid sample kit (2 straight + 1 corner + documentation); fee credited against your first order
- **Payment:** 30% deposit, 70% before shipment (T/T); custom orders agreed per order at quotation
- **Lead time:** in-stock configurations ship in 2–7 days; production orders confirmed at quotation
- **OEM / private label:** moulded-in logo, printed labels, custom cartons and documentation

Send photos of your site with the RFQ — paving vs gravel changes the recommendation, and **we will say honestly when boxwall is the wrong tool** and a tube dam or plank gate fits better.