

Water & Air-Filled Flood Tube Dams

TB-TD series · 1 m protection height · deploys on grass, mud and broken ground where rigid barriers can't seal

Tucsenberg
2026.07
TB-TD-SPEC · v1

1 m	5 / 10 m	~450 s	52 kg
protection height per tube	section lengths, spliceable	inflation to 6 PSI (pump incl.)	per 10 m section (±5%)

Where rigid barriers can't seal — grass, mud, gravel, long uneven runs — a tube dam can. Roll it out, inflate with the included pump (about 7–8 minutes per 10 m section), pin the skirt, and you have a metre-high wall. Sections connect for runs of any length. **Air-inflated as standard; water-fill supported** where compressors aren't practical.

Specifications confirmed with quotation

Models	TB-TD500 (5 m section) · TB-TD1000 (10 m section)
Tube wall	0.9 mm PVC tarpaulin, thermally moulded · fabric weight 1,120 g/m ²
Ground mat	0.6 mm PVC, 10.8 m × 2 m per 10 m section
Tear / tensile strength	warp 280 N, weft 320 N · 2,800 / 2,500 N/5 cm
Flex durability	100,000 cycles
Fire performance	Flame-retardant fabric
Working temperature	−30 °C to +70 °C · anti-UV surface with reflective marking
In the bag, per section	pressure-relief tube, AC inflation pump, 10 ground nails, 5 wind ropes, splicing sleeve, 2 repair patches, carry bag

Where tube dams win

- Unpaved and uneven ground — the reason this product exists
- Long perimeters fast: hundreds of metres from a pallet and a pump
- Emergency and municipal stock — one SKU covers unknown future sites
- Reflective marking keeps night deployments visible
- Field repair is a patch-and-reinflate job; patches included

Plan the deployment

- A planned-response product, not a last-minute one: it needs a **pump or water source, fill time, a crew, and space to set the line**
- Set the line first, then fill — a filled tube is heavy and hard to reposition
- On hard paving with narrow recessed joints, water can track under the skirt — use the ground mat
- Overtopping ends protection: plan height with margin; a pre-season dry run is worth an hour

Ordering

- **OEM:** printed sleeve marking, custom section lengths, your carton and manual
- **Spares:** repair patches, pumps, nails and splicing sleeves reorderable
- **Payment:** 30% deposit, 70% before shipment (T/T) · **Warranty:** 3 years, consumable accessories excluded
- **Lead time:** in-stock ships in 2–7 days; custom lengths confirmed at quotation

Tell us run length, ground type, air or water fill, and what pump or water source the site will have — **quoted within 12 hours.**