



PRODUCT CATALOG · 2026 EDITION

Flood Protection, Factory-Direct from China

Five product lines, one coordinated factory pool, one QC standard — from a single carton to mixed full containers.

- ABS Interlocking Boxwall Barriers · TB-BW
- Aluminum Flood Gates & Demountable Barriers · TB-AG
- Absorbent Flood Bags (Sandless Sandbags) · TB-FB
- Water & Air-Filled Tube Dams · TB-TD
- FRP Composite Planks · TB-CP (in development)

Tucsenberg — trading name of Jiangsu Tucson Borg Technology Co., Ltd.

Lianyungang, Jiangsu, China · tucsenberg.com · sales@tucsenberg.com

OEM · Private Label · Custom-Cut | Standard items quoted within 12 hours

Who You're Buying From

the due-diligence page — read this one first

Tucsenberg is the trading name of **Jiangsu Tucson Borg Technology Co., Ltd.**, founded in 2021 and based in Lianyungang, Jiangsu — one of China's major coastal port cities, within reach of the Yangtze Delta manufacturing cluster where our factory pool operates.

Why a young company, on purpose

We won't pretend to decades of history. The factories in our pool carry the manufacturing years — they have supplied established flood protection brands for years. What's ours: the product designs and specifications, the QC standard every factory ships against, and a front end that answers in your time zone and treats a one-carton buyer like a future container buyer. Ask why any number in this catalog is what it is, and you'll get the engineering reason — that's what the design work buys you.

How the factory pool works

- **One spec sheet per product**, whichever factory produces it — your reorder next year matches your order this year
- **One QC standard** — pre-shipment inspection across all lines, one report to your inbox before anything sails
- **Mixed-container consolidation** — gates + boxwall + bag cartons + spares in one 40'HQ
- **Spare-parts continuity** — seals, joints and end-caps stay orderable across years

How we work

1	Send your RFQ — openings, quantities, market; photos and drawings welcome
2	Quote in 12 hours for standard items; custom configurations within 48
3	Paid sample — the sample fee is credited against your first order
4	Production & QC — inspection report with photos before shipment
5	Ship carton to container — mixed-line consolidation available

How to verify us

- Factory audits welcome — in person or live video, any factory in the pool
- References on request; company registration details available for your compliance file
- Paid samples before any volume — judge the product, not the catalog
- Start small: our minimums are cartons and pallets, not containers

The Range at a Glance

match the material to the failure point — no single product covers everything

Line	Best at	Protection height	Fixing needed	Trade entry
TB-BW ABS boxwall	perimeters, no-drilling sites	50–85 cm	none — freestanding	carton / pallet
TB-AG aluminum gates	doors, garages, loading docks	to 1.8 m stacked	posts / channels, once	per opening schedule
TB-FB flood bags	leaks, thresholds, low points	~12 cm/layer; stack 2	none	carton (MOQ 300)
TB-TD tube dams	long runs, rough ground	1 m	none — ground nails	from 10 m
TB-CP FRP planks	coastal / corrosive / electrical sites	as aluminum, per span data	as aluminum	project (order-driven)

Choose by scenario

Your situation	First choice	Backed by
Shop or home doorways, flood-prone every year	TB-AG gates	TB-FB bags for thresholds
Warehouse or campus perimeter, no drilling allowed	TB-BW boxwall	TB-TD for rough sections
Coastal facility, decades-long specification	TB-CP composite (or TB-AG)	hard barriers only — no bags in salt water
Municipal / emergency stock, unknown future sites	TB-TD + TB-FB	fastest to deploy anywhere
Building a retail flood-protection product line	TB-FB + TB-BW to start	add TB-AG as your installed base grows

We manufacture and supply all five classes, so we don't need to talk you into any one of them. Send site photos with your RFQ and we'll say **honestly which tool your site needs** — including when it isn't ours.

ABS Interlocking Boxwall Barriers

TB-BW

freestanding L-profile · no fixing to the building · tool-free

50–85

cm heights · 4 models

4–5

mm wall (±0.5)

–40...95

°C working range

3 yr

materials warranty

Each ABS unit locks into the next; rising water presses the L-shaped base down and seals it harder against the ground. No anchors, no drilling, no damage to the surface — and straight, curved and gable-end units at every height, so the wall actually closes around real sites.

Specifications weights ±5% · confirmed with quotation

Model	Protection height	Straight unit	Curve units (in / out)	Wall thickness
TB-BW50	50 cm	3.8 kg	2.8 / 2.7 kg	4 mm
TB-BW60	60 cm	7.4 kg	3.3 / 3.3 kg	4–5 mm
TB-BW75	75 cm	9.8 kg	3.2 / 3.2 kg	4–5 mm
TB-BW85	85 cm (with handle)	9.8 kg	5 / 5 kg	5 mm

TB-BW85 effective stop height is 75 cm — the handle section sits above the waterline. Straight-unit footprint at 75 cm: 100 cm W × 85 cm D. Gable-end units available at every height.

System

- Water load improves the ground seal — the flood does the clamping
- Tool-free locking-and-coupling joints
- Curve and gable-end units follow driveways and property lines
- Anti-slip seals, bottom and edges; ground sheet for rough surfaces
- Stacks flat; spare joints and seals sold separately

Material & testing

- UV-stabilised ABS, tested to ASTM G154-2016 (0.76 W/m² @340 nm, BPT 60 °C, 8 h)
- Working temperature –40 °C to +95 °C
- Repeated seasonal deployment: rinse, dry, restack
- Custom colours and moulded-in logos from moulded-batch quantities

Aluminum Flood Gates & Demountable Barriers

TB-AG

stacked planks between posts · measure once, deploy in minutes every season

180

mm plank profile

6063-T6

alloy · ≥ 2.0 mm wall

~3 m

single span; mid-posts beyond standard stacked height

1.8 m

The trade standard for defined openings — doors, garages, loading docks, shopfronts. One measured installation of the fixings; from then on the opening seals in minutes with planks that store flat the rest of the year. Every order is custom-cut to your opening schedule, labelled per opening.

The system, part by part

Planks	Extruded 6063-T6 profiles, 180 mm per plank, wall ≥ 2.0 mm; typical 4.5–6.5 kg/m class, confirmed per profile at quotation
Seals	EPDM on every horizontal joint and at the base — compression sealing; replacement seals sold separately, forever
Posts	Wall-mounted channels · removable ground-socket posts (flush off-season) · freestanding posts where drilling isn't allowed
Clamps	Screw-down clamps lock the stack; form confirmed per configuration

Configurations

- **Single opening** — two channels + planks: the bread-and-butter configuration
- **Wide spans** — beyond ~3 m, removable intermediate posts split the span; we quote post count from your opening width
- **Perimeter runs** — corner posts take the system around building lines; combine with boxwall where fixing isn't allowed
- **Custom-cut, always** — from tested profiles, per approved drawings; cut, labelled and packed per opening

Boundary, stated plainly: we are supply-only. Drawings, fixing specifications, manuals and responsive support for your installer — **not site engineering, not stamped drawings**. Coastal spec? Ask us to quote FRP planks alongside and we'll give you the honest trade-off.

Absorbent Flood Bags — Sandless Sandbags

TB-FB

ships flat at 230 g · a 20 kg sandbag in 3–4 minutes · no sand, no shoveling

0.23→20

kg dry → deployed

3–4

min activation

3 yr

shelf life, vacuum-packed

300

bags MOQ (cartons)

Specifications

	TB-FB400 (no handle)	TB-FB436 (with handle)
Dry size	400 × 600 mm	400 × 360 × 150 mm
Dry / deployed weight	0.23 kg / 20 kg (±5%)	0.25 kg / 20 kg (±5%)
Deployed height	~12 cm	~12 cm
Packing	5/vacuum bag · 50/carton	4/vacuum bag · 40/carton
Carton (NW/GW)	50×36×42 cm · 13.5/14.5 kg	50×36×42 cm · 14.5/15.5 kg
Materials · colours	PP non-woven shell, SAP core (non-toxic) · white / black	

How many bags does a job take?

Application (two layers, ~15% overlap)	Bags
Standard doorway (0.9 m)	5–6
Double door / single garage (2.4 m)	9–11
Double garage (4.9 m)	18–22
Whole-house entry points	30–50

Dealers: this table is yours to reuse in your own sales material once you stock the line.

Fresh water only. SAP cores do not activate properly in salt or brackish water — for coastal storm surge, pair bags with hard barriers. Bags are single-event products for low-level water, leaks and gap sealing; above shin height they're the wrong tool, and we'll say so.

Built for resale: consumable demand, private label from the first order (printed shell, your carton — no mould cost), and cartons fill the gaps in any mixed container.

Water & Air-Filled Tube Dams

TB-TD

where rigid barriers can't seal — grass, mud, gravel, long uneven runs

1 m

protection height

5 / 10 m

section lengths

0.9

mm PVC tube wall

~7.5

min inflation / 10 m

Roll it out, inflate with the included pump, pin the skirt — a metre-high wall on ground no rigid barrier can seal. Sections connect for runs of any length; water-fill deployment supported where compressors aren't practical.

Specifications

	TB-TD500	TB-TD1000
Section length × height	5 m × 1 m	10 m × 1 m
Tube / ground mat	0.9 mm PVC tarpaulin, thermally moulded · 0.6 mm mat (10.8 × 2 m on 10 m section)	
Fabric · weight	1,120 g/m ² , anti-UV surface with reflective marking · 52 kg ±5% per 10 m section	
Strength	tear 280/320 N (warp/weft) · tensile 2,800/2,500 N/5 cm · 100,000 flex cycles	
Ratings	fire EN 13501 B1 · working temperature –30 °C to +70 °C	
Inflation	~450 s to 6 PSI per 10 m section, pump included	

In the bag, per section

Pressure-relief tube · AC inflation pump · 10 ground nails · 5 wind ropes · splicing sleeve · 2 repair patches · carry bag. The accessory kit is complete on day one — and repair patches, pumps and sleeves stay orderable as consumables.

A tube dam is a planned-response product — it needs deployment time and space. For openings that must seal in minutes, use aluminum gates; for paved perimeters, boxwall stacks tighter in storage.

Trade entry from 10 metres. OEM printed sleeves, custom section lengths, your carton and manual.

FRP Composite Flood Planks

TB-CP · IN DEVELOPMENT

corrosion-free, non-conductive — the coastal and industrial specification

A flood plank that never corrodes, conducts nothing, and shrugs off salt air — pultruded fiberglass in the same stacked-plank logic as our aluminum gates, so posts, seals and deployment practice carry over. This page tells you honestly what's ready, what's in testing, and what it takes to open a profile — because nobody else in this category writes that down.

Where FRP earns its premium

- **Coastal and salt-air sites** — corrosion is aluminum's one real weakness over decades; FRP simply doesn't participate
- **Chemical and industrial exposure** — process plants, wastewater sites, de-icing salt zones
- **Electrical infrastructure** — substations and switchyards, where non-conductive isn't a preference but a spec

Everywhere else, aluminum remains the value answer — and we'll tell you so in the quote.

How order-driven production works

Tooling	One-time pultrusion die cost, quoted per profile, amortised across your first run
First run	Minimum volumes apply — hundreds of metres, not thousands; a real project usually clears it
Testing	Span and deflection verification on the produced profile — data delivered with the goods
Reorders	The die is cut; subsequent runs price like a standard product

Span and deflection data for the first profiles is being compiled with our pultrusion partners. [Register interest](#) at tucsenberg.com and you'll receive the actual test tables as they complete — no marketing sheet, the numbers.

Ordering, OEM & Terms

the commercial page — read before you send money, ours or anyone's

Ordering

- **Minimums:** cartons and pallets, not containers; no single retail units (freight economics punish everyone)
- **Samples:** paid, plus freight — the fee is credited against your first order
- **Payment:** 30% deposit, 70% before shipment (T/T); custom orders agreed per order and confirmed with your quotation
- **Lead time:** in-stock ships in 2–7 days; production orders confirmed at quotation
- **Consolidation:** gates + boxwall + bags + spares, one container, one QC report

Warranty

- 3 years on materials and workmanship, standard lines — a year longer than the market standard
- Consumables (bags, seals, patches) warranted to spec on arrival; bag shelf life 3 years vacuum-packed
- Custom-cut and custom-branded items are final sale
- Full terms: tucsonberg.com/warranty

OEM & private label — every line

- **On-product:** moulded-in logo (ABS), printed shells and sleeves (bags, tubes), plank marking (aluminum)
- **Packaging:** your carton artwork, pallet presentation, inserts and manuals in your layout
- **Documentation:** spec sheets and QC reports issued under your brand
- **Boundaries:** moulded logos carry a one-time mould contribution, quoted before you commit

Dealer economics, protected

- We don't retail and we don't publish prices — no channel undercutting you
- Consumables anchor reorders through you
- **Exclusivity:** a conversation once there's order history — we don't sell promises before product

Get a quote: send your product mix, quantities and port to sales@tucsonberg.com — standard items quoted within 12 hours, custom configurations within 48. RFQ form at tucsonberg.com.

Company	Jiangsu Tucson Borg Technology Co., Ltd. (trading as Tucsonberg)
Registered address	No. 47, Houhe Village, Dongwangji Town, Guanyun County, Lianyungang City, Jiangsu, China
Contact	sales@tucsonberg.com · tucsonberg.com
Catalog	2026 Edition, v1 — specifications typical, confirmed with quotation; we'd rather re-quote than surprise-invoice