

Aluminum Flood Gates & Demountable Barriers

Tucsenberg

TB-AG series · stacked planks, EPDM seals, three post types · custom-cut to your opening schedule

2026.07

TB-AG-SPEC · v1

180 mm

plank profile height

6063-T6

alloy · temper, ≥ 2.0 mm wall

1.8 m

standard stacked height

12 h

standard-item quote

The trade standard for defined openings — doors, garages, loading docks, shopfronts. Measure once, install the fixings once; from then on the opening seals in minutes, every season. Also known as **flood boards** (UK) or removable flood panels — same system, same parts. Planks, posts, seals and spares supplied factory-direct, cut and labelled per opening.

Specifications confirmed per cut list at quotation

Plank profile height	180 mm
Alloy / temper	6063-T6, wall thickness ≥ 2.0 mm
Plank weight	typical 4.5–6.5 kg/m class — confirmed per profile at quotation
Protection height	up to 1.8 m stacked as standard; above on engineering review
Span between posts	height-dependent — ~ 3 m single span at typical heights; post count quoted from width $\times$ protection height
Seals	EPDM on every horizontal joint and base — replaceable, sold separately
Post options	wall-mounted channel / ground-socket (flush off-season) / freestanding
Surface finish	mill finish standard; anodised on request

Custom-cut, always

- Every order cut to your opening schedule — widths & heights per opening
- Delivered labelled per opening: your installer unpacks kit #3 for door #3
- Top clamps lock the stack; exact form confirmed per configuration
- Spares continuity: seals, clamps and single planks stay orderable for years
- From tested profiles, per approved drawings — no site engineering, stated upfront

Honest boundaries

- Protects a **defined opening** — not water rising through slab, soil or drains
- Rain can still fall or blow in behind any barrier: plan a pump or drain on the dry side
- Wall channels stay on the reveal off-season; ground sockets sit flush; freestanding leaves nothing
- Fixings are surface-specific (masonry / concrete / steel / timber) — we ask before quoting

Ordering

- **Quoted from your opening schedule** — width $\times$ height per opening, mounting surface, photos welcome
- **Payment:** 30% deposit, 70% before shipment (T/T); custom orders agreed per order at quotation
- **Warranty:** 3 years materials and workmanship; custom-cut items are final sale — use our quotation review before committing
- **Lead time:** cut-to-order confirmed at quotation; in-stock standard planks ship in 2–7 days
- **OEM:** plank marking, your branding on documentation and packaging

A supplier who won't name alloy and wall thickness **is telling you something** — ours are in the first table. Send your opening schedule: standard configurations quoted within 12 hours, custom cut lists within 48.